

SAR evaluation
FCC ID:2AACS-TAD321-A

MPE Calculation Method

$$E \text{ (V/m)} = (30 * P * G)^{0.5} / d$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 * P * G) / (377 * d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well

as the gain of the used antenna, the RF power density can be obtained.

Calculated WIFI Result and Limit (WORSE CASE IS AS BELOW)

Antenna Gain (Numeric)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.319 (5.21dBi)	100 (20.00dBm)	0.0660	1	Complies

Note:

Antenna Gain: 2.20dBi (2.4G Band)

Assembly Antenna Gain: 5.21dBi

Assembly Antenna Gain (Numeric): 3.319dBi

ERP=20.00+5.21-2.15=23.06dBm(202.302mW)

WIFI 2.4G band and 5G band cannot transmit Simultaneously

Calculated Bluetooth Result and Limit (WORSE CASE IS AS BELOW)

Antenna Gain (Numeric)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
1.660 (2.2dBi)	5.741 (7.59dBm)	0.0019	1	Complies

Note:

Antenna Gain: 2.20dBi (2.4G Band)

Assembly Antenna Gain (Numeric): 1.660dBi

ERP=7.59+2.2-2.15=7.64dBm(5.808mW)

BT BDR/EDR and BLE cannot transmit Simultaneously

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} = 100/3060 + 5.741/3060 = 0.0346$$

$$\sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} = (202.302 + 5.808) / 3060 = 0.0680$$

$$\sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} = (0.0660 + 0.0019) / 1 = 0.0679$$

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

$$0.0346 + 0.0680 + 0.0679 = 0.1705 < 1$$