# **Maximum Permissible Exposure**

## FCC ID: 2AACS-ULT156-03

## **Applicable Standard**

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

# (a) Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field<br>Strength (E)<br>(V/m) | Magnetic Field<br>Strength (H)<br>(A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   2 ,   H   2 or S (minutes) |
|-----------------------|---|---|---|--|
| 0.3-3.0               | 614                                     | 1.63                                    | (100)*                                  | 6  |
| 3.0-30                | 1842/f                                  | 4.89/f                                  | (900/f)*                                | 6  |
| 30-300                | 61.4                                    | 0.163                                   | 1.0                                     | 6  |
| 300-1500              |   |   | F/300                                   | 6  |
| 1500-100000           |   |   | 5                                       | 6  |

## (b) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field<br>Strength (H)<br>(A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   2 ,   H   2 or S (minutes) |
|-----------------------|-----------------------------------|---|---|--|
| 0.3-1.34              | 614                               | 1.63                                    | (100)*                                  | 30   |
| 1.34-30               | 824/f                             | 2.19/f                                  | (180/f)*                                | 30   |
| 30-300                | 27.5                              | 0.073                                   | 0.2                                     | 30   |
| 300-1500              |                                   |   | F/1500                                  | 30   |
| 1500-100000           |                                   |   | 1.0                                     | 30   |

Note: f=frequency in MHz; \*Plane-wave equivalent power density

#### **MPE Calculation Method**

 $E (V/m) = (30*P*G)^{0.5}/d$  Power Density: Pd  $(W/m^2) = E^2/377$ 

 $\mathbf{E} = \text{Electric Field (V/m)}$ 

 $\mathbf{P}$  = Peak RF output Power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

 $Pd = (30*P*G) / (377*d^2)$ 

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

## **Calculated Result and Limit**

Antenna Gain: 2.0dBi

WIFI:

| Antenna<br>Gain<br>(Numeric) | Output<br>Power (dBm) | Peak Output<br>Power (mW) | Power Density (S) (mW/cm²) | Limit of Power Density (S) (mW/cm²) | Test<br>Result |
|------------------------------|-----------------------|---------------------------|----------------------------|-------------------------------------|----------------|
| 1.585                        | 19.90                 | 97.72                     | 0.03                       | 1                                   | Compiles       |

BT:

| Antenna<br>Gain<br>(Numeric) | Output<br>Power (dBm) | Peak Output<br>Power (mW) | Power Density (S) (mW/cm²) | Limit of Power Density (S) (mW/cm²) | Test<br>Result |
|------------------------------|-----------------------|---------------------------|----------------------------|-------------------------------------|----------------|
| 1.585                        | 3.01                  | 2                         | 0.00063                    | 1                                   | Compiles       |

0.00063+0.03=0.03063<1

Note: the worse case was recorded.