

FCC REPORT

Applicant: i.safe MOBILE GmbH

Address of Applicant: i_Park Tauberfranken 14 97922 Lauda-Koenigshofen, Germany

Equipment Under Test (EUT)

Product Name: Mobile phone

Model No.: ADVANTAGE 1.0,ADVANTAGE 1.1

Trade mark: i.safe MOBILE

FCC ID: 2AACZ-ADVANTAGE1X

Applicable standards: FCC CFR Title 47 Part 15 Subpart B

Date of sample receipt: 09 May 2013

Date of Test: 10 May to 04 June 2013

Date of report issued: 06 June 2013

Test Result : Pass *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	06 June 2013	<i>Original</i>

Prepared by:



Date:

06 June 2013

Report Clerk

Reviewed by:



Date:

06 June 2013

Project Engineer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF E.U.T	5
5.3 OPERATING MODES	5
5.4 DESCRIPTION OF SUPPORT UNITS	6
5.5 LABORATORY FACILITY	6
5.6 LABORATORY LOCATION	6
5.7 TEST INSTRUMENTS LIST	7
6 TEST RESULTS AND MEASUREMENT DATA	8
6.1 CONDUCTED EMISSION	8
6.2 RADIATED EMISSION	11
7 TEST SETUP PHOTO	17
8 EUT CONSTRUCTIONAL DETAILS	18

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part 15.107	Pass
Radiated Emission	Part 15.109	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	i.safe MOBILE GmbH
Address of Applicant:	i_Park Tauberfranken 14 97922 Lauda-Koenigshofen, Germany
Manufacturer:	Power Idea Technology (Shenzhen) Co., Ltd
Address of Manufacturer:	1401A, Building 8, Bin Hai Zhi Chuang Garden, Huandong Road and Xihuan North Road, NanShan District, Shenzhen City, China.

5.2 General Description of E.U.T.

Product Name:	Mobile phone
Model No.:	ADVANTAGE 1.0, ADVANTAGE 1.1
Trade mark:	i.safe MOBILE
AC adapter:	Input: 100-240V AC, 50/60Hz 0.15A Output: 5.0V DC MAX1000mA
Power supply:	Rechargeable Li-ion Battery DC3.7V-1000mAh
Remark:	The Model: ADVANTAGE 1.0, ADVANTAGE 1.1 were identical inside, the electrical circuit design, layout, components used and internal wiring, with only difference between them is the camera of model ADVANTAGE 1.1 was switched off by software, but the camera module is still inside. We selected the model ADVANTAGE 1.0 for full test.

5.3 Operating Modes

Operating mode	Detail description
Downloading mode	Keep the EUT in EUT transfer data with pc mode (Worst case)
Playing mode	Keep the EUT in Playing mode
Recording mode	Keep the EUT in Recording mode
FM mode	Keep the EUT in FM receiver mode
GPS mode	Keep the EUT in GPS receiver mode

The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

5.4 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX745	N/A	DoC
DELL	MONITOR	E178FPC	N/A	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC
HP	Printer	CB495A	05257893	DoC

5.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Registration No.: 817957**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in out files. Registration 817957, February 27, 2012.

● **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

5.6 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
Address: No.B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China
Tel: 0755-23118282
Fax: 0755-23116366

5.7 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	June 09 2012	June 08 2013
2	EMI Test Receiver	Rohde & Schwarz	ESPI	CCIS0022	Apr.01 2013	Mar. 31 2014
3	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	CCIS0005	June 04 2012	June 03 2013
4	Double-ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	CCIS0006	May 30 2013	May. 29 2014
5	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
6	Coaxial Cable	CCIS	N/A	CCIS0016	Apr. 01 2013	Mar. 31 2014
7	Coaxial Cable	CCIS	N/A	CCIS0017	Apr. 01 2013	Mar. 31 2014
8	Coaxial cable	CCIS	N/A	CCIS0018	Apr. 01 2013	Mar. 31 2014
9	Coaxial Cable	CCIS	N/A	CCIS0019	Apr. 01 2013	Mar. 31 2014
10	Coaxial Cable	CCIS	N/A	CCIS0087	Apr. 01 2013	Mar. 31 2014
11	Amplifier(10kHz-1.3GHz)	HP	8447D	CCIS0003	Apr. 01 2013	Mar. 31 2014
12	Amplifier(1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	June 09 2012	June 08 2013
13	Spectrum analyzer	Rohde & Schwarz	FSP	CCIS0023	May 29 2013	May 28 2014
14	Printer	HP	HP LaserJet P1007	N/A	N/A	N/A
15	Positioning Controller	UC	UC3000	CCIS0015	N/A	N/A

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	June 09 2012	June 08 2013
2	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	May 25 2013	May. 24 2014
3	LISN	CHASE	MN2050D	CCIS0074	Apr. 01 2013	Mar. 31 2014
4	Coaxial Cable	CCIS	N/A	CCIS0086	Apr. 01 2013	Mar. 31 2014


6 Test results and Measurement Data

6.1 Conducted Emission

Test Requirement:	FCC Part15 B Section 15.107																
Test Method:	ANSI C63.4:2003																
Test Frequency Range:	150 kHz to 30 MHz																
Class / Severity:	Class B																
Receiver setup:	RBW=9 kHz, VBW=30 kHz																
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBμV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>0.5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>			Frequency range (MHz)	Limit (dB μ V)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	0.5-30	60	50
Frequency range (MHz)	Limit (dB μ V)																
	Quasi-peak	Average															
0.15-0.5	66 to 56*	56 to 46*															
0.5-5	56	46															
0.5-30	60	50															
Test setup:	<p style="text-align: center;">Reference Plane</p> <p><i>Remark</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>																
Test procedure	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). Which provide a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement. 																
Test environment:	Temp.:	23 °C	Humid.:	56%	Press.:	1 01kPa											
Measurement Record:						Uncertainty: 3.28dB											
Test Instruments:	Refer to section 5.7 for details																
Test mode:	Refer to section 5.3 for details																
Test results:	Pass																


Measurement data:

Line:



	Freq	Read Level	LISN Factor	Cable Loss	Limit Level	Over Line	Over Limit	Remark
	MHz	dBuV		dB	dBuV	dBuV	dB	
1	0.150	27.29		10.25	0.79	38.33	66.00	-27.67 QP
2	0.158	20.15		10.24	0.79	31.18	55.56	-24.38 Average
3	0.258	13.77		10.24	0.75	24.76	51.51	-26.75 Average
4	0.337	11.69		10.27	0.73	22.69	49.27	-26.58 Average
5	0.747	16.04		10.19	0.78	27.01	56.00	-28.99 QP
6	3.258	21.47		10.29	0.90	32.66	56.00	-23.34 QP
7	3.276	12.70		10.29	0.90	23.89	46.00	-22.11 Average
8	8.637	21.18		10.26	0.89	32.33	60.00	-27.67 QP
9	8.683	12.84		10.26	0.89	23.99	50.00	-26.01 Average
10	17.661	25.11		10.29	0.92	36.32	60.00	-23.68 QP
11	22.655	22.20		10.45	0.90	33.55	50.00	-16.45 Average
12	22.775	25.73		10.46	0.89	37.08	60.00	-22.92 QP

Neutral:





Site : CCIS Conducted Test Site
 Condition : FCC PART15 B QP LISN NEUTRAL
 Job No. : 129RF
 EUT : Mobile Phone
 Model : ADVANTAGE1.0
 Test Mode : Downloading Mode
 Power Rating : AC 120V/60Hz
 Environment : Temp: 23 °C Huni:56% Atmos:101KPa
 Test Engineer: Roger

Freq	Read	LISN	Cable	Limit	Over	Remark
	MHz	dBuV	Factor	Loss	Level	
1	0.154	30.10	10.27	0.79	41.16	65.78 -24.62 QP
2	0.158	19.20	10.26	0.79	30.25	55.56 -25.31 Average
3	0.258	13.20	10.24	0.75	24.19	51.51 -27.32 Average
4	0.337	21.07	10.25	0.73	32.05	59.27 -27.22 QP
5	2.567	8.81	10.27	0.94	20.02	46.00 -25.98 Average
6	3.207	12.57	10.28	0.91	23.76	46.00 -22.24 Average
7	3.276	21.65	10.28	0.90	32.83	56.00 -23.17 QP
8	8.729	22.49	10.24	0.89	33.62	60.00 -26.38 QP
9	16.839	22.62	10.27	0.91	33.80	50.00 -16.20 Average
10	17.568	27.52	10.29	0.92	38.73	60.00 -21.27 QP
11	22.655	23.55	10.45	0.90	34.90	50.00 -15.10 Average
12	23.140	27.41	10.48	0.89	38.78	60.00 -21.22 QP

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. The value of Average is too low, so not show in test data.

6.2 Radiated Emission

Test Requirement:	FCC Part15 B Section 15.109				
Test Method:	ANSI C63.4:2003				
Test Frequency Range:	30MHz to 6000MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
	Peak	1MHz	10Hz		Average Value
Limit:	Frequency	Limit (dBuV/m @3m)		Remark	
	30MHz-88MHz	40.0		Quasi-peak Value	
	88MHz-216MHz	43.5		Quasi-peak Value	
	216MHz-960MHz	46.0		Quasi-peak Value	
	960MHz-1GHz	54.0		Quasi-peak Value	
	Above 1GHz	54.0		Average Value	
		74.0		Peak Value	
Test setup:	<p>Below 1GHz</p>  <p>Above 1GHz</p> 				

Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test environment:	Temp.: 25 °C Humid.: 55% Press.: 101kPa
Measurement Record:	Uncertainty: 4.88dB
Test Instruments:	Refer to section 5.7 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed


Remark:

1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case.

Measurement Data

Below 1GHz


Horizontal:



Site : 3m chamber
Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) HORIZONTAL
Job NO. : 129RF
EUT : Mobile phone
Model : ADVANTAGE1.0
Test mode : Downloading mode
Power Rating : AC 120V /60Hz
Environment : Temp:24°C Huni:65% Atmos:101Kpa
Test Engineer: Vincent

	ReadAntenna	Cable	Preamp	Limit	Over	
Freq	Level	Factor	Loss	Level	Line	Limit
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m
1	134.559	53.50	8.56	2.34	29.46	34.94
2	268.485	49.28	12.34	2.86	29.53	34.95
3	307.831	52.44	13.17	2.97	29.47	39.11
4	383.932	51.38	14.68	3.09	29.83	39.32
5	423.540	50.46	15.49	3.14	30.19	38.90
6	900.147	46.63	21.09	3.71	30.14	41.29

Vertical:




Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M1G) VERTICAL
 Job NO. : 129RF
 EUT : Mobile phone
 Model : ADVANTAGE1.0
 Test mode : Downloading mode
 Power Rating : AC 120V /60Hz
 Environment : Temp:24°C Huni:65% Atmos:101Kpa
 Test Engineer: Vincent

Freq	Read		Antenna		Cable		Preamp		Limit	Over	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB			
1	33.095	40.28	12.31	0.91	26.61	26.89	40.00	-13.11	QP		
2	57.594	43.98	12.87	1.37	28.99	29.23	40.00	-10.77	QP		
3	134.559	52.33	8.56	2.34	29.46	33.77	43.50	-9.73	QP		
4	269.428	49.02	12.34	2.86	29.53	34.69	46.00	-11.31	QP		
5	383.932	51.36	14.68	3.09	29.83	39.30	46.00	-6.70	QP		
6	423.540	44.72	15.49	3.14	30.19	33.16	46.00	-12.84	QP		

Above 1GHz


Horizontal:



Site : 3m chamber
Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
Job No. : 129RF
EUT : Mobile phone
Model : ADVANTAGE1.0
Test mode : Downloading mode
Power Rating : AC 120V/60Hz
Environment : Temp:25°C Huni:55% Atmos:101Kpa
Test Engineer: Vincent

Freq	ReadAntenna		Cable		Preamp	Limit	Over	Remark
	Level	Factor	Loss	Factor				
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1390.000	51.18	25.50	3.70	40.94	39.44	74.00	-34.56 Peak
2	1390.000	39.64	25.50	3.70	40.94	27.90	54.00	-26.10 Average
3	2330.000	45.96	27.89	5.35	35.98	43.22	74.00	-30.78 Peak
4	2330.000	32.69	27.89	5.35	35.98	29.95	54.00	-24.05 Average
5	4635.000	48.43	31.13	8.70	40.48	47.78	74.00	-26.22 Peak
6	4635.000	35.79	31.13	8.70	40.48	35.14	54.00	-18.86 Average

Vertical:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 Job No. : 129RF
 EUT : Mobile phone
 Model : ADVANTAGE1.0
 Test mode : Downloading mode
 Power Rating : AC 120V/60Hz
 Environment : Temp:25°C Huni:55% Atmos:101Kpa
 Test Engineer: Vincent

Freq	Read	Antenna	Cable	Preamp	Limit		Over	Remark
					Level	Factor		
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1240.000	56.10	25.49	3.54	40.90	44.23	74.00	-29.77 Peak
2	1240.000	44.54	25.49	3.54	40.90	32.67	54.00	-21.33 Average
3	1590.000	55.93	24.98	4.08	40.97	44.02	74.00	-29.98 Peak
4	1590.000	43.73	24.98	4.08	40.97	31.82	54.00	-22.18 Average
5	3950.000	49.98	29.80	7.61	41.05	46.34	74.00	-27.66 Peak
6	3950.000	38.59	29.80	7.61	41.05	34.95	54.00	-19.05 Average