

# FCC Test Report

Product Name	802.11b/g/n+BT 4.1 Module
Model No	WM-BN-BM-26_A
FCC ID.	2AAD3JA0D0J0

Applicant	ABILITY ENTERPRISE CO., LTD.
Address	4Fl., No.8,Lane 7, Wuchiuan Road Wugu Shiang, Taipei, Taiwan 248 R.O.C.

Date of Receipt	Mar. 26, 2015
Issue Date	Aug. 18, 2015
Report No.	1540010R-RFUSP26V00
Report Version	V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of Quietek Corporation.

# Test Report

Issue Date: Aug. 18, 2015

Report No.: 1540010R-RFUSP26V00



Product Name	802.11b/g/n+BT 4.1 Module
Applicant	ABILITY ENTERPRISE CO., LTD.
Address	4Fl., No.8,Lane 7, Wuchiuan Road Wugu Shiang,Taipei,Taiwan 248 R.O.C.
Manufacturer	ABILITY ENTERPRISE CO., LTD.
Model No.	WM-BN-BM-26_A
FCC ID.	2AAD3JA0D0J0
EUT Rated Voltage	DC 3.3V
EUT Test Voltage	AC 120V/60Hz
Trade Name	ability
Applicable Standard	FCC CFR Title 47 Part 15 Subpart C: 2014 ANSI C63.4: 2014, ANSI C63.10: 2013 KDB 558074 D01 DTS Meas Guidance v03r03
Test Result	Complied

Documented By :

*Rita Huang*

( Senior Adm. Specialist / Rita Huang )

Tested By :

*Nick Chen*

( Engineer / Nick Chen )

Approved By :

*Vincent Lin*

( Director / Vincent Lin )

## TABLE OF CONTENTS

Description	Page
<b>1. GENERAL INFORMATION .....</b>	<b>5</b>
1.1. EUT Description.....	5
1.2. Operational Description .....	7
1.3. Tested System Details.....	8
1.4. Configuration of Tested System .....	8
1.5. EUT Exercise Software .....	8
1.6. Test Facility .....	9
<b>2. Conducted Emission.....</b>	<b>10</b>
2.1. Test Equipment.....	10
2.2. Test Setup .....	10
2.3. Limits .....	11
2.4. Test Procedure .....	11
2.5. Uncertainty .....	11
2.6. Test Result of Conducted Emission.....	12
<b>3. Peak Power Output .....</b>	<b>14</b>
3.1. Test Equipment.....	14
3.2. Test Setup .....	14
3.3. Limits .....	14
3.4. Test Procedure .....	14
3.5. Uncertainty .....	14
3.6. Test Result of Peak Power Output.....	15
<b>4. Radiated Emission.....</b>	<b>18</b>
4.1. Test Equipment.....	18
4.2. Test Setup .....	18
4.3. Limits .....	19
4.4. Test Procedure .....	20
4.5. Uncertainty .....	20
4.6. Test Result of Radiated Emission.....	21
<b>5. RF antenna conducted test.....</b>	<b>33</b>
5.1. Test Equipment.....	33
5.2. Test Setup .....	33
5.3. Limits .....	33
5.4. Test Procedure .....	33
5.5. Uncertainty .....	33
5.6. Test Result of RF antenna conducted test.....	34
<b>6. Band Edge .....</b>	<b>37</b>
6.1. Test Equipment.....	37
6.2. Test Setup .....	37
6.3. Limits .....	38
6.4. Test Procedure .....	38
6.5. Uncertainty .....	38
6.6. Test Result of Band Edge .....	39

<b>7.</b>	<b>Occupied Bandwidth .....</b>	<b>51</b>
7.1.	Test Equipment .....	51
7.2.	Test Setup .....	51
7.3.	Limits .....	51
7.4.	Test Procedure .....	51
7.5.	Uncertainty .....	51
7.6.	Test Result of Occupied Bandwidth .....	52
<b>8.</b>	<b>Power Density .....</b>	<b>58</b>
8.1.	Test Equipment .....	58
8.2.	Test Setup .....	58
8.3.	Limits .....	58
8.4.	Test Procedure .....	58
8.5.	Uncertainty .....	58
8.6.	Test Result of Power Density .....	59
<b>9.</b>	<b>EMI Reduction Method During Compliance Testing .....</b>	<b>65</b>

Attachment 1: EUT Test Photographs

Attachment 2: EUT Detailed Photographs

## 1. GENERAL INFORMATION

### 1.1. EUT Description

Product Name	802.11b/g/n+BT 4.1 Module
Trade Name	ability
Model No.	WM-BN-BM-26_A
FCC ID.	2AAD3JA0D0J0
Frequency Range	2412-2462MHz for 802.11b/g/n-20BW
Number of Channels	802.11b/g/n-20MHz: 11
Data Speed	802.11b: 1-11Mbps, 802.11g: 6-54Mbps, 802.11n: up to 72.2Mbps
Type of Modulation	802.11b:DSSS (DBPSK, DQPSK, CCK) 802.11g/n:OFDM (BPSK, QPSK, 16QAM, 64QAM)
Antenna Type	Chip Antenna
Antenna Gain	Refer to the table "Antenna List"
Channel Control	Auto

#### Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	YAGEO	ANT3216LL11R2400A	Chip	3.68 dBi for 2.4 GHz

Note:

1. The antenna of EUT conforms to FCC 15.203.

802.11b/g/n-20MHz Center Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 01:	2412 MHz	Channel 02:	2417 MHz	Channel 03:	2422 MHz	Channel 04:	2427 MHz
Channel 05:	2432 MHz	Channel 06:	2437 MHz	Channel 07:	2442 MHz	Channel 08:	2447 MHz
Channel 09:	2452 MHz	Channel 10:	2457 MHz	Channel 11:	2462 MHz		

Note:

1. The EUT is a 802.11b/g/n+BT 4.1 Module with a built-in 2.4GHz WLAN and Bluetooth transceiver, this report for 2.4GHz WLAN.
2. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.
3. Lowest and highest data rates are tested in each mode. Only worst case is shown in the report. (802.11b is 1Mbps 、 802.11g is 6Mbps 、 802.11n(20M-BW) is 7.2Mbps)
4. These tests are conducted on a sample for the purpose of demonstrating compliance of 802.11b/g/n transmitter with Part 15 Subpart C Paragraph 15.247 of spread spectrum devices.

Test Mode:	Mode 1: Transmit (802.11b 1Mbps)
	Mode 2: Transmit (802.11g 6Mbps)
	Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)


### 1.3. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	Power Cord	
1	Notebook PC	DELL	PPT	N/A	Non-Shielded, 0.8m
2	Test Fixture	ABILITY	N/A	N/A	N/A

Signal Cable Type	Signal cable Description	
A	USB Cable	Shielded, 1.2m, with one ferrite core bonded.
B	Signal Cable	Non-Shielded, 0.03m

### 1.4. Configuration of Tested System



### 1.5. EUT Exercise Software

- (1) Connect EUT and PC via Test Fixture.
- (2) Execute program “Sample Project V1.1.0.1“on the PC
- (3) Configure the test mode, the test channel, and the data rate.
- (4) Press “OK” to start the continuous transmission.
- (5) Verify that the EUT works properly.

**1.6. Test Facility**

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

The related certificate for our laboratories about the test site and management system can be downloaded from Quietek Corporation's Web Site: <http://www.quietek.com/chinese/about/certificates.aspx?bval=5>  
 The address and introduction of Quietek Corporation's laboratories can be founded in our Web site: <http://www.quietek.com/>

Site Description: File on  
 Federal Communications Commission  
 FCC Engineering Laboratory  
 7435 Oakland Mills Road  
 Columbia, MD 21046  
 Registration Number: 92195

Site Name: Quietek Corporation  
 Site Address: No.5-22, Ruishukeng,  
 Linkou Dist. New Taipei City 24451,  
 Taiwan, R.O.C.  
 TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789  
 E-Mail : [service@quietek.com](mailto:service@quietek.com)

FCC Accreditation Number: TW1014



## 2. Conducted Emission


### 2.1. Test Equipment

	Equipment	Manufacturer	Model No. / Serial No.	Last Cal.	Remark
X	Test Receiver	R & S	ESCS 30 / 825442/018	Sep., 2014	
X	Artificial Mains Network	R & S	ENV4200 / 848411/10	Feb., 2015	Peripherals
X	LISN	R & S	ESH3-Z5 / 825562/002	Feb., 2015	EUT
	DC LISN	Schwarzbeck	8226 / 176	Mar., 2015	EUT
X	Pulse Limiter	R & S	ESH3-Z2 / 357.8810.52	Feb., 2015	
	No.1 Shielded Room				

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked by “X” are used to measure the final test results.

### 2.2. Test Setup



**2.3. Limits**

<b>FCC Part 15 Subpart C Paragraph 15.207 (dBµV) Limit</b>		
Frequency MHz	Limits	
	QP	AVG
0.15 - 0.50	66-56	56-46
0.50-5.0	56	46
5.0 - 30	60	50

**2.4. Test Procedure**

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.

Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

**2.5. Uncertainty**

± 2.26 dB

**2.6. Test Result of Conducted Emission**

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Conducted Emission Test  
 Power Line : Line 1  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2437MHz)

Frequency MHz	Correct Factor dB	Reading Level dBμV	Measurement Level dBμV	Margin dB	Limit dBμV
<b>Line 1</b>					
<b>Quasi-Peak</b>					
0.150	9.671	35.850	45.521	-20.479	66.000
0.209	9.661	25.990	35.651	-28.663	64.314
0.552	9.680	32.450	42.130	-13.870	56.000
1.533	9.743	21.390	31.133	-24.867	56.000
2.263	9.781	22.110	31.891	-24.109	56.000
18.357	10.047	12.430	22.477	-37.523	60.000
<b>Average</b>					
0.150	9.671	24.130	33.801	-22.199	56.000
0.209	9.661	16.370	26.031	-28.283	54.314
0.552	9.680	29.700	39.380	-6.620	46.000
1.533	9.743	14.660	24.403	-21.597	46.000
2.263	9.781	14.080	23.861	-22.139	46.000
18.357	10.047	2.050	12.097	-37.903	50.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. “█” means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Conducted Emission Test  
 Power Line : Line 2  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2437MHz)

Frequency MHz	Correct Factor dB	Reading Level dBμV	Measurement Level dBμV	Margin dB	Limit dBμV
<b>Line 2</b>					
<b>Quasi-Peak</b>					
0.150	9.671	35.040	44.711	-21.289	66.000
0.181	9.662	31.750	41.412	-23.702	65.114
0.552	9.680	31.500	41.180	-14.820	56.000
1.556	9.744	20.520	30.264	-25.736	56.000
2.326	9.783	23.200	32.983	-23.017	56.000
18.689	10.170	13.650	23.820	-36.180	60.000
<b>Average</b>					
0.150	9.671	21.610	31.281	-24.719	56.000
0.181	9.662	19.710	29.372	-25.742	55.114
0.552	9.680	27.950	37.630	-8.370	46.000
1.556	9.744	14.620	24.364	-21.636	46.000
2.326	9.783	14.970	24.753	-21.247	46.000
18.689	10.170	4.220	14.390	-35.610	50.000

Note:

1. All Reading Levels are Quasi-Peak and average value.
2. "■" means the worst emission level.
3. Measurement Level = Reading Level + Correct Factor

### 3. Peak Power Output


#### 3.1. Test Equipment

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X	Power Meter	Anritsu	ML2495A/6K00003357	May, 2015
X	Power Sensor	Anritsu	MA2411B/0738448	Jun., 2015

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with “X” are used to measure the final test results.

#### 3.2. Test Setup



#### 3.3. Limits

The maximum peak power shall be less 1 Watt.

#### 3.4. Test Procedure

The EUT was tested according to DTS test procedure of KDB 558074 for compliance to FCC 47CFR 15.247 requirements. The maximum peak conducted output power using KDB 558074 D01 DTS Meas Guidance v03r03 section 9.1.2 PKPM1 Peak power meter method.

#### 3.5. Uncertainty

± 1.27 dB

### 3.6. Test Result of Peak Power Output

Product : 802.11b/g/n+BT 4.1 Module  
Test Item : Peak Power Output Data  
Test Site : No.3 OATS  
Test Mode : Mode 1: Transmit (802.11b 1Mbps)

Channel No	Frequency (MHz)	Average Power For different Data Rate (Mbps)				Peak Power	Required Limit	Result
		1	2	5.5	11			
		Measurement Level (dBm)						
01	2412	11.09	--	--	--	13.81	<30dBm	Pass
06	2437	10.85	10.83	10.8	10.77	13.46	<30dBm	Pass
11	2462	11.26	--	--	--	13.91	<30dBm	Pass

Note: Peak Power Output Value = Reading value on power meter + cable loss

Product : 802.11b/g/n+BT 4.1 Module  
Test Item : Peak Power Output Data  
Test Site : No.3 OATS  
Test Mode : Mode 2: Transmit (802.11g 6Mbps)

Channel No	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit	Result
		6	9	12	18	24	36	48	54	6		
		Measurement Level (dBm)										
01	2412	10.57	--	--	--	--	--	--	--	21.42	<30dBm	Pass
06	2437	10.26	10.24	10.21	10.18	10.16	10.12	10.1	10.08	21.04	<30dBm	Pass
11	2462	11.31	--	--	--	--	--	--	--	22.04	<30dBm	Pass

Note: Peak Power Output Value =Reading value on power meter + cable loss

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Peak Power Output Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)

Channel No	Frequency (MHz)	Average Power								Peak Power	Required Limit	Result
		For different Data Rate (Mbps)										
		7.2	14.4	21.7	28.9	43.3	57.8	65	72.2	7.2		
Measurement Level (dBm)												
01	2412	11.73	--	--	--	--	--	--	--	22.17	<30dBm	Pass
06	2437	11.51	11.49	11.47	11.44	11.42	11.39	11.37	11.34	22.07	<30dBm	Pass
11	2462	11.23	--	--	--	--	--	--	--	21.64	<30dBm	Pass

Note: Peak Power Output Value = Reading value on power meter + cable loss



## 4. Radiated Emission

### 4.1. Test Equipment

The following test equipments are used during the radiated emission test:


Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
☒ Site # 3	X	Magnetic Loop Antenna	Teseq	HLA6121/ 37133	Sep., 2014
	X	Bilog Antenna	Schaffner Chase	CBL6112B/ 2707	Jun., 2015
	X	EMI Test Receiver	R&S	ESCS 30/838251/ 001	Jun., 2015
	X	Coaxial Cable	QTK(Arnist)	RG 214/ LC003-RG	Jun., 2015
	X	Coaxial signal switch	Arnist	MP59B/ 6200798682	Jun., 2015

Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
☒ CB # 8	X	Spectrum Analyzer	R&S	FSP40/ 100339	Oct., 2014
	X	Horn Antenna	ETS-Lindgren	3117/ 35205	Mar., 2015
	X	Horn Antenna	Schwarzbeck	BBHA9170/209	Jan., 2015
	X	Horn Antenna	TRC	AH-0801/95051	Aug., 2015
	X	Pre-Amplifier	EMCI	EMC012630SE/980210	Jan., 2015
	X	Pre-Amplifier	MITEQ	JS41-001040000-58-5P/153945	Jul., 2015
	X	Pre-Amplifier	NARDA	DBL-1840N506/013	Jul., 2015


- Note: 1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.  
2. The test instruments marked with "X" are used to measure the final test results.

### 4.2. Test Setup

Radiated Emission Below 1GHz



Radiated Emission Above 1GHz



**4.3. Limits**

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

FCC Part 15 Subpart C Paragraph 15.209(a) Limits		
Frequency MHz	Field strength (microvolts/meter)	Measurement distance (meter)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remarks: E field strength (dB $\mu$ V/m) = 20 log E field strength (uV/m)

#### 4.4. Test Procedure

The EUT was setup according to ANSI C63.10: 2013 and tested according to DTS test procedure of KDB558074 for compliance to FCC 47CFR 15.247 requirements.

Measuring the frequency range below 1GHz, the EUT is placed on a turn table which is 0.8 meter above ground, when measuring the frequency range above 1GHz, the EUT is placed on a turn table which is 1.5 meter above ground.

The turn table is rotated 360 degrees to determine the position of the maximum emission level.

The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10: 2013 on radiated measurement.

The resolution bandwidth below 30MHz setting on the field strength meter is 9kHz and 30MHz~1GHz is 120kHz and above 1GHz is 1MHz.

Radiated emission measurements below 30MHz are made using Loop Antenna and 30MHz~1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB bandwidth of the antenna.

The worst radiated emission is measured in the Open Area Test Site on the Final Measurement.

The measurement frequency range from 9kHz - 10th Harmonic of fundamental was investigated.

#### 4.5. Uncertainty

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

**4.6. Test Result of Radiated Emission**

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2412MHz)

Frequency MHz	Correct Factor dB	Reading Level dBμV	Measurement Level dBμV/m	Margin dB	Limit dBμV/m
------------------	-------------------------	--------------------------	--------------------------------	--------------	-----------------

**Horizontal**

**Peak Detector:**

4824.000	2.428	40.830	43.259	-30.741	74.000
7236.000	9.177	38.690	47.867	-26.133	74.000
9648.000	10.019	39.070	49.090	-24.910	74.000

**Average Detector:**

--

**Vertical**

**Peak Detector:**

4824.000	2.836	41.080	43.917	-30.083	74.000
7236.000	9.676	38.850	48.526	-25.474	74.000
9648.000	10.556	39.080	49.637	-24.363	74.000

**Average Detector:**

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2437 MHz)

Frequency MHz	Correct Factor dB	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V/m	Margin dB	Limit dB $\mu$ V/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4874.000	2.076	44.010	46.087	-27.913	74.000
7311.000	9.512	42.780	52.292	-21.708	74.000
9748.000	9.630	44.160	53.790	-20.210	74.000
<b>Average Detector:</b>					
--					
<b>Vertical</b>					
<b>Peak Detector:</b>					
4874.000	2.532	40.660	43.192	-30.808	74.000
7311.000	10.089	38.510	48.599	-25.401	74.000
9748.000	10.266	38.470	48.737	-25.263	74.000
<b>Average Detector:</b>					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : 802.11b/g/n+BT 4.1 Module  
Test Item : Harmonic Radiated Emission Data  
Test Site : No.3 OATS  
Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2462 MHz)

Frequency MHz	Correct Factor dB	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V/m	Margin dB	Limit dB $\mu$ V/m
------------------	-------------------------	--------------------------------	--------------------------------------	--------------	-----------------------

**Horizontal**

**Peak Detector:**

4924.000	2.191	40.990	43.181	-30.819	74.000
7386.000	10.373	37.910	48.284	-25.716	74.000
9848.000	9.964	39.330	49.294	-24.706	74.000

**Average Detector:**

--

**Vertical**

**Peak Detector:**

4924.000	2.805	41.070	43.875	-30.125	74.000
7386.000	11.180	37.960	49.140	-24.860	74.000
9848.000	10.801	39.330	50.131	-23.869	74.000

**Average Detector:**

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : 802.11b/g/n+BT 4.1 Module  
Test Item : Harmonic Radiated Emission Data  
Test Site : No.3 OATS  
Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2412MHz)

Frequency MHz	Correct Factor dB	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V/m	Margin dB	Limit dB $\mu$ V/m
------------------	-------------------------	--------------------------------	--------------------------------------	--------------	-----------------------

**Horizontal**

**Peak Detector:**

4824.000	2.428	40.780	43.209	-30.791	74.000
7236.000	9.177	39.180	48.357	-25.643	74.000
9648.000	10.019	38.990	49.010	-24.990	74.000

**Average Detector:**

--

**Vertical**

**Peak Detector:**

4824.000	2.836	40.890	43.727	-30.273	74.000
7236.000	9.676	39.010	48.686	-25.314	74.000
9648.000	10.556	39.260	49.817	-24.183	74.000

**Average Detector:**

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2437 MHz)

Frequency MHz	Correct Factor dB	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V/m	Margin dB	Limit dB $\mu$ V/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4874.000	2.076	42.060	44.137	-29.863	74.000
7311.000	9.512	38.450	47.962	-26.038	74.000
9748.000	9.630	38.440	48.070	-25.930	74.000
<b>Average Detector:</b>					
--					
<b>Vertical</b>					
<b>Peak Detector:</b>					
4874.000	2.532	41.620	44.152	-29.848	74.000
7311.000	10.089	38.430	48.519	-25.481	74.000
9748.000	10.266	39.170	49.437	-24.563	74.000
<b>Average Detector:</b>					
--					

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.



Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2462 MHz)

Frequency MHz	Correct Factor dB	Reading Level dBμV	Measurement Level dBμV/m	Margin dB	Limit dBμV/m
------------------	-------------------------	--------------------------	--------------------------------	--------------	-----------------

**Horizontal**

**Peak Detector:**

4924.000	2.191	41.540	43.731	-30.269	74.000
7386.000	10.373	37.290	47.664	-26.336	74.000
9848.000	9.964	38.640	48.604	-25.396	74.000

**Average Detector:**

--

**Vertical**

**Peak Detector:**

4924.000	2.805	40.630	43.435	-30.565	74.000
7386.000	11.180	37.820	49.000	-25.000	74.000
9848.000	10.801	39.420	50.221	-23.779	74.000

**Average Detector:**

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)(2412MHz)

Frequency MHz	Correct Factor dB	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V/m	Margin dB	Limit dB $\mu$ V/m
------------------	-------------------------	--------------------------------	--------------------------------------	--------------	-----------------------

**Horizontal**

**Peak Detector:**

4824.000	2.428	41.090	43.519	-30.481	74.000
7236.000	9.177	38.520	47.697	-26.303	74.000
9648.000	10.019	38.430	48.450	-25.550	74.000

**Average Detector:**

--

**Vertical**

**Peak Detector:**

4824.000	2.836	40.930	43.767	-30.233	74.000
7236.000	9.676	38.100	47.776	-26.224	74.000
9648.000	10.556	38.940	49.497	-24.503	74.000

**Average Detector:**

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Harmonic Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2437 MHz)

Frequency MHz	Correct Factor dB	Reading Level dBμV	Measurement Level dBμV/m	Margin dB	Limit dBμV/m
------------------	-------------------------	--------------------------	--------------------------------	--------------	-----------------

**Horizontal**

**Peak Detector:**

4874.000	2.076	40.800	42.877	-31.123	74.000
7311.000	9.512	38.010	47.522	-26.478	74.000
9748.000	9.630	38.510	48.140	-25.860	74.000

**Average Detector:**

--

**Vertical**

**Peak Detector:**

4874.000	2.532	40.440	42.972	-31.028	74.000
7311.000	10.089	38.160	48.249	-25.751	74.000
9748.000	10.266	39.100	49.367	-24.633	74.000

**Average Detector:**

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : 802.11b/g/n+BT 4.1 Module  
Test Item : Harmonic Radiated Emission Data  
Test Site : No.3 OATS  
Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2462 MHz)

Frequency MHz	Correct Factor dB	Reading Level dBμV	Measurement Level dBμV/m	Margin dB	Limit dBμV/m
<b>Horizontal</b>					
<b>Peak Detector:</b>					
4924.000	2.191	40.670	42.861	-31.139	74.000
7386.000	10.373	37.330	47.704	-26.296	74.000
9848.000	9.964	38.190	48.154	-25.846	74.000
<b>Average Detector:</b>					
--					
<b>Vertical</b>					
<b>Peak Detector:</b>					
4924.000	2.805	40.260	43.065	-30.935	74.000
7386.000	11.180	37.830	49.010	-24.990	74.000
9848.000	10.801	39.020	49.821	-24.179	74.000

**Average Detector:**  
--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : General Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)(2437 MHz)

Frequency MHz	Correct Factor dB	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V/m	Margin dB	Limit dB $\mu$ V/m
<b>Horizontal</b>					
191.020	-9.679	51.216	41.537	-1.963	43.500
385.020	1.209	38.054	39.263	-6.737	46.000
528.580	3.074	33.010	36.084	-9.916	46.000
699.300	2.956	40.659	43.615	-2.385	46.000
879.720	6.618	29.704	36.322	-9.678	46.000
1000.000	9.564	34.811	44.375	-9.625	54.000
<b>Vertical</b>					
202.660	-5.573	45.888	40.316	-3.184	43.500
383.080	0.195	35.362	35.557	-10.443	46.000
499.480	-0.199	34.689	34.489	-11.511	46.000
608.120	2.175	35.816	37.991	-8.009	46.000
767.200	2.199	33.039	35.239	-10.761	46.000
953.440	3.015	34.125	37.140	-8.860	46.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.
8. No emission found between lowest internal used/generated frequency to 30MHz.

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : General Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)(2437 MHz)

Frequency MHz	Correct Factor dB	Reading Level dB $\mu$ V	Measurement Level dB $\mu$ V/m	Margin dB	Limit dB $\mu$ V/m
<b>Horizontal</b>					
191.020	-9.679	35.419	25.740	-17.760	43.500
332.640	-3.895	34.874	30.979	-15.021	46.000
499.480	1.991	28.299	30.289	-15.711	46.000
608.120	3.925	27.421	31.346	-14.654	46.000
699.300	2.956	33.214	36.170	-9.830	46.000
1000.000	9.564	23.496	33.060	-20.940	54.000
<b>Vertical</b>					
179.380	-0.824	24.683	23.859	-19.641	43.500
381.140	0.816	22.565	23.381	-22.619	46.000
540.220	2.169	22.428	24.597	-21.403	46.000
610.060	2.087	24.226	26.313	-19.687	46.000
819.580	3.001	21.919	24.920	-21.080	46.000
965.080	3.832	21.274	25.106	-28.894	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.
8. No emission found between lowest internal used/generated frequency to 30MHz.

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : General Radiated Emission Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)(2437 MHz)

Frequency MHz	Correct Factor dB	Reading Level dBμV	Measurement Level dBμV/m	Margin dB	Limit dBμV/m
<b>Horizontal</b>					
309.360	-4.463	29.275	24.812	-21.188	46.000
460.680	4.030	22.499	26.529	-19.471	46.000
544.100	4.373	23.030	27.403	-18.597	46.000
699.300	2.956	31.958	34.914	-11.086	46.000
852.560	7.106	21.746	28.852	-17.148	46.000
986.420	8.189	21.445	29.634	-24.366	54.000
<b>Vertical</b>					
177.440	-1.248	26.230	24.982	-18.518	43.500
379.200	0.881	23.214	24.095	-21.905	46.000
542.160	1.855	22.680	24.535	-21.465	46.000
608.120	2.175	23.570	25.745	-20.255	46.000
771.080	2.766	23.150	25.917	-20.083	46.000
961.200	3.310	21.891	25.201	-28.799	54.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.
8. No emission found between lowest internal used/generated frequency to 30MHz.

**5. RF antenna conducted test**


**5.1. Test Equipment**

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun., 2015
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun., 2015
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2015

Note: 1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.  
2. The test instruments marked with “X” are used to measure the final test results.

**5.2. Test Setup**

**RF antenna Conducted Measurement:**



**5.3. Limits**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

**5.4. Test Procedure**

The EUT was tested according to DTS test procedure of KDB558074 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Set VBW > RBW, scan up through 10th harmonic.

**5.5. Uncertainty**

The measurement uncertainty


Conducted is defined as  $\pm 1.27\text{dB}$




**5.6. Test Result of RF antenna conducted test**

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : RF antenna conducted test  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)


**Channel 01 (2412MHz)**



**Channel 06 (2437MHz)**




**Channel 11 (2462MHz)**




Note: The above test pattern is synthesized by multiple of the frequency range.

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : RF Antenna Conducted Spurious  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)


**Channel 01 (2412MHz)**



**Channel 06 (2437MHz)**




**Channel 11 (2462MHz)**




Note: The above test pattern is synthesized by multiple of the frequency range.

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : RF Antenna Conducted Spurious  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)


**Channel 01 (2412MHz)**



**Channel 06 (2437MHz)**



**Channel 11 (2462MHz)**



Note: The above test pattern is synthesized by multiple of the frequency range.

## 6. Band Edge

### 6.1. Test Equipment

#### RF Radiated Measurement:


The following test equipments are used during the band edge tests:

Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
☒ CB # 8	X	Spectrum Analyzer	R&S	FSP40/ 100339	Oct., 2014
	X	Horn Antenna	ETS-Lindgren	3117/ 35205	Mar., 2015
	X	Horn Antenna	Schwarzbeck	BBHA9170/209	Jan., 2015
	X	Horn Antenna	TRC	AH-0801/95051	Aug., 2015
	X	Pre-Amplifier	EMCI	EMC012630SE/980210	Jan., 2015
	X	Pre-Amplifier	MITEQ	JS41-001040000-58-5P/153945	Jul., 2015
	X	Pre-Amplifier	NARDA	DBL-1840N506/013	Jul., 2015

- Note:
1. All instruments are calibrated every one year.
  2. The test instruments marked by "X" are used to measure the final test results.

### 6.2. Test Setup

#### RF Radiated Measurement:



### **6.3. Limits**

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

### **6.4. Test Procedure**

The EUT was setup according to ANSI C63.10, 2013 and tested according to DTS test procedure of KDB558074 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.

### **6.5. Uncertainty**

± 3.9 dB above 1GHz

± 3.8 dB below 1GHz

### 6.6. Test Result of Band Edge

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2412MHz)

#### RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
01 (Peak)	2371.000	33.723	25.099	58.823	74.00	54.00	Pass
01 (Peak)	2390.000	33.739	24.113	57.852	74.00	54.00	Pass
01 (Peak)	2400.000	33.752	27.400	61.151	--	--	--
01 (Peak)	2413.200	33.775	68.854	102.629	--	--	--
01 (Average)	2389.400	33.738	13.299	47.037	74.00	54.00	Pass
01 (Average)	2390.000	33.739	12.653	46.392	74.00	54.00	Pass
01 (Average)	2400.000	33.752	20.240	53.991	--	--	--
01 (Average)	2411.600	33.771	64.570	98.341	--	--	--

Figure Channel 01: Horizontal (Peak)





Figure Channel 01: Horizontal (Average)




- Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.  
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.  
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.  
 4. “ \* ”, means this data is the worst emission level.  
 5. Measurement Level = Reading Level + Correct Factor.  
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2412MHz)


**RF Radiated Measurement (VERTICAL):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
01 (Peak)	2385.200	32.301	24.224	56.524	74.00	54.00	Pass
01 (Peak)	2390.000	32.267	23.002	55.269	74.00	54.00	Pass
01 (Peak)	2400.000	32.241	25.606	57.847	--	--	--
01 (Peak)	2413.200	32.254	62.958	95.212	--	--	--
01 (Average)	2390.000	32.267	11.834	44.101	74.00	54.00	Pass
01 (Average)	2400.000	32.241	15.980	48.221	--	--	--
01 (Average)	2411.600	32.247	59.090	91.337	--	--	--

**Figure Channel 01: VERTICAL (Peak)**



**Figure Channel 01: VERTICAL (Average)**




- Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.  
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.  
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.  
 4. “ \* ”, means this data is the worst emission level.  
 5. Measurement Level = Reading Level + Correct Factor.  
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2462MHz)


**RF Radiated Measurement (Horizontal):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
11 (Peak)	2461.100	33.890	68.584	102.474	--	--	--
11 (Peak)	2483.500	33.951	22.856	56.806	74.00	54.00	Pass
11 (Peak)	2485.100	33.954	24.212	58.166	74.00	54.00	Pass
11 (Average)	2461.500	33.891	65.205	99.096	--	--	--
11 (Average)	2483.500	33.951	13.447	47.397	74.00	54.00	Pass
11 (Average)	2485.100	33.954	14.627	48.581	74.00	54.00	Pass

**Figure Channel 11: Horizontal (Peak)**



**Figure Channel 11: Horizontal (Average)**



- Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.  
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.  
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.  
 4. “ \* ”, means this data is the worst emission level.  
 5. Measurement Level = Reading Level + Correct Factor.  
 6. The average measurement was not performed when the peak measured data under the limit of average detection.




Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2462MHz)


**RF Radiated Measurement (VERTICAL):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
11 (Peak)	2461.100	32.476	61.408	93.884	--	--	--
11 (Peak)	2483.500	32.586	22.302	54.887	74.00	54.00	Pass
11 (Peak)	2486.700	32.601	23.710	56.310	74.00	54.00	Pass
11 (Average)	2461.300	32.477	57.441	89.918	--	--	--
11 (Average)	2483.500	32.586	11.666	44.251	74.00	54.00	Pass

**Figure Channel 11: VERTICAL (Peak)**



**Figure Channel 11: VERTICAL (Average)**




- Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.  
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.  
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.  
 4. “ \* ”, means this data is the worst emission level.  
 5. Measurement Level = Reading Level + Correct Factor.  
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2412MHz)


**RF Radiated Measurement (Horizontal):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
01 (Peak)	2388.000	33.737	29.297	63.034	74.00	54.00	Pass
01 (Peak)	2390.000	33.739	25.237	58.976	74.00	54.00	Pass
01 (Peak)	2400.000	33.752	43.336	77.087	--	--	--
01 (Peak)	2411.600	33.771	70.194	103.965	--	--	--
01 (Average)	2390.000	32.287	12.544	46.283	74.00	54.00	Pass
01 (Average)	2400.000	32.308	20.121	53.872	--	--	--
01 (Average)	2413.800	32.327	55.847	89.623	--	--	--

**Figure Channel 01: Horizontal (Peak)**



**Figure Channel 01: Horizontal (Average)**




- Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.  
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.  
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.  
 4. “ \* ”, means this data is the worst emission level.  
 5. Measurement Level = Reading Level + Correct Factor.  
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2412MHz)


**RF Radiated Measurement (VERTICAL):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
01 (Peak)	2390.000	32.267	24.768	57.035	74.00	54.00	Pass
01 (Peak)	2400.000	32.241	37.461	69.702	74.00	54.00	Pass
01 (Peak)	2414.600	32.261	64.791	97.052	--	--	--
01 (Average)	2390.000	32.267	12.110	44.377	74.00	54.00	Pass
01 (Average)	2400.000	32.241	18.023	50.264	--	--	--
01 (Average)	2413.600	32.256	51.208	83.464	--	--	--

**Figure Channel 01: VERTICAL (Peak)**



**Figure Channel 01: VERTICAL (Average)**




- Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.  
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.  
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.  
 4. “ \* ”, means this data is the worst emission level.  
 5. Measurement Level = Reading Level + Correct Factor.  
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2462MHz)


**RF Radiated Measurement (Horizontal):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
11 (Peak)	2461.900	33.892	74.774	108.666	--	--	--
11 (Peak)	2483.500	33.951	36.831	70.781	74.00	54.00	Pass
11 (Average)	2460.900	33.890	60.179	94.069	--	--	--
11 (Average)	2483.500	33.951	17.575	51.525	74.00	54.00	Pass

**Figure Channel 11: Horizontal (Peak)**



**Figure Channel 11: Horizontal (Average)**




- Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.  
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.  
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.  
 4. “ \* ”, means this data is the worst emission level.  
 5. Measurement Level = Reading Level + Correct Factor.  
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2462MHz)


**RF Radiated Measurement (VERTICAL):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
11 (Peak)	2459.700	32.469	68.482	100.951	--	--	--
11 (Peak)	2483.500	32.586	29.045	61.630	74.00	54.00	Pass
11 (Peak)	2484.300	32.588	29.507	62.096	74.00	54.00	Pass
11 (Average)	2460.900	32.476	54.187	86.662	--	--	--
11 (Average)	2483.500	32.586	13.836	46.421	74.00	54.00	Pass

**Figure Channel 11: VERTICAL (Peak)**



**Figure Channel 11: VERTICAL (Average)**




- Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.  
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.  
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.  
 4. “ \* ”, means this data is the worst emission level.  
 5. Measurement Level = Reading Level + Correct Factor.  
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2412MHz)


**RF Radiated Measurement (Horizontal):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
01 (Peak)	2389.600	33.739	25.869	59.607	74.00	54.00	Pass
01 (Peak)	2390.000	33.739	24.909	58.648	74.00	54.00	Pass
01 (Peak)	2400.000	33.752	41.196	74.947	--	--	--
01 (Peak)	2410.200	33.768	69.240	103.008	--	--	--
01 (Average)	2390.000	33.739	12.804	46.543	74.00	54.00	Pass
01 (Average)	2400.000	33.752	20.543	54.294	--	--	--
01 (Average)	2413.600	33.776	56.456	90.232	--	--	--

**Figure Channel 01: Horizontal (Peak)**



**Figure Channel 01: Horizontal (Average)**




- Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.  
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.  
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.  
 4. “ \* ”, means this data is the worst emission level.  
 5. Measurement Level = Reading Level + Correct Factor.  
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2412MHz)


**RF Radiated Measurement (VERTICAL):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
01 (Peak)	2388.200	32.279	24.226	56.505	74.00	54.00	Pass
01 (Peak)	2390.000	32.267	23.304	55.571	74.00	54.00	Pass
01 (Peak)	2400.000	32.241	37.923	70.164	--	--	--
01 (Peak)	2410.400	32.244	64.640	96.884	--	--	--
01 (Average)	2390.000	32.267	12.062	44.329	74.00	54.00	Pass
01 (Average)	2400.000	32.241	17.271	49.512	--	--	--
01 (Average)	2413.600	32.256	50.618	82.874	--	--	--

**Figure Channel 01: VERTICAL (Peak)**



**Figure Channel 01: VERTICAL (Average)**




- Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.  
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.  
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.  
 4. “ \* ”, means this data is the worst emission level.  
 5. Measurement Level = Reading Level + Correct Factor.  
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2462MHz)


**RF Radiated Measurement (Horizontal):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
11 (Peak)	2459.900	33.887	72.628	106.515	--	--	--
11 (Peak)	2483.500	33.951	31.213	65.163	74.00	54.00	Pass
11 (Peak)	2483.900	33.951	31.407	65.358	74.00	54.00	Pass
11 (Average)	2460.700	33.890	57.843	91.732	--	--	--
11 (Average)	2483.500	33.951	13.691	47.641	74.00	54.00	Pass

**Figure Channel 11: Horizontal (Peak)**



**Figure Channel 11: Horizontal (Average)**



- Note: 1. All readings above 1GHz are performed with peak and/or average measurements as necessary.  
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.  
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.  
 4. “ \* ”, means this data is the worst emission level.  
 5. Measurement Level = Reading Level + Correct Factor.  
 6. The average measurement was not performed when the peak measured data under the limit of average detection.




Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Band Edge Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2462MHz)


**RF Radiated Measurement (VERTICAL):**

Channel No.	Frequency (MHz)	Correct Factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Result
11 (Peak)	2460.900	32.476	66.574	99.049	--	--	--
11 (Peak)	2483.500	32.586	24.638	57.223	74.00	54.00	Pass
11 (Peak)	2483.700	32.586	26.631	59.217	74.00	54.00	Pass
11 (Average)	2460.700	32.475	52.483	84.957	--	--	--
11 (Average)	2483.500	32.586	12.033	44.618	74.00	54.00	Pass

**Figure Channel 11: VERTICAL (Peak)**



**Figure Channel 11: VERTICAL (Average)**



- Note:1. All readings above 1GHz are performed with peak and/or average measurements as necessary.  
 2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.  
 3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.  
 4. “ \* ”, means this data is the worst emission level.  
 5. Measurement Level = Reading Level + Correct Factor.  
 6. The average measurement was not performed when the peak measured data under the limit of average detection.

## 7. Occupied Bandwidth


### 7.1. Test Equipment

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun., 2015
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun., 2015
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2015

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with “X” are used to measure the final test results.

### 7.2. Test Setup



### 7.3. Limits

The minimum bandwidth shall be at least 500 kHz.

### 7.4. Test Procedure

The EUT was setup according to ANSI C63.4: 2014; tested according to DTS test procedure of Jan KDB558074 for compliance to FCC 47CFR 15.247 requirements.

### 7.5. Uncertainty

± 150Hz

### 7.6. Test Result of Occupied Bandwidth

Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
01	2412	9150	>500	Pass
06	2437	9150	>500	Pass
11	2462	9150	>500	Pass

**Figure Channel 01:**




Figure Channel 06:





Figure Channel 11:



Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2412MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
01	2412	15200	>500	Pass
06	2437	15200	>500	Pass
11	2462	15200	>500	Pass

**Figure Channel 01:**




Figure Channel 06:






Figure Channel 11:




Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
01	2412	15200	>500	Pass
06	2437	15200	>500	Pass
11	2462	15200	>500	Pass


**Figure Channel 01:**



**Figure Channel 06:**



**Figure Channel 11:**





## 8. Power Density


### 8.1. Test Equipment

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun., 2015
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun., 2015
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2015

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with “X” are used to measure the final test results.

### 8.2. Test Setup



### 8.3. Limits

The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3kHz bandwidth.

### 8.4. Test Procedure

The EUT was setup according to ANSI C63.10, 2013; tested according to DTS test procedure of KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

The maximum power spectral density using KDB 558074 section 10.2 PKPSD (peak PSD) method.

### 8.5. Uncertainty


± 1.27 dB

### 8.6. Test Result of Power Density


Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Power Density Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
01	2412	2.350	< 8dBm	Pass
06	2437	2.308	< 8dBm	Pass
11	2462	2.597	< 8dBm	Pass


**Figure Channel 01:**



**Figure Channel 06:**




**Figure Channel 11:**




Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Power Density Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
01	2412	-0.466	< 8dBm	Pass
06	2437	0.976	< 8dBm	Pass
11	2462	0.944	< 8dBm	Pass


**Figure Channel 01:**



**Figure Channel 06:**




**Figure Channel 11:**




Product : 802.11b/g/n+BT 4.1 Module  
 Test Item : Power Density Data  
 Test Site : No.3 OATS  
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
01	2412	1.430	< 8dBm	Pass
06	2437	1.028	< 8dBm	Pass
11	2462	2.301	< 8dBm	Pass


**Figure Channel 01:**



**Figure Channel 06:**



**Figure Channel 11:**



**9. EMI Reduction Method During Compliance Testing**

No modification was made during testing.



## Attachment 1: EUT Test Photographs

## Attachment 2: EUT Detailed Photographs