

TEST REPORT

Reference No...... : WTD21D08085388W V1
FCC ID : 2AADC-BK7
Applicant..... : Inspectron, Inc.
Address..... : 29108 Lorie Lane Wixom, MI 48393 USA
Manufacturer : Wuxi Vision Optoelectronic Technology Co., Ltd
Address..... : Room 102, No.42 Building Wuxi Zhongguancun Software Park
Xinwu District, Wuxi City, Jiangsu Province, China
Product..... : BK7000
Model(s) : BK7000
Standards..... : FCC CFR47 Part 15.247
Date of Receipt sample : 2021-08-19
Date of Test : 2021-08-19 to 2021-10-09
Date of Issue..... : 2021-11-15
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China

Tel: +86-769-2267 6998

Fax: +86-769-2267 6828

Compiled by:



Andy Feng / Project Engineer

Approved by:



Daniel Liu / Designated Reviewer

2 Contents

	Page
1 COVER PAGE.....	1
2 CONTENTS	2
3 REVISION HISTORY	4
4 GENERAL INFORMATION.....	5
4.1 GENERAL DESCRIPTION OF E.U.T.	5
4.2 DETAILS OF E.U.T.	5
4.3 CHANNEL LIST	6
4.4 TEST MODE	7
4.5 TEST FACILITY	8
5 TEST SUMMARY	9
6 EQUIPMENT USED DURING TEST	10
6.1 EQUIPMENTS LIST	10
6.2 DESCRIPTION OF SUPPORT UNITS	10
6.3 MEASUREMENT UNCERTAINTY	11
6.4 TEST EQUIPMENT CALIBRATION	11
7 DUTY CYCLE.....	12
8 CONDUCTED EMISSION	15
8.1 E.U.T. OPERATION	15
8.2 EUT SETUP.....	15
8.3 MEASUREMENT DESCRIPTION	15
8.4 CONDUCTED EMISSION TEST RESULT	16
9 RADIATED EMISSIONS.....	18
9.1 EUT OPERATION.....	18
9.2 TEST SETUP	19
9.3 SPECTRUM ANALYZER SETUP	20
9.4 TEST PROCEDURE	21
9.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	21
9.6 SUMMARY OF TEST RESULTS	22
10 CONDUCTED SPURIOUS EMISSIONS.....	38
10.1 TEST PROCEDURE.....	38
10.2 TEST RESULT	39
11 BAND EDGE MEASUREMENT	54
11.1 TEST PRODUCE	54
11.2 TEST RESULT	55
12 6 DB BANDWIDTH AND 99% BANDWIDTH MEASUREMENT	60
12.1 TEST PROCEDURE:.....	60
12.2 TEST RESULT:	60
13 MAXIMUM PEAK OUTPUT POWER	76
13.1 TEST PROCEDURE:.....	76
13.2 TEST RESULT:	78
14 POWER SPECTRAL DENSITY	87
14.1 TEST PROCEDURE:.....	87
14.2 TEST RESULT:	87
15 ANTENNA REQUIREMENT	97
16 RF EXPOSURE.....	98

17 **PHOTOGRAPHS OF TEST SETUP AND EUT..... 99**

3 Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTD21D08085388 W	2021-08-19	2021-08-19 to 2021-10-09	2021-10-09	Original	-	Replaced
WTD21D08085388 W V1	2021-08-19	2021-08-19 to 2021-10-09	2021-11-15	Version 1	Updated	Valid

4 General Information

4.1 General Description of E.U.T.

Product:	BK7000
Model(s):	BK7000
Model Description:	N/A
Wi-Fi Specification:	2.4G-802.11b/g/n HT20/n HT40
Bluetooth Version:	Bluetooth v4.1 with BLE
Hardware Version:	REV.E
Software Version:	20.09.21
Highest frequency (Exclude Radio):	26MHz
Storage Location:	Internal Storage
Note:	N/A

4.2 Details of E.U.T.

Operation Frequency:	WiFi: 802.11b/g/n HT20: 2412~2462MHz 802.11n HT40: 2422~2452MHz BLE:2402-2480MHz
Max. RF output power:	WiFi(2.4G): 13.58dBm BLE: 9.52dBm
Type of Modulation:	WiFi: CCK, OFDM BLE:GFSK
Antenna installation:	WiFi: internal permanent antenna BLE: internal permanent antenna
Antenna Gain:	WiFi(2.4G): 2.0dBi BLE: 2.0dBi
Ratings:	Battery DC 3.7V, 3000mAh DC 5.0V, 3.0A, 15.0W charging from adapter (Adapter: Input:100-240V~ 50/60Hz, 0.6A)
Adapter:	Model: ICP20-050-3000B

4.3 Channel List

WIFI

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2452	10	2457	11	2462	12	-

BT BLE

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	1	2404	2	2406	3	2408
4	2410	5	2412	6	2414	7	2416
8	2418	9	2420	10	2422	11	2424
12	2426	13	2428	14	2430	15	2432
16	2434	17	2436	18	2438	19	2440
20	2442	21	2444	22	2446	23	2448
24	2450	25	2452	26	2454	27	2456
28	2458	29	2460	30	2462	31	2464
32	2466	33	2468	34	2470	35	2472
36	2474	37	2476	38	2478	39	2480

4.4 Test Mode

Table 1 Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
	802.11n HT40	150 Mbps	3/6/9	TX
Power Spectral Density	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
	802.11n HT40	150 Mbps	3/6/9	TX
6dB Bandwidth	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
	802.11n HT40	150 Mbps	3/6/9	TX
Band Edge	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
	802.11n HT40	150 Mbps	3/6/9	TX
Transmitter Spurious Emissions	802.11b	11 Mbps	1/6/11	TX
	802.11g	54 Mbps	1/6/11	TX
	802.11n HT20	108 Mbps	1/6/11	TX
	802.11n HT40	150 Mbps	3/6/9	TX

Table 2 Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	BT BLE	1 Mbps	0/19/39	TX
Power Spectral Density	BT BLE	1 Mbps	0/19/39	TX
6dB Bandwidth	BT BLE	1 Mbps	0/19/39	TX
Band Edge	BT BLE	1 Mbps	0/19/39	TX
Transmitter Spurious Emissions	BT BLE	1 Mbps	0/19/39	TX

Note :Parameters set by test software during channel & power tests, the software provided by the customer was used to set the operating channels as well as the output power level. The RF output power set is the power expected by the manufacturer and is going to be fixed on the firmware of the final product .

4.5 Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Testing Group Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Testing Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

5 Test Summary

Test Items	Test Requirement	Result
Radiated Emissions	15.247(d) 15.205(a) 15.209(a)	PASS
Conducted Spurious Emissions	15.247(d)	PASS
Conducted Emissions	15.207(a)	PASS
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(3),(4)	PASS
Power Spectral Density	15.247(e)	PASS
Band Edge	15.247(d)	PASS
Antenna Requirement	15.203	PASS
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS

6 Equipment Used during Test

6.1 Equipments List

3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Spectrum Analyzer	R&S	FSP30	100091	2021-04-26	2022-04-25
2	Amplifier	Agilent	8447D	2944A10178	2021-07-26	2022-07-25
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	2021-04-26	2022-04-25
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	2021-08-23	2022-08-22
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	2021-04-26	2022-04-25
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	2021-07-30	2022-07-29
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2021-07-26	2022-07-25
8	Coaxial Cable (above 1GHz)	ZT26-NJ-NJ-8M/FA	1GHz-18GHz	NA	2021-04-26	2022-04-25
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	2021-04-26	2022-04-25
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2020-10-31	2022-10-30
3	Active Loop Antenna	Com-Power Corp.	AL-130R	10160007	2021-05-05	2022-05-04
4	Amplifier	ANRITSU	MH648A	M43381	2021-04-29	2022-04-28
5	Cable	HUBER+SUHNER	CBL2	525178	2021-04-26	2022-04-25
RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	Signal Generator	Agilent	N5182A	MY46240814	2021-07-26	2022-07-25
2.	Spectrum Analyzer	R&S	FSP30	100091	2021-04-26	2022-04-25
3.	EXA Signal Analyzer	Malaysia Keysight	N9010A	MY50520207	2021-04-26	2022-04-25

6.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
/	/	/	/

6.3 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Radiated Spurious Emissions test	± 5.03 dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)
Conducted Emissions test	± 3.64 dB (AC mains 150KHz~30MHz)
Conducted Spurious Emissions test	± 3.12 dB (9kHz~30MHz)
	± 4.21 dB (30M~1000MHz)
	± 5.14 dB (1000M~26500MHz)

6.4 Test Equipment Calibration


All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

7 Duty Cycle


Modulation	On time(ms)	Period(ms)	Duty Cycle(%)	Duty Cycle Factor(dB)	Average Factor(dB)
802.11b	8.21	8.30	98.92	0.05	-0.094
802.11g	1.330	1.385	96.03	0.18	-0.352
802.11n20	1.260	1.300	96.92	0.14	-0.272
802.11n40	0.600	0.675	88.89	0.51	-1.023
GFSK	2.136	2.508	85.17	0.70	-1.394

Remark:


- 1) Duty Cycle=On Time/Period
- 2) Duty Cycle Factor= $10 \cdot \log(1/\text{Duty cycle})$
- 3) Average Factor= $20 \log_{10} \text{Duty Cycle}$




802.11g



802.11n20



802.11n40



8 Conducted Emission

Test Requirement: FCC CFR 47 Part 15 Section 15.207

Test Method: ANSI C63.10:2013

Test Result: PASS

Frequency Range: 150kHz to 30MHz

Class/Severity: Class B

Limit:

Frequency (MHz)	Limit (dB μ V)	
	Quasi-peak	Average
0.15 to 0.5	66 to 56*	56 to 46
0.5 to 5	56	46
5 to 30	60	50

8.1 E.U.T. Operation

Operating Environment :

Temperature: 21.5 °C

Humidity: 51.9 % RH


Atmospheric Pressure: 101.2kPa

EUT Operation :

The test was performed in TX transmitting mode, the worst data were shown in the report.

8.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10.



8.3 Measurement Description


The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

8.4 Conducted Emission Test Result

An initial pre-scan was performed on the live and neutral lines.


Worst Mode: WIFI mode (802.11b mode low channel)

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1940	25.55	10.69	36.24	63.86	-27.62	QP	
2	0.1940	9.34	10.69	20.03	53.86	-33.83	AVG	
3	0.2580	26.48	10.64	37.12	61.49	-24.37	QP	
4	0.2580	11.23	10.64	21.87	51.49	-29.62	AVG	
5	0.3540	28.24	10.59	38.83	58.87	-20.04	QP	
6	0.3540	14.53	10.59	25.12	48.87	-23.75	AVG	
7	0.4820	25.29	10.53	35.82	56.30	-20.48	QP	
8	0.4820	12.73	10.53	23.26	46.30	-23.04	AVG	
9	0.5460	30.58	10.54	41.12	56.00	-14.88	QP	
10	0.5460	11.44	10.54	21.98	46.00	-24.02	AVG	
11	0.7700	29.35	10.60	39.95	56.00	-16.05	QP	
12	0.7700	11.69	10.60	22.29	46.00	-23.71	AVG	

Neutral line:



9 Radiated Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2013

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

9.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 52.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in WIFI link mode, the test data were shown in the report.


9.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



9.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed Auto
 IF Bandwidth..... 10kHz
 Video Bandwidth..... 10kHz
 Resolution Bandwidth..... 10kHz

30MHz ~ 1GHz

Sweep Speed Auto
 Detector PK
 Resolution Bandwidth..... 100kHz
 Video Bandwidth..... 300kHz

Above 1GHz

Sweep Speed Auto
 Detector PK
 Resolution Bandwidth..... 1MHz
 Video Bandwidth..... 3MHz
 Detector Ave.
 Resolution Bandwidth..... 1MHz
 Video Bandwidth..... 10Hz

9.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in Z axis,so the worst data were shown as follow.
8. A 2.4GHz high –pass filter is used during radiated emissions above 1GHz measurement.

9.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

9.6 Summary of Test Results

Wifi:

Test Frequency: 9KHz~30MHz

Remark: only the worst data (802.11b/g/n Low channel mode) were recorded.

Frequency	Measurement results dBμV @3m	Detector PK/QP	Correct factor dB/m	Extrapolation factor dB	Measurement results (calculated) dBμV/m @30m	Limits dBμV/m @30m	Margin dB
(MHz)	Measurement results	Detector	Correct factor	Extrapolation factor	Measurement results (calculated)	Limits	Margin
802.11b							
6.108	25.48	QP	21.84	40.00	7.32	29.54	-22.22
15.358	25.35	QP	21.35	40.00	6.70	29.54	-22.84
25.398	25.34	QP	20.67	40.00	6.01	29.54	-23.53
802.11g							
6.574	24.39	QP	21.84	40.00	6.23	29.54	-23.31
15.347	24.47	QP	21.35	40.00	5.82	29.54	-23.72
25.589	25.26	QP	20.67	40.00	5.93	29.54	-23.61
802.11n(HT20)							
6.341	24.36	QP	21.84	40.00	6.20	29.54	-23.34
15.475	25.98	QP	21.35	40.00	7.33	29.54	-22.21
25.587	24.35	QP	20.67	40.00	5.02	29.54	-24.52
802.11n(HT40)							
6.214	25.14	QP	21.84	40.00	6.98	29.54	-22.56
15.324	24.36	QP	21.35	40.00	5.71	29.54	-23.83
25.317	25.17	QP	20.67	40.00	5.84	29.54	-23.70

Test Frequency : 30MHz ~ 8GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: Low Channel 2412MHz									
223.79	36.12	QP	158	1.6	H	-11.62	24.50	46.00	-21.50
223.79	31.03	QP	108	1.1	V	-11.62	19.41	46.00	-26.59
4824.00	48.57	PK	161	1.6	V	-1.06	47.51	74.00	-26.49
4824.00	47.35	Ave	161	1.6	V	-1.06	46.29	54.00	-7.71
7236.00	46.46	PK	252	1.9	H	1.33	47.79	74.00	-26.21
7236.00	40.05	Ave	252	1.9	H	1.33	41.38	54.00	-12.62
2339.59	46.88	PK	81	1.5	V	-13.19	33.69	74.00	-40.31
2339.59	38.43	Ave	81	1.5	V	-13.19	25.24	54.00	-28.76
2374.51	43.89	PK	327	1.9	H	-13.14	30.75	74.00	-43.25
2374.51	37.77	Ave	327	1.9	H	-13.14	24.63	54.00	-29.37
2495.68	43.36	PK	258	1.7	V	-13.08	30.28	74.00	-43.72
2495.68	38.49	Ave	258	1.7	V	-13.08	25.41	54.00	-28.59

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: Middle Channel 2437MHz									
223.79	36.99	QP	322	1.9	H	-11.62	25.37	46.00	-20.63
223.79	30.15	QP	7	1.7	V	-11.62	18.53	46.00	-27.47
4874.00	48.90	PK	162	1.7	V	-0.62	48.28	74.00	-25.72
4874.00	47.25	Ave	162	1.7	V	-0.62	46.63	54.00	-7.37
7311.00	47.85	PK	28	1.6	H	2.21	50.06	74.00	-23.94
7311.00	39.45	Ave	28	1.6	H	2.21	41.66	54.00	-12.34
2341.10	46.09	PK	99	1.8	V	-13.19	32.90	74.00	-41.10
2341.10	38.09	Ave	99	1.8	V	-13.19	24.90	54.00	-29.10
2387.60	42.66	PK	64	1.6	H	-13.14	29.52	74.00	-44.48
2387.60	38.37	Ave	64	1.6	H	-13.14	25.23	54.00	-28.77
2488.29	43.45	PK	232	1.1	V	-13.08	30.37	74.00	-43.63
2488.29	36.80	Ave	232	1.1	V	-13.08	23.72	54.00	-30.28

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: High Channel 2462MHz									
223.79	38.32	QP	309	1.6	H	-11.62	26.70	46.00	-19.30
223.79	28.72	QP	157	1.4	V	-11.62	17.10	46.00	-28.90
4924.00	49.89	PK	176	1.7	V	-0.24	49.65	74.00	-24.35
4924.00	46.50	Ave	176	1.7	V	-0.24	46.26	54.00	-7.74
7386.00	47.07	PK	164	1.3	H	2.84	49.91	74.00	-24.09
7386.00	39.81	Ave	164	1.3	H	2.84	42.65	54.00	-11.35
2320.09	46.11	PK	4	1.9	V	-13.19	32.92	74.00	-41.08
2320.09	37.41	Ave	4	1.9	V	-13.19	24.22	54.00	-29.78
2370.97	42.63	PK	226	1.5	H	-13.14	29.49	74.00	-44.51
2370.97	37.40	Ave	226	1.5	H	-13.14	24.26	54.00	-29.74
2492.58	42.38	PK	52	1.6	V	-13.08	29.30	74.00	-44.70
2492.58	38.32	Ave	52	1.6	V	-13.08	25.24	54.00	-28.76

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: Low Channel 2412MHz									
223.79	37.52	QP	71	1.6	H	-11.62	25.90	46.00	-20.10
223.79	27.78	QP	275	1.4	V	-11.62	16.16	46.00	-29.84
4824.00	49.72	PK	160	1.9	V	-1.06	48.66	74.00	-25.34
4824.00	46.97	Ave	160	1.9	V	-1.06	45.91	54.00	-8.09
7236.00	46.83	PK	63	1.3	H	1.33	48.16	74.00	-25.84
7236.00	39.44	Ave	63	1.3	H	1.33	40.77	54.00	-13.23
2333.12	46.78	PK	78	1.2	V	-13.19	33.59	74.00	-40.41
2333.12	39.26	Ave	78	1.2	V	-13.19	26.07	54.00	-27.93
2368.07	43.88	PK	340	1.9	H	-13.14	30.74	74.00	-43.26
2368.07	37.03	Ave	340	1.9	H	-13.14	23.89	54.00	-30.11
2498.20	42.35	PK	342	1.9	V	-13.08	29.27	74.00	-44.73
2498.20	38.99	Ave	342	1.9	V	-13.08	25.91	54.00	-28.09

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: Middle Channel 2437MHz									
223.79	38.45	QP	288	1.0	H	-11.62	26.83	46.00	-19.17
223.79	27.67	QP	174	1.7	V	-11.62	16.05	46.00	-29.95
4874.00	48.38	PK	268	1.6	V	-0.62	47.76	74.00	-26.24
4874.00	48.11	Ave	268	1.6	V	-0.62	47.49	54.00	-6.51
7311.00	46.94	PK	170	1.1	H	2.21	49.15	74.00	-24.85
7311.00	40.65	Ave	170	1.1	H	2.21	42.86	54.00	-11.14
2330.60	46.96	PK	33	2.0	V	-13.19	33.77	74.00	-40.23
2330.60	39.60	Ave	33	2.0	V	-13.19	26.41	54.00	-27.59
2362.99	44.68	PK	190	1.3	H	-13.14	31.54	74.00	-42.46
2362.99	38.92	Ave	190	1.3	H	-13.14	25.78	54.00	-28.22
2488.76	44.61	PK	321	1.4	V	-13.08	31.53	74.00	-42.47
2488.76	36.78	Ave	321	1.4	V	-13.08	23.70	54.00	-30.30

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: High Channel 2462MHz									
223.79	37.22	QP	108	1.8	H	-11.62	25.60	46.00	-20.40
223.79	27.16	QP	244	1.9	V	-11.62	15.54	46.00	-30.46
4924.00	47.35	PK	8	1.2	V	-0.24	47.11	74.00	-26.89
4924.00	46.25	Ave	8	1.2	V	-0.24	46.01	54.00	-7.99
7386.00	47.83	PK	278	1.1	H	2.84	50.67	74.00	-23.33
7386.00	39.69	Ave	278	1.1	H	2.84	42.53	54.00	-11.47
2323.94	45.84	PK	169	1.7	V	-13.19	32.65	74.00	-41.35
2323.94	38.18	Ave	169	1.7	V	-13.19	24.99	54.00	-29.01
2389.93	42.69	PK	240	1.5	H	-13.14	29.55	74.00	-44.45
2389.93	38.03	Ave	240	1.5	H	-13.14	24.89	54.00	-29.11
2490.49	43.66	PK	224	1.8	V	-13.08	30.58	74.00	-43.42
2490.49	38.73	Ave	224	1.8	V	-13.08	25.65	54.00	-28.35

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n20: Low Channel 2412MHz									
223.79	37.70	QP	29	1.1	H	-11.62	26.08	46.00	-19.92
223.79	26.99	QP	211	1.1	V	-11.62	15.37	46.00	-30.63
4824.00	46.66	PK	103	1.0	V	-1.06	45.60	74.00	-28.40
4824.00	46.38	Ave	103	1.0	V	-1.06	45.32	54.00	-8.68
7236.00	46.79	PK	114	1.7	H	1.33	48.12	74.00	-25.88
7236.00	39.21	Ave	114	1.7	H	1.33	40.54	54.00	-13.46
2314.47	46.41	PK	174	1.1	V	-13.19	33.22	74.00	-40.78
2314.47	37.64	Ave	174	1.1	V	-13.19	24.45	54.00	-29.55
2358.25	44.48	PK	11	1.6	H	-13.14	31.34	74.00	-42.66
2358.25	36.78	Ave	11	1.6	H	-13.14	23.64	54.00	-30.36
2492.96	44.69	PK	263	1.9	V	-13.08	31.61	74.00	-42.39
2492.96	37.04	Ave	263	1.9	V	-13.08	23.96	54.00	-30.04

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11n20: Middle Channel 2437MHz									
223.79	38.03	QP	79	1.1	H	-11.62	26.41	46.00	-19.59
223.79	26.15	QP	360	1.9	V	-11.62	14.53	46.00	-31.47
4874.00	47.97	PK	348	1.3	V	-0.62	47.35	74.00	-26.65
4874.00	47.28	Ave	348	1.3	V	-0.62	46.66	54.00	-7.34
7311.00	45.31	PK	107	1.5	H	2.21	47.52	74.00	-26.48
7311.00	38.11	Ave	107	1.5	H	2.21	40.32	54.00	-13.68
2318.07	46.62	PK	354	2.0	V	-13.19	33.43	74.00	-40.57
2318.07	39.79	Ave	354	2.0	V	-13.19	26.60	54.00	-27.40
2366.08	42.61	PK	274	1.5	H	-13.14	29.47	74.00	-44.53
2366.08	37.70	Ave	274	1.5	H	-13.14	24.56	54.00	-29.44
2499.69	43.02	PK	53	1.7	V	-13.08	29.94	74.00	-44.06
2499.69	36.38	Ave	53	1.7	V	-13.08	23.30	54.00	-30.70

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11n20: High Channel 2462MHz									
223.79	36.55	QP	131	1.7	H	-11.62	24.93	46.00	-21.07
223.79	25.24	QP	193	1.9	V	-11.62	13.62	46.00	-32.38
4924.00	47.78	PK	184	1.2	V	-0.24	47.54	74.00	-26.46
4924.00	46.38	Ave	184	1.2	V	-0.24	46.14	54.00	-7.86
7386.00	46.56	PK	154	1.6	H	2.84	49.40	74.00	-24.60
7386.00	38.54	Ave	154	1.6	H	2.84	41.38	54.00	-12.62
2328.25	45.13	PK	18	1.6	V	-13.19	31.94	74.00	-42.06
2328.25	39.40	Ave	18	1.6	V	-13.19	26.21	54.00	-27.79
2387.64	43.61	PK	284	1.4	H	-13.14	30.47	74.00	-43.53
2387.64	37.36	Ave	284	1.4	H	-13.14	24.22	54.00	-29.78
2493.66	44.61	PK	254	1.9	V	-13.08	31.53	74.00	-42.47
2493.66	36.42	Ave	254	1.9	V	-13.08	23.34	54.00	-30.66

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n40: Low Channel 2422MHz									
223.79	35.10	QP	349	1.3	H	-11.62	23.48	46.00	-22.52
223.79	23.74	QP	96	1.7	V	-11.62	12.12	46.00	-33.88
4844.00	44.94	PK	130	1.9	V	-1.06	43.88	74.00	-30.12
4844.00	45.03	Ave	130	1.9	V	-1.06	43.97	54.00	-10.03
7266.00	44.29	PK	15	1.2	H	1.33	45.62	74.00	-28.38
7266.00	36.36	Ave	15	1.2	H	1.33	37.69	54.00	-16.31
2341.10	46.33	PK	223	1.2	V	-13.19	33.14	74.00	-40.86
2341.10	39.90	Ave	223	1.2	V	-13.19	26.71	54.00	-27.29
2368.20	44.81	PK	144	1.9	H	-13.14	31.67	74.00	-42.33
2368.20	37.95	Ave	144	1.9	H	-13.14	24.81	54.00	-29.19
2487.94	44.47	PK	95	1.4	V	-13.08	31.39	74.00	-42.61
2487.94	38.76	Ave	95	1.4	V	-13.08	25.68	54.00	-28.32

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n40: Middle Channel 2437MHz									
223.79	34.64	QP	130	2.0	H	-11.62	23.02	46.00	-22.98
223.79	23.16	QP	82	2.0	V	-11.62	11.54	46.00	-34.46
4874.00	45.58	PK	49	2.0	V	-0.62	44.96	74.00	-29.04
4874.00	44.71	Ave	49	2.0	V	-0.62	44.09	54.00	-9.91
7311.00	45.14	PK	47	1.8	H	2.21	47.35	74.00	-26.65
7311.00	35.76	Ave	47	1.8	H	2.21	37.97	54.00	-16.03
2347.13	45.66	PK	65	1.4	V	-13.19	32.47	74.00	-41.53
2347.13	38.34	Ave	65	1.4	V	-13.19	25.15	54.00	-28.85
2350.04	43.11	PK	14	1.8	H	-13.14	29.97	74.00	-44.03
2350.04	36.09	Ave	14	1.8	H	-13.14	22.95	54.00	-31.05
2490.14	44.92	PK	40	1.6	V	-13.08	31.84	74.00	-42.16
2490.14	38.26	Ave	40	1.6	V	-13.08	25.18	54.00	-28.82

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n40: High Channel 2452MHz									
223.79	34.84	QP	105	1.9	H	-11.62	23.22	46.00	-22.78
223.79	23.67	QP	120	1.9	V	-11.62	12.05	46.00	-33.95
4904.00	46.44	PK	190	1.4	V	-0.24	46.20	74.00	-27.80
4904.00	45.38	Ave	190	1.4	V	-0.24	45.14	54.00	-8.86
7356.00	45.31	PK	1	1.7	H	2.84	48.15	74.00	-25.85
7356.00	35.36	Ave	1	1.7	H	2.84	38.20	54.00	-15.80
2329.43	45.26	PK	219	1.7	V	-13.19	32.07	74.00	-41.93
2329.43	39.20	Ave	219	1.7	V	-13.19	26.01	54.00	-27.99
2384.86	42.48	PK	17	1.6	H	-13.14	29.34	74.00	-44.66
2384.86	37.40	Ave	17	1.6	H	-13.14	24.26	54.00	-29.74
2498.65	44.43	PK	99	1.8	V	-13.08	31.35	74.00	-42.65
2498.65	37.19	Ave	99	1.8	V	-13.08	24.11	54.00	-29.89

Test Frequency: 8GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

BT BLE:**Test Frequency: 9KHz~26MHz**

Remark: only the worst data (GFSK modulation Low channel mode) were recorded.

Frequency	Measurement results dB μ V @3m	Detector PK/QP	Correct factor dB/m	Extrapolation factor dB	Measurement results (calculated) dB μ V/m @30m	Limits dB μ V/m @30m	Margin dB
(MHz)	Measurement results	Detector	Correct factor	Extrapolation factor	Measurement results (calculated)	Limits	Margin
6.258	25.14	QP	21.84	40.00	6.98	29.54	-22.56
15.234	24.12	QP	21.35	40.00	5.47	29.54	-24.07
25.369	25.48	QP	20.67	40.00	6.15	29.54	-23.39

Test Frequency : 26MHz ~ 30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency : 30MHz ~ 18GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
GFSK Low Channel 2402MHz									
269.47	33.59	QP	347	1.7	H	-13.35	20.24	46.00	-25.76
269.47	40.48	QP	164	1.8	V	-13.35	27.13	46.00	-18.87
4804.00	44.71	PK	147	1.3	V	-1.06	43.65	74.00	-30.35
4804.00	42.36	Ave	147	1.3	V	-1.06	41.30	54.00	-12.70
7206.00	44.58	PK	164	1.9	H	1.33	45.91	74.00	-28.09
7206.00	37.15	Ave	164	1.9	H	1.33	38.48	54.00	-15.52
2343.38	46.79	PK	175	1.8	V	-13.19	33.60	74.00	-40.40
2343.38	38.50	Ave	175	1.8	V	-13.19	25.31	54.00	-28.69
2377.07	43.73	PK	87	1.4	H	-13.14	30.59	74.00	-43.41
2377.07	36.83	Ave	87	1.4	H	-13.14	23.69	54.00	-30.31
2489.39	42.92	PK	159	1.6	V	-13.08	29.84	74.00	-44.16
2489.39	36.21	Ave	159	1.6	V	-13.08	23.13	54.00	-30.87

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK Middle Channel 2440MHz									
269.47	34.14	QP	219	1.4	H	-13.35	20.79	46.00	-25.21
269.47	40.30	QP	14	1.6	V	-13.35	26.95	46.00	-19.05
4880.00	43.46	PK	309	1.8	V	-0.62	42.84	74.00	-31.16
4880.00	43.09	Ave	309	1.8	V	-0.62	42.47	54.00	-11.53
7320.00	43.22	PK	243	1.1	H	2.21	45.43	74.00	-28.57
7320.00	36.64	Ave	243	1.1	H	2.21	38.85	54.00	-15.15
2311.09	46.71	PK	348	1.4	V	-13.19	33.52	74.00	-40.48
2311.09	37.34	Ave	348	1.4	V	-13.19	24.15	54.00	-29.85
2383.86	42.08	PK	296	1.4	H	-13.14	28.94	74.00	-45.06
2383.86	36.44	Ave	296	1.4	H	-13.14	23.30	54.00	-30.70
2498.80	44.90	PK	266	1.1	V	-13.08	31.82	74.00	-42.18
2498.80	36.64	Ave	266	1.1	V	-13.08	23.56	54.00	-30.44

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
GFSK High Channel 2480MHz									
269.47	34.88	QP	62	1.1	H	-13.35	21.53	46.00	-24.47
269.47	38.46	QP	306	1.2	V	-13.35	25.11	46.00	-20.89
4960.00	43.34	PK	110	1.3	V	-0.24	43.10	74.00	-30.90
4960.00	42.15	Ave	110	1.3	V	-0.24	41.91	54.00	-12.09
7440.00	42.26	PK	270	1.9	H	2.84	45.10	74.00	-28.90
7440.00	36.29	Ave	270	1.9	H	2.84	39.13	54.00	-14.87
2311.77	45.15	PK	283	1.9	V	-13.19	31.96	74.00	-42.04
2311.77	39.36	Ave	283	1.9	V	-13.19	26.17	54.00	-27.83
2386.70	44.65	PK	287	1.7	H	-13.14	31.51	74.00	-42.49
2386.70	38.38	Ave	287	1.7	H	-13.14	25.24	54.00	-28.76
2498.35	44.85	PK	122	1.3	V	-13.08	31.77	74.00	-42.23
2498.35	38.16	Ave	122	1.3	V	-13.08	25.08	54.00	-28.92

Test Frequency: 18GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

10 Conducted Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2013

Test Result: PASS

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

10.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:
 - a) Set instrument center frequency to DTS channel center frequency.
 - b) Set the span to _ 1.5 times the DTS bandwidth.
 - c) Set the RBW = 100 kHz.
 - d) Set the VBW _ $[3 \times \text{RBW}]$.
 - e) Detector = peak.
 - f) Sweep time = auto couple.
 - g) Trace mode = max hold.
 - h) Allow trace to fully stabilize.
 - i) Use the peak marker function to determine the maximum PSD level.


Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

10.2 Test Result


9KHz – 30MHz

802.11b


Low Channel



Middle Channel




High Channel




802.11g


Low Channel



Middle Channel




High Channel




802.11n HT20


Low Channel



Middle Channel




High Channel




802.11n HT40


Low Channel



Middle Channel



High Channel




Above 30MHz

802.11b


Low Channel

Fundamental




Middle Channel

Fundamental



High Channel


Fundamental



802.11g


Low Channel

Fundamental




Middle Channel

Fundamental



High Channel


Fundamental



802.11n HT20


Low Channel

Fundamental




Middle Channel

Fundamental



High Channel


Fundamental



802.11n HT40


Low Channel

Fundamental




Middle Channel

Fundamental



High Channel


Fundamental




9KHz – 30MHz

BLE


Low Channel



Middle Channel



High Channel




Above 30MHz


BLE

Low Channel


Fundamental



Middle Channel



High Channel



11 Band Edge Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2013

Test Limit: Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Mode: Transmitting


11.1 Test Produce

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

11.2 Test Result


Test result plots shown as follows:

TX 11b: Band edge-left side




Date: 26.SEP.2021 10:45:53

TX 11b: Band edge-right side




Date: 26.SEP.2021 10:47:57

TX 11g: Band edge-left side




Date: 26.SEP.2021 10:44:11

TX 11g: Band edge-right side




Date: 26.SEP.2021 10:50:11

TX 11n HT20: Band edge-left side




Date: 26.SEP.2021 10:41:37

TX 11n HT20: Band edge-right side




Date: 26.SEP.2021 10:52:41

TX 11n HT40: Band edge-left side




Date: 26.SEP.2021 10:39:54

TX 11n HT40: Band edge-right side




Date: 26.SEP.2021 10:38:07

BLE: Band edge-left side



BLE: Band edge-right side



12 6 dB Bandwidth and 99% Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;

ANSI C63.10:2013

12.1 Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;

2. 6dB Bandwidth Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz

99% Bandwidth Set the spectrum analyzer : RBW = 1~5% DTS OBW, VBW = 3 RBW


12.2 Test Result:

Operation mode	Test Channel	6dB Bandwidth (MHz)	99% Bandwidth (MHz)
TX 11b	Channel 1	10.112	14.400
	Channel 6	10.144	14.400
	Channel 11	10.080	14.336
TX 11g	Channel 1	16.400	17.000
	Channel 6	16.500	16.950
	Channel 11	16.400	17.000
TX 11n HT20	Channel 1	17.334	17.928
	Channel 6	17.388	17.928
	Channel 11	17.388	17.928
TX 11n HT40	Channel 3	35.640	37.070
	Channel 6	35.750	36.960
	Channel 9	36.190	37.070
BLE	Channel 0	0.738	1.044
	Channel 19	0.732	1.050
	Channel 39	0.714	1.050


Test result plot:

6dB Bandwidth


Mode: TX 11b channel 1




Mode: TX 11b channel 6




Mode: TX 11b channel 11




Mode: TX 11g channel 1




Mode: TX 11g channel 6




Mode: TX 11g channel 11




Mode: TX 11n HT20 channel 1




Mode: TX 11n HT20 channel 6




Mode: TX 11n HT20 channel 11




Mode: TX 11n HT40 channel 3



Mode: TX 11n HT40 channel 6




Mode: TX 11n HT40 channel 9




99% Bandwidth


Mode: TX 11b channel 1




Mode: TX 11b channel 6




Mode: TX 11b channel 11




Mode: TX 11g channel 1




Mode: TX 11g channel 6




Mode: TX 11g channel 11




Mode: TX 11n HT20 channel 1




Mode: TX 11n HT20 channel 6




Mode: TX 11n HT20 channel 11




Mode: TX 11n HT40 channel 3



Mode: TX 11n HT40 channel 6




Mode: TX 11n HT40 channel 9




6dB Bandwidth


BLE: channel 0



BLE: channel 19




BLE: channel 39




99% Bandwidth


BLE: channel 0



BLE: channel 19



BLE: channel 39



13 Maximum Peak Output Power

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2013

13.1 Test Procedure:

KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019

section 8.3.1.1 (For BLE)

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the $RBW \geq DTS$ bandwidth.
- b) Set $VBW \geq 3 \times RBW$.
- c) Set span $\geq 3 \times RBW$
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

section 8.3.1.2 (For WIFI)

This procedure may be used when the maximum available RBW of the measurement instrument is less than the DTS bandwidth.

- a) Set the $RBW = 1\%$ to 5% of the OBW, not to exceed 1 MHz..
- b) Set the $VBW \geq 3 \times RBW$
- c) Set the span $\geq 1.5 \times OBW$.
- d) Detector = RMS.
- e) Sweep time = auto couple.
- f) trigger = free run..
- g) Number of points in sweep $\geq [2 \times \text{span} / RBW]$. (This gives bin-to-bin spacing $\geq RBW / 2$, so that narrowband signals are not lost between frequency bins.)
- h) Trace average at least 100 traces in power averaging (rms) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum..
- j) Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured power to compute the average power during the actual transmission times (because the measurement represents an average

over both the ON and OFF times of the transmission), duty cycle test results please refer to the section 7.


13.2 Test Result:

Operation mode	Channel Frequency (MHz)	Maximum Peak Output Power (dBm)	Limit
TX 11b	Low-2412	13.32	1W/30dBm
	Middle-2437	13.13	1W/30dBm
	High-2462	13.58	1W/30dBm
TX 11g	Low-2412	11.72	1W/30dBm
	Middle-2437	11.54	1W/30dBm
	High-2462	11.73	1W/30dBm
TX 11n HT20	Low-2412	11.57	1W/30dBm
	Middle-2437	11.38	1W/30dBm
	High-2462	11.65	1W/30dBm
TX 11n HT40	Low-2422	12.14	1W/30dBm
	Middle-2437	12.07	1W/30dBm
	High-2452	12.20	1W/30dBm
BLE	Low-2402	7.8	1W/30dBm
	Middle-2440	8.7	1W/30dBm
	High-2480	9.52	1W/30dBm


Note: duty cycle test results please refer to the section 7.

Test Plot


Mode: TX 11b channel 1




Mode: TX 11b channel 6




Mode: TX 11b channel 11




Mode :TX 11g channel 1




Mode :TX 11g channel 6




Mode :TX 11g channel 11




Mode: TX 11n HT20 channel 1




Mode: TX 11n HT20 channel 6




Mode: TX 11n HT20 channel 11




Mode: TX 11n HT40 channel 3




Mode: TX 11n HT40 channel 6




Mode: TX 11n HT40 channel 9




BLE: channel 0



BLE: channel 19





14 Power Spectral density

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2013

14.1 Test Procedure:

KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019 section 10.2

For 2.4G WiFi:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = RMS. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.
4. Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured PSD to compute the average PSD during the actual transmission time when the EUT cannot be configured to transmit continuously (i.e., $D < 98\%$), duty cycle test results please refer to the section 7.

For BLE:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.


14.2 Test Result:

Operation mode	Channel Frequency (MHz)	Power Spectral (dBm per 3kHz)	Limit
TX 11b	Low-2412	-10.08	8dBm per 3kHz
	Middle-2437	-9.91	8dBm per 3kHz
	High-2462	-9.82	8dBm per 3kHz
TX 11g	Low-2412	-17.93	8dBm per 3kHz
	Middle-2437	-17.49	8dBm per 3kHz
	High-2462	-18.12	8dBm per 3kHz
TX 11n HT20	Low-2412	-20.59	8dBm per 3kHz


	Middle-2437	-21.72	8dBm per 3kHz
	High-2462	-20.63	8dBm per 3kHz
TX 11n HT40	Low-2422	-19.77	8dBm per 3kHz
	Middle-2437	-20.45	8dBm per 3kHz
	High-2452	-20.55	8dBm per 3kHz
BLE	Low-2402	-9.42	8dBm per 3kHz
	Middle-2440	-6.4	8dBm per 3kHz
	High-2480	-5.41	8dBm per 3kHz

Note: duty cycle test results please refer to the section 7.


Test Plot
Mode: TX 11b channel 1




Mode: TX 11b channel 6




Mode: TX 11b channel 11




Mode :TX 11g channel 1




Mode :TX 11g channel 6




Mode :TX 11g channel 11




Mode: TX 11n HT20 channel 1




Mode: TX 11n HT20 channel 6




Mode: TX 11n HT20 channel 11




Mode: TX 11n HT40 channel 3




Mode: TX 11n HT40 channel 6




Mode: TX 11n HT40 channel 9




BLE: channel 0



BLE: channel 19





15 Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has an integrated antenna fulfill the requirement of this section.

16 RF Exposure

Remark: refer to WTD21D08085387W002 FCC SAR Test report.

17 Photographs of test setup and EUT.

Note: Please refer to appendix: Appendix-BK7000 -Photos.

=====End of Report=====