



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V03

Report Template Revision Date: Mar.1st, 2017

Test Report

Report No.: CQASZ20201100031EX-01
Applicant: GNJ Manufacturing Inc
Address of Applicant: 5811 West Hallandale Beach Blvd. West Park, FL 33023, Hallandale, Florida, United States
Equipment Under Test (EUT):
Product: Smart UV Lamp
Model No.: CAUVST05-01
Brand Name: CellAllure
FCC ID: 2AAE9CAUVST05
Standards: 47 CFR FCC Part 15 Subpart C 15.247
Date of Test: Oct. 30, 2020 to Nov. 09, 2020
Date of Issue: Nov. 12, 2020
Test Result: **PASS**

Tested By:

Tiny You

(Tiny You)

Reviewed By:

Sheek Luo

(Sheek Luo)

Approved By:

Jack Ai

(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20201100031EX-01	Rev.01	Initial report	Nov. 12, 2020

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2013	PASS
Conducted Peak & Average Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2013	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS

3 Contents

	Page
1 VERSION	2
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION.....	5
4.1 CLIENT INFORMATION	5
4.2 GENERAL DESCRIPTION OF EUT	5
4.3 DESCRIPTION OF SUPPORT UNITS	7
4.4 TEST LOCATION	7
4.5 TEST FACILITY	7
4.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY	8
4.7 DEVIATION FROM STANDARDS	8
4.8 ABNORMALITIES FROM STANDARD CONDITIONS	8
4.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	8
4.10 EQUIPMENT LIST	9
5 TEST RESULTS AND MEASUREMENT DATA.....	10
5.1 ANTENNA REQUIREMENT	10
5.2 CONDUCTED EMISSIONS	11
5.3 CONDUCTED PEAK & AVERAGE OUTPUT POWER	14
5.4 6dB OCCUPY BANDWIDTH	15
5.5 POWER SPECTRAL DENSITY	19
5.6 BAND-EDGE FOR RF CONDUCTED EMISSIONS	23
5.7 RF CONDUCTED SPURIOUS EMISSIONS	26
5.8 RADIATED SPURIOUS EMISSIONS.....	37
5.8.1 Radiated emission below 1GHz.....	40
5.8.2 Transmitter emission above 1GHz.....	42
5.9 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	44
6 PHOTOGRAPHS - EUT TEST SETUP	49
6.1 RADIATED EMISSION TEST SETUP	49
6.2 CONDUCTED EMISSION TEST SETUP	50

4 General Information

4.1 Client Information

Applicant:	GNJ Manufacturing Inc
Address of Applicant:	5811 West Hallandale Beach Blvd. West Park, FL 33023, Hallandale, Florida, United States
Manufacturer:	GNJ Manufacturing Inc. china
Address of Manufacturer:	4/F, Building A, No. 45 Industrial Park, Zhongkai HighTech Zone, Huizhou City, GuangDong Province. 516006.

4.2 General Description of EUT

Product Name:	Smart UV Lamp
Model No.:	CAUVST05-01
Trade Mark:	CellAllure
Hardware version:	V1.0
Software version:	V8.0.3
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM IEEE for 802.11n(HT20): OFDM
Product Type:	<input type="checkbox"/> Mobile <input type="checkbox"/> Portable <input checked="" type="checkbox"/> Fix Location
Test Software of EUT:	RF test (manufacturer declare)
Antenna Type	PCB Antenna
Antenna Gain	0dBi
Power Supply:	AC 120V 50/60Hz
Adapter Information:	/

Note: Please refer to the instruction manual for details.

Operation Frequency each of channel(802.11b/g/n HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

For 802.11b/g/n (HT20):

Channel	Frequency
The Lowest channel	2412MHz
The Middle channel	2437MHz
The Highest channel	2462MHz

Note: Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.3 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.	Remark	FCC certification
/	/	/	/	/

4.4 Test Location

All tests were performed at:

Shenzhen Huaxia Testing Technology Co., Ltd.,

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua New District, Shenzhen, Guangdong, China

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **ISED Registration No.: 22984-1**

The 3m Semi-anechoic chamber of Shenzhen Huaxia Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

• **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.6 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty	Notes
1	Radiated Emission (Below 1GHz)	5.12dB	(1)
2	Radiated Emission (Above 1GHz)	4.60dB	(1)
3	Conducted Disturbance (0.15~30MHz)	3.34dB	(1)
4	Radio Frequency	3×10^{-8}	(1)
5	Duty cycle	0.6 %.	(1)
6	Occupied Bandwidth	1.1%	(1)
7	RF conducted power	0.86dB	(1)
8	RF power density	0.74	(1)
9	Conducted Spurious emissions	0.86dB	(1)
10	Temperature test	0.8°C	(1)
11	Humidity test	2.0%	(1)
12	Supply voltages	0.5 %.	(1)
13	Frequency Error	5.5 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

4.7 Deviation from Standards

None.

4.8 Abnormalities from Standard Conditions

None.

4.9 Other Information Requested by the Customer

None.

4.10 Equipment List


Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2020/10/25	2021/10/24
Spectrum analyzer	R&S	FSU26	CQA-038	2020/10/25	2021/10/24
EXA Spectrum Analyzer	KEYSIGHT	N9010A	CQA-106	2020/9/26	2021/9/25
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2020/10/25	2021/10/24
Loop antenna	Schwarzbeck	FMZB1516	CQA-060	2020/10/21	2021/10/20
Bilog Antenna	R&S	HL562	CQA-011	2020/9/26	2021/9/25
Horn Antenna	R&S	HF906	CQA-012	2020/9/26	2021/9/25
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2020/9/25	2021/9/24
Coaxial Cable (Above 1GHz)	CQA	N/A	C007	2020/9/26	2021/9/25
Coaxial Cable (Below 1GHz)	CQA	N/A	C013	2020/9/26	2021/9/25
Antenna Connector	CQA	RFC-01	CQA-080	2020/9/26	2021/9/25
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2020/9/26	2021/9/25
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2020/9/26	2021/9/25
EMI Test Receiver	R&S	ESR7	CQA-005	2020/10/25	2021/10/24
LISN	R&S	ENV216	CQA-003	2020/10/23	2021/10/22
Coaxial cable	CQA	N/A	CQA-C009	2020/9/26	2021/9/25
DC power	KEYSIGHT	E3631A	CQA-028	2020/9/26	2021/9/25

Note:


The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
<p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p>	
EUT Antenna:	
<p>The antenna is PCB antenna. The best case gain of the antenna is 0dBi.</p>	


5.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207														
Test Method:	ANSI C63.10: 2013														
Test Frequency Range:	150kHz to 30MHz														
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
	Frequency range (MHz)		Limit (dBuV)												
		Quasi-peak	Average												
	0.15-0.5	66 to 56*	56 to 46*												
0.5-5	56	46													
5-30	60	50													
* Decreases with the logarithm of the frequency.															
Test Procedure:	<ol style="list-style-type: none"> 1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement. 														
Test Setup:															
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel.														

Final Test Mode:	All modes of 802.11b/g/n were tested at Low, Middle, and High channel; only the worst result of 802.11b CH11 was reported as below
Test Voltage:	AC120V/60Hz
Test Results:	Pass

Measurement Data

Live Line:




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1780	62.26	-0.13	62.13	64.57	-2.44	peak	
2		0.1780	48.61	-0.13	48.48	54.57	-6.09	AVG	
3		0.2500	57.39	-0.11	57.28	61.75	-4.47	peak	
4		0.2500	46.67	-0.11	46.56	51.75	-5.19	AVG	
5		0.8820	52.96	-0.09	52.87	56.00	-3.13	peak	
6		0.8820	33.61	-0.09	33.52	46.00	-12.48	AVG	
7		0.1780	58.13	-0.13	58.00	64.57	-6.57	QP	

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral Line:

80.0 dBuV




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2500	57.91	-0.11	57.80	61.75	-3.95	peak	
2		0.1780	61.83	-0.13	61.70	64.57	-2.87	peak	
3	*	16.6940	58.96	-0.28	58.68	60.00	-1.32	peak	
4		0.1835	32.34	-0.13	32.21	54.32	-22.11	AVG	
5		0.2980	31.61	-0.01	31.60	50.30	-18.70	AVG	
6		16.6940	51.68	-0.28	51.40	60.00	-8.60	QP	

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

5.3 Conducted Peak & Average Output Power


Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10: 2013
Test Setup:	
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 11Mbps of rate is the worst case of 802.11b; 54Mbps of rate is the worst case of 802.11g; MCS7Mbps of rate is the worst case of 802.11n(HT20); Only the worst case is recorded in the report.
Limit:	30dBm
Test Results:	Pass

WIFI

Type	Test channel	Peak Output Power (dBm)	Average Output Power dBm)	Limit (dBm)	Result
802.11b	Lowest	16.091	11.03	30.00	Pass
	Middle	16.780	10.97		
	Highest	16.938	11.16		
802.11g	Lowest	15.981	10.33	30.00	Pass
	Middle	12.123	8.76		
	Highest	12.932	8.43		
802.11n(HT20)	Lowest	12.971	8.50	30.00	Pass
	Middle	12.153	8.15		
	Highest	12.851	8.36		

Note: 1.The test results including the cable lose.




5.4 6dB Occupy Bandwidth




Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10: 2013
Test Setup:	 <p>Offset=cable loss+ attenuation factor</p>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 11Mbps of rate is the worst case of 802.11b; 54Mbps of rate is the worst case of 802.11g; MCS7Mbps of rate is the worst case of 802.11n(HT20); Only the worst case is recorded in the report.
Limit:	≥ 500 kHz
Test Results:	Pass




Measurement Data

Type	Channel	6dB Bandwidth (MHz)	Limit (KHz)	Result
802.11b	Lowest	8.878	≥500	Pass
	Middle	8.165		
	Highest	8.879		
802.11g	Lowest	16.50	≥500	Pass
	Middle	16.51		
	Highest	16.51		
802.11n(HT20)	L west	17.77	≥500	Pass
	Middle	17.70		
	Highest	17.71		


Test plot as follows:

Graphs_6dB Occupy Bandwidth	
11B/LCH	 <p>Center Freq: 2.41200000 GHz</p> <p>Occupied Bandwidth: 15.108 MHz</p> <p>Total Power: 23.7 dBm</p> <p>Transmit Freq Error: 38.565 kHz</p> <p>x dB Bandwidth: 8.878 MHz</p> <p>% of OBW Power: 99.00 %</p> <p>x dB: -6.00 dB</p>
11B/MCH	 <p>Center Freq: 2.43700000 GHz</p> <p>Occupied Bandwidth: 15.154 MHz</p> <p>Total Power: 24.4 dBm</p> <p>Transmit Freq Error: 27.640 kHz</p> <p>x dB Bandwidth: 8.165 MHz</p> <p>% of OBW Power: 99.00 %</p> <p>x dB: -6.00 dB</p>
11B/HCH	 <p>Center Freq: 2.46200000 GHz</p> <p>Occupied Bandwidth: 15.178 MHz</p> <p>Total Power: 24.4 dBm</p> <p>Transmit Freq Error: -52.869 kHz</p> <p>x dB Bandwidth: 8.879 MHz</p> <p>% of OBW Power: 99.00 %</p> <p>x dB: -6.00 dB</p>

<p>11G/LCH</p>	 <p>Center Freq: 2.41200000 GHz</p> <p>Occupied Bandwidth: 16.575 MHz</p> <p>Total Power: 19.6 dBm</p> <p>Transmit Freq Error: -5.584 kHz</p> <p>x dB Bandwidth: 16.50 MHz</p>	<p>Frequency</p> <p>Center Freq: 2.41200000 GHz</p> <p>CF Step: 4.000000 MHz</p> <p>Freq Offset: 0 Hz</p>
<p>11G/MCH</p>	 <p>Center Freq: 2.43700000 GHz</p> <p>Occupied Bandwidth: 16.505 MHz</p> <p>Total Power: 20.5 dBm</p> <p>Transmit Freq Error: -734 Hz</p> <p>x dB Bandwidth: 16.51 MHz</p>	<p>Frequency</p> <p>Center Freq: 2.43700000 GHz</p> <p>CF Step: 4.000000 MHz</p> <p>Freq Offset: 0 Hz</p>
<p>11G/HCH</p>	 <p>Center Freq: 2.46200000 GHz</p> <p>Occupied Bandwidth: 16.549 MHz</p> <p>Total Power: 20.6 dBm</p> <p>Transmit Freq Error: -17.014 kHz</p> <p>x dB Bandwidth: 16.51 MHz</p>	<p>Frequency</p> <p>Center Freq: 2.46200000 GHz</p> <p>CF Step: 4.000000 MHz</p> <p>Freq Offset: 0 Hz</p>

<p>11N20/LCH</p>	 <p>Center Freq: 2.41200000 GHz</p> <p>Center Freq: 2.412 GHz</p> <p>Occupied Bandwidth: 17.707 MHz</p> <p>Total Power: 19.5 dBm</p> <p>Transmit Freq Error: -25.304 kHz</p> <p>x dB Bandwidth: 17.77 MHz</p>	<p>Frequency</p> <p>Center Freq: 2.41200000 GHz</p> <p>CF Step: 4.000000 MHz</p> <p>Freq Offset: 0 Hz</p>
<p>11N20/MCH</p>	 <p>Center Freq: 2.43700000 GHz</p> <p>Center Freq: 2.437 GHz</p> <p>Occupied Bandwidth: 17.655 MHz</p> <p>Total Power: 20.1 dBm</p> <p>Transmit Freq Error: -6.106 kHz</p> <p>x dB Bandwidth: 17.70 MHz</p>	<p>Frequency</p> <p>Center Freq: 2.43700000 GHz</p> <p>CF Step: 4.000000 MHz</p> <p>Freq Offset: 0 Hz</p>
<p>11N20/HCH</p>	 <p>Center Freq: 2.46200000 GHz</p> <p>Center Freq: 2.462 GHz</p> <p>Occupied Bandwidth: 17.654 MHz</p> <p>Total Power: 20.1 dBm</p> <p>Transmit Freq Error: -11.868 kHz</p> <p>x dB Bandwidth: 17.71 MHz</p>	<p>Frequency</p> <p>Center Freq: 2.46200000 GHz</p> <p>CF Step: 4.000000 MHz</p> <p>Freq Offset: 0 Hz</p>




5.5 Power Spectral Density




Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10: 2013
Test Setup:	 <p>Offset=cable loss+ attenuation factor</p>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 11Mbps of rate is the worst case of 802.11b; 54Mbps of rate is the worst case of 802.11g; MCS7Mbps of rate is the worst case of 802.11n(HT20); Only the worst case is recorded in the report.
Limit:	≤8.00dBm/3kHz
Test Results:	Pass


Measurement Data

Type	Channel	Power Spectral Density (dBm/3KHz)	Limit (dBm/3KHz)	Result
02.11b	Lowest	-6.324	8	Pass
	Middle	-5.651		
	Highest	-5.274		
802.1 g	Lowest	-12.649	8	Pass
	Middle	-12.147		
	Highest	-12.353		
802.11n(HT20)	Lowest	-13.946	8	Pass
	Middle	-13.570		
	Highest	-13.302		


Test plot as follows:

Graphs	
11B/LCH	
11B/MCH	
11B/HCH	


<p>11G/LCH</p>		<p>Frequency</p> <p>Auto Tune</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.399622000 GHz</p> <p>Stop Freq 2.424378000 GHz</p> <p>CF Step 2.475600 MHz Auto Man</p> <p>Freq Offset 0 Hz</p> <p>Scale Type Log Lin</p>
<p>11G/MCH</p>		<p>Frequency</p> <p>Auto Tune</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.424615250 GHz</p> <p>Stop Freq 2.449384750 GHz</p> <p>CF Step 2.476950 MHz Auto Man</p> <p>Freq Offset 0 Hz</p> <p>Scale Type Log Lin</p>
<p>11G/HCH</p>		<p>Frequency</p> <p>Auto Tune</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.449613750 GHz</p> <p>Stop Freq 2.474386250 GHz</p> <p>CF Step 2.477250 MHz Auto Man</p> <p>Freq Offset 0 Hz</p> <p>Scale Type Log Lin</p>

<p>11N20/LCH</p>		<p>Frequency</p> <p>Auto Tune</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.398673250 GHz</p> <p>Stop Freq 2.425326750 GHz</p> <p>CF Step 2.665350 MHz Auto Man</p> <p>Freq Offset 0 Hz</p> <p>Scale Type Log Lin</p>
<p>11N20/MCH</p>		<p>Frequency</p> <p>Auto Tune</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.423723500 GHz</p> <p>Stop Freq 2.450276500 GHz</p> <p>CF Step 2.655300 MHz Auto Man</p> <p>Freq Offset 0 Hz</p> <p>Scale Type Log Lin</p>
<p>11N20/HCH</p>		<p>Frequency</p> <p>Auto Tune</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.448718250 GHz</p> <p>Stop Freq 2.475281750 GHz</p> <p>CF Step 2.656350 MHz Auto Man</p> <p>Freq Offset 0 Hz</p> <p>Scale Type Log Lin</p>

5.6 Band-edge for RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013
Test Setup:	 <p>Offset=cable loss+ attenuation factor</p>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 11Mbps of rate is the worst case of 802.11b; 54Mbps of rate is the worst case of 802.11g; MCS7Mbps of rate is the worst case of 802.11n(HT20); Only the worst case is recorded in the report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass

Test plot as follows:





<p>11G/HCH</p>		<p>Frequency</p> <p>Auto Tune</p> <p>Center Freq 2.46600000 GHz</p> <p>Start Freq 2.43200000 GHz</p> <p>Stop Freq 2.50000000 GHz</p> <p>CF Step 6.800000 MHz</p> <p>Freq Offset 0 Hz</p> <p>Scale Type Log Lin</p>
<p>11N20/LCH</p>		<p>Frequency</p> <p>Auto Tune</p> <p>Center Freq 2.37600000 GHz</p> <p>Start Freq 2.31000000 GHz</p> <p>Stop Freq 2.44200000 GHz</p> <p>CF Step 13.200000 MHz</p> <p>Freq Offset 0 Hz</p> <p>Scale Type Log Lin</p>
<p>11N20/HCH</p>		<p>Frequency</p> <p>Auto Tune</p> <p>Center Freq 2.46600000 GHz</p> <p>Start Freq 2.43200000 GHz</p> <p>Stop Freq 2.50000000 GHz</p> <p>CF Step 6.800000 MHz</p> <p>Freq Offset 0 Hz</p> <p>Scale Type Log Lin</p>

5.7 RF Conducted Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013
Test Setup:	 <p>The diagram illustrates the test setup for RF conducted spurious emissions. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table, which is supported by two vertical legs. Below the table is a Ground Reference Plane, represented by a thick grey bar.</p>
	Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the 11Mbps of rate is the worst case of 802.11b; 54Mbps of rate is the worst case of 802.11g; MCS7Mbps of rate is the worst case of 802.11n(HT20); Only the worst case is recorded in the report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass

Test plot as follows:








11B_HCH_Graphs	
Reference	
30MHz-10GHz	
10GHz-26.5GHz	


11G_LCH_Graphs	
Reference	
30MHz-10GHz	
10GHz-26.5GHz	


11G_MCH_Graphs																			
Reference	<p>Keysight Spectrum Analyzer - Swept SA Center Freq 2.43700000 GHz #Avg Type: RMS AvgHold: 100/100 Mkr1 2.438 255 GHz 1.964 dBm Ref 20.00 dBm Span 40.00 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4.267 ms (8001 pts)</p>																		
30MHz-10GHz	<p>Keysight Spectrum Analyzer - Swept SA Start Freq 30.000000 MHz #Avg Type: RMS AvgHold: 100/100 Mkr1 2.533 5 GHz -38.527 dBm Ref 10.00 dBm Stop 10.000 GHz #Res BW 100 kHz #VBW 300 kHz #Sweep 200.0 ms (20001 pts)</p> <table border="1"> <thead> <tr> <th>MKR</th> <th>MODE</th> <th>TRC</th> <th>SCL</th> <th>X</th> <th>Y</th> <th>FUNCTION</th> <th>FUNCTION WIDTH</th> <th>FUNCTION VALUE</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>1</td> <td>f</td> <td>2.533 5 GHz</td> <td>-38.527 dBm</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.533 5 GHz	-38.527 dBm			
MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE											
1	N	1	f	2.533 5 GHz	-38.527 dBm														
10GHz-26.5GHz	<p>Keysight Spectrum Analyzer - Swept SA Start Freq 10.00000000 GHz #Avg Type: RMS AvgHold: 100/100 Mkr1 24.576 100 GHz -53.163 dBm Ref 10.00 dBm Stop 26.500 GHz #Res BW 100 kHz #VBW 300 kHz #Sweep 200.0 ms (20001 pts)</p> <table border="1"> <thead> <tr> <th>MKR</th> <th>MODE</th> <th>TRC</th> <th>SCL</th> <th>X</th> <th>Y</th> <th>FUNCTION</th> <th>FUNCTION WIDTH</th> <th>FUNCTION VALUE</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>1</td> <td>f</td> <td>24.576 100 GHz</td> <td>-53.163 dBm</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	24.576 100 GHz	-53.163 dBm			
MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE											
1	N	1	f	24.576 100 GHz	-53.163 dBm														

11G_HCH_Graphs																			
Reference	 <p>Keysight Spectrum Analyzer - Swept SA Center Freq 2.46200000 GHz Mkr1 2.455 725 GHz 1.859 dBm Ref 20.00 dBm Span 40.00 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4.267 ms (8001 pts)</p>																		
30MHz-10GHz	 <p>Keysight Spectrum Analyzer - Swept SA Start Freq 30.000000 MHz Mkr1 2.527 0 GHz -29.703 dBm Ref 10.00 dBm Start 0.030 GHz Stop 10.000 GHz #Res BW 100 kHz #VBW 300 kHz #Sweep 200.0 ms (20001 pts)</p> <table border="1"> <thead> <tr> <th>MKR</th> <th>MODE</th> <th>TRC</th> <th>SCL</th> <th>X</th> <th>Y</th> <th>FUNCTION</th> <th>FUNCTION WIDTH</th> <th>FUNCTION VALUE</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>1</td> <td>f</td> <td>2.527 0 GHz</td> <td>-29.703 dBm</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.527 0 GHz	-29.703 dBm			
MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE											
1	N	1	f	2.527 0 GHz	-29.703 dBm														
10GHz-26.5GHz	 <p>Keysight Spectrum Analyzer - Swept SA Start Freq 10.00000000 GHz Mkr1 24.491 125 GHz -52.617 dBm Ref 10.00 dBm Start 10.000 GHz Stop 26.500 GHz #Res BW 100 kHz #VBW 300 kHz #Sweep 200.0 ms (20001 pts)</p> <table border="1"> <thead> <tr> <th>MKR</th> <th>MODE</th> <th>TRC</th> <th>SCL</th> <th>X</th> <th>Y</th> <th>FUNCTION</th> <th>FUNCTION WIDTH</th> <th>FUNCTION VALUE</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>1</td> <td>f</td> <td>24.491 125 GHz</td> <td>-52.617 dBm</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	24.491 125 GHz	-52.617 dBm			
MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE											
1	N	1	f	24.491 125 GHz	-52.617 dBm														

11N20_LCH_Graphs

Reference	
30MHz-10GHz	
10GHz-26.5GHz	





Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

5.8 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
<p>Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.</p>					

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz


Test Procedure:

- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 - 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- Note: For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
 - c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
 - d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for

	<p>the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel ,the middle channel ,the Highest channel</p> <p>h. Repeat above procedures until all frequencies measured was complete.</p>
Exploratory Test Mode:	<p>Transmitting with all kind of modulations, data rates.</p> <p>Transmitting mode, Charge + Transmitting mode.</p>
Final Test Mode:	<p>Pretest the EUT at Transmitting mode and Charge +Transmitting mode, found the Charge +Transmitting mode which it is worse case</p> <p>Through Pre-scan, find the 11Mbps of rate is the worst case of 802.11b; 54Mbps of rate is the worst case of 802.11g; MCS7Mbps of rate is the worst case of 802.11n(HT20);</p> <p>For below 1GHz, through Pre-scan, find the 11Mbps of rate of 802.11b at lowest channel is the worst case.</p> <p>Only the worst case is recorded in the report.</p>
Test Results:	Pass

5.8.1 Radiated emission below 1GHz

30MHz~1GHz		
Test mode:	Charge +Transmitting	Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	30.9619	43.40	-5.71	37.69	40.00	-2.31			peak
2		64.2074	49.07	-18.81	30.26	40.00	-9.74			peak
3		84.7019	52.07	-18.39	33.68	40.00	-6.32			peak
4		166.6514	44.88	-13.34	31.54	43.50	-11.96			peak
5		196.5098	49.57	-13.68	35.89	43.50	-7.61			peak
6		208.5803	46.59	-14.28	32.31	43.50	-11.19			peak

Remark:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

Test mode:	Charge +Transmitting	Horizontal
------------	----------------------	------------



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		31.1798	36.62	-5.88	30.74	40.00	-9.26			peak
2		54.8348	47.33	-19.17	28.16	40.00	-11.84			peak
3	*	84.1100	54.70	-18.45	36.25	40.00	-3.75			peak
4		95.0930	45.68	-16.19	29.49	43.50	-14.01			peak
5		166.6514	45.06	-13.34	31.72	43.50	-11.78			peak
6		207.8501	43.48	-14.18	29.30	43.50	-14.20			peak

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Pre-amplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Pre-amplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

5.8.2 Transmitter emission above 1GHz

Test mode:		802.11b(11Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
4824.000	58.70	-4.26	54.44	74	-19.56	PK	H
4824.000	42.09	-4.26	37.83	54	-16.17	AV	H
7236.000	60.61	1.18	61.79	74	-12.21	PK	H
7236.000	38.73	1.18	39.91	54	-14.09	AV	H
4824.000	58.81	-4.26	54.55	74	-19.45	PK	V
4824.000	41.32	-4.26	37.06	54	-16.94	AV	V
7236.000	61.85	1.18	63.03	74	-10.97	PK	V
7236.000	38.35	1.18	39.53	54	-14.47	AV	V

Test mode:		802.11b(11Mbps)		Test channel:		Middle	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
4874.000	60.84	-4.12	56.72	74	-17.28	PK	H
4874.000	42.03	-4.12	37.91	54	-16.09	AV	H
7311.000	62.35	1.46	63.81	74	-10.19	PK	H
7311.000	39.31	1.46	40.77	54	-13.23	AV	H
4874.000	61.48	-4.12	57.36	74	-16.64	PK	V
4874.000	40.13	-4.12	36.01	54	-17.99	AV	V
7311.000	62.00	1.46	63.46	74	-10.54	PK	V
7311.000	40.90	1.46	42.36	54	-11.64	AV	V

Test mode:		802.11b(11Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
4924.000	60.92	-4.03	56.89	74	-17.11	PK	H
4924.000	42.02	-4.03	37.99	54	-16.01	AV	H
7386.000	60.47	1.66	62.13	74	-11.87	PK	H
7386.000	38.63	1.66	40.29	54	-13.71	AV	H
4924.000	60.31	-4.03	56.28	74	-17.72	PK	V
4924.000	43.03	-4.03	39.00	54	-15.00	AV	V
7386.000	60.20	1.66	61.86	74	-12.14	PK	V
7386.000	39.29	1.66	40.95	54	-13.05	AV	V

Remark:

- 1) The 1Mbps of rate of 802.11b is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Preamplifier Factor}$$
- 3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

5.9 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10 2013		
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value

Test Setup:




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz

Test Procedure:

- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
Note: For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

	<p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel</p> <p>g. Test the EUT in the lowest channel , the Highest channel</p> <p>h. Repeat above procedures until all frequencies measured was complete.</p>
Exploratory Test Mode:	<p>Transmitting with all kind of modulations, data rates.</p> <p>Transmitting mode.</p>
Final Test Mode:	<p>Pretest the EUT at Transmitting mode, found the Transmitting mode which it is worse case</p> <p>Through Pre-scan, find the 11Mbps of rate is the worst case of 802.11b; 54Mbps of rate is the worst case of 802.11g; MCS7Mbps of rate is the worst case of 802.11n(HT20);</p> <p>Only the worst case is recorded in the report.</p>
Test Results:	<p>Pass</p>

Test data:

Worse case mode:		802.11b(11Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
2390.000	57.84	-9.2	48.64	74	-25.36	PK	H
2390.000	36.19	-9.2	26.99	54	-27.01	AV	H
2400.000	58.43	-9.39	49.04	74	-24.96	PK	H
2400.000	37.70	-9.39	28.31	54	-25.69	AV	H
2390.000	58.26	-9.2	49.06	74	-24.94	PK	V
2390.000	36.20	-9.2	27.00	54	-27.00	AV	V
2400.000	58.44	-9.39	49.05	74	-24.95	PK	V
2400.000	36.87	-9.39	27.48	54	-26.52	AV	V

Worse case mode:		802.11b(11Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
2483.500	57.42	-9.29	48.13	74	-25.87	PK	H
2483.500	37.14	-9.29	27.85	54	-26.15	AV	H
2483.500	57.34	-9.29	48.05	74	-25.95	PK	V
2483.500	36.94	-9.29	27.65	54	-26.35	AV	V

Worse case mode:		802.11g(54Mbps)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
2390.000	55.58	-9.2	46.38	74	-27.62	PK	H
2390.000	36.86	-9.2	27.66	54	-26.34	AV	H
2400.000	57.66	-9.39	48.27	74	-25.73	PK	H
2400.000	37.66	-9.39	28.27	54	-25.73	AV	H
2390.000	56.48	-9.2	47.28	74	-26.72	PK	V
2390.000	35.87	-9.2	26.67	54	-27.33	AV	V
2400.000	57.05	-9.39	47.66	74	-26.34	PK	V
2400.000	37.34	-9.39	27.95	54	-26.05	AV	V

Worse case mode:		802.11g(54Mbps)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dB μ V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)		H/V
2483.500	57.23	-9.29	47.94	74	-26.06	PK	H
2483.500	36.63	-9.29	27.34	54	-26.66	AV	H
2483.500	56.96	-9.29	47.67	74	-26.33	PK	V
2483.500	36.00	-9.29	26.71	54	-27.29	AV	V

Worse case mode:		802.11n(HT20)(MCS7)		Test channel:		Lowest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2390.000	55.78	-9.29	46.49	74	-27.51	PK	H
2390.000	36.96	-9.29	27.67	54	-26.33	AV	H
2400.000	57.17	-9.29	47.88	74	-26.12	PK	H
2400.000	37.21	-9.29	27.92	54	-26.08	AV	H
2390.000	58.00	-9.29	48.71	74	-25.29	PK	V
2390.000	35.72	-9.29	26.43	54	-27.57	AV	V
2400.000	57.30	-9.29	48.01	74	-25.99	PK	V
2400.000	35.57	-9.29	26.28	54	-27.72	AV	V

Worse case mode:		802.11n(HT20)(MCS7)		Test channel:		Highest	
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V
2483.500	58.33	-9.29	49.04	74	-24.96	PK	H
2483.500	35.59	-9.29	26.30	54	-27.70	AV	H
2483.500	58.23	-9.29	48.94	74	-25.06	PK	V
2483.500	35.49	-9.29	26.20	54	-27.80	AV	V

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

6 Photographs - EUT Test Setup

6.1 Radiated Emission Test Setup


9KHz~30MHz



30MHz~1GHz:



Above 1GHz:



6.2 Conducted Emission Test Setup

9KHz~30MHz



THE END