

FCC - TEST REPORT

Report Number : **68.910.15.025.01** Date of Issue: April 22, 2016

Model : Koogeek-S1

Product Type : Bluetooth wi-fi smart health scale

Applicant : Shenzhen Belter Health Measurement and Analysis Technology Co., Ltd.

Address : 702, 704, Block C, Tsinghua Unis Science Park, Hi-Tech Industrial Park North, Nanshan

Production Facility : Shenzhen Belter Health Measurement and Analysis Technology Co., Ltd.

Address : 702, 704, Block C, Tsinghua Unis Science Park, Hi-Tech Industrial Park North, Nanshan

Test Result : **Positive** **Negative**

Total pages including Appendices : 23

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval



1 Table of Contents

| | | |
|-----|---|----|
| 1 | Table of Contents | 2 |
| 2 | Details about the Test Laboratory | 3 |
| 3 | Description of the Equipment Under Test | 4 |
| 4 | Summary of Test Standards | 5 |
| 5 | Summary of Test Results | 6 |
| 6 | General Remarks..... | 7 |
| 7 | Test Setups..... | 8 |
| 8 | Systems test configuration | 9 |
| 9 | Technical Requirement | 10 |
| 9.1 | Conducted peak output power..... | 10 |
| 9.2 | Power spectral density..... | 11 |
| 9.3 | 6 dB Bandwidth | 12 |
| 9.4 | Spurious RF conducted emissions..... | 14 |
| 9.5 | Band edge testing | 18 |
| 9.6 | Spurious radiated emissions for transmitter | 20 |
| 10 | Test Equipment List..... | 22 |
| 11 | System Measurement Uncertainty | 23 |

2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12&13, Zhiheng Wisdomland Business Park,
Nantou Checkpoint Road 2,
Nanshan District, 518052,
Shenzhen, P.R.C.

Telephone: 86 755 8828 6998

Fax: 86 755 8828 5299

FCC Registration Number: 502708

3 Description of the Equipment Under Test

| | |
|----------------------------|--|
| Product: | Bluetooth wi-fi smart health scale |
| Model no.: | Koogeek-S1 |
| FCC ID: | 2AAEEE656 |
| Options and accessories: | NIL |
| Rating: | DC6.0V (Supplied by 4xAA batteries) |
| RF Transmission Frequency: | 2402-2480MHz |
| No. of Operated Channel: | 40 |
| Modulation: | GFSK |
| Antenna Type: | PCB |
| Antenna Gain: | 0dBi |
| Description of the EUT: | The Equipment Under Test (EUT) is a scale with BLE and 2.4G wifi function. |

4 Summary of Test Standards

| Test Standards | |
|--|--|
| FCC Part 15 Subpart C 10-1-2015 Edition | PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators |

All the test methods were according to FCC KDB 558074 D01 DTS Meas Guidance and ANSI C63.10-2013.

5 Summary of Test Results

| Technical Requirements | | | | |
|-------------------------------|---|------------|-----------|-------------|
| FCC Part 15 Subpart C | | | | |
| Test Condition | | Pages | Test Site | Test Result |
| §15.207 | Conducted emission AC power port | --- | --- | N/A |
| §15.247(b)(1) | Conducted peak output power | 10 | Site 1 | Pass |
| §15.247(e) | Power spectral density | 11 | Site 1 | Pass |
| §15.247(a)(2) | 6dB bandwidth | 12 | Site 1 | Pass |
| §15.247(a)(1) | 20dB bandwidth and 99% Occupied Bandwidth | --- | --- | N/A |
| §15.247(a)(1) | Carrier frequency separation | --- | --- | N/A |
| §15.247(a)(1)(iii) | Number of hopping frequencies | --- | --- | N/A |
| §15.247(a)(1)(iii) | Dwell Time | --- | --- | N/A |
| §15.247(d) | Spurious RF conducted emissions | 14 | Site 1 | Pass |
| §15.247(d) | Band edge | 18 | Site 1 | Pass |
| §15.247(d) & §15.209 & 15.205 | Spurious radiated emissions for transmitter | 20 | Site 1 | Pass |
| §15.203 | Antenna requirement | See note 2 | | Pass |

Note 1: N/A=Not Applicable.

Note 2: The EUT uses a permanently PCB antenna, which gain is 0dBi. In accordance to §15.203, It is considered sufficiently to comply with the provisions of this section.

6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: 2AAEEE656 complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules.

SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: 15 January, 2016

Testing Start Date: 15 January, 2016

Testing End Date: 15 April, 2016

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch

Reviewed by:

Prepared by:

Tested by:



Phoebe Hu
EMC Project Manager




Felix Li
EMC Project Engineer




Leon Zhang
EMC Test Engineer

7 Test Setups

7.1 Radiated test setups



7.2 Conducted RF test setups



8 Systems test configuration

Auxiliary Equipment Used during Test:

| DESCRIPTION | MANUFACTURER | MODEL NO.(SHIELD) | S/N(LENGTH) |
|-------------|--------------|-------------------|-------------|
| -- | -- | -- | --- |

The system was configured to channel 0, 19, and 39 for the test.

9 Technical Requirement

9.1 Conducted peak output power

Test Method

1. Use the following spectrum analyzer settings:
RBW > the 6 dB bandwidth of the emission being measured, VBW \geq 3RBW, Span \geq 3RBW
Sweep = auto, Detector function = peak, Trace = max hold.
2. Add a correction factor to the display.
3. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

Limits

According to §15.247 (b) (1), conducted peak output power limit as below:

| Frequency Range MHz | Limit W | Limit dBm |
|------------------------|------------|--------------|
| 2400-2483.5 | ≤ 1 | ≤ 30 |

Test Result

| Frequency MHz | Conducted Peak Output Power dBm | Result |
|------------------------|---------------------------------------|--------|
| Low channel 2402MHz | -8.18 | Pass |
| Middle channel 2440MHz | -8.84 | Pass |
| High channel 2480MHz | -9.80 | Pass |

9.2 Power spectral density

Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:

1. Set analyzer center frequency to DTS channel center frequency.
RBW=3kHz,VBW≥3RBW,Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold
2. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
3. Repeat above procedures until other frequencies measured were completed

Limit

Limit [dBm]

≤8

Test Result

| Frequency MHz | Power spectral density | Limit dBm | Result |
|------------------|---------------------------|--------------|--------|
| 2402 | -19.94 | 8 | Pass |
| 2440 | -20.73 | 8 | Pass |
| 2480 | -21.43 | 8 | Pass |

9.3 6 dB Bandwidth

Test Method

1. Use the following spectrum analyzer settings:
RBW=100K, VBW≥3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, may be employed using the X dB bandwidth mode with X set to 6 dB, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.
3. Allow the trace to stabilize, record the X dB Bandwidth value.

Limit


Limit [kHz]

≥500

Test result


| Frequency MHz | 6 dB Bandwidth kHz | Limit kHz | Result |
|------------------|-----------------------|--------------|--------|
| 2402 | 703.3 | 500 | Pass |
| 2440 | 707.7 | 500 | Pass |
| 2480 | 703.3 | 500 | Pass |

6 dB Bandwidth




Date: 19.FEB.2016 14:15:31

6 dB Bandwidth



Date: 19.FEB.2016 14:17:33



Date: 19.FEB.2016 14:18:53

9.4 Spurious RF conducted emissions

Test Method


1. Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
RBW = 100 kHz, VBW ≥ RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
3. The level displayed must comply with the limit specified in this Section. Submit these plots.
4. Repeat above procedures until all frequencies measured were complete.

Limit


| Frequency Range MHz | Limit (dBc) |
|------------------------|-------------|
| 30-25000 | -20 |

Spurious RF conducted emissions

BT4.0 GFSK Modulation:
2402MHz




Date: 19.FEB.2016 14:25:41




Date: 19.FEB.2016 14:23:20

2440MHz




Date: 19.FEB.2016 14:24:01




Date: 19.FEB.2016 14:20:00

2480MHz



Date: 19.FEB.2016 14:21:03



Date: 19.FEB.2016 14:20:00

9.5 Band edge testing

Test Method


- 1 Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 kHz, VBW \geq RBW, Sweep = auto, Detector function = peak, Trace = max hold
- 2 Allow the trace to stabilize, use the peak and delta measurement to record the result.
- 3 The level displayed must comply with the limit specified in this Section. .
- 4 Repeat the test at the hopping off and hopping on mode, submit all the plots.

Limit:


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.

Band edge testing

BT4.0 GFSK Modulation Test Result



Date: 19.FEB.2016 14:27:28



Date: 19.FEB.2016 14:29:06

9.6 Spurious radiated emissions for transmitter

Test Method

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
3. Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured, RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz, VBW \geq RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Follow the guidelines in ANSI C63.4-1992 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc.
The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
5. Set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the duty cycle per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{duty cycle}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Limit

According to part 15.247(d), the radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205, must comply with the radiated emission limits specified in section 15.209.

| Frequency MHz | Field Strength uV/m | Field Strength dB μ V/m | Detector |
|------------------|------------------------|--------------------------------|----------|
| 30-88 | 100 | 40 | QP |
| 88-216 | 150 | 43.5 | QP |
| 216-960 | 200 | 46 | QP |
| 960-1000 | 500 | 54 | QP |
| Above 1000 | 500 | 54 | AV |
| Above 1000 | 5000 | 74 | PK |

Spurious radiated emissions for transmitter

According to ANSI C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

Transmitting spurious emission test result as below:

2402MHz Test Result

| Frequency | Emission Level | Polarization | Limit | Detector | Result |
|-----------|----------------|--------------|--------|----------|--------|
| MHz | dBuV/m | | dBµV/m | | |
| 30-1000 | -- | Horizontal | -- | QP | Pass |
| 30-1000 | -- | Vertical | -- | QP | Pass |
| *4804 | 41.16 | Horizontal | 74 | PK | Pass |
| *4804 | -- | Horizontal | 54 | AV | Pass |
| *4804 | 41.34 | Vertical | 74 | PK | Pass |
| *4804 | -- | Vertical | 54 | AV | Pass |

2440MHz Test Result

| Frequency | Emission Level | Polarization | Limit | Detector | Result |
|-----------|----------------|--------------|--------|----------|--------|
| MHz | dBuV/m | | dBµV/m | | |
| *4880 | 44.45 | Horizontal | 74 | PK | Pass |
| *4880 | -- | Horizontal | 54 | AV | Pass |
| *4880 | 44.56 | Vertical | 74 | PK | Pass |
| *4880 | -- | Vertical | 74 | AV | Pass |

2480MHz Test Result

| Frequency | Emission Level | Polarization | Limit | Detector | Result |
|-----------|----------------|--------------|--------|----------|--------|
| MHz | dBuV/m | | dBµV/m | | |
| *4960 | 45.34 | Horizontal | 74 | PK | Pass |
| *4960 | -- | Horizontal | 54 | AV | Pass |
| *4960 | 45.42 | Vertical | 74 | PK | Pass |
| *4960 | -- | Vertical | 54 | AV | Pass |

Remark:

- (1) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20db below the permissible limits or the field strength is too small to be measured.
- (2) "*" means the emission(s) appear within the restrict bands shall follow the requirement of section 15.205.

10 Test Equipment List

List of Test Instruments

| | DESCRIPTION | MANUFACTURER | MODEL NO. | SERIAL NO. | CAL. DUE DATE |
|----|-------------------------------------|-----------------|------------------|-------------------|---------------|
| C | Signal Generator | Rohde & Schwarz | SMB100A | 108272 | 2016-7-24 |
| RE | Signal Analyzer | Rohde & Schwarz | FSV40 | 101030 | 2016-7-24 |
| | Vector Signal Generator | Rohde & Schwarz | SMU 200A | 105324 | 2016-7-24 |
| | RF Switch Module | Rohde & Schwarz | OSP120/OS P-B157 | 101226/10085 1 | 2016-7-24 |
| | EMI Test Receiver | Rohde & Schwarz | ESR 26 | 101269 | 2016-7-24 |
| | Trilog Super Broadband Test Antenna | Schwarzbeck | VULB 9163 | 707 | 2016-8-14 |
| | Horn Antenna | Rohde & Schwarz | HF907 | 102294 | 2016-7-24 |
| | Pre-amplifier | Rohde & Schwarz | SCU 18 | 102230 | 2016-7-24 |
| | 3m Semi-anechoic chamber | TDK | 9X6X6 | ---- | 2019-5-29 |

C - Conducted RF tests

- Conducted peak output power
- 6dB bandwidth
- 20dB bandwidth and 99% Occupied Bandwidth
- Carrier frequency separation
- Number of hopping frequencies
- Dwell Time
- Power spectral density
- Spurious RF conducted emissions
- Band edge

11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty

| Items | Extended Uncertainty |
|-----------------------------|---|
| Radiated spurious emission | 4.32dB (30MHz-1GHz) 2.27dB (1GHz -25GHz) |
| Conducted spurious emission | 2.10dB(30MHz-25GHz) |
| Bandwidth test | 1×10^{-9} |
| Conducted emission | 2.4dB |