



**BUREAU
VERITAS**

TEST REPORT NUMBER: (8523)156-0342(A)

TEST REPORT

Applicant:	DOUBLEEAGLE INDUSTRY (CHINA) LIMITED	Fax:	---
		E-mail:	---
Address :	XINGDA INDUSTRIAL PARK, CHENGHAI SHANTOU CITY, GUANGDONG PROVINCE, China		
Test Date :	2023-6-15 to 2023-6-27		

Manufacturer or Supplier :	DOUBLEEAGLE INDUSTRY (CHINA) LIMITED
Address :	XINGDA INDUSTRIAL PARK, CHENGHAI SHANTOU CITY, GUANGDONG PROVINCE, China
Sample Description:	Building Blocks
Model number:	C61503W
Additional Model :	---
Rated Voltage:	DC3V (AA*2)
FCC ID :	2AAFASY-C61503W-04

The submitted sample of the above equipment has been tested according to following standard(s)

47 CFR Part 1.1307

47 CFR Part 2.1093

KDB447498D01 General RF Exposure Guidance v06

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Assistant Manager

Name: Nick Lung

Date: JUN 28,2023

Bureau Veritas Shenzhen Co., Ltd

1st Floor, Block A, Minlida Industrial Building, 4th
Zone of Honghualing Industrial Park, Shenzhen,
Guangdong Province, China

Tel: 0755 -86135643
Email: <http://www.bureauveritas.com>



TEST REPORT NUMBER: (8523)156-0342(A)

1 Contents

	Page
TEST REPORT	1
1 CONTENTS	2
2 GENERAL INFORMATION	3
2.1 CLIENT INFORMATION	3
2.2 GENERAL DESCRIPTION OF EUT	3
3 SAR EVALUATION	4
3.1 IC RF EXPOSURE COMPLIANCE REQUIREMENT	4
3.1.1 <i>Standard Requirement</i>	4
3.1.2 <i>Limits</i>	4
3.1.3 <i>EUT RF Exposure</i>	6



TEST REPORT NUMBER: (8523)156-0342(A)

2 General Information

2.1 Client Information

Applicant:	DOUBLEEAGLE INDUSTRY (CHINA) LIMITED
Address of Applicant:	XINGDA INDUSTRIAL PARK, CHENGHAI SHANTOU CITY, GUANGDONG PROVINCE, China
Manufacturer:	DOUBLEEAGLE INDUSTRY (CHINA) LIMITED
Address of Manufacturer:	XINGDA INDUSTRIAL PARK, CHENGHAI SHANTOU CITY, GUANGDONG PROVINCE, China

2.2 General Description of EUT

Name:	Building Blocks
Test Model No.:	C61503W
Trade Mark :	N/A
Software Version:	SY-JV1077-2.4G
Hardware Version:	SY-JV8011T- 2.4G
Frequency Range:	2405-2475MHz
Modulation Type:	GFSK
Number of Channels:	71
Sample Type:	Portable product
Antenna Type:	Wire antenna
Antenna Gain:	0dBi



TEST REPORT NUMBER: (8523)156-0342(A)

3 SAR Evaluation

3.1 IC RF Exposure Compliance Requirement

3.1.1 Standard Requirement

IC:According to RSS-102 Issue 5 March 2015

2.5.1 Exemption Limits for Routine Evaluation – SAR Evaluation

SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1.

FCC:

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

3.1.2 Limits

FCC:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion



TEST REPORT NUMBER: (8523)156-0342(A)

IC:

Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance^{4,5}

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of ≤ 5 mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
≤ 300	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7 mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7 mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of 30 mm	At separation distance of 35 mm	At separation distance of 40 mm	At separation distance of 45 mm	At separation distance of ≥ 50 mm
≤ 300	223 mW	254 mW	284 mW	315 mW	345 mW
450	141 mW	159 mW	177 mW	195 mW	213 mW
835	80 mW	92 mW	105 mW	117 mW	130 mW
1900	99 mW	153 mW	225 mW	316 mW	431 mW
2450	83 mW	123 mW	173 mW	235 mW	309 mW
3500	86 mW	124 mW	170 mW	225 mW	290 mW
5800	56 mW	71 mW	85 mW	97 mW	106 mW

Remakr: If the operating frequency of the device is between two frequencies located in Table 1, linear interpolation shall be applied for the applicable separation distance. For test separation distance less than 5 mm, the exemption limits for a separation distance of 5 mm can be applied to determine if a routine evaluation is required.



TEST REPORT NUMBER: (8523)156-0342(A)

3.1.3 EUT RF Exposure

Measurement Data

The worst case refer to report (8523)156-0342 is below:

Antenna polarization: Horizontal		
Frequency (MHz)	Level (dB μ V/m)	Value
2.405	91.86	Peak

For 2405MHz:

Field strength = 91.86dB μ V/m @3m

Ant. gain 0dBi; so Ant numeric gain=1

So $P_t = \{ [10^{(91.86/20)} / 10^6 \times 3]^2 / 30 / 1 \} \times 1000 \text{mW} = 0.460 \text{mW}$

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g

Calculated value = $0.460 / 5 \cdot \sqrt{2.405} = 0.143 < 3$

So the SAR test is not required.