

Remate controller battery 2 gos of 15 VA A batteries.

Turn On OFF

DEMO Key

Left Trigger

Left Right Trigger

Left/Right Rotation Indicates Pumper Key Indicator

3 Satory Installation

1-Open the overview of basinery case locates in the back of controller, insuring 2 pos of LYAA Abstracts into the battery case and then screen the overfug 2 No.

2 Please screen out the cover at the back of cut by screen driver, input the cover as a few covers and the back of cut by screen driver, input the cover as critical and the back of cut by screen driver, input the cover as a few covers and the back of cut by screen driver, input the cover as a few covers. In the back of cut by screen driver, income the cover as a few covers and the covers and the covers and the back of cut by screen driver, income the covers and the back of cut by screen driver, income the covers and the back of cut by screen driver, income the covers and the back of cut by screen driver, income the covers and the back of cut by screen driver, income the covers and the back of cut by screen driver, income the cut by screen d





Installing the sprinkler head and filling the water tank
Open the colorful box, unpack the blister packing in the upper left corner of the remote control car, take the car out, rotate the fountain, and install the sprinkler bead, Clig 3A3.

To operate the function of spraying, open the water tank and fill it with clean water (in order to avoid damaging the car, the water tank should be empty, when the remote control car is not used or the function of spraying is not performed for a long period). (Fig 3B)





The state of the s

• To press the Horn Key on remove consumers are constrained and the control an







Recharging

Notice Please pash the power switch to "OFF" position if the product will not be used for a long time. Take the batteries out of the remote controller and the track for storing. Please charge the battery for 4 to 5 hours. Shours for initial use.

for nations; Plauce charge the battery for 4 to 3 hours. 8 hours for initial use.

3 Notice

1. Does it play the try on the mod, select a side place for operating to award
diagerous.

2. Plays the lay in water may cause short circuit school progress.

2. Plays the lays for a side of the state of the state of the diagerous.

3. Plause interest of a reaction, I may a divide a state of the state Frequency bands: 2405MHz to 2475MHz Maximum output power: -4.14dBm (for EU compliance)

Manufacturer Doubleeagle Industry (China) Limited.
Adérese: Xingda Industrial Park, Chinaja) Limited.
District, Shantiou City, Guangdong Province, China.
Importer: JAMARA e.K.
Address: Inh. Manuel Nasterer
An Lauerbolh 5 – DE-8817 Alchstetten Germany

An Lauerboll 5 - DE-BIST7 Aichselstein Germany Anna Anna Air Air Seide S

If this equipment does cause harmful interference to radio or television re-ception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

Recrient or relocate the receiving entenns
Increase the separation between the equipment and receiver.
Connect the equipment into an outlet on a circuit different from that to which the reconvirt is connected.
Consult the dealer or an experienced radio/TV technician for help.

Note: changes or modifications not expressly approved by the party re-sponsible for compliance could void the user's authority to operate the equipment.

MODIFICATION: Any changes or modifications not expressly approved by the grantee of this device could void the user's authority to operate the device.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.