



Notes:

1. Material: 詳細材質+表面處理+背膠型式(可移膠 or 永久膠)
(含膠厚度 t=**mm+/-15%)
2. Background:
3. Printing color:
4. Tolerance +/-0.2mm unless otherwise specified.
5. Label gap throughout the entire roll of 3mm.
6. 特殊需求(需符合UL、.....等)
7. 測試規範(依C201文件規範隨鍵盤環測 or 客戶規範、.....等)
8. 判定標準(不可產生起泡、皺褶、翹起、脫膠、溢膠等情形, 如為可移膠需加入"撕下後產品上不可以有殘膠"字樣)
9. 入料方式: 卷裝

003	修改安規	Vicky	10/25 2021
002	ADD WEEE LOGO ADD UL LOGO	Vicky	05/03 2021
001	RELEASE DRAWING	Vicky	04/26 2021
REV	DESCRIPTION	SIGN	DATE

UNITS OR ASSEMBLY	T16U	NAME			SCALE	DIM IN	M.M	STOCK NO.
		LABEL SPEC FOR EU &UK T16U			LIMITS UNLESS OTHERWISE NOTED			
DRN		MATERIAL		1-6	±0.1	300-1000	±0.8	SHEET
DSN		FINISH		6-30	±0.2	1000-2000	±1.2	
CKD				30-100	±0.3	2000-	±2.0	1 OF 1
APPD				100-300	±0.5	ANG	±1/2'	
		達方電子 Darfon Electronics Corp.			ASSEMBLY DR.NO.			
					DRAWING NO.		4E+20001.AKU	