

RF Exposure Report

Report No.: MFBGPU-WTW-P22020418

FCC ID: 2AAFMRLP0001

Test Model: RLP0001

Received Date: 2022/2/16

Test Date: 2022/4/13 ~ 2022/5/19

Issued Date: 2022/5/31

Applicant: CORSAIR MEMORY, Inc.

Address: 115 North McCarthy Blvd, Milpitas, CA 95035, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**FCC Registration /
Designation Number:** 198487 / TW2021

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Evaluation Result	5
2.1 Antenna Gain	6
2.2 Antenna Location	7
3 SAR Test Exclusion Thresholds	8
4 Conclusion	8

Release Control Record

Issue No.	Description	Date Issued
MFBGPU-WTW-P22020418	Original release.	2022/5/31

1 Certificate of Conformity

Product: Laptop

Brand: CORSAIR

Test Model: RLP0001

Sample Status: Engineering sample

Applicant: CORSAIR MEMORY, Inc.

Test Date: 2022/4/13 ~ 2022/5/19

FCC Rule Part: FCC Part 2 (Section 2.1093)

Standards: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :



Date: 2022/5/31

Jessica Cheng / Senior Specialist

Approved by :



Date: 2022/5/31

Jeremy Lin / Project Engineer

2 Evaluation Result

Following FCC KDB 447498 D01 "General SAR test exclusion guidance"

The corresponding SAR Exclusion Threshold condition, listed below:

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot [\sqrt{f(\text{GHz})}]$$
$$\leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$
 - $f(\text{GHz})$ is the RF channel transmit frequency in GHz.
 - Power and distance are rounded to the nearest mW and mm before calculation.
 - The result is rounded to one decimal place for comparison. The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.
- 2) At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following:
 - a) [Threshold at 50 mm in step 1) + (test separation distance - 50mm) · ($f(\text{MHz})/150$)] mW, at 100MHz to 1500 MHz
 - b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · 10] mW at > 1500 MHz and ≤ 6 GHz
- 3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion.
 - a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by $[1 + \log(100/f(\text{MHz}))]$ for test separation distances > 50 mm and < 200 mm.
 - b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$ for test separation distances ≤ 50 mm.
 - c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

2.1 Antenna Gain







The antenna information is listed as below.

FCC ID	Frequency Range (MHz)	Antenna Peak Gain (dBi)	Antenna Type	Antenna Connector
2AAFMRP0001	2402-2478	5.46	Slot	N/A

FCC ID	Frequency Range (MHz)	Antenna Peak Gain (dBi)		Antenna Type	Antenna Connector
		Main	AUX		
2AQ68RLP0003	2400-2483.5	5.13	4.64	PIFA (Slot)	N/A
	5150-5250	2.7	3.36		
	5250-5350	2.7	3.07		
	5470-5725	2.50	1.08		
	5725-5850	2.68	0.42		
	5925-6425	2.18	1.2		
	6425-6525	1.98	0.59		
	6525-6875	2.42	1.72		
	6875-7125	1.48	0.62		

*The above Antenna information refers to the manufacturer's antenna specifications, the laboratory shall not be held responsible.

2.2 Antenna Location

FCC ID: 2AAFMRP0001	FCC ID: 2AQ68RLP0003
	
	
	

3 SAR Test Exclusion Thresholds

The EUT contains WiFi module as below:

Contains WLAN+BT Combo Module
FCC ID: 2AQ68RLP0003

Maximum measured transmitter power:

Function	Frequency (MHz)	Max. Radiated Field Strength (dBuV/m)	Max. Radiated Power (mW)	Min. test separation distance (mm)	SAR test exclusion calculation value ^(NOTE 3)	1-g extremity SAR test exclusion thresholds	Result
GFSK	2402-2478	87.3	0.162	5	0.050	3	Pass

Note:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. The antenna type is Slot antenna with 5.46dBi gain.
3. Calculate SAR test exclusion thresholds from condition "1" formulas.
4. Max. Radiated Power (dBm) = Max. Radiated Field Strength (dBuV/m) - 95.2.
Max. Radiated Power (mW) = $10^{(\text{Max Radiated Power (dBm)}/10)}$.
5. FCC ID: 2AAFMRLP0001 & FCC ID: 2AQ68RLP0003 cannot transmit at same time.

4 Conclusion

Since Source-base time average power is below SAR test exclusion power thresholds, the SAR evaluation is not required.

--- END ---