

# INSTALLATION INSTRUCTIONS

**Title** 

CZ76372\_19\_20131015\_1633\_FRAGPROOF 15OCT13 (ENGLISH)

Model Number(s) and Product Type

John Deere Ag Management Solutions cz76372\_19\_20131015\_1633\_fragproof (15OCT13)

PROOF COPYRIGHT © 2005 DEERE & COMPANY Moline, Illinois All rights reserved.

All rights reserved.
A John Deere ILLUSTRUCTION ® Manual cz76372\_19\_20131015\_1633\_fragproof-19-15OCT13

# T フ つ つ T

T 刀 O O T

# Generation 4 CommandCenter™ Processor

Generation 4 CommandCenter™ software runs on a processor separate from the display. There are two processor options available.

NOTE: Maximum capabilities for each processor are listed. Depending on machine configuration, some functions may not be available.

#### 4600 Processor

- 4 Video Camera Inputs
- 4 USB Inputs
- 2 Display Outputs
- Upgradable for future applications

#### 4600 Processor Wi-Fi Capabilities

The CommandCenter<sup>™</sup> 4600 processor contains a non-enabled wireless (Wi-Fi) transmitter. Hardware is present to enable future functionality.


### FCC Part 15.21 Statement:

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with Industry Canada licence-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

RF Exposure Guidance: This equipment complies with FCC and Industry Canada radiation exposure limits set

CommandCenter is a trademark of Deere & Company



A-4600 Processor

B-4100 Processor

PC15299 —UN—18MAR13

forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 2.5cm between the radiator and persons. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter, except in accordance with FCC and Industry Canada multi-transmitter product procedures.

## 4100 Processor

- 1 Video Camera Input
- 1 USB Input
- 1 Display Output

HC94949,00002A8 -19-15OCT13-1/1

PN=3

フ フ 〇 つ

T 刀 O つ T