



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V05
Report Template Revision Date: 2021-11-03

RF Exposure Evaluation Report

Report No. : CQASZ20220100086E-05
Applicant: Chengdu Vantron Technology Co., Ltd.
Address of Applicant: No.5 GaoPeng Road, Hi-Tech Zone, Chengdu, SiChuan, P.R. China 610045
Equipment Under Test (EUT):
EUT Name: Portable electronic tablet computer
Model No.: IQRemote PG, V MPG
Test Model No.: IQRemote PG
Brand Name: N/A
FCC ID: 2AAGE-IQRTPGV4
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2022-01-14
Date of Test: 2022-01-14 to 2022-06-25
Date of Issue: 2022-9-20
Test Result : **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By: _____

Lewis Zhou

(Lewis Zhou)

Reviewed By: _____

Timo Lei

(Timo Lei)

Approved By: _____

Jack Ai

(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20220100086E-05	Rev.01	Initial report	2022-9-20

Note:

This test report (Ref. No.: CQASZ20220100086E-05)

All test data comes from source test reports (Ref. No.: CQASZ20220100087E-05).

Only on the basis of the original report Change Applicant, Address of Applicant.

The tested samples have not been changed.

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
4 MPE EVALUATION	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1.1 <i>Limits</i>	6
4.1.2 <i>Test Procedure</i>	7
4.1.3 <i>EUT RF Exposure</i>	8

3 General Information

3.1 Client Information

Applicant:	Chengdu Vantron Technology Co., Ltd.
Address of Applicant:	No.5 GaoPeng Road, Hi-Tech Zone, Chengdu, SiChuan, P.R. China 610045
Manufacturer:	Chengdu Vantron Technology Co., Ltd.
Address of Manufacturer:	No.5 GaoPeng Road, Hi-Tech Zone, Chengdu, SiChuan, P.R. China 610045
Factory:	Chengdu Vantron Technology Co., Ltd.
Address of Factory:	No.5 GaoPeng Road, Hi-Tech Zone, Chengdu, SiChuan, P.R. China 610045

3.2 General Description of EUT

Product Name:	Portable electronic tablet computer
Model No.:	IQRemote PG, V MPG
Test Model No.:	IQRemote PG
Trade Mark:	N/A
Software Version:	1.0 FCC
Hardware Version:	Rev 5.1.1
Frequency Range:	PowerG:912.75~919.106MHz Bluetooth: 2402MHz~2480MHz WiFi 802.11 b/g/n: 2412MHz to 2462MHz IEEE 802.11a/n/ac(20M): 5150MHz ~5250 MHz IEEE802.11n/ac(40M): 5150MHz ~5250 MHz IEEE802.11ac(80M): 5150MHz ~5250 MHz IEEE 802.11a/n/ac(20M): 5725MHz ~5850 MHz IEEE802.11n/ac(40M): 5725MHz ~5850 MHz IEEE802.11ac(80M): 5725MHz ~5850 MHz
Modulation Type:	PowerG: GFSK Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK WiFi 802.11 b/g/n: DSSS, OFDM IEEE802.11a/n/ac: OFDM
Sample Type:	<input type="checkbox"/> Mobile <input type="checkbox"/> Portable <input checked="" type="checkbox"/> Fix Location

The product has four wireless functions: BT, 2.4GHz WIFI, 5GHz WIFI, BLE, Power G. All the possible Simultaneous TX & co-location modes have been evaluated, and only the worst case results are presented in this report.

Radio	Non Simultaneous TX & co-location	Possible Simultaneous TX & co-location with
BT:	BLE, 2.4GHz WIFI, 5G WIFI	BT+PowerG
BLE:	BT, 2.4GHz WIFI, 5G WIFI	BLE+Power G
2.4GHz WIFI:	BT, 5G WIFI	2.4G WIFI+PowerG
5GHz WIFI:	BT, 2.4G WIFI	5G WIFI+PowerG
PowerG:	/	2.4G WIFI Or 5G WIFI Or BT Or BLE

4 MPE Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

1. According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2. According to KDB447498D01 General RF Exposure Guidance v06 4.3.1. Standalone SAR test exclusion considerations Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≥ 20 cm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure

$$eirp = pt \times gt = (E \times d)^2 / 30$$

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, $---10^{((dB\mu V/m)/20)/10^6}$,

d = measurement distance in meters (m)---3m,

$$\text{So } pt = (E \times d)^2 / 30 / gt$$

MPE evaluation for single transmission:

Mode	Frequency Range (MHz)	Ant gain		TUNE-UP Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBm)	(numeric)	(dBm)	(mw)			
WiFi	2412-2462	2.67	1.85	15.77	37.757	20	0.012	1.0
	5180-5240	1.02	1.26	17.25	53.088	20	0.013	1.0
	5745-5825	1.02	1.26	16.15	41.21	20	0.010	1.0
BT	2402-2480	2.67	1.85	4.79	3.013	20	0.001	1.0
BLE	2402-2480	2.67	1.85	5.5	3.548	20	0.001	1.0
PowerG	912.755-919.106	2	1.58	13.45	22.13	20	0.007	0.61

MPE evaluation for single transmission:

Note: Wi-Fi&BT&BLE can't transmit simultaneously.

Wi-Fi (2.4G)&Wi-Fi (5G) can't transmit simultaneously.

Wi-Fi&PowerG can transmit simultaneously, MPE evaluation is as below formula.

$PD1/Limit1 + PD2/Limit2 + \dots < 1$, PD (Power Density)

The worst case is as below:

MAX MPE of Wi-Fi(5G)&PowerG

$$= 0.013/1.0 + 0.007/0.61 = 0.024 < 1.0$$

Result: MPE evaluation of single and simultaneous transmission meet the requirement of standard.

*** END OF REPORT***