



**CFR 47 FCC PART 15 SUBPART C**

**TEST REPORT**

*For*

**Tablet**

**MODEL NUMBER: M081**

**REPORT NUMBER: 4790607923-RF-1**

**ISSUE DATE: October 24, 2022**

**FCC ID:2AAGE5081WNC**

*Prepared for*

**Chengdu Vantron Technology Co., Ltd.  
No.5 GaoPeng Road, Hi-Tech Zone, Chengdu, SiChuan, ChengDu, China**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch**

**Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China**

**Tel: +86 769 22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.



Revision History

Rev.	Issue Date	Revisions	Revised By
V0	October 24, 2022	Initial Issue	



### Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC Part 15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	ANSI C63.10-2013, Clause 6.2	FCC Part 15.207	Pass
Conducted Output Power	ANSI C63.10-2013, Clause 11.9.1.3	FCC Part 15.247 (b)(3)	Pass
6dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2013, Clause 11.8.1	FCC Part 15.247 (a)(2)	Pass
Power Spectral Density	ANSI C63.10-2013, Clause 11.10.2	FCC Part 15.247 (e)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2013, Clause 11.11	FCC Part 15.247(d)	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2013, Clause 11.12 & Clause 11.13	FCC Part 15.205/15.209	Pass
Duty Cycle	ANSI C63.10-2013, Clause 11.6	None; for reporting purposes only.	Pass

\*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

\*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C> when <Accuracy Method> decision rule is applied.



## CONTENTS

<b>1. ATTESTATION OF TEST RESULTS</b> .....	<b>6</b>
<b>2. TEST METHODOLOGY</b> .....	<b>7</b>
<b>3. FACILITIES AND ACCREDITATION</b> .....	<b>7</b>
<b>4. CALIBRATION AND UNCERTAINTY</b> .....	<b>8</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i> .....	8
4.2. <i>MEASUREMENT UNCERTAINTY</i> .....	8
<b>5. EQUIPMENT UNDER TEST</b> .....	<b>9</b>
5.1. <i>DESCRIPTION OF EUT</i> .....	9
5.2. <i>CHANNEL LIST</i> .....	9
5.3. <i>MAXIMUM EIRP</i> .....	9
5.4. <i>TEST CHANNEL CONFIGURATION</i> .....	10
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER</i> .....	10
5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i> .....	10
5.7. <i>SUPPORT UNITS FOR SYSTEM TEST</i> .....	11
<b>6. MEASURING EQUIPMENT AND SOFTWARE USED</b> .....	<b>12</b>
<b>7. ANTENNA PORT TEST RESULTS</b> .....	<b>15</b>
7.1. <i>CONDUCTED OUTPUT POWER</i> .....	15
7.2. <i>6DB BANDWIDTH AND 99 % OCCUPIED BANDWIDTH</i> .....	16
7.3. <i>POWER SPECTRAL DENSITY</i> .....	18
7.4. <i>CONDUCTED BAND EDGE AND SPURIOUS EMISSION</i> .....	19
7.5. <i>DUTY CYCLE</i> .....	21
<b>8. RADIATED TEST RESULTS</b> .....	<b>22</b>
8.1. <i>RESTRICTED BANDEDGE</i> .....	30
8.2. <i>SPURIOUS EMISSIONS(1 GHZ~3 GHZ)</i> .....	34
8.3. <i>SPURIOUS EMISSIONS(3 GHZ~18 GHZ)</i> .....	40
8.4. <i>SPURIOUS EMISSIONS(9 KHZ~30 MHZ)</i> .....	52
8.5. <i>SPURIOUS EMISSIONS(18 GHZ~26 GHZ)</i> .....	55
8.6. <i>SPURIOUS EMISSIONS(30 MHZ~1 GHZ)</i> .....	57
<b>9. ANTENNA REQUIREMENTS</b> .....	<b>59</b>
<b>10. AC POWER LINE CONDUCTED EMISSION</b> .....	<b>60</b>
<b>11. TEST DATA</b> .....	<b>63</b>
11.1. <i>APPENDIX A: DTS BANDWIDTH</i> .....	63



11.1.1.	Test Result .....	63
11.1.2.	Test Graphs .....	64
11.2.	<i>APPENDIX B: OCCUPIED CHANNEL BANDWIDTH</i> .....	66
11.2.1.	Test Result .....	66
11.2.2.	Test Graphs .....	67
11.3.	<i>APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER</i> .....	69
11.3.1.	Test Result .....	69
11.4.	<i>APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY</i> .....	70
11.4.1.	Test Result .....	70
11.4.2.	Test Graphs .....	71
11.5.	<i>APPENDIX E: BAND EDGE MEASUREMENTS</i> .....	73
11.5.1.	Test Result .....	73
11.5.2.	Test Graphs .....	74
11.6.	<i>APPENDIX F: CONDUCTED SPURIOUS EMISSION</i> .....	76
11.6.1.	Test Result .....	76
11.6.2.	Test Graphs .....	77
11.7.	<i>APPENDIX G: DUTY CYCLE</i> .....	83
11.7.1.	Test Result .....	83
11.7.2.	Test Graphs .....	84



# 1. ATTESTATION OF TEST RESULTS

## Applicant Information

Company Name: Chengdu Vantron Technology Co., Ltd.  
Address: No.5 GaoPeng Road, Hi-Tech Zone, Chengdu, SiChuan, ChengDu, China

## Manufacturer Information

Company Name: Chengdu Vantron Technology Co., Ltd.  
Address: No.5 GaoPeng Road, Hi-Tech Zone, Chengdu, SiChuan, ChengDu, China

## EUT Information

EUT Name: Tablet  
Model: M081  
Sample Received Date: September 21, 2022  
Sample Status: Normal  
Sample ID: NA  
Date of Tested: September 21, 2022 to October 21, 2022

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	Pass

Prepared By:

Kebo Zhang  
Senior Project Engineer

Checked By:

Denny Huang  
Senior Project Engineer

Approved By:

Stephen Guo  
Operations Manager



## 2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C, KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, CFR 47 FCC Part 15, ANSI C63.10-2013.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>ISED (Company No.: 21320)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p><b>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	---

### Note1:

All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China.

### Note2:

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

### Note3:

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.



## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	





## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

EUT Name	Tablet
Model	M081
Frequency Range:	2402 MHz to 2480 MHz
Type of Modulation:	GFSK(LE 1M, LE 2M)
Normal Test Voltage:	AC 120 V, 60 Hz

### 5.2. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	11	2424	22	2446	33	2468
1	2404	12	2426	23	2448	34	2470
2	2406	13	2428	24	2450	35	2472
3	2408	14	2430	25	2452	36	2474
4	2410	15	2432	26	2454	37	2476
5	2412	16	2434	27	2456	38	2478
6	2414	17	2436	28	2458	39	2480
7	2416	18	2438	29	2460	/	/
8	2418	19	2440	30	2462	/	/
9	2420	20	2442	31	2464	/	/
10	2422	21	2444	32	2468	/	/

### 5.3. MAXIMUM EIRP

Test Mode	Frequency (MHz)	Channel Number	Maximum Peak Output Power (dBm)	Maximum EIRP (dBm)
LE 1M	2402 ~ 2480	0-39[40]	3.23	4.49
LE 2M	2402 ~ 2480	0-39[40]	3.15	4.41

Test Mode	Frequency (MHz)	Channel Number	Maximum AVG Output Power (dBm)	Maximum EIRP (dBm)
LE 1M	2402 ~ 2480	0-39[40]	1.42	2.68
LE 2M	2402 ~ 2480	0-39[40]	-1.16	0.10

#### 5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
LE 1M	CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel)	2402 MHz, 2440 MHz, 2480 MHz
LE 2M	CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel)	2402 MHz, 2440 MHz, 2480 MHz

#### 5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software Version		RF Test Tool		
Modulation Type	Transmit Antenna Number	Test Software setting value		
		CH 0	CH 19	CH 39
GFSK(1Mbps)	1	default	default	default
GFSK(2Mbps)	1	default	default	default

#### 5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2402-2480	FPC Antenna	1.26

Test Mode	Transmit and Receive Mode	Description
LE 1M	<input checked="" type="checkbox"/> 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
LE 2M	<input checked="" type="checkbox"/> 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
Note: 1.BT&WLAN 2.4G, BT & WLAN 5G, WLAN 2.4G & WLAN 5G can't transmit simultaneously. (declared by client)		

Note: The value of the antenna gain was declared by customer.

## 5.7. SUPPORT UNITS FOR SYSTEM TEST

### SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remark
1	Earphone	Apple	/	/

### I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	/	/	1.0	/


### ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
1	AC Adapter	TEKA	TEKA-TC050300US	Input: 100-240V~, 50/60Hz, 0.5A Max Output: DC 5V, 3A

### TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.

### SETUP DIAGRAM FOR TESTS



**6. MEASURING EQUIPMENT AND SOFTWARE USED**

<b>R&amp;S TS 8997 Test System</b>					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	Apr.02,2022	Apr.01,2023
Vector Signal Generator	R&S	SMBV100A	261637	Oct.30, 2021	Oct.29, 2022
Signal Generator	R&S	SMB100A	178553	Oct.30, 2021	Oct.29, 2022
Signal Analyzer	R&S	FSV40	101118	Oct.30, 2021	Oct.29, 2022
<b>Software</b>					
Description	Manufacturer	Name		Version	
For R&S TS 8997 Test System	Rohde & Schwarz	EMC 32		10.60.10	
<b>Tonsend RF Test System</b>					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wideband Radio Communication Tester	R&S	CMW500	155523	Oct.30, 2021	Oct.29, 2022
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Oct.30, 2021	Oct.29, 2022
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Oct.30, 2021	Oct.29, 2022
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Oct.30, 2021	Oct.29, 2022
DC power supply	Keysight	E3642A	MY55159130	Oct.30, 2021	Oct.29, 2022
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Nov.20,2020	Nov.19,2022
<b>Software</b>					
Description	Manufacturer	Name		Version	
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System		2.6.77.0518	



Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Oct.30, 2021	Oct.29, 2022
Two-Line V-Network	R&S	ENV216	101983	Oct.30, 2021	Oct.29, 2022
Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Oct.30, 2021	Oct.29, 2022
Software					
Description			Manufacturer	Name	Version
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Oct.30, 2021	Oct.29, 2022
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130959	Aug.02, 2021	Aug.01, 2024
Preamplifier	HP	8447D	2944A09099	Oct.30, 2021	Oct.29, 2022
EMI Measurement Receiver	R&S	ESR26	101377	Oct.30, 2021	Oct.29, 2022
Horn Antenna	TDK	HRN-0118	130940	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Oct.30, 2021	Oct.29, 2022
Horn Antenna	Schwarzbeck	BBHA9170	697	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-2	TRS-307-00003	Oct.31, 2021	Oct.30, 2022
Preamplifier	TDK	PA-02-3	TRS-308-00002	Oct.31, 2021	Oct.30, 2022
Loop antenna	Schwarzbeck	1519B	00008	Dec.14, 2021	Dec.13, 2024
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Oct.31, 2021	Oct.30, 2022
Preamplifier	Mini-Circuits	ZX60-83LN-S+	SUP01201941	Oct.31, 2021	Oct.30, 2022
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Oct.31, 2021	Oct.30, 2022
Highpass Filter	Wainwright	WHKX10-5850-6500-1800-40SS	4	Oct.31, 2021	Oct.30, 2022
Band Reject Filter	Wainwright	WRCJV12-5695-5725-5850-5880-40SS	4	Oct.31, 2021	Oct.30, 2022
Band Reject Filter	Wainwright	WRCJV20-5120-5150-	2	Oct.31, 2021	Oct.30, 2022



		5350-5380-60SS			
Band Reject Filter	Wainwright	WRCJV20-5440-5470-5725-5755-60SS	1	Oct.31, 2021	Oct.30, 2022
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Oct.31, 2021	Oct.30, 2022
Band Reject Filter	Wainwright	WRCD5-1879-1879.85-1880.15-1881-40SS	1	Oct.31, 2021	Oct.30, 2022
Notch Filter	Wainwright	WHJ10-882-980-7000-40SS	1	Oct.31, 2021	Oct.30, 2022
<b>Software</b>					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1

<b>Other Instrument</b>					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Temperature humidity probe	OMEGA	ITHX-SD-5	18470007	Nov. 4, 2021	Nov. 3, 2022
Barometer	Yiyi	Baro	N/A	Nov. 15, 2021	Nov. 14, 2022
Attenuator	Agilent	8495B	2814a12853	Oct.31, 2021	Oct.30, 2022

## 7. ANTENNA PORT TEST RESULTS

### 7.1. CONDUCTED OUTPUT POWER

#### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3)	Peak/AVG Conduct Output Power	1 watt or 30 dBm	2400-2483.5

#### TEST PROCEDURE

For Peak Power:

Refer to ANSI C63.10-2013 clause 11.9.1.3.

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

For AVG Power:


Refer to ANSI C63.10-2013 clause 11.9.2.3.1.

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the average output power, after any corrections for external attenuators and cables.

The test result in dBm by adding  $[10 \log (1 / D)]$ , where D is the duty cycle.

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	25°C	Relative Humidity	50%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V 60Hz

#### TEST RESULTS

Please refer to section "Test Data" - Appendix C

## 7.2. 6DB BANDWIDTH AND 99 % OCCUPIED BANDWIDTH

### LIMITS

CFR 47FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2)	6 dB Bandwidth	$\geq 500$ kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	None; for reporting purposes only.	2400-2483.5

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.


Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: $\geq 3 \times$ RBW For 99 % Occupied Bandwidth: $\geq 3 \times$ RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### TEST SETUP







**TEST ENVIRONMENT**

Temperature	25°C	Relative Humidity	50%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V 60Hz

**TEST RESULTS**

Please refer to section "Test Data" - Appendix A&B

### 7.3. POWER SPECTRAL DENSITY

#### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

#### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.


Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	PEAK
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	25°C	Relative Humidity	50%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

#### TEST RESULTS

Please refer to section "Test Data" - Appendix D

## 7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d)	Conducted Bandedge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyser and use the following settings for reference level measurement:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.


Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.



**TEST SETUP**



**TEST ENVIRONMENT**

Temperature	25°C	Relative Humidity	50%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

**TEST RESULTS**

Please refer to section "Test Data" - Appendix E&F

## 7.5. DUTY CYCLE


### LIMITS

None; for reporting purposes only.

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

### TEST SETUP



### TEST ENVIRONMENT

Temperature	25°C	Relative Humidity	50%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

### TEST RESULTS

Please refer to section "Test Data" - Appendix G



## 8. RADIATED TEST RESULTS

### LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup>Above 38.6c

## **TEST PROCEDURE**

Below 30 MHz

The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made

to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of  $377\Omega$ . For example, the measurement frequency X KHz resulted in a level of Y dBuV/m, which is equivalent to  $Y-51.5 = Z$  dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1G

The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold


1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.





2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.5.ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

For Band edge note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Horizontal and Vertical have been tested, only the worst data was recorded in the report.
8. All modes and channels have been tested, only the worst data was recorded in the report.

For Radiate Spurious emission 1GHz-3GHz note:

- Note:
1. Measurement = Reading Level + Correct Factor.
  2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
  3. Peak: Peak detector.
  4. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.
  5. For the transmitting duration, please refer to clause 7.5.
  6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
  7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
  8. All modes and channels have been tested, only the worst data was recorded in the report.

For Radiate Spurious emission 3GHz-18GHz note:

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. AVG:  $VBW=1/Ton$ , where: Ton is the transmitting duration.

5. For the transmitting duration, please refer to clause 7.5.

6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

For Radiate Spurious emission 9kHz-30MHz note:

1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

4. All modes and channels have been tested, only the worst data was recorded in the report.

For Radiate Spurious emission 18GHz-26GHz note:

1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. All modes and channels have been tested, only the worst data was recorded in the report.

For Radiate Spurious emission 30MHz-1GHz note:


1. Result Level = Read Level + Correct Factor.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.


3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

4. All modes and channels have been tested, only the worst data was recorded in the report.


**TEST SETUP**



Below 1 GHz and above 30 MHz



Above 1 GHz





**TEST ENVIRONMENT**


Temperature	25.3°C	Relative Humidity	61%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

**TEST RESULTS**



### 8.1. RESTRICTED BANDEDGE


Test Mode:	BLE 1M PK	Channel:	2402
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	13.28	32.16	45.44	74.00	-28.56	peak




Test Mode:	BLE 1M PK	Channel:	2480
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	15.78	32.44	48.22	74.00	-25.78	peak



Test Mode:	BLE 2M PK	Channel:	2402
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	13.32	32.16	45.48	74.00	-28.52	peak





Test Mode:	BLE 2M PK	Channel:	2480
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	16.66	32.44	49.10	74.00	-24.90	peak



### 8.2. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)


Test Mode:	BLE 1M	Channel:	2402
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1188.000	66.37	-14.16	52.21	74.00	-21.79	peak
2	1440.000	48.54	-12.98	35.56	74.00	-38.44	peak
3	1588.000	51.04	-12.42	38.62	74.00	-35.38	peak
4	1976.000	69.38	-11.14	58.24	74.00	-15.76	peak
5	1976.000	60.26	-11.14	49.12	54.00	-4.88	AVG
6	2376.000	48.79	-9.13	39.66	74.00	-34.34	peak
7	2770.000	45.81	-7.67	38.14	74.00	-35.86	peak




Test Mode:	BLE 1M	Channel:	2402
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1188.000	64.28	-14.16	50.12	74.00	-23.88	peak
2	1490.000	52.13	-12.75	39.38	74.00	-34.62	peak
3	1588.000	51.31	-12.42	38.89	74.00	-35.11	peak
4	1980.000	69.65	-11.13	58.52	74.00	-15.48	peak
5	1980.000	61.35	-11.13	50.22	54.00	-3.78	AVG
6	2372.000	50.35	-9.15	41.20	74.00	-32.80	peak
7	2766.000	46.09	-7.68	38.41	74.00	-35.59	peak




Test Mode:	BLE 1M	Channel:	2440
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1188.000	63.74	-14.16	49.58	74.00	-24.42	peak
2	1594.000	52.96	-12.40	40.56	74.00	-33.44	peak
3	1978.000	68.63	-11.13	57.50	74.00	-16.50	peak
4	1978.000	60.94	-11.13	49.81	54.00	-4.19	AVG
5	2100.000	48.57	-10.55	38.02	74.00	-35.98	peak
6	2372.000	48.13	-9.15	38.98	74.00	-35.02	peak
7	2774.000	44.58	-7.67	36.91	74.00	-37.09	peak




Test Mode:	BLE 1M	Channel:	2440
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1186.000	64.81	-14.17	50.64	74.00	-23.36	peak
2	1588.000	51.47	-12.42	39.05	74.00	-34.95	peak
3	1838.000	51.76	-11.60	40.16	74.00	-33.84	peak
4	1976.000	69.93	-11.14	58.79	74.00	-15.21	peak
5	1976.000	61.86	-11.14	50.72	54.00	-3.28	AVG
6	2376.000	49.57	-9.13	40.44	74.00	-33.56	peak
7	2772.000	46.05	-7.67	38.38	74.00	-35.62	peak




Test Mode:	BLE 1M	Channel:	2480
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1188.000	64.48	-14.16	50.32	74.00	-23.68	peak
2	1414.000	62.38	-13.11	49.27	74.00	-24.73	peak
3	1588.000	51.55	-12.42	39.13	74.00	-34.87	peak
4	1976.000	69.33	-11.14	58.19	74.00	-15.81	peak
5	1976.000	62.35	-11.14	51.21	54.00	-2.79	AVG
6	2378.000	47.45	-9.12	38.33	74.00	-35.67	peak
7	2772.000	46.59	-7.67	38.92	74.00	-35.08	peak



Test Mode:	BLE 1M	Channel:	2480
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1188.000	57.33	-14.16	43.17	74.00	-30.83	peak
2	1432.000	54.08	-13.02	41.06	74.00	-32.94	peak
3	1586.000	50.36	-12.42	37.94	74.00	-36.06	peak
4	1980.000	60.55	-11.13	49.42	74.00	-24.58	peak
5	2384.000	44.51	-9.08	35.43	74.00	-38.57	peak
6	2776.000	46.17	-7.66	38.51	74.00	-35.49	peak



### 8.3. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)

Test Mode:	BLE 1M	Channel:	2402
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	46.60	-0.31	46.29	74.00	-27.71	peak
2	7890.000	38.13	6.31	44.44	74.00	-29.56	peak
3	10230.000	35.53	12.46	47.99	74.00	-26.01	peak
4	12300.000	33.05	17.74	50.79	74.00	-23.21	peak
5	13920.000	30.97	21.79	52.76	74.00	-21.24	peak
6	16545.000	32.49	18.88	51.37	74.00	-22.63	peak






Test Mode:	BLE 1M	Channel:	2402
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	41.07	-0.31	40.76	74.00	-33.24	peak
2	7200.000	37.78	6.55	44.33	74.00	-29.67	peak
3	9150.000	36.95	10.54	47.49	74.00	-26.51	peak
4	11685.000	33.47	17.10	50.57	74.00	-23.43	peak
5	13560.000	31.99	21.04	53.03	74.00	-20.97	peak
6	17010.000	29.33	20.93	50.26	74.00	-23.74	peak




Test Mode:	BLE 1M	Channel:	2440
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	43.88	-0.03	43.85	74.00	-30.15	peak
2	7590.000	37.48	6.32	43.80	74.00	-30.20	peak
3	8940.000	38.38	10.04	48.42	74.00	-25.58	peak
4	11955.000	32.19	17.83	50.02	74.00	-23.98	peak
5	13995.000	30.22	21.95	52.17	74.00	-21.83	peak
6	17055.000	28.30	21.08	49.38	74.00	-24.62	peak




Test Mode:	BLE 1M	Channel:	2440
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	41.94	-0.03	41.91	74.00	-32.09	peak
2	7320.000	38.34	6.46	44.80	74.00	-29.20	peak
3	9075.000	37.02	10.52	47.54	74.00	-26.46	peak
4	11700.000	34.13	17.14	51.27	74.00	-22.73	peak
5	13590.000	31.03	21.09	52.12	74.00	-21.88	peak
6	17385.000	26.95	22.31	49.26	74.00	-24.74	peak




Test Mode:	BLE 1M	Channel:	2480
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3480.000	44.42	-4.97	39.45	74.00	-34.55	peak
2	5655.000	39.36	1.29	40.65	74.00	-33.35	peak
3	9135.000	37.02	10.55	47.57	74.00	-26.43	peak
4	11865.000	32.00	17.59	49.59	74.00	-24.41	peak
5	14085.000	29.83	21.61	51.44	74.00	-22.56	peak
6	17715.000	26.65	24.00	50.65	74.00	-23.35	peak




Test Mode:	BLE 1M	Channel:	2480
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4275.000	42.08	-2.52	39.56	74.00	-34.44	peak
2	5955.000	38.34	2.13	40.47	74.00	-33.53	peak
3	9345.000	37.17	10.63	47.80	74.00	-26.20	peak
4	11355.000	35.33	16.06	51.39	74.00	-22.61	peak
5	13590.000	31.38	21.09	52.47	74.00	-21.53	peak
6	17655.000	28.22	23.64	51.86	74.00	-22.14	peak




Test Mode:	BLE 2M	Channel:	2402
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4665.000	40.63	-0.83	39.80	74.00	-34.20	peak
2	7500.000	37.11	6.33	43.44	74.00	-30.56	peak
3	9195.000	37.01	10.56	47.57	74.00	-26.43	peak
4	11700.000	32.88	17.14	50.02	74.00	-23.98	peak
5	13980.000	30.27	21.92	52.19	74.00	-21.81	peak
6	17700.000	27.83	23.91	51.74	74.00	-22.26	peak




Test Mode:	BLE 2M	Channel:	2402
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5970.000	38.18	2.17	40.35	74.00	-33.65	peak
2	7485.000	37.38	6.34	43.72	74.00	-30.28	peak
3	9255.000	37.31	10.59	47.90	74.00	-26.10	peak
4	11820.000	33.18	17.47	50.65	74.00	-23.35	peak
5	13935.000	29.95	21.82	51.77	74.00	-22.23	peak
6	17760.000	25.78	24.27	50.05	74.00	-23.95	peak



Test Mode:	BLE 2M	Channel:	2440
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	43.86	-0.03	43.83	74.00	-30.17	peak
2	8025.000	39.04	6.34	45.38	74.00	-28.62	peak
3	9150.000	37.54	10.54	48.08	74.00	-25.92	peak
4	11835.000	34.08	17.51	51.59	74.00	-22.41	peak
5	13560.000	29.61	21.04	50.65	74.00	-23.35	peak
6	17490.000	26.90	22.69	49.59	74.00	-24.41	peak






Test Mode:	BLE 2M	Channel:	2440
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4665.000	40.80	-0.83	39.97	74.00	-34.03	peak
2	7860.000	38.95	6.32	45.27	74.00	-28.73	peak
3	9375.000	37.41	10.64	48.05	74.00	-25.95	peak
4	11610.000	33.59	16.90	50.49	74.00	-23.51	peak
5	13935.000	29.92	21.82	51.74	74.00	-22.26	peak
6	17625.000	27.29	23.47	50.76	74.00	-23.24	peak




Test Mode:	BLE 2M	Channel:	2480
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4860.000	40.46	-0.09	40.37	74.00	-33.63	peak
2	7890.000	38.62	6.31	44.93	74.00	-29.07	peak
3	9075.000	36.88	10.52	47.40	74.00	-26.60	peak
4	11880.000	33.59	17.63	51.22	74.00	-22.78	peak
5	13785.000	31.31	21.51	52.82	74.00	-21.18	peak
6	17310.000	27.70	22.03	49.73	74.00	-24.27	peak



Test Mode:	BLE 2M	Channel:	2480
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4755.000	40.75	-0.48	40.27	74.00	-33.73	peak
2	7845.000	38.03	6.32	44.35	74.00	-29.65	peak
3	8940.000	37.84	10.04	47.88	74.00	-26.12	peak
4	11835.000	32.41	17.51	49.92	74.00	-24.08	peak
5	13995.000	29.65	21.95	51.60	74.00	-22.40	peak
6	17715.000	26.66	24.00	50.66	74.00	-23.34	peak



### 8.4. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)


Test Mode:	BLE 1M	Channel:	2402
Polarity:	FACE ON TO THE EUT	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0100	76.22	-101.40	-25.18	47.60	-72.78	peak
2	0.0131	72.97	-101.38	-28.41	45.25	-73.66	peak
3	0.0181	70.85	-101.36	-30.51	42.45	-72.96	peak
4	0.0279	68.17	-101.38	-33.21	38.69	-71.90	peak
5	0.0675	62.64	-101.56	-38.92	31.02	-69.94	peak
6	0.1174	61.83	-101.74	-39.91	26.21	-66.12	peak




Test Mode:	BLE 1M	Channel:	2402
Polarity:	FACE ON TO THE EUT	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1567	74.95	-101.65	-26.70	23.70	-50.40	peak
2	0.1621	74.42	-101.65	-27.23	23.41	-50.64	peak
3	0.1794	73.27	-101.68	-28.41	22.53	-50.94	peak
4	0.2472	65.95	-101.80	-35.85	19.74	-55.59	peak
5	0.3382	62.23	-101.90	-39.67	17.02	-56.69	peak
6	0.3800	60.52	-101.94	-41.42	16.01	-57.43	peak



Test Mode:	BLE 1M	Channel:	2402
Polarity:	FACE ON TO THE EUT	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.5917	63.24	-62.08	1.16	32.16	-31.00	peak
2	1.5564	58.18	-62.02	-3.84	23.76	-27.60	peak
3	2.0539	56.70	-61.81	-5.11	29.54	-34.65	peak
4	5.5952	55.55	-61.41	-5.86	29.54	-35.40	peak
5	10.7299	55.48	-60.83	-5.35	29.54	-34.89	peak
6	18.2545	55.93	-60.90	-4.97	29.54	-34.51	peak



### 8.5. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)


Test Mode:	BLE 1M	Channel:	2402
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18232.000	50.25	-5.54	44.71	74.00	-29.29	peak
2	19392.000	50.12	-5.57	44.55	74.00	-29.45	peak
3	20016.000	49.56	-5.47	44.09	74.00	-29.91	peak
4	21600.000	49.02	-4.54	44.48	74.00	-29.52	peak
5	24208.000	46.71	-2.81	43.90	74.00	-30.10	peak
6	25000.000	46.36	-2.10	44.26	74.00	-29.74	peak



Test Mode:	BLE 1M	Channel:	2402
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18576.000	49.79	-5.30	44.49	74.00	-29.51	peak
2	19984.000	49.71	-5.44	44.27	74.00	-29.73	peak
3	22328.000	48.20	-4.11	44.09	74.00	-29.91	peak
4	23088.000	50.02	-3.41	46.61	74.00	-27.39	peak
5	24568.000	48.10	-2.33	45.77	74.00	-28.23	peak
6	25728.000	46.11	-0.72	45.39	74.00	-28.61	peak





### 8.6. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)


Test Mode:	BLE 1M	Channel:	2402
Polarity:	Horizontal	Test Voltage:	AC120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.0000	36.85	-18.94	17.91	40.00	-22.09	QP
2	67.8300	44.99	-20.55	24.44	40.00	-15.56	QP
3	263.7700	39.44	-18.25	21.19	46.00	-24.81	QP
4	395.6900	53.94	-13.41	40.53	46.00	-5.47	QP
5	667.2900	48.20	-8.65	39.55	46.00	-6.45	QP
6	792.4200	45.47	-7.37	38.10	46.00	-7.90	QP



Test Mode:	BLE 1M	Channel:	2402
Polarity:	Vertical	Test Voltage:	AC120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	66.8600	45.46	-20.56	24.90	40.00	-15.10	QP
2	106.6300	40.28	-20.65	19.63	43.50	-23.87	QP
3	216.2400	35.68	-17.84	17.84	46.00	-28.16	QP
4	263.7700	39.02	-18.25	20.77	46.00	-25.23	QP
5	395.6900	53.86	-13.41	40.45	46.00	-5.55	QP
6	660.5000	43.75	-8.68	35.07	46.00	-10.93	QP



## 9. ANTENNA REQUIREMENTS

### APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### RESULTS

Complies

## 10. AC POWER LINE CONDUCTED EMISSION

### LIMITS

Please refer to CFR 47 FCC §15.207 (a) .


FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

### TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

### TEST SETUP




### TEST ENVIRONMENT

Temperature	24.2°C	Relative Humidity	59.4%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

**TEST RESULTS**

Test Mode:	BLE 1M	Channel:	2402
Line:	Line	Test Voltage:	AC120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1539	41.34	9.59	50.93	65.79	-14.86	QP
2	0.1539	16.74	9.59	26.33	55.79	-29.46	AVG
3	0.1695	40.65	9.59	50.24	64.98	-14.74	QP
4	0.1695	14.37	9.59	23.96	54.98	-31.02	AVG
5	0.1934	39.12	9.59	48.71	63.89	-15.18	QP
6	0.1934	11.66	9.59	21.25	53.89	-32.64	AVG
7	0.2669	33.47	9.52	42.99	61.21	-18.22	QP
8	0.2669	14.02	9.52	23.54	51.21	-27.67	AVG
9	0.9786	15.73	9.61	25.34	56.00	-30.66	QP
10	0.9786	8.45	9.61	18.06	46.00	-27.94	AVG
11	6.9920	29.97	9.63	39.60	60.00	-20.40	QP
12	6.9920	19.89	9.63	29.52	50.00	-20.48	AVG


Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.



Test Mode:	BLE 1M	Channel:	2402
Line:	Neutral	Test Voltage:	AC120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1520	42.96	9.49	52.45	65.89	-13.44	QP
2	0.1520	17.81	9.49	27.30	55.89	-28.59	AVG
3	0.1916	37.97	9.57	47.54	63.97	-16.43	QP
4	0.1916	17.45	9.57	27.02	53.97	-26.95	AVG
5	0.2091	37.37	9.59	46.96	63.24	-16.28	QP
6	0.2091	12.90	9.59	22.49	53.24	-30.75	AVG
7	0.3462	28.45	9.54	37.99	59.05	-21.06	QP
8	0.3462	2.66	9.54	12.20	49.05	-36.85	AVG
9	0.4582	21.67	9.51	31.18	56.73	-25.55	QP
10	0.4582	6.15	9.51	15.66	46.73	-31.07	AVG
11	7.0554	29.46	9.04	38.50	60.00	-21.50	QP
12	7.0554	20.92	9.04	29.96	50.00	-20.04	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.




## 11. TEST DATA

### 11.1. APPENDIX A: DTS BANDWIDTH


#### 11.1.1. Test Result

Test Mode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.72	2401.66	2402.38	0.5	PASS
		2440	0.72	2439.66	2440.38	0.5	PASS
		2480	0.72	2479.66	2480.39	0.5	PASS
BLE_2M	Ant1	2402	1.10	2401.47	2402.57	0.5	PASS
		2440	1.10	2439.48	2440.58	0.5	PASS
		2480	1.10	2479.48	2480.58	0.5	PASS


### 11.1.2. Test Graphs








BLE\_2M\_Ant1\_2402



BLE\_2M\_Ant1\_2440



BLE\_2M\_Ant1\_2480





## 11.2. APPENDIX B: OCCUPIED CHANNEL BANDWIDTH

### 11.2.1. Test Result

Test Mode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Verdict
BLE_1M	Ant1	2402	1.063	2401.4965	2402.5594	PASS
		2440	1.063	2439.5005	2440.5634	PASS
		2480	1.063	2479.5045	2480.5674	PASS
BLE_2M	Ant1	2402	2.07	2400.9970	2403.0669	PASS
		2440	2.07	2439.0010	2441.0709	PASS
		2480	2.07	2479.0050	2481.0749	PASS

### 11.2.2. Test Graphs





**BLE\_2M\_Ant1\_2480**



### 11.3. APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER

#### 11.3.1. Test Result

Test Mode	Antenna	Channel	PEAK Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	1.42	≤30	PASS
		2440	2.46	≤30	PASS
		2480	3.23	≤30	PASS
BLE_2M	Ant1	2402	1.31	≤30	PASS
		2440	2.38	≤30	PASS
		2480	3.15	≤30	PASS

Test Mode	Antenna	Channel	AVG Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	-0.4	≤30	PASS
		2440	0.77	≤30	PASS
		2480	1.42	≤30	PASS
BLE_2M	Ant1	2402	-3.1	≤30	PASS
		2440	-2.08	≤30	PASS
		2480	-1.16	≤30	PASS

Note: 1. Conducted Power=Meas. Level+ Correction Factor

2. The Duty Cycle Factor (refer to section 7.5) had already compensated to the test data in AVG Result.





## 11.4. APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY

### 11.4.1. Test Result


Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-13.10	≤8.00	PASS
		2440	-12.03	≤8.00	PASS
		2480	-11.35	≤8.00	PASS
BLE_2M	Ant1	2402	-16.02	≤8.00	PASS
		2440	-14.89	≤8.00	PASS
		2480	-14.37	≤8.00	PASS

### 11.4.2. Test Graphs






BLE\_2M\_Ant1\_2402



BLE\_2M\_Ant1\_2440



BLE\_2M\_Ant1\_2480







## 11.5. APPENDIX E: BAND EDGE MEASUREMENTS

### 11.5.1. Test Result

Test Mode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	0.47	-46.77	≤-19.53	PASS
		High	2480	2.31	-44.88	≤-17.69	PASS
BLE_2M	Ant1	Low	2402	0.36	-32.19	≤-19.64	PASS
		High	2480	2.24	-45.3	≤-17.76	PASS

### 11.5.2. Test Graphs









## 11.6. APPENDIX F: CONDUCTED SPURIOUS EMISSION

### 11.6.1. Test Result


Test Mode	Antenna	Channel	FreqRange [MHz]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	Reference	0.42	---	PASS
			30~1000	-54.88	$\leq -19.58$	PASS
			1000~26500	-49.89	$\leq -19.58$	PASS
		2440	Reference	1.60	---	PASS
			30~1000	-55.13	$\leq -18.4$	PASS
			1000~26500	-49.08	$\leq -18.4$	PASS
		2480	Reference	2.28	---	PASS
			30~1000	-54.84	$\leq -17.72$	PASS
			1000~26500	-49.96	$\leq -17.72$	PASS
BLE_2M	Ant1	2402	Reference	0.33	---	PASS
			30~1000	-55.26	$\leq -19.67$	PASS
			1000~26500	-50.12	$\leq -19.67$	PASS
		2440	Reference	1.51	---	PASS
			30~1000	-55.59	$\leq -18.49$	PASS
			1000~26500	-49.41	$\leq -18.49$	PASS
		2480	Reference	2.21	---	PASS
			30~1000	-55.12	$\leq -17.79$	PASS
			1000~26500	-50.52	$\leq -17.79$	PASS

### 11.6.2. Test Graphs







BLE\_1M\_Ant1\_2440\_0~Reference




BLE\_1M\_Ant1\_2440\_30~1000




BLE\_1M\_Ant1\_2440\_1000~26500




BLE\_1M\_Ant1\_2480\_0~Reference




BLE\_1M\_Ant1\_2480\_30~1000




BLE\_1M\_Ant1\_2480\_1000~26500



BLE\_2M\_Ant1\_2402\_0~Reference




BLE\_2M\_Ant1\_2402\_30~1000




BLE\_2M\_Ant1\_2402\_1000~26500






BLE\_2M\_Ant1\_2440\_0~Reference




BLE\_2M\_Ant1\_2440\_30~1000




BLE\_2M\_Ant1\_2440\_1000~26500



BLE\_2M\_Ant1\_2480\_0~Reference



BLE\_2M\_Ant1\_2480\_30~1000



BLE\_2M\_Ant1\_2480\_1000~26500



## 11.7. APPENDIX G: DUTY CYCLE

### 11.7.1. Test Result

Test Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
BLE_1M	0.38	0.61	0.6230	62.30	2.06	2.63	3
BLE_2M	0.21	0.62	0.3387	33.87	4.70	4.76	5

Note:


Duty Cycle Correction Factor= $10\log(1/x)$ .

Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.

### 11.7.2. Test Graphs



**END OF REPORT**