

RF EXPOSURE REPORT

						
Applicant	Zound Industries International AB					
Address	Centralplan 15 SE-111 20 Stockholm Sweden					
Manufacturer or Supplier	Zound Industries International AB					
Address	Centralplan 15 SE-111 20 Stockho	olm Sweden				
Product	WIRELESS HOME BLUETOOTH	SPEAKER				
Brand Name	Marshall	Marshall				
Model	ACTON II					
Additional Model & Model Difference	N/A					
Date of tests	ate of tests Aug. 01, 2019 ~ Oct. 17, 2019					
 ☑ KDB 447498 D01 ☑ IEEE C95.1 CONCLUSION: The 		COMPLY with the test requirement				
	sted by Andy Zhu jineer / EMC Department	Approved by Glyn He Assistant Manager / EMC Department				
Andy Atu						
Date: Nov. 06, 2019 This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report on notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.						

Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan City, Guangdong 523942, China Tel: +86 769 8998 2098 Fax: +86 769 8593 1080 Email: <u>customerservice.dg@cn.bureauveritas.com</u>



Table of Contents

RELE	ASE CONTROL RECORD	. 3
1.	CERTIFICATION	. 4
	RF EXPOSURE LIMIT	
3.	MPE CALCULATION FORMULA	5
	CLASSIFICATION	
	ANTENNA GAIN	
6.	CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM190801N002	Original release	Nov. 06, 2019



BUREAU VERITAS Test Report No.: FM190801N002

1. CERTIFICATION

FCC ID:	2AAGF-ACTONIIBT	
PRODUCT:	WIRELESS HOME BLUETOOTH SPEAKER	
BRAND NAME:	Marshall	
MODEL NO.:	ACTON II	
ADDITIONAL NO.:	N/A	
APPLICANT:	Zound Industries International AB	
STANDARDS:	FCC Part 2 (Section 2.1091)	
	KDB 447498 D01	
	IEEE C95.1	

Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan City, Guangdong 523942, China Tel: +86 769 8998 2098 Fax: +86 769 8593 1080 Email: <u>customerservice.dg@cn.bureauveritas.com</u>



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)			
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE						
300-1500 F/1500 30						
1500-100,000			1.0	30		

F = Frequency in MHz

3. MPE CALCULATION FORMULA

 $Pd = (Pout^{*}G) / (4^{*}pi^{*}r^{2})$

where

 $Pd = power density in mW/cm^2$

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type	
Chain 0	4.89	PCB Antenna	

6. CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER

The tuned conducted Average Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
GFSK	2402-2480	4	+-2	2	6
8DPSK	2402-2480	1	+-2	-1	3
LE-GFSK	2402-2480	3	+-2	1	5

The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)
GFSK	2402	5.04
8DPSK	2480	1.83
LE-GFSK	2402	3.57

FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm²)	LIMIT (mW/cm²)
2402-2480	6	4.89	20	0.002442	1.0

--- END ----

No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan City, Guangdong 523942, China

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080 Email: <u>customerservice.dg@cn.bureauveritas.com</u>