



**Neutron Engineering Inc.**

# FCC RF EXPOSURE REPORT

**FCC ID:2AAGJDHTS514A**

**Project No.** : 1310C090

**Equipment :** HOME THEATER SYSTEM

**Model :** DSW-S514

**Applicant :** Tymphony HK Limited

**Address :** Room 1307-8 Dominion Centre 43-59 Queens Road East, WanChai, Hong Kong,China

**According:** : FCC Guidelines for Human Exposure IEEE C95.1

**Neutron Engineering Inc.**

*No.3, Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.*

*TEL : (0769) 8318-3000 FAX : (0769) 8319-6000*



**Neutron Engineering Inc.**

## MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Ant.	Brand name	Model Name	Antenna Type	Connector	Gain (dBi)
A	SMSC	DWAM83-TB	Printed	N/A	2.0
B	SMSC	DWAM83-TB	Printed	N/A	2.0

## TEST RESULTS

EUT: HOME	THEATER SYSTEM	Model Name :	DSW-S514
Temperature:	25 °C	Relative Humidity:	58 %
Test Voltage:	AC 120V/60Hz		
Test Mode :	TX Mode/CH01, CH02, CH03		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)	Test Result
2	1.5849	8.00	6.3096	0.00199045	1	Complies
2	1.5849	6.58	4.5499	0.00143533	1	Complies
2	1.5849	6.67	4.6452	0.00146538	1	Complies

The calculated distance is 20cm