

## RF Exposure Evaluation

### **REQUIREMENT**

KDB447498 D01 General RF Exposure Guidance v06, Clause 4.3.1(a)

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 7.5$

Where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

-Power and distance are rounded to the nearest mW and mm before calculation

-The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

### **TEST RESULT**

**Passed**       **Not Applicable**

Test mode	Channel	Maximum Output Power (dBm)	Calculating data	Limit	Result
1Mbps	02	-1.94	0.198	7.5	Pass
	40	-1.80	0.206	7.5	Pass
	80	-2.36	0.183	7.5	Pass
2Mbps	02	-1.95	0.198	7.5	Pass
	40	-1.82	0.205	7.5	Pass
	80	-2.36	0.183	7.5	Pass

*Note:*

- 1) The maximum antenna gain is 3dBi
- 2) The exposure safety distance is less than 5mm.