

TEST REPORT

Reference No..... : WTX23X02023511W008
FCC ID : 2AAH8-OSIDDV2
Applicant : Orpyx Medical Technologies Inc.
Address..... : Suite 205, 1240 - 20th Avenue S.E. Calgary, AB T2G 1M8 Canada
Manufacturer : The same as Applicant
Address..... : The same as Applicant
Product Name : Mobile Phone
Model No..... : OSIDDV2
Standards : FCC Part 15.247
Date of Receipt sample : 2023-02-17
Date of Test..... : 2023-02-17 to 2023-03-10
Date of Issue : 2023-03-10
Test Report Form No. : WTX_Part 15_247W
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.


Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,

Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:

Approved by:



Dashan Chen



Silin Chen

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY	5
1.4 TEST FACILITY	5
1.5 EUT SETUP AND TEST MODE	6
1.6 MEASUREMENT UNCERTAINTY.....	7
1.7 TEST EQUIPMENT LIST AND DETAILS	8
2. SUMMARY OF TEST RESULTS.....	11
3. ANTENNA REQUIREMENT	12
3.1 STANDARD APPLICABLE	12
3.2 EVALUATION INFORMATION	12
4. POWER SPECTRAL DENSITY.....	13
4.1 STANDARD APPLICABLE	13
4.2 TEST SETUP BLOCK DIAGRAM	13
4.3 TEST PROCEDURE.....	13
4.4 SUMMARY OF TEST RESULTS/PLOTS.....	13
5. DTS BANDWIDTH	14
5.1 STANDARD APPLICABLE	14
5.2 TEST SETUP BLOCK DIAGRAM	14
5.3 TEST PROCEDURE.....	14
5.4 SUMMARY OF TEST RESULTS/PLOTS.....	14
6. RF OUTPUT POWER.....	15
6.1 STANDARD APPLICABLE	15
6.2 TEST SETUP BLOCK DIAGRAM	15
6.3 TEST PROCEDURE.....	15
6.4 SUMMARY OF TEST RESULTS/PLOTS.....	15
7. FIELD STRENGTH OF SPURIOUS EMISSIONS.....	16
7.1 STANDARD APPLICABLE	16
7.2 TEST PROCEDURE.....	16
7.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	18
7.4 SUMMARY OF TEST RESULTS/PLOTS.....	18
8. OUT OF BAND EMISSIONS.....	24
8.1 STANDARD APPLICABLE	24
8.2 TEST PROCEDURE.....	24
8.3 SUMMARY OF TEST RESULTS/PLOTS.....	25
9. CONDUCTED EMISSIONS	30
9.1 TEST PROCEDURE	30
9.2 BASIC TEST SETUP BLOCK DIAGRAM	30
9.3 TEST RECEIVER SETUP.....	30
9.4 SUMMARY OF TEST RESULTS/PLOTS.....	30
APPENDIX SUMMARY	33
APPENDIX A.....	34
APPENDIX B.....	37
APPENDIX C.....	40
APPENDIX D.....	43
APPENDIX PHOTOGRAPHS.....	47

Report version

Version No.	Date of issue	Description
Rev.00	2023-03-10	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	Mobile Phone
Trade Name	Orpyx
Model No.:	OSIDDV2
Adding Model(s):	/
Rated Voltage:	DC3.85V
Battery Capacity:	4000mAh (15.4Wh)
Adapter Model:	TPA-46050200UU INPUT:AC100-240V 50/60Hz 0.3A OUTPUT:DC5V 2.0A
<i>Note: The test data is gathered from a production sample, provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Bluetooth Version:	V5.0 (BLE mode)
Frequency Range:	2402-2480MHz
RF Output Power:	1Mbps:-5.20dBm (Conducted) 2Mbps:-4.93dBm (Conducted)
Data Rate:	1Mbps, 2Mbps
Modulation:	GFSK
Quantity of Channels:	40
Channel Separation:	2MHz
Type of Antenna:	PIFA Antenna
Antenna Gain:	-0.31dBi

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.

558074 D01 15.247 Meas Guidance v05r02: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under section 15.247 of the Fcc rules.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low	2402MHz
TM2	Middle	2440MHz
TM3	High	2480MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	45~55 %
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	±0.42dB
Occupied Bandwidth	Conducted	±1.5%
Power Spectral Density	Conducted	±1.8dB
Conducted Spurious Emission	Conducted	±2.17dB
Conducted Emissions	Conducted	9-150kHz ±3.74dB
		0.15-30MHz ±3.34dB
Transmitter Spurious Emissions	Radiated	30-200MHz ±4.52dB
		0.2-1GHz ±5.56dB
		1-6GHz ±3.84dB
		6-26GHz ±3.92dB

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
SEMT-1075	Communication Tester	Rohde & Schwarz	CMW500	148650	2022-03-22	2023-03-21
SEMT-1063	GSM Tester	Rohde & Schwarz	CMU200	114403	2022-03-22	2023-03-21
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2022-03-25	2023-03-24
SEMT-1079	Spectrum Analyzer	Agilent	N9020A	US47140102	2022-03-22	2023-03-21
SMET-1313	Spectrum Analyzer	Agilent	N9020A	MY54320548	2022-03-22	2023-03-21
SEMT-1080	Signal Generator	Agilent	83752A	3610A01453	2022-03-22	2023-03-21
SEMT-1081	Vector Signal Generator	Agilent	N5182A	MY47070202	2022-03-22	2023-03-21
SEMT-1028	Power Divider	Weinschel	1506A	PM204	2022-03-22	2023-03-21
SEMT-1082	Power Divider	RF-Lambda	RFLT4W5M18G	14110400027	2022-03-22	2023-03-21
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	/	/
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	/	/
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	/	/
SEMT-C004	Cable	Zheng DI	2M0RFC	/	/	/
SEMT-C005	Cable	Zheng DI	1M0RFC	/	/	/
SEMT-C006	Cable	Zheng DI	1M0RFC	/	/	/
<input checked="" type="checkbox"/> Chamber A: Below 1GHz						
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2022-03-22	2023-03-21
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2022-03-22	2023-03-21
SEMT-1008	Amplifier	HP	8447F	2805A03475	2022-12-30	2023-12-29
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2021-03-20	2023-03-19
SEMT-1068	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2021-03-20	2023-03-19
<input checked="" type="checkbox"/> Chamber A: Above 1GHz						
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2022-03-22	2023-03-21

SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2022-03-22	2023-03-21
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2022-03-22	2023-03-21
SEMT-1042	Horn Antenna	ETS	3117	00086197	2021-03-19	2023-03-18
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2021-04-27	2023-04-26
SEMT-1216	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2022-03-25	2023-03-24
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2022-03-22	2023-03-21
<input type="checkbox"/> Chamber B:Below 1GHz						
SEMT-1068	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2021-04-09	2023-04-08
SEMT-1067	Amplifier	Agilent	8447D	2944A10179	2022-03-22	2023-03-21
SEMT-1066	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2022-03-22	2023-03-21
<input type="checkbox"/> Chamber C:Below 1GHz						
SEMT-1319	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2022-12-30	2023-12-29
SEMT-1343	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2021-05-28	2023-05-27
SEMT-1333	Amplifier	HP	8447F	2944A03869	2022-03-22	2023-03-21
<input checked="" type="checkbox"/> Conducted Room 1#						
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2022-03-21	2023-03-20
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2022-03-25	2023-03-24
SEMT-1003	AC LISN	Schwarz beck	NSLK8126	8126-224	2022-03-22	2023-03-21
<input type="checkbox"/> Conducted Room 2#						
SEMT-1334	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2022-03-22	2023-03-21
SEMT-1336	LISN	Rohde & Schwarz	ENV 216	100097	2022-03-22	2023-03-21

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203; §15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	DTS Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: Not applicable.

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Evaluation Information


This product has a PIFA Antenna, fulfill the requirement of this section.

4. Power Spectral Density

4.1 Standard Applicable

According to 15.247(a)(1)(iii), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

4.2 Test Setup Block Diagram



4.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.2, the test method of power spectral density as below:

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3kHz) and repeat.

4.4 Summary of Test Results/Plots


Please refer to Appendix A

5. DTS Bandwidth

5.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928MHz, 2400–2483.5MHz, and 5725–5850 MHz bands. The minimum 6dB bandwidth shall be at least 500kHz.

5.2 Test Setup Block Diagram



5.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:

- a) Set RBW = 100kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

5.4 Summary of Test Results/Plots


Please refer to Appendix B

6. RF Output Power

6.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928MHz, 2400–2483.5MHz, and 5725–5850MHz bands: 1 Watt.

6.2 Test Setup Block Diagram



6.3 Test Procedure

According to the KDB-558074 D01 v05r02 Subclause 8.3.1.1 and ANSI C63.10-2013 Subclause 11.9.1.1, this procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the RBW \geq DTS bandwidth.
- b) Set VBW $\geq 3 \times$ RBW.
- c) Set span $\geq 3 \times$ RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

6.4 Summary of Test Results/Plots

Please refer to Appendix C

7. Field Strength of Spurious Emissions

7.1 Standard Applicable

According to §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

7.2 Test Procedure


The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Reference No.: WTX23X02023511W008

Detector function = peak

Detector function = peak, QP

Detector function = peak, AV

7.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

7.4 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


- Spurious Emissions Below 1GHz
- 1Mbps

Test Channel	Low(worst case)	Polarity:	Horizontal
--------------	-----------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	32.5198	34.50	-8.16	26.34	40.00	-13.66	-	-	peak
2	52.5753	28.11	-6.69	21.42	40.00	-18.58	-	-	peak
3	99.5281	27.65	-8.24	19.41	43.50	-24.09	-	-	peak
4	277.0935	27.16	-7.21	19.95	46.00	-26.05	-	-	peak
5	499.4247	28.02	-1.10	26.92	46.00	-19.08	-	-	peak
6	909.6667	31.15	2.80	33.95	46.00	-12.05	-	-	peak


Test Channel	Low(worst case)	Polarity:	Vertical
--------------	-----------------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	33.2112	33.05	-8.00	25.05	40.00	-14.95	-	-	peak
2	99.1797	28.05	-8.31	19.74	43.50	-23.76	-	-	peak
3	211.5265	26.92	-8.96	17.96	43.50	-25.54	-	-	peak
4	339.5888	27.50	-5.39	22.11	46.00	-23.89	-	-	peak
5	556.7744	28.12	-0.10	28.02	46.00	-17.98	-	-	peak
6	909.6667	31.15	2.80	33.95	46.00	-12.05	-	-	peak


➤ 2Mbps

Test Channel	Low(worst case)	Polarity:	Horizontal
--------------	-----------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	49.3594	28.17	-6.32	21.85	40.00	-18.15	-	-	peak
2	61.9951	28.61	-8.14	20.47	40.00	-19.53	-	-	peak
3	103.4421	28.30	-8.22	20.08	43.50	-23.42	-	-	peak
4	336.0352	27.21	-5.50	21.71	46.00	-24.29	-	-	peak
5	477.1694	29.06	-1.67	27.39	46.00	-18.61	-	-	peak
6	903.3094	32.51	2.86	35.37	46.00	-10.63	-	-	peak

Test Channel	Low(worst case)	Polarity:	Vertical
--------------	-----------------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	32.4059	34.81	-8.18	26.63	40.00	-13.37	-	-	peak
2	48.8429	27.74	-6.32	21.42	40.00	-18.58	-	-	peak
3	114.5146	27.79	-8.66	19.13	43.50	-24.37	-	-	peak
4	327.8873	25.65	-5.75	19.90	46.00	-26.10	-	-	peak
5	572.6144	28.73	0.13	28.86	46.00	-17.14	-	-	peak
6	942.1305	28.17	2.50	30.67	46.00	-15.33	-	-	peak

Remark: '-Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

➤ Spurious Emissions Above 1GHz

1Mbps

Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2402MHz							
4804.000	51.26	-2.87	48.39	74.00	-25.61	H	PK
7206.000	51.94	2.72	54.66	74.00	-19.34	H	PK
4804.000	49.98	-2.87	47.11	74.00	-26.89	V	PK
7206.000	52.18	2.72	54.90	74.00	-19.10	V	PK
Middle Channel-2440MHz							
4880.000	52.28	-2.71	49.57	74.00	-24.43	H	PK
7320.000	49.46	3.12	52.58	74.00	-21.42	H	PK
4880.000	50.70	-2.71	47.99	74.00	-26.01	V	PK
7320.000	48.56	3.12	51.68	74.00	-22.32	V	PK
High Channel-2480MHz							
4960.000	50.15	-2.56	47.59	74.00	-26.41	H	PK
7440.000	48.55	3.54	52.09	74.00	-21.91	H	PK
4960.000	50.68	-2.56	48.12	74.00	-25.88	V	PK
7440.000	48.94	3.54	52.48	74.00	-21.52	V	PK

2Mbps

Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2402MHz							
4804.000	51.82	-2.87	48.95	74.00	-25.05	H	PK
7206.000	51.78	2.72	54.50	74.00	-19.50	H	PK
4804.000	52.82	-2.87	49.95	74.00	-24.05	V	PK
7206.000	51.48	2.72	54.20	74.00	-19.80	V	PK
Middle Channel-2440MHz							
4880.000	52.41	-2.71	49.70	74.00	-24.30	H	PK
7320.000	48.88	3.12	52.00	74.00	-22.00	H	PK
4880.000	51.10	-2.71	48.39	74.00	-25.61	V	PK
7320.000	47.18	3.12	50.30	74.00	-23.70	V	PK
High Channel-2480MHz							
4960.000	51.03	-2.56	48.47	74.00	-25.53	H	PK
7440.000	49.09	3.54	52.63	74.00	-21.37	H	PK
4960.000	51.40	-2.56	48.84	74.00	-25.16	V	PK
7440.000	48.90	3.54	52.44	74.00	-21.56	V	PK

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

8. Out of Band Emissions

8.1 Standard Applicable

According to §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

8.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission

must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9.
- b) VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

RBW as a function of frequency

Frequency	RBW
9kHz to 150kHz	200Hz to 300Hz
0.15MHz to 30MHz	9kHz to 10kHz
30MHz to 1000MHz	100kHz to 120kHz
>1000MHz	1MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.


Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

8.3 Summary of Test Results/Plots

➤ Radiated test


1Mbps

Test Channel	Low	Polarity:	Horizontal(worst case)
--------------	-----	-----------	------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	40.67	-8.78	31.89	54.00	-22.11	Average Detector
	2310.000	52.83	-8.78	44.05	74.00	-29.95	Peak Detector
2	2390.000	40.62	-8.48	32.14	54.00	-21.86	Average Detector
	2390.000	53.32	-8.48	44.84	74.00	-29.16	Peak Detector
3	2402.000	93.46	-8.44	85.02	/	/	Average Detector
	2402.200	103.59	-8.44	95.15	/	/	Peak Detector


Test Channel	High	Polarity:	Horizontal(worst case)
--------------	------	-----------	------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.975	95.88	-6.79	89.09	/	/	Average Detector
	2479.800	97.31	-6.79	90.52	/	/	Peak Detector
2	2483.500	54.72	-6.77	47.95	54.00	-6.05	Average Detector
	2483.500	64.53	-6.77	57.76	74.00	-16.24	Peak Detector
3	2500.000	39.53	-6.67	32.86	54.00	-21.14	Average Detector
	2494.150	66.36	-6.71	59.65	74.00	-14.35	Peak Detector


2Mbps

Test Channel	Low	Polarity:	Horizontal(worst case)
--------------	-----	-----------	------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	40.63	-8.78	31.85	54.00	-22.15	Average Detector
	2310.000	53.90	-8.78	45.12	74.00	-28.88	Peak Detector
2	2390.000	40.52	-8.48	32.04	54.00	-21.96	Average Detector
	2390.000	54.00	-8.48	45.52	74.00	-28.48	Peak Detector
3	2402.000	76.21	-8.44	67.77	/	/	Average Detector
	2402.600	104.48	-8.44	96.04	/	/	Peak Detector

Test Channel	High	Polarity:	Horizontal(worst case)
--------------	------	-----------	------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.975	73.01	-8.15	64.86	/	/	Average Detector
	2479.475	98.91	-8.15	90.76	/	/	Peak Detector
2	2483.500	50.09	-8.14	41.95	54.00	-12.05	Average Detector
	2483.500	64.57	-8.14	56.43	74.00	-17.57	Peak Detector
3	2500.000	40.01	-8.08	31.93	54.00	-22.07	Average Detector
	2500.000	53.05	-8.08	44.97	74.00	-29.03	Peak Detector

➤ Conducted test

Please refer to Appendix D


9. Conducted Emissions

9.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

9.2 Basic Test Setup Block Diagram




9.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency	150kHz
Stop Frequency	30MHz
Sweep Speed	Auto
IF Bandwidth.....	10kHz
Quasi-Peak Adapter Bandwidth	9kHz
Quasi-Peak Adapter Mode	Normal


9.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.5380	30.47	10.22	40.69	56.00	-15.31	QP
2*	0.5380	23.45	10.22	33.67	46.00	-12.33	AVG
3	16.2700	32.12	10.28	42.40	60.00	-17.60	QP
4	19.2420	17.53	10.35	27.88	50.00	-22.12	AVG
5	25.9980	30.46	10.39	40.85	60.00	-19.15	QP
6	25.9980	16.41	10.39	26.80	50.00	-23.20	AVG

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.5620	28.04	10.21	38.25	56.00	-17.75	QP
2	0.5620	17.22	10.21	27.43	46.00	-18.57	AVG
3	19.5020	20.59	10.36	30.95	50.00	-19.05	AVG
4	19.8300	35.75	10.37	46.12	60.00	-13.88	QP
5*	26.0020	40.67	10.39	51.06	60.00	-8.94	QP
6	26.0020	22.82	10.39	33.21	50.00	-16.79	AVG




APPENDIX SUMMARY




Project No.	WTX23X02023511W	Test Engineer	Timi Huang
Start date	2023/2/22	Finish date	2023/2/22
Temperature	23°C	Humidity	47%
RF specifications	BT-BLE		

APPENDIX	Description of Test Item	Result
A	Power Spectral Density	Compliant
B	DTS Bandwidth	Compliant
C	RF Output Power	Compliant
D	Conducted Out of Band Emissions	Compliant

APPENDIX A


Power Spectral Density			
Test Mode	Test Channel	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
BLE-GFSK-1Mbps	Low	-22.48	8
	Middle	-22.12	8
	High	-21.78	8
BLE-GFSK-1Mbps	Low	-24.96	8
	Middle	-24.51	8
	High	-24.17	8




<p>Low-1Mbps</p>	 <p>Date: 22.FEB.2023 09:16:07</p>
<p>Middle-1Mbps</p>	 <p>Date: 22.FEB.2023 09:16:24</p>
<p>High-1Mbps</p>	 <p>Date: 22.FEB.2023 09:16:39</p>

<p>Low-2Mbps</p>	 <p>Ref 20 dBm +Att 30 dB +RBW 3 kHz Marker 1 [T1] -24.96 dBm +VBW 10 kHz -24.96 dBm -SWT 340 ms 2.401970000 GHz</p> <p>20 Offset 1 dB 10 0 -10 -20 -30 -40 -50 -60 -70 -80</p> <p>Center 2.402 GHz 300 kHz/ Span 3 MHz</p> <p>Date: 22.FEB.2023 09:32:28</p>
<p>Middle-2Mbps</p>	 <p>Ref 20 dBm +Att 30 dB +RBW 3 kHz Marker 1 [T1] -24.51 dBm +VBW 10 kHz -24.51 dBm -SWT 340 ms 2.439970000 GHz</p> <p>20 Offset 1 dB 10 0 -10 -20 -30 -40 -50 -60 -70 -80</p> <p>Center 2.44 GHz 300 kHz/ Span 3 MHz</p> <p>Date: 22.FEB.2023 09:32:48</p>
<p>High-2Mbps</p>	 <p>Ref 20 dBm +Att 30 dB +RBW 3 kHz Marker 1 [T1] -24.17 dBm +VBW 10 kHz -24.17 dBm -SWT 340 ms 2.479970000 GHz</p> <p>20 Offset 1 dB 10 0 -10 -20 -30 -40 -50 -60 -70 -80</p> <p>Center 2.48 GHz 300 kHz/ Span 3 MHz</p> <p>Date: 22.FEB.2023 09:33:07</p>

APPENDIX B




Test Mode	Test Channel	6 dB Bandwidth kHz	Limit kHz
BLE-GFSK-1Mbps	Low	672	≥500
	Middle	672	≥500
	High	690	≥500
BLE-GFSK-2Mbps	Low	1200	≥500
	Middle	1176	≥500
	High	1176	≥500






<p>Low-2Mbps</p>	 <p>Ref 20 dBm +Att 30 dB Ref 20 dBm +Att 30 dB +RBW 100 kHz Marker 1 [T1] -6.71 dBm +VBW 300 kHz 2.401988000 GHz +SWT 2.5 ms n dB [T1] 6.00 dB BW 1.200000000 MHz Temp 1 [T1] n dB -12.78 dBm 2.401400000 GHz -13.32 dBm 2.402600000 GHz</p> <p>Center 2.402 GHz 600 kHz/ Span 6 MHz</p> <p>Date: 22.FEB.2023 09:26:22</p>
<p>Middle-2Mbps</p>	 <p>Ref 20 dBm +Att 30 dB Ref 20 dBm +Att 30 dB +RBW 100 kHz Marker 1 [T1] -6.23 dBm +VBW 300 kHz 2.440000000 GHz +SWT 2.5 ms n dB [T1] 6.00 dB BW 1.176000000 MHz Temp 1 [T1] n dB -12.10 dBm 2.439412000 GHz -11.83 dBm 2.440588000 GHz</p> <p>Center 2.44 GHz 600 kHz/ Span 6 MHz</p> <p>Date: 22.FEB.2023 09:26:56</p>
<p>High-2Mbps</p>	 <p>Ref 20 dBm +Att 30 dB Ref 20 dBm +Att 30 dB +RBW 100 kHz Marker 1 [T1] -5.84 dBm +VBW 300 kHz 2.480000000 GHz +SWT 2.5 ms n dB [T1] 6.00 dB BW 1.176000000 MHz Temp 1 [T1] n dB -11.69 dBm 2.479412000 GHz -11.31 dBm 2.480588000 GHz</p> <p>Center 2.48 GHz 600 kHz/ Span 6 MHz</p> <p>Date: 22.FEB.2023 09:27:25</p>

APPENDIX C




RF Output Power				
Modulation type	Channel	Output power (dBm)	Limit (dBm)	Result
GFSK-1Mbps	Low	-5.84	30.00	Pass
	Middle	-5.49		
	High	-5.20		
GFSK-2Mbps	Low	-5.67		
	Middle	-5.36		
	High	-4.93		


<p>Low-1Mbps</p>	 <p>Date: 22.FEB.2023 09:11:16</p>
<p>Middle-1Mbps</p>	 <p>Date: 22.FEB.2023 09:12:30</p>
<p>High-1Mbps</p>	 <p>Date: 22.FEB.2023 09:12:47</p>

<p>Low-2Mbps</p>	 <p>Date: 22.FEB.2023 09:30:51</p>
<p>Middle-2Mbps</p>	 <p>Date: 22.FEB.2023 09:31:08</p>
<p>High-2Mbps</p>	 <p>Date: 22.FEB.2023 09:31:22</p>


APPENDIX D

Conducted Out of Band Emissions


<p>Low-1Mbps</p>	 <p>Date: 22.FEB.2023 09:21:45</p>
	 <p>Date: 22.FEB.2023 09:22:11</p>
<p>Middle-1Mbps</p>	 <p>Date: 22.FEB.2023 09:22:38</p>



Low-2Mbps




Date: 22.FEB.2023 09:36:36




Date: 22.FEB.2023 09:37:01

Middle-2Mbps



Date: 22.FEB.2023 09:37:25



APPENDIX PHOTOGRAPHS

Please refer to "ANNEX"

**** END OF REPORT ****