






# Radio Test Report

## FCC ID: 2AAH9-3700A

**Report No.** : TBR-C-202211-0053-53  
**Applicant** : Navori Inc  
**Equipment Under Test (EUT)**  
**EUT Name** : StiX  
**Model No.** : 3700  
**Series Model No.** : ----  
**Brand Name** : Navori  
**Sample ID** : 202211-0053-01-1 & 202211-0053-01-2  
**Receipt Date** : 2022-11-11  
**Test Date** : 2022-11-11 to 2022-12-12  
**Issue Date** : 2022-12-12  
**Standards** : FCC Part 15 Subpart E 15.407  
RSS-247 Issue 2 February 2017  
**Test Method** : ANSI C63.10: 2013  
KDB 789033 D02 General UNII Test Procedures New Rules v02r01  
**Conclusions** : **PASS**

In the configuration tested, the EUT complied with the standards specified above.

**Witness Engineer** :  Camille Li  
**Engineer Supervisor** :  Ivan Su  
**Engineer Manager** :  Ray Lai



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.



# Contents

<b>CONTENTS</b> .....	<b>2</b>
<b>1. GENERAL INFORMATION ABOUT EUT</b> .....	<b>6</b>
1.1 Client Information.....	6
1.2 General Description of EUT (Equipment Under Test) .....	6
1.3 Block Diagram Showing the Configuration of System Tested.....	7
1.4 Description of Support Units .....	8
1.5 Description of Test Mode.....	8
1.6 Description of Test Software Setting .....	10
1.7 Measurement Uncertainty .....	11
1.8 Test Facility.....	11
<b>2. TEST SUMMARY</b> .....	<b>13</b>
<b>3. TEST SOFTWARE</b> .....	<b>13</b>
<b>4. TEST EQUIPMENT</b> .....	<b>14</b>
<b>5. CONDUCTED EMISSION TEST</b> .....	<b>16</b>
5.1 Test Standard and Limit.....	16
5.2 Test Setup.....	16
5.3 Test Procedure.....	16
5.4 Deviation From Test Standard.....	17
5.5 EUT Operating Mode .....	17
5.6 Test Data.....	17
<b>6. RADIATED AND CONDUCTED UNWANTED EMISSIONS</b> .....	<b>18</b>
6.1 Test Standard and Limit.....	18
6.2 Test Setup.....	19
6.3 Test Procedure.....	20
6.4 Deviation From Test Standard.....	22
6.5 EUT Operating Mode .....	22
6.6 Test Data.....	22
<b>7. RESTRICTED BANDS REQUIREMENT</b> .....	<b>23</b>
7.1 Test Standard and Limit.....	23
7.2 Test Setup.....	24
7.3 Test Procedure.....	24
7.4 Deviation From Test Standard.....	25





7.5 EUT Operating Mode .....	25
7.6 Test Data .....	25
<b>8. BANDWIDTH TEST .....</b>	<b>26</b>
8.1 Test Standard and Limit.....	26
8.2 Test Setup.....	26
8.3 Test Procedure.....	26
8.4 Deviation From Test Standard.....	29
8.5 EUT Operating Mode .....	29
8.6 Test Data.....	29
<b>9. MAXIMUM CONDUCTED OUTPUT POWER.....</b>	<b>30</b>
9.1 Test Standard and Limit.....	30
9.2 Test Setup.....	31
9.3 Test Procedure.....	31
9.4 Deviation From Test Standard.....	31
9.5 EUT Operating Mode .....	31
9.6 Test Data.....	31
<b>10. POWER SPECTRAL DENSITY TEST .....</b>	<b>32</b>
10.1 Test Standard and Limit .....	32
10.2 Test Setup.....	32
10.3 Test Procedure.....	32
10.4 Deviation From Test Standard.....	33
10.5 Antenna Connected Construction .....	33
10.6 Test Data.....	33
<b>11. FREQUENCY STABILITY.....</b>	<b>34</b>
11.1 Test Standard and Limit .....	34
11.2 Test Setup.....	34
11.3 Test Procedure.....	34
11.4 Deviation From Test Standard.....	35
11.5 Antenna Connected Construction .....	35
11.6 Test Data.....	35
<b>12. ANTENNA REQUIREMENT.....</b>	<b>36</b>
12.1 Test Standard and Limit .....	36
12.2 Deviation From Test Standard.....	36
12.3 Antenna Connected Construction .....	36
12.4 Test Data.....	36





---

ATTACHMENT A-- CONDUCTED EMISSION TEST DATA .....	37
ATTACHMENT B--UNWANTED EMISSIONS DATA .....	39





## Revision History

Report No.	Version	Description	Issued Date
TBR-C-202211-0053-53	Rev.01	Initial issue of report	2022-12-12





# 1. General Information about EUT

## 1.1 Client Information

<b>Applicant</b>	:	Navori Inc
<b>Address</b>	:	1000 rue Sherbrooke st W, Suite 710, Montreal, QC, Canada H3A 3G4
<b>Manufacturer</b>	:	Shenzhen MicoRose Technology Co., Ltd.
<b>Address</b>	:	8B2A, Daqing Building, southeast of the intersection of Shennan Road and Guangshen Expressway, Futian District, Shenzhen, China

## 1.2 General Description of EUT (Equipment Under Test)

<b>EUT Name</b>	:	StiX
<b>HVIN/Models No.</b>	:	3700
<b>Model Difference</b>	:	----
<b>Product Description</b>	Operation Frequency:	U-NII-1: 5180MHz~5240MHz U-NII-3: 5745MHz~5825MHz
	Antenna Gain:	2dBi RP-SMA Antenna
	Modulation Type:	802.11a: OFDM (QPSK, BPSK, 16QAM) 802.11n: OFDM (QPSK, BPSK, 16QAM, 64QAM) 802.11ac: OFDM (QPSK, BPSK, 16QAM, 64QAM, 256QAM)
	Bit Rate of Transmitter:	802.11a: 6/9/12/18/24/36/48/54 Mbps 802.11n: up to 150Mbps 802.11ac: at most 433.3 Mbps
<b>Power Rating</b>	:	Adapter (FJ-SW7260502500DU) Input: 100-240V~ 50/60Hz 0.4A Max Output: 5V=2500mA
<b>Software Version</b>	:	android 9.0
<b>Hardware Version</b>	:	V1

**Remark:**

- (1) The antenna gain and adapter provided by the applicant, the verified for the RF conduction test provided by TOBY test lab.
- (2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- (3) Antenna information provided by the applicant.




(4) Channel List:


Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5180~5240MHz (U-NII-1)	36	5180 MHz	44	5220 MHz
	38	5190 MHz	46	5230 MHz
	40	5200 MHz	48	5240 MHz
	42	5210 MHz		
For 20 MHz Bandwidth, use channel 36, 40, 44, 48. For 40 MHz Bandwidth, use channel 38, 46. For 80 MHz Bandwidth, use channel 42.				
Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5745~5825MHz (U-NII-3)	149	5745 MHz	157	5785 MHz
	151	5755 MHz	159	5795 MHz
	153	5765 MHz	161	5805 MHz
	155	5775 MHz	165	5825 MHz
For 20 MHz Bandwidth, use channel 149, 153, 157, 161, 165. For 40 MHz Bandwidth, use channel 151, 159. For 80 MHz Bandwidth, use channel 155.				

### 1.3 Block Diagram Showing the Configuration of System Tested

#### Conducted Test



#### Radiated Test





### 1.4 Description of Support Units

Equipment Information				
Name	Model	FCC ID/VOC	Manufacturer	Used “√”
Adapter	FJ-SW7260502500DU	----	SHENZHEN FUJIA	√
Cable Information				
Number	Shielded Type	Ferrite Core	Length	Note
Cable 1	----	----	----	----
Remark: the USB Cable and adapter provided by the Applicant.				

### 1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test		
Final Test Mode	Description	
Mode 1	Charging + TX a Mode(5180MHz)	
For Radiated Test Below 1GHz		
Final Test Mode	Description	
Mode 2	Charging + TX a Mode(5180MHz)	
For Radiated Above 1GHz and RF Conducted Test		
Test Band	Final Test Mode	Description
U-NII-1	Mode 3	TX Mode 802.11a Mode Channel 36/40/48
	Mode 4	TX Mode 802.11n(HT20) Mode Channel 36/40/48
	Mode 5	TX Mode 802.11ac(VHT20) Mode Channel 36/40/48
	Mode 6	TX Mode 802.11n(HT40) Mode Channel 38/46
	Mode 7	TX Mode 802.11ac(VHT40) Mode Channel 38/46
	Mode 8	TX Mode 802.11ac(VHT80) Mode Channel 42
U-NII-3	Mode 9	TX Mode 802.11a Mode Channel 149/157/165
	Mode 10	TX Mode 802.11n(HT20) Mode Channel 149/157/165
	Mode 11	TX Mode 802.11ac(vHT20) Mode Channel 149/157/165
	Mode 12	TX Mode 802.11n(HT40) Mode Channel 151/159





	Mode 13	TX Mode 802.11ac(VHT40) Mode Channel 151/159
	Mode 14	TX Mode 802.11ac(VHT80) Mode Channel 155

**Note:**

(1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.

According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:

802.11a Mode: OFDM (6 Mbps)

802.11n (HT20) Mode: MCS 0

802.11n (HT40) Mode: MCS 0

802.11ac(VHT20) Mode: MCS 0/ Nss1

802.11ac(VHT40) Mode: MCS 0/ Nss1

802.11ac(VHT80) Mode: MCS 0/ Nss1

(2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.

(3) The EUT is considered a Mobile unit; in normal use it was positioned on X-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.





## 1.6 Description of Test Software Setting

During testing channel & Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of RF setting.

<b>Test Software: RF Test Tool</b>		
<b>U-NII-1</b>		
<b>Mode</b>	<b>Frequency (MHz)</b>	<b>Parameters</b>
<b>802.11a</b>	5180	64
	5200	64
	5240	64
<b>802.11n(HT20)</b>	5180	66
	5200	66
	5240	66
<b>802.11ac(VHT20)</b>	5180	66
	5200	66
	5240	66
<b>802.11n(HT40)</b>	5190	66
	5230	66
<b>802.11ac(VHT40)</b>	5190	65
	5230	65
<b>802.11ac(VHT80)</b>	5210	65
<b>U-NII-3</b>		
<b>Mode</b>	<b>Frequency (MHz)</b>	<b>Parameters</b>
<b>802.11a</b>	5745	74
	5785	74
	5825	74
<b>802.11n(HT20)</b>	5745	74
	5785	74
	5825	75
<b>802.11ac(VHT20)</b>	5745	75
	5785	75
	5825	75
<b>802.11n(HT40)</b>	5755	73





	5795	73
802.11ac(VHT40)	5755	73
	5795	73
802.11ac(VHT80)	5775	72

### 1.7 Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty ( $U_{Lab}$ )
Conducted Emission	Level Accuracy: 9kHz~150kHz	$\pm 3.50$ dB
	150kHz to 30MHz	$\pm 3.10$ dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	$\pm 4.60$ dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	$\pm 4.50$ dB
Radiated Emission	Level Accuracy: Above 1000MHz	$\pm 4.20$ dB

### 1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1/F., Building 6, Rundongsheng Industrial Zone, Longzhu, Xixiang, Bao'an District, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

#### **A2LA Certificate No.: 4750.01**

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.FCC Accredited Test Site Number: 854351. Designation Number: CN1223.

#### **IC Registration No.: (11950A)**





The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A. CAB identifier: CN0056.





## 2. Test Summary

Standard Section	Test Item	Test Sample(s)	Judgment	Remark
FCC				
FCC 15.207(a)	Conducted Emission	202211-0053-01-1	PASS	N/A
FCC 15.209 & 15.407(b)	Radiated Unwanted Emissions	202211-0053-01-1	PASS	N/A
FCC 15.203	Antenna Requirement	202211-0053-01-2	PASS	N/A
FCC 15.407(a)	-26dB Emission Bandwidth	202211-0053-01-2	PASS	N/A
FCC 15.407(a)	99% Occupied Bandwidth	202211-0053-01-2	PASS	N/A
FCC 15.407(e)	-6dB Min Emission Bandwidth	202211-0053-01-2	PASS	N/A
FCC 15.407(a)	Maximum Conducted Output Power and E.I.R.P	202211-0053-01-2	PASS	N/A
FCC 15.407(a)	Power Spectral Density	202211-0053-01-2	PASS	N/A
FCC 15.407(b)& 15.205	Emissions in Restricted Bands	202211-0053-01-2	PASS	N/A
FCC 15.407(b)&15.209	Conducted Unwanted Emissions	202211-0053-01-2	PASS	N/A
FCC 15.407(g)	Frequency Stability	202211-0053-01-2	PASS	N/A
/	On Time and Duty Cycle	202211-0053-01-2	/	N/A

**Note:** N/A is an abbreviation for Not Applicable.

## 3. Test Software

Test Item	Test Software	Manufacturer	Version No.
Conducted Emission	EZ-EMC	EZ	CDI-03A2
Radiation Emission	EZ-EMC	EZ	FA-03A2RE
RF Conducted Measurement	MTS-8310	MWRftest	V2.0.0.0
RF Test System	JS1120	Tonscend	V2.6.88.0336





## 4. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jun. 23, 2022	Jun. 22, 2023
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jun. 23, 2022	Jun. 22, 2023
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jun. 22, 2022	Jun. 21, 2023
LISN	Rohde & Schwarz	ENV216	101131	Jun. 22, 2022	Jun. 21, 2023
ISN	SCHWARZBECK	NTFM 8131	8131-193	Jun. 22, 2022	Jun. 21, 2023
ISN	SCHWARZBECK	CAT3 8158	cat3 5158-0094	Jun. 22, 2022	Jun. 21, 2023
ISN	SCHWARZBECK	NTFM5158	NTFM5158 0145	Jun. 22, 2022	Jun. 21, 2023
ISN	SCHWARZBECK	CAT 8158	cat5 8158-179	Jun. 22, 2022	Jun. 21, 2023
Radiation Emission Test (B Site)					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	N9020A	MY49100060	Sep. 01, 2022	Aug. 31, 2023
Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102197	Jun. 23, 2022	Jun. 22, 2023
EMI Test Receiver	Rohde & Schwarz	ESU-8	100472/008	Feb. 26, 2022	Feb.25, 2023
Bilog Antenna	SCHWARZBECK	VULB 9168	1225	Dec. 05, 2021	Dec. 04, 2023
Horn Antenna	SCHWARZBECK	BBHA 9120 D	2463	Feb. 26, 2022	Feb.25, 2024
Horn Antenna	SCHWARZBECK	BBHA 9170	1118	Jun. 26, 2022	Jun.25, 2024
Loop Antenna	SCHWARZBECK	FMZB 1519 B	1519B-059	Jun. 26, 2022	Jun.25, 2024
HF Amplifier	Tonscend	TAP9E6343	AP21C806117	Sep. 01, 2022	Aug. 31, 2023
HF Amplifier	Tonscend	TAP051845	AP21C806141	Sep. 01, 2022	Aug. 31, 2023
HF Amplifier	Tonscend	TAP0184050	AP21C806129	Sep. 01, 2022	Aug. 31, 2023
Antenna Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jun. 23, 2022	Jun. 22, 2023
Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102197	Jun. 23, 2022	Jun. 22, 2023
MXA Signal Analyzer	KEYSIGT	N9020B	MY60110172	Sep. 01, 2022	Aug. 31, 2023
MXA Signal Analyzer	Agilent	N9020A	MY47380425	Sep. 01, 2022	Aug. 31, 2023
Vector Signal Generator	Agilent	N5182A	MY50141294	Sep. 01, 2022	Aug. 31, 2023
Analog Signal Generator	Agilent	N5181A	MY48180463	Sep. 01, 2022	Aug. 31, 2023
Vector Signal Generator	KEYSIGT	N5182B	MY59101429	Sep. 01, 2022	Aug. 31, 2023
Analog Signal Generator	KEYSIGHT	N5173B	MY61252685	Dec. 16, 2021	Dec. 15, 2022
RF Power Sensor	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO26	Sep. 01, 2022	Aug. 31, 2023
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO29	Sep. 01, 2022	Aug. 31, 2023
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO31	Sep. 01, 2022	Aug. 31, 2023
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO33	Sep. 01, 2022	Aug. 31, 2023
RF Control Unit	Tonsced	JS0806-1	21C8060380	N/A	N/A
RF Control Unit	Tonsced	JS0806-2	21F8060439	Sep. 01, 2022	Aug. 31, 2023
Band Reject Filter Group	Tonsced	JS0806-F	21D8060414	Jun. 23, 2022	Jun. 22, 2023
Power Control Box	Tonsced	JS0806-4ADC	21C8060387	N/A	N/A





Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	144382	Sep. 01, 2022	Aug. 31, 2023
Universal Radio Communication Tester	Rohde&Schwarz	CMW500	168796	Jun. 23, 2022	Jun. 22, 2023
Temperature and Humidity Chamber	ZhengHang	ZH-QTH-1500	ZH2107264	Jun. 22, 2022	Jun. 21, 2023





## 5. Conducted Emission Test

### 5.1 Test Standard and Limit

#### 5.1.1 Test Standard

#### FCC Part 15.207


#### 5.1.2 Test Limit

Frequency	Maximum RF Line Voltage (dB $\mu$ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

**Notes:**

- (1) \*Decreasing linearly with logarithm of the frequency.
- (2) The lower limit shall apply at the transition frequencies.
- (3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 5.2 Test Setup



### 5.3 Test Procedure

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.





- The bandwidth of EMI test receiver is set at 9 kHz, and the test frequency band is from 0.15MHz to 30MHz.

#### 5.4 Deviation From Test Standard

No deviation

#### 5.5 EUT Operating Mode

Please refer to the description of test mode.

#### 5.6 Test Data

Please refer to the Attachment A inside test report.





## 6. Radiated and Conducted Unwanted Emissions

### 6.1 Test Standard and Limit

#### 6.1.1 Test Standard

**FCC Part 15.209 & FCC Part 15.407(b)**

#### 6.1.2 Test Limit

General field strength limits at frequencies Below 30MHz			
Frequency (MHz)	Field Strength ( $\mu\text{A/m}$ )*	Field Strength (microvolt/meter)**	Measurement Distance (meters)
0.009~0.490	6.37/F (F in kHz)	2400/F(KHz)	300
0.490~1.705	63.7/F (F in kHz)	24000/F(KHz)	30
1.705~30.0	0.08	30	30

**Note:** 1, The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.  
2, \*is for RSS Standard, \*\*is for FCC Standard.

General field strength limits at frequencies above 30 MHz		
Frequency (MHz)	Field strength ( $\mu\text{V/m}$ at 3 m)	Measurement Distance (meters)
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

General field strength limits at frequencies Above 1000MHz		
Frequency (MHz)	Distance of 3m (dBuV/m)	
	Peak	Average
Above 1000	74	54

**Note:**  
(1) The tighter limit applies at the band edges.  
(2) Emission Level(dBuV/m)=20log Emission Level( $\mu\text{V/m}$ )

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided







that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

## 6.2 Test Setup

### Radiated measurement




### Below 30MHz Test Setup




### Below 1000MHz Test Setup







**Above 1GHz Test Setup  
Conducted measurement**



### 6.3 Test Procedure

#### ---Radiated measurement

- The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Below 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode





measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.

- Testing frequency range 30MHz-1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection. Testing frequency range 9KHz-150Hz the measuring instrument use VBW=200Hz with Quasi-peak detection. Testing frequency range 9KHz-30MHz the measuring instrument use VBW=9kHz with Quasi-peak detection.

- Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

- For the actual test configuration, please see the test setup photo.





**--- Conducted measurement****● Reference level measurement**

Establish a reference level by using the following procedure:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set the span to  $\geq 1.5$  times the DTS bandwidth.
- c) Set the RBW = 100 kHz.
- d) Set the VBW  $\geq [3 \cdot \text{RBW}]$ .
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

**● Emission level measurement**

Establish an emission level by using the following procedure:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq [3 \cdot \text{RBW}]$ .
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

**6.4 Deviation From Test Standard**

No deviation

**6.5 EUT Operating Mode**

Please refer to the description of test mode.

**6.6 Test Data**

Radiated measurement please refer to the Attachment B inside test report.

Conducted measurement please refer to the Appendix D.





## 7. Restricted Bands Requirement

### 7.1 Test Standard and Limit

#### 7.1.1 Test Standard

#### FCC Part 15.205 & FCC Part 15.407(b)

#### 7.1.2 Test Limit

Frequency (MHz)	EIRP Limits (dBm)	Equivalent Field Strength at 3m (dBuV/m)
5150~5250	-27	68.3
5250~5350	-27	68.3
5470~5725	-27	68.3
5725~5825	-27(Note 2)	68.3
	10(Note 2)	105.3
	15.6(Note 2)	110.9
	27(Note 2)	122.3

**NOTE:**

1, The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \text{ uV/m, where P is the eirp (Watts)}$$

2, According to FCC 16-24, All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.


**Note:** According the ANSI C63.10 11.12.2 antenna-port conducted measurements may also be used as an alternative to radiated measurements for determining compliance in the restricted frequency bands requirements. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case emissions is required.






## 7.2 Test Setup

### Radiated measurement



### Conducted measurement



## 7.3 Test Procedure

### ---Radiated measurement

- Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- The Peak Value and average value both need to comply with applicable limit above 1 GHz.
- Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- For the actual test configuration, please see the test setup photo.





**--- Conducted measurement**

- a) Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency (see 11.12.2.3 through 11.12.2.5 for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP (see 11.12.2.6 for guidance on determining the applicable antenna gain).
- c) Add the appropriate maximum ground reflection factor to the EIRP (6 dB for frequencies  $\leq 30$  MHz; 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive; and 0 dB for frequencies  $> 1000$  MHz).
- d) For MIMO devices, measure the power of each chain and sum the EIRP of all chains in linear terms (i.e., watts and mW).
- e) Convert the resultant EIRP to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20 \log d + 104.8$$

where

$E$  is the electric field strength in dBuV/m

EIRP is the equivalent isotropically radiated power in dBm

$d$  is the specified measurement distance in m

f) Compare the resultant electric field strength level with the applicable regulatory limit.

g) Perform the radiated spurious emission test.

**7.4 Deviation From Test Standard**

No deviation

**7.5 EUT Operating Mode**

Please refer to the description of test mode.

**7.6 Test Data**

Remark: The test uses antenna-port conducted measurements as an alternative to radiated measurements for determining compliance in the restricted frequency bands requirements.

Please refer to the Appendix D.





## 8. Bandwidth Test

### 8.1 Test Standard and Limit


#### 8.1.1 Test Standard

**FCC Part 15.407(a) & FCC Part 15.407(e)**

#### 8.1.2 Test Limit

Test Item	Limit	Frequency Range (MHz)
26 Bandwidth	N/A	5150~5250
		5250~5350
		5500~5725
6 dB Bandwidth	>500kHz	5725~5850
99% Bandwidth	N/A	5150~5250
		5250~5350
		5500~5725
		5725~5850

### 8.2 Test Setup



### 8.3 Test Procedure

#### ---Emission bandwidth

● The procedure for this method is as follows:

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from the peak of the emission.

Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

NOTE—The automatic bandwidth measurement capability of a spectrum analyzer or an EMI receiver may be employed if it implements the functionality described in the preceding items.





**---DTS bandwidth**

● The steps for the first option are as follows:

- a) Set RBW = 100 kHz.
- b) Set the VBW  $\geq [3 \cdot \text{RBW}]$ .
- c) Detector = peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

**---occupied bandwidth**

● The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than  $[10 \log (\text{OBW}/\text{RBW})]$  below the reference level. Specific guidance is given in 4.1.5.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated





until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.

h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled.

Tabular data may be reported in addition to the plot(s).





#### 8.4 Deviation From Test Standard

No deviation

#### 8.5 EUT Operating Mode

Please refer to the description of test mode.

#### 8.6 Test Data

Please refer to the Appendix D.





## 9. Maximum Conducted Output Power

### 9.1 Test Standard and Limit

#### 9.1.1 Test Standard

#### FCC Part 15.407(a)

#### 9.1.2 Test Limit


RSS-247				
Limit	Frequency Range(MHz)			
	5150~5250	5250~5350	5500~5725	5725~5850
Max Conducted TX Power	N/A	The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$ , dBm		1 Watt (30dBm)
Max E.I.R.P	For other devices, the maximum e.i.r.p. shall not exceed 200 mW or $10 + 10 \log_{10} B$ , dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.	The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$ , dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.		4 W (36 dBm) with 6 dBi antenna
TPC	NO	YES, if Max_EIRP $\geq$ 500 mW (27 dBm) and able to lower EIRP below 24dBm		NO
		NO, if Max_EIRP < 500mW (27dBm)		
FCC Part 15 Subpart E(15.407)				
Limit	Frequency Range(MHz)			
	5150~5250	5250~5350	5500~5725	5725~5850
Max Conducted TX Power	Master Device: 1 Watt(30dBm) Client Device: 250mW(24dBm)	24dBm (250 mW) or $11 \text{ dBm} + 10 \log B$ , whichever is lower (B= 26-dB emission BW)		1 Watt (30dBm)
Max E.I.R.P	4 W (36 dBm) with 6 dBi antenna 200 W (53 dBm) for fixed P-t-P application with 23 dBiantenna Additional rule for outdoor operation: Max_EIRP < 125 mW(21 dBm) at any elevation angle > 30°from horizon	1 W (30 dBm) with 6 dBi antenna		4 W (36 dBm) with 6 dBi antenna
TPC	NO	YES, if Max_EIRP $\geq$ 500 mW (27		NO





		dBm) and able to lower EIRP below 24dBm	
		NO, if Max_EIRP < 500mW (27dBm)	

## 9.2 Test Setup



## 9.3 Test Procedure

- The EUT was connected to RF power meter via a broadband power sensor as show the block above. The power sensor video bandwidth is greater than or equal to the DTS bandwidth of the equipment.

## 9.4 Deviation From Test Standard

No deviation

## 9.5 EUT Operating Mode

Please refer to the description of test mode.

## 9.6 Test Data

Please refer to the Appendix D.





## 10. Power Spectral Density Test

### 10.1 Test Standard and Limit


#### 10.1.1 Test Standard

#### FCC Part 15.407(a)

#### 10.1.2 Test Limit

Test Item	Limit		Frequency Range(MHz)
Power Spectral Density	FCC	Master Device: 17dBm/MHz	5150~5250
		Client Device: 11dBm/MHz	
	IC	10dBm/MHz	
		11dBm/MHz	5250~5350
		11dBm/MHz	5500~5725
	30dBm/500kHz	5725~5850	

### 10.2 Test Setup



### 10.3 Test Procedure

● Notwithstanding that some regulatory requirements refer to peak power spectral density (PPSD), in some cases the intent is to measure the maximum value of the time average of the power spectral density during a period of continuous transmission. The procedure for this method is as follows:

- a) Create an average power spectrum for the EUT operating mode being tested by following the instructions in 12.3.2 for measuring maximum conducted output power using a spectrum analyzer or EMI receiver; that is, select the appropriate test method (SA-1, SA-2, SA-3, or their respective alternatives) and apply it up to, but not including, the step labeled, "Compute power...". (This procedure is required even if the maximum conducted output power measurement was performed using the power meter method PM.)
- b) Use the peak search function on the instrument to find the peak of the spectrum.
- c) Make the following adjustments to the peak value of the spectrum, if applicable:
  - 1) If method SA-2 or SA-2A was used, then add  $[10 \log (1 / D)]$ , where D is the duty cycle, to the peak of the spectrum.





- 2) If method SA-3A was used and the linear mode was used in step h) of 12.3.2.7, add 1 dB to the final result to compensate for the difference between linear averaging and power averaging.
- d) The result is the PPSD.
- e) The procedure in item a) through item c) requires the use of 1 MHz resolution bandwidth to satisfy the 1 MHz measurement bandwidth specified by some regulatory authorities.<sup>95</sup> This requirement also permits use of resolution bandwidths less than 1 MHz"provided that the measured power is integrated to show the total power over the measurement bandwidth"(i.e., 1 MHz). If measurements are performed using a reduced resolution bandwidth and integrated over 1 MHz bandwidth, the following adjustments to the procedures apply:
- 1) Set  $RBW \geq 1 / T$ , where T is defined in 12.2 a).
  - 2) Set  $VBW \geq [3 * RBW]$ .
  - 3) Care shall be taken such that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

#### 10.4 Deviation From Test Standard

No deviation

#### 10.5 Antenna Connected Construction

Please refer to the description of test mode.

#### 10.6 Test Data

Please refer to the Appendix D.





## 11. Frequency Stability

### 11.1 Test Standard and Limit


#### 11.1.1 Test Standard

##### **FCC Part 15.407(g)**

#### 11.1.2 Test Limit

If the frequency stability of the licence-exempt radio apparatus is not specified in the applicable RSS, the fundamental emissions of the radio apparatus should be kept within at least the central 80% of its permitted operating frequency band in order to minimize the possibility of out-of-band operation.

### 11.2 Test Setup



### 11.3 Test Procedure

● Determining compliance with the peak excursion requirement shall be done by confirming that the ratio of the maximum of the peak-max-hold spectrum to the maximum of the average spectrum for continuous transmission does not exceed the regulatory requirement.<sup>96</sup> The procedure for this method is as follows:

a) The following guidance for limiting the number of tests applies only to peak excursion measurements:

1) Testing each modulation mode on a single channel in a single operating band is sufficient to determine compliance with the peak excursion requirement. (If all modulation modes are not available on a single channel in a single band, then testing must be extended to other channels and bands as needed to ensure that all modulation modes are tested.)

2) Tests must include all variations in signal structure, such as:

- i) All signal types [e.g., direct sequence spread spectrum (DSSS) and OFDM].
- ii) All modulation types [e.g., binary phase-shift keying (BPSK), quadrature phase-shift keying (QPSK), 16-QAM, 64-QAM, and 256-QAM].
- iii) All bandwidth modes.
- iv) All variations in signal parameters (e.g., changes in subcarrier spacing or number of subcarriers).

3) For a given signal structure, testing of multiple error-correction coding rates is not





required (e.g., 1/2, 2/3, and 3/4).

4) For MIMO devices, testing of a single output port is sufficient to determine compliance with the peak excursion requirement. If a given signal structure can be exercised with various combinations of spatial multiplexing (such as different numbers of spatial streams), beamforming, and cyclic delay diversity, peak excursion tests are not required to include those variations.

b) The procedure is as follows:

1) Set the span of the spectrum analyzer or EMI receiver to view the entire emission bandwidth or occupied bandwidth.

2) Find the maximum of the peak-max-hold spectrum:

i) Set RBW = 1 MHz.

ii) VBW  $\square$  3 MHz.

iii) Detector = peak.

iv) Trace mode = max-hold.

v) Allow the sweeps to continue until the trace stabilizes.

vi) Use the peak search function to find the peak of the spectrum.

3) Use the procedure found in 12.5 to measure the PPSD.

4) Compute the ratio of the maximum of the peak-max-hold spectrum to the PPSD.

#### 11.4 Deviation From Test Standard

No deviation

#### 11.5 Antenna Connected Construction

Please refer to the description of test mode.

#### 11.6 Test Data

Please refer to the Appendix D.





## 12. Antenna Requirement

### 12.1 Test Standard and Limit

#### 12.1.1 Test Standard

##### **FCC Part 15.203**

#### 12.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 12.2 Deviation From Test Standard

No deviation

### 12.3 Antenna Connected Construction

The gains of the antenna used for transmitting is 2dBi, and the antenna de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

### 12.4 Test Data

The EUT antenna is a RP-SMA Antenna. It complies with the standard requirement.


Antenna Type
<input checked="" type="checkbox"/> Permanent attached antenna
<input type="checkbox"/> Unique connector antenna
<input type="checkbox"/> Professional installation antenna





## Attachment A-- Conducted Emission Test Data

Temperature:	24.3°C	Relative Humidity:	58%
Test Voltage:	AC 120V 60Hz		
Terminal:	Line		
Test Mode:	Mode 1		
Remark:	Only worse case is reported.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1580	30.13	11.09	41.22	65.56	-24.34	QP
2		0.1580	16.77	11.09	27.86	55.56	-27.70	AVG
3		0.3379	32.18	10.87	43.05	59.25	-16.20	QP
4	*	0.3379	25.80	10.87	36.67	49.25	-12.58	AVG
5		1.2620	17.14	10.64	27.78	56.00	-28.22	QP
6		1.2620	11.93	10.64	22.57	46.00	-23.43	AVG
7		6.6020	21.00	10.03	31.03	60.00	-28.97	QP
8		6.6020	15.43	10.03	25.46	50.00	-24.54	AVG
9		10.9580	26.66	10.17	36.83	60.00	-23.17	QP
10		10.9580	21.06	10.17	31.23	50.00	-18.77	AVG
11		29.4300	25.99	10.84	36.83	60.00	-23.17	QP
12		29.4300	20.15	10.84	30.99	50.00	-19.01	AVG


**Remark:**

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = QuasiPeak/Average (dBuV) - Limit (dBuV)





<b>Temperature:</b>	24.3°C	<b>Relative Humidity:</b>	58%
<b>Test Voltage:</b>	AC 120V 60Hz		
<b>Terminal:</b>	Neutral		
<b>Test Mode:</b>	Mode 1		
<b>Remark:</b>	Only worse case is reported.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1500	30.38	10.98	41.36	65.99	-24.63	QP
2		0.1500	16.00	10.98	26.98	55.99	-29.01	AVG
3		0.2260	20.73	11.08	31.81	62.59	-30.78	QP
4		0.2260	7.99	11.08	19.07	52.59	-33.52	AVG
5		0.3379	29.41	10.94	40.35	59.25	-18.90	QP
6		0.3379	22.50	10.94	33.44	49.25	-15.81	AVG
7		6.7980	21.24	10.06	31.30	60.00	-28.70	QP
8		6.7980	13.02	10.06	23.08	50.00	-26.92	AVG
9		11.3620	30.64	10.23	40.87	60.00	-19.13	QP
10		11.3620	23.96	10.23	34.19	50.00	-15.81	AVG
11		28.6380	32.56	10.97	43.53	60.00	-16.47	QP
12	*	28.6380	23.79	10.97	34.76	50.00	-15.24	AVG

**Remark:**  
 1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)  
 2. Margin (dB) = QuasiPeak/Average (dBuV) - Limit (dBuV)





## Attachment B--Unwanted Emissions Data

### ---Radiated Unwanted Emissions

#### 9 KHz~30 MHz


From 9 KHz to 30 MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB

Below the permissible value has no need to be reported.

#### 30MHz~1GHz

Temperature:	24.3°C	Relative Humidity:	45%
Test Voltage:	AC 120V 60Hz		
Ant. Pol.	Horizontal		
Test Mode:	Mode 2		
Remark:	Only worse case is reported.		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	73.1025	50.77	-25.21	25.56	40.00	-14.44	peak
2	148.4410	57.03	-22.48	34.55	43.50	-8.95	peak
3	186.4404	57.21	-24.21	33.00	43.50	-10.50	peak
4 !	297.2238	61.78	-20.94	40.84	46.00	-5.16	peak
5	444.8514	52.63	-16.78	35.85	46.00	-10.15	peak
6 *	760.7033	51.33	-9.84	41.49	46.00	-4.51	peak

\*:Maximum data    x:Over limit    !:over margin


#### Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = QuasiPeak (dBμV/m)-Limit QPK(dBμV/m)





<b>Temperature:</b>	24.3°C	<b>Relative Humidity:</b>	45%
<b>Test Voltage:</b>	AC 120V 60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	Mode 2		
<b>Remark:</b>	Only worse case is reported.		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	148.4410	58.71	-22.48	36.23	43.50	-7.27	peak
2 *	301.4223	59.84	-20.82	39.02	46.00	-6.98	peak
3	302.4811	58.74	-20.80	37.94	46.00	-8.06	peak
4	438.6553	50.70	-16.94	33.76	46.00	-12.24	peak
5	511.8351	52.75	-15.05	37.70	46.00	-8.30	peak
6	605.6592	50.47	-12.74	37.73	46.00	-8.27	peak

\*:Maximum data x:Over limit !:over margin

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = QuasiPeak (dBμV/m)-Limit QPK(dBμV/m)





**Above 1GHz**

**5180MHz-5240MHz(U-NII-1)**

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11a Mode 5180MHz (U-NII-1)		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	10360.325	48.20	6.06	54.26	68.30	-14.04	peak
2 *	10360.457	40.32	6.06	46.38	54.00	-7.62	AVG

**Remark:**  
**Remark:**  
 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)  
 2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)  
 3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)  
 4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.  
 5. No report for the emission which more than 20dB below the prescribed limit.

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11a Mode 5180MHz (U-NII-1)		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	10360.457	41.50	6.06	47.56	54.00	-6.44	AVG
2	10360.658	50.68	6.06	56.74	68.30	-11.56	peak

**Remark:**  
 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)  
 2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)  
 3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)  
 4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.  
 5. No report for the emission which more than 20dB below the prescribed limit.





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11a Mode 5200MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10400.174</td> <td>49.42</td> <td>6.21</td> <td>55.63</td> <td>68.30</td> <td>-12.67</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>10400.644</td> <td>40.31</td> <td>6.21</td> <td>46.52</td> <td>54.00</td> <td>-7.48</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10400.174	49.42	6.21	55.63	68.30	-12.67	peak	2 *	10400.644	40.31	6.21	46.52	54.00	-7.48	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	10400.174	49.42	6.21	55.63	68.30	-12.67	peak																				
2 *	10400.644	40.31	6.21	46.52	54.00	-7.48	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11a Mode 5200MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10400.253</td> <td>49.65</td> <td>6.21</td> <td>55.86</td> <td>68.30</td> <td>-12.44</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>10400.657</td> <td>40.50</td> <td>6.21</td> <td>46.71</td> <td>54.00</td> <td>-7.29</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10400.253	49.65	6.21	55.86	68.30	-12.44	peak	2 *	10400.657	40.50	6.21	46.71	54.00	-7.29	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	10400.253	49.65	6.21	55.86	68.30	-12.44	peak																				
2 *	10400.657	40.50	6.21	46.71	54.00	-7.29	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11a Mode 5240MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10480.245</td> <td>49.87</td> <td>6.36</td> <td>56.23</td> <td>68.30</td> <td>-12.07</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>10480.387</td> <td>40.35</td> <td>6.36</td> <td>46.71</td> <td>54.00</td> <td>-7.29</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10480.245	49.87	6.36	56.23	68.30	-12.07	peak	2 *	10480.387	40.35	6.36	46.71	54.00	-7.29	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	10480.245	49.87	6.36	56.23	68.30	-12.07	peak																				
2 *	10480.387	40.35	6.36	46.71	54.00	-7.29	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11a Mode 5240MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>10480.447</td> <td>39.35</td> <td>6.36</td> <td>45.71</td> <td>54.00</td> <td>-8.29</td> <td>AVG</td> </tr> <tr> <td>2</td> <td>10480.687</td> <td>49.76</td> <td>6.36</td> <td>56.12</td> <td>68.30</td> <td>-12.18</td> <td>peak</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10480.447	39.35	6.36	45.71	54.00	-8.29	AVG	2	10480.687	49.76	6.36	56.12	68.30	-12.18	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1 *	10480.447	39.35	6.36	45.71	54.00	-8.29	AVG																				
2	10480.687	49.76	6.36	56.12	68.30	-12.18	peak																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5180MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10360.317</td> <td>50.72</td> <td>6.06</td> <td>56.78</td> <td>68.30</td> <td>-11.52</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>10360.786</td> <td>41.50</td> <td>6.06</td> <td>47.56</td> <td>54.00</td> <td>-6.44</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10360.317	50.72	6.06	56.78	68.30	-11.52	peak	2 *	10360.786	41.50	6.06	47.56	54.00	-6.44	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	10360.317	50.72	6.06	56.78	68.30	-11.52	peak																				
2 *	10360.786	41.50	6.06	47.56	54.00	-6.44	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5180MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10360.287</td> <td>50.39</td> <td>6.06</td> <td>56.45</td> <td>68.30</td> <td>-11.85</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>10360.341</td> <td>41.50</td> <td>6.06</td> <td>47.56</td> <td>54.00</td> <td>-6.44</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10360.287	50.39	6.06	56.45	68.30	-11.85	peak	2 *	10360.341	41.50	6.06	47.56	54.00	-6.44	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	10360.287	50.39	6.06	56.45	68.30	-11.85	peak																				
2 *	10360.341	41.50	6.06	47.56	54.00	-6.44	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5200MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10400.325</td> <td>49.68</td> <td>6.21</td> <td>55.89</td> <td>68.30</td> <td>-12.41</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>10400.387</td> <td>40.38</td> <td>6.21</td> <td>46.59</td> <td>54.00</td> <td>-7.41</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10400.325	49.68	6.21	55.89	68.30	-12.41	peak	2 *	10400.387	40.38	6.21	46.59	54.00	-7.41	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	10400.325	49.68	6.21	55.89	68.30	-12.41	peak																				
2 *	10400.387	40.38	6.21	46.59	54.00	-7.41	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5200MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10400.315</td> <td>50.52</td> <td>6.21</td> <td>56.73</td> <td>68.30</td> <td>-11.57</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>10400.786</td> <td>41.34</td> <td>6.21</td> <td>47.55</td> <td>54.00</td> <td>-6.45</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10400.315	50.52	6.21	56.73	68.30	-11.57	peak	2 *	10400.786	41.34	6.21	47.55	54.00	-6.45	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	10400.315	50.52	6.21	56.73	68.30	-11.57	peak																				
2 *	10400.786	41.34	6.21	47.55	54.00	-6.45	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5240MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10480.668</td> <td>50.83</td> <td>6.36</td> <td>57.19</td> <td>68.30</td> <td>-11.11</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>10480.677</td> <td>40.39</td> <td>6.36</td> <td>46.75</td> <td>54.00</td> <td>-7.25</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10480.668	50.83	6.36	57.19	68.30	-11.11	peak	2 *	10480.677	40.39	6.36	46.75	54.00	-7.25	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	10480.668	50.83	6.36	57.19	68.30	-11.11	peak																				
2 *	10480.677	40.39	6.36	46.75	54.00	-7.25	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5240MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>10480.228</td> <td>39.92</td> <td>6.36</td> <td>46.28</td> <td>54.00</td> <td>-7.72</td> <td>AVG</td> </tr> <tr> <td>2</td> <td>10480.382</td> <td>48.20</td> <td>6.36</td> <td>54.56</td> <td>68.30</td> <td>-13.74</td> <td>peak</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10480.228	39.92	6.36	46.28	54.00	-7.72	AVG	2	10480.382	48.20	6.36	54.56	68.30	-13.74	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1 *	10480.228	39.92	6.36	46.28	54.00	-7.72	AVG																				
2	10480.382	48.20	6.36	54.56	68.30	-13.74	peak																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5180MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>10360.147</td> <td>40.19</td> <td>6.06</td> <td>46.25</td> <td>54.00</td> <td>-7.75</td> <td>AVG</td> </tr> <tr> <td>2</td> <td>10360.328</td> <td>50.78</td> <td>6.06</td> <td>56.84</td> <td>68.30</td> <td>-11.46</td> <td>peak</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10360.147	40.19	6.06	46.25	54.00	-7.75	AVG	2	10360.328	50.78	6.06	56.84	68.30	-11.46	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1 *	10360.147	40.19	6.06	46.25	54.00	-7.75	AVG																				
2	10360.328	50.78	6.06	56.84	68.30	-11.46	peak																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5180MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10360.296</td> <td>50.22</td> <td>6.06</td> <td>56.28</td> <td>68.30</td> <td>-12.02</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>10360.956</td> <td>41.45</td> <td>6.06</td> <td>47.51</td> <td>54.00</td> <td>-6.49</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10360.296	50.22	6.06	56.28	68.30	-12.02	peak	2 *	10360.956	41.45	6.06	47.51	54.00	-6.49	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	10360.296	50.22	6.06	56.28	68.30	-12.02	peak																				
2 *	10360.956	41.45	6.06	47.51	54.00	-6.49	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5200MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>10400.441</td> <td>40.37</td> <td>6.21</td> <td>46.58</td> <td>54.00</td> <td>-7.42</td> <td>AVG</td> </tr> <tr> <td>2</td> <td>10400.652</td> <td>50.85</td> <td>6.21</td> <td>57.06</td> <td>68.30</td> <td>-11.24</td> <td>peak</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10400.441	40.37	6.21	46.58	54.00	-7.42	AVG	2	10400.652	50.85	6.21	57.06	68.30	-11.24	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1 *	10400.441	40.37	6.21	46.58	54.00	-7.42	AVG																				
2	10400.652	50.85	6.21	57.06	68.30	-11.24	peak																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5200MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>10400.336</td> <td>39.61</td> <td>6.21</td> <td>45.82</td> <td>54.00</td> <td>-8.18</td> <td>AVG</td> </tr> <tr> <td>2</td> <td>10400.785</td> <td>49.98</td> <td>6.21</td> <td>56.19</td> <td>68.30</td> <td>-12.11</td> <td>peak</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10400.336	39.61	6.21	45.82	54.00	-8.18	AVG	2	10400.785	49.98	6.21	56.19	68.30	-12.11	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1 *	10400.336	39.61	6.21	45.82	54.00	-8.18	AVG																				
2	10400.785	49.98	6.21	56.19	68.30	-12.11	peak																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11 ac(VHT20) Mode 5240MHz (U-NII-1)		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	10480.445	50.93	6.36	57.29	68.30	-11.01	peak
2 *	10480.625	39.77	6.36	46.13	54.00	-7.87	AVG

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5240MHz (U-NII-1)		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	10480.374	38.83	6.36	45.19	54.00	-8.81	AVG
2	10480.659	49.90	6.36	56.26	68.30	-12.04	peak

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG (dBμV/m)
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5190MHz (U-NII-1)		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	10380.377	50.14	6.14	56.28	68.30	-12.02	peak
2 *	10380.653	40.89	6.14	47.03	54.00	-6.97	AVG

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)
4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5190MHz (U-NII-1)		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	10380.269	50.61	6.14	56.75	68.30	-11.55	peak
2 *	10380.882	40.41	6.14	46.55	54.00	-7.45	AVG

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)
4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5230MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10460.259</td> <td>49.93</td> <td>6.32</td> <td>56.25</td> <td>68.30</td> <td>-12.05</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>10460.357</td> <td>40.53</td> <td>6.32</td> <td>46.85</td> <td>54.00</td> <td>-7.15</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10460.259	49.93	6.32	56.25	68.30	-12.05	peak	2 *	10460.357	40.53	6.32	46.85	54.00	-7.15	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	10460.259	49.93	6.32	56.25	68.30	-12.05	peak																				
2 *	10460.357	40.53	6.32	46.85	54.00	-7.15	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5230MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10460.113</td> <td>50.96</td> <td>6.32</td> <td>57.28</td> <td>68.30</td> <td>-11.02</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>10460.451</td> <td>40.50</td> <td>6.32</td> <td>46.82</td> <td>54.00</td> <td>-7.18</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10460.113	50.96	6.32	57.28	68.30	-11.02	peak	2 *	10460.451	40.50	6.32	46.82	54.00	-7.18	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	10460.113	50.96	6.32	57.28	68.30	-11.02	peak																				
2 *	10460.451	40.50	6.32	46.82	54.00	-7.18	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5190MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>10380.264</td> <td>40.39</td> <td>6.14</td> <td>46.53</td> <td>54.00</td> <td>-7.47</td> <td>AVG</td> </tr> <tr> <td>2</td> <td>10380.388</td> <td>50.57</td> <td>6.14</td> <td>56.71</td> <td>68.30</td> <td>-11.59</td> <td>peak</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10380.264	40.39	6.14	46.53	54.00	-7.47	AVG	2	10380.388	50.57	6.14	56.71	68.30	-11.59	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1 *	10380.264	40.39	6.14	46.53	54.00	-7.47	AVG																				
2	10380.388	50.57	6.14	56.71	68.30	-11.59	peak																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5190MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10380.254</td> <td>49.97</td> <td>6.14</td> <td>56.11</td> <td>68.30</td> <td>-12.19</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>10380.345</td> <td>39.72</td> <td>6.14</td> <td>45.86</td> <td>54.00</td> <td>-8.14</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10380.254	49.97	6.14	56.11	68.30	-12.19	peak	2 *	10380.345	39.72	6.14	45.86	54.00	-8.14	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	10380.254	49.97	6.14	56.11	68.30	-12.19	peak																				
2 *	10380.345	39.72	6.14	45.86	54.00	-8.14	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5230MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10460.341</td> <td>49.64</td> <td>6.32</td> <td>55.96</td> <td>68.30</td> <td>-12.34</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>10460.389</td> <td>39.86</td> <td>6.32</td> <td>46.18</td> <td>54.00</td> <td>-7.82</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10460.341	49.64	6.32	55.96	68.30	-12.34	peak	2 *	10460.389	39.86	6.32	46.18	54.00	-7.82	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	10460.341	49.64	6.32	55.96	68.30	-12.34	peak																				
2 *	10460.389	39.86	6.32	46.18	54.00	-7.82	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5230MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10460.441</td> <td>50.05</td> <td>6.32</td> <td>56.37</td> <td>68.30</td> <td>-11.93</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>10460.454</td> <td>40.20</td> <td>6.32</td> <td>46.52</td> <td>54.00</td> <td>-7.48</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10460.441	50.05	6.32	56.37	68.30	-11.93	peak	2 *	10460.454	40.20	6.32	46.52	54.00	-7.48	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	10460.441	50.05	6.32	56.37	68.30	-11.93	peak																				
2 *	10460.454	40.20	6.32	46.52	54.00	-7.48	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11ac(VHT80) Mode 5210MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>10420.356</td> <td>40.57</td> <td>6.25</td> <td>46.82</td> <td>54.00</td> <td>-7.18</td> <td>AVG</td> </tr> <tr> <td>2</td> <td>10420.358</td> <td>50.86</td> <td>6.25</td> <td>57.11</td> <td>68.30</td> <td>-11.19</td> <td>peak</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10420.356	40.57	6.25	46.82	54.00	-7.18	AVG	2	10420.358	50.86	6.25	57.11	68.30	-11.19	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1 *	10420.356	40.57	6.25	46.82	54.00	-7.18	AVG																				
2	10420.358	50.86	6.25	57.11	68.30	-11.19	peak																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11ac(VHT80) Mode 5210MHz (U-NII-1)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>10420.145</td> <td>50.58</td> <td>6.25</td> <td>56.83</td> <td>68.30</td> <td>-11.47</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>10420.451</td> <td>39.67</td> <td>6.25</td> <td>45.92</td> <td>54.00</td> <td>-8.08</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10420.145	50.58	6.25	56.83	68.30	-11.47	peak	2 *	10420.451	39.67	6.25	45.92	54.00	-8.08	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	10420.145	50.58	6.25	56.83	68.30	-11.47	peak																				
2 *	10420.451	39.67	6.25	45.92	54.00	-8.08	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											





**5745MHz-5825MHz(U-NII-3)**

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11a Mode 5745MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11490.325</td> <td>46.37</td> <td>8.99</td> <td>55.36</td> <td>68.30</td> <td>-12.94</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>11490.685</td> <td>37.54</td> <td>8.99</td> <td>46.53</td> <td>54.00</td> <td>-7.47</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11490.325	46.37	8.99	55.36	68.30	-12.94	peak	2 *	11490.685	37.54	8.99	46.53	54.00	-7.47	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	11490.325	46.37	8.99	55.36	68.30	-12.94	peak																				
2 *	11490.685	37.54	8.99	46.53	54.00	-7.47	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11a Mode 5745MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11490.544</td> <td>36.73</td> <td>8.99</td> <td>45.72</td> <td>54.00</td> <td>-8.28</td> <td>AVG</td> </tr> <tr> <td>2</td> <td>11490.716</td> <td>47.12</td> <td>8.99</td> <td>56.11</td> <td>68.30</td> <td>-12.19</td> <td>peak</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11490.544	36.73	8.99	45.72	54.00	-8.28	AVG	2	11490.716	47.12	8.99	56.11	68.30	-12.19	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1 *	11490.544	36.73	8.99	45.72	54.00	-8.28	AVG																				
2	11490.716	47.12	8.99	56.11	68.30	-12.19	peak																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11a Mode 5785MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11570.312</td> <td>37.83</td> <td>8.75</td> <td>46.58</td> <td>54.00</td> <td>-7.42</td> <td>AVG</td> </tr> <tr> <td>2</td> <td>11570.657</td> <td>47.67</td> <td>8.75</td> <td>56.42</td> <td>68.30</td> <td>-11.88</td> <td>peak</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11570.312	37.83	8.75	46.58	54.00	-7.42	AVG	2	11570.657	47.67	8.75	56.42	68.30	-11.88	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1 *	11570.312	37.83	8.75	46.58	54.00	-7.42	AVG																				
2	11570.657	47.67	8.75	56.42	68.30	-11.88	peak																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11a Mode 5785MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11570.268</td> <td>48.37</td> <td>8.75</td> <td>57.12</td> <td>68.30</td> <td>-11.18</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>11570.753</td> <td>36.93</td> <td>8.75</td> <td>45.68</td> <td>54.00</td> <td>-8.32</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11570.268	48.37	8.75	57.12	68.30	-11.18	peak	2 *	11570.753	36.93	8.75	45.68	54.00	-8.32	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	11570.268	48.37	8.75	57.12	68.30	-11.18	peak																				
2 *	11570.753	36.93	8.75	45.68	54.00	-8.32	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11a Mode 5825MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11650.237</td> <td>37.48</td> <td>8.70</td> <td>46.18</td> <td>54.00</td> <td>-7.82</td> <td>AVG</td> </tr> <tr> <td>2</td> <td>11650.544</td> <td>46.75</td> <td>8.70</td> <td>55.45</td> <td>68.30</td> <td>-12.85</td> <td>peak</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11650.237	37.48	8.70	46.18	54.00	-7.82	AVG	2	11650.544	46.75	8.70	55.45	68.30	-12.85	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1 *	11650.237	37.48	8.70	46.18	54.00	-7.82	AVG																				
2	11650.544	46.75	8.70	55.45	68.30	-12.85	peak																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11a Mode 5825MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11650.476</td> <td>46.66</td> <td>8.70</td> <td>55.36</td> <td>68.30</td> <td>-12.94</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>11650.654</td> <td>36.75</td> <td>8.70</td> <td>45.45</td> <td>54.00</td> <td>-8.55</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11650.476	46.66	8.70	55.36	68.30	-12.94	peak	2 *	11650.654	36.75	8.70	45.45	54.00	-8.55	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	11650.476	46.66	8.70	55.36	68.30	-12.94	peak																				
2 *	11650.654	36.75	8.70	45.45	54.00	-8.55	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5745MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11490.597</td> <td>47.74</td> <td>8.99</td> <td>56.73</td> <td>68.30</td> <td>-11.57</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>11490.964</td> <td>36.84</td> <td>8.99</td> <td>45.83</td> <td>54.00</td> <td>-8.17</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11490.597	47.74	8.99	56.73	68.30	-11.57	peak	2 *	11490.964	36.84	8.99	45.83	54.00	-8.17	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	11490.597	47.74	8.99	56.73	68.30	-11.57	peak																				
2 *	11490.964	36.84	8.99	45.83	54.00	-8.17	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5745MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11490.335</td> <td>48.20</td> <td>8.99</td> <td>57.19</td> <td>68.30</td> <td>-11.11</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>11490.828</td> <td>37.83</td> <td>8.99</td> <td>46.82</td> <td>54.00</td> <td>-7.18</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11490.335	48.20	8.99	57.19	68.30	-11.11	peak	2 *	11490.828	37.83	8.99	46.82	54.00	-7.18	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	11490.335	48.20	8.99	57.19	68.30	-11.11	peak																				
2 *	11490.828	37.83	8.99	46.82	54.00	-7.18	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m) - Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5785MHz (U-NII-3)		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	11570.329	48.49	8.75	57.24	68.30	-11.06	peak
2 *	11570.891	37.76	8.75	46.51	54.00	-7.49	AVG

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)
4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5785MHz (U-NII-3)		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	11570.398	37.24	8.75	45.99	54.00	-8.01	AVG
2	11570.652	47.51	8.75	56.26	68.30	-12.04	peak

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)
4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5825MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11650.265</td> <td>49.51</td> <td>8.70</td> <td>58.21</td> <td>68.30</td> <td>-10.09</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>11650.554</td> <td>38.39</td> <td>8.70</td> <td>47.09</td> <td>54.00</td> <td>-6.91</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11650.265	49.51	8.70	58.21	68.30	-10.09	peak	2 *	11650.554	38.39	8.70	47.09	54.00	-6.91	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	11650.265	49.51	8.70	58.21	68.30	-10.09	peak																				
2 *	11650.554	38.39	8.70	47.09	54.00	-6.91	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5825MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11650.349</td> <td>48.01</td> <td>8.70</td> <td>56.71</td> <td>68.30</td> <td>-11.59</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>11650.455</td> <td>37.52</td> <td>8.70</td> <td>46.22</td> <td>54.00</td> <td>-7.78</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11650.349	48.01	8.70	56.71	68.30	-11.59	peak	2 *	11650.455	37.52	8.70	46.22	54.00	-7.78	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	11650.349	48.01	8.70	56.71	68.30	-11.59	peak																				
2 *	11650.455	37.52	8.70	46.22	54.00	-7.78	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5745MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11490.537</td> <td>38.53</td> <td>8.99</td> <td>47.52</td> <td>54.00</td> <td>-6.48</td> <td>AVG</td> </tr> <tr> <td>2</td> <td>11490.645</td> <td>47.53</td> <td>8.99</td> <td>56.52</td> <td>68.30</td> <td>-11.78</td> <td>peak</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11490.537	38.53	8.99	47.52	54.00	-6.48	AVG	2	11490.645	47.53	8.99	56.52	68.30	-11.78	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1 *	11490.537	38.53	8.99	47.52	54.00	-6.48	AVG																				
2	11490.645	47.53	8.99	56.52	68.30	-11.78	peak																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5745MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11490.123</td> <td>37.53</td> <td>8.99</td> <td>46.52</td> <td>54.00</td> <td>-7.48</td> <td>AVG</td> </tr> <tr> <td>2</td> <td>11490.327</td> <td>46.63</td> <td>8.99</td> <td>55.62</td> <td>68.30</td> <td>-12.68</td> <td>peak</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11490.123	37.53	8.99	46.52	54.00	-7.48	AVG	2	11490.327	46.63	8.99	55.62	68.30	-12.68	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1 *	11490.123	37.53	8.99	46.52	54.00	-7.48	AVG																				
2	11490.327	46.63	8.99	55.62	68.30	-12.68	peak																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											



<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5785MHz (U-NII-3)		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	11570.547	47.82	8.75	56.57	68.30	-11.73	peak
2 *	11570.657	36.97	8.75	45.72	54.00	-8.28	AVG

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)
4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%
<b>Test Voltage:</b>	DC 5V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5785MHz (U-NII-3)		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	11570.574	37.77	8.75	46.52	54.00	-7.48	AVG
2	11570.648	48.48	8.75	57.23	68.30	-11.07	peak

**Remark:**

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)
4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.
5. No report for the emission which more than 20dB below the prescribed limit.





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5825MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11650.246</td> <td>48.42</td> <td>8.70</td> <td>57.12</td> <td>68.30</td> <td>-11.18</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>11650.958</td> <td>37.82</td> <td>8.70</td> <td>46.52</td> <td>54.00</td> <td>-7.48</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11650.246	48.42	8.70	57.12	68.30	-11.18	peak	2 *	11650.958	37.82	8.70	46.52	54.00	-7.48	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	11650.246	48.42	8.70	57.12	68.30	-11.18	peak																				
2 *	11650.958	37.82	8.70	46.52	54.00	-7.48	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5825MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11650.324</td> <td>48.02</td> <td>8.70</td> <td>56.72</td> <td>68.30</td> <td>-11.58</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>11650.431</td> <td>38.83</td> <td>8.70</td> <td>47.53</td> <td>54.00</td> <td>-6.47</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11650.324	48.02	8.70	56.72	68.30	-11.58	peak	2 *	11650.431	38.83	8.70	47.53	54.00	-6.47	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	11650.324	48.02	8.70	56.72	68.30	-11.58	peak																				
2 *	11650.431	38.83	8.70	47.53	54.00	-6.47	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											



<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5755MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11510.257</td> <td>37.93</td> <td>8.95</td> <td>46.88</td> <td>54.00</td> <td>-7.12</td> <td>AVG</td> </tr> <tr> <td>2</td> <td>11510.628</td> <td>48.07</td> <td>8.95</td> <td>57.02</td> <td>68.30</td> <td>-11.28</td> <td>peak</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11510.257	37.93	8.95	46.88	54.00	-7.12	AVG	2	11510.628	48.07	8.95	57.02	68.30	-11.28	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1 *	11510.257	37.93	8.95	46.88	54.00	-7.12	AVG																				
2	11510.628	48.07	8.95	57.02	68.30	-11.28	peak																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5755MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11510.338</td> <td>47.91</td> <td>8.95</td> <td>56.86</td> <td>68.30</td> <td>-11.44</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>11510.685</td> <td>38.08</td> <td>8.95</td> <td>47.03</td> <td>54.00</td> <td>-6.97</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11510.338	47.91	8.95	56.86	68.30	-11.44	peak	2 *	11510.685	38.08	8.95	47.03	54.00	-6.97	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	11510.338	47.91	8.95	56.86	68.30	-11.44	peak																				
2 *	11510.685	38.08	8.95	47.03	54.00	-6.97	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5795MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11590.442</td> <td>48.08</td> <td>8.69</td> <td>56.77</td> <td>68.30</td> <td>-11.53</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>11590.895</td> <td>37.66</td> <td>8.69</td> <td>46.35</td> <td>54.00</td> <td>-7.65</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11590.442	48.08	8.69	56.77	68.30	-11.53	peak	2 *	11590.895	37.66	8.69	46.35	54.00	-7.65	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	11590.442	48.08	8.69	56.77	68.30	-11.53	peak																				
2 *	11590.895	37.66	8.69	46.35	54.00	-7.65	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)</li> <li>3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG(dBuV/m)</li> <li>4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5795MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11590.667</td> <td>37.29</td> <td>8.69</td> <td>45.98</td> <td>54.00</td> <td>-8.02</td> <td>AVG</td> </tr> <tr> <td>2</td> <td>11590.678</td> <td>48.77</td> <td>8.69</td> <td>57.46</td> <td>68.30</td> <td>-10.84</td> <td>peak</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11590.667	37.29	8.69	45.98	54.00	-8.02	AVG	2	11590.678	48.77	8.69	57.46	68.30	-10.84	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1 *	11590.667	37.29	8.69	45.98	54.00	-8.02	AVG																				
2	11590.678	48.77	8.69	57.46	68.30	-10.84	peak																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBuV/m) = Corr. (dB/m) + Read Level (dBuV)</li> <li>3. Margin (dB) = Peak/AVG (dBuV/m) - Limit PK/AVG(dBuV/m)</li> <li>4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											



<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5755MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11510.385</td> <td>37.76</td> <td>8.95</td> <td>46.71</td> <td>54.00</td> <td>-7.29</td> <td>AVG</td> </tr> <tr> <td>2</td> <td>11510.658</td> <td>46.73</td> <td>8.95</td> <td>55.68</td> <td>68.30</td> <td>-12.62</td> <td>peak</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11510.385	37.76	8.95	46.71	54.00	-7.29	AVG	2	11510.658	46.73	8.95	55.68	68.30	-12.62	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1 *	11510.385	37.76	8.95	46.71	54.00	-7.29	AVG																				
2	11510.658	46.73	8.95	55.68	68.30	-12.62	peak																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5755MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11510.128</td> <td>47.42</td> <td>8.95</td> <td>56.37</td> <td>68.30</td> <td>-11.93</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>11510.545</td> <td>37.58</td> <td>8.95</td> <td>46.53</td> <td>54.00</td> <td>-7.47</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11510.128	47.42	8.95	56.37	68.30	-11.93	peak	2 *	11510.545	37.58	8.95	46.53	54.00	-7.47	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	11510.128	47.42	8.95	56.37	68.30	-11.93	peak																				
2 *	11510.545	37.58	8.95	46.53	54.00	-7.47	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											





<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5795MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11590.357</td> <td>48.85</td> <td>8.69</td> <td>57.54</td> <td>68.30</td> <td>-10.76</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>11590.564</td> <td>37.89</td> <td>8.69</td> <td>46.58</td> <td>54.00</td> <td>-7.42</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11590.357	48.85	8.69	57.54	68.30	-10.76	peak	2 *	11590.564	37.89	8.69	46.58	54.00	-7.42	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	11590.357	48.85	8.69	57.54	68.30	-10.76	peak																				
2 *	11590.564	37.89	8.69	46.58	54.00	-7.42	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBµV/m)= Corr. (dB/m)+ Read Level (dBµV)</li> <li>3. Margin (dB) = Peak/AVG (dBµV/m)-Limit PK/AVG(dBµV/m)</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5795MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11590.143</td> <td>37.69</td> <td>8.69</td> <td>46.38</td> <td>54.00</td> <td>-7.62</td> <td>AVG</td> </tr> <tr> <td>2</td> <td>11590.245</td> <td>47.66</td> <td>8.69</td> <td>56.35</td> <td>68.30</td> <td>-11.95</td> <td>peak</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11590.143	37.69	8.69	46.38	54.00	-7.62	AVG	2	11590.245	47.66	8.69	56.35	68.30	-11.95	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1 *	11590.143	37.69	8.69	46.38	54.00	-7.62	AVG																				
2	11590.245	47.66	8.69	56.35	68.30	-11.95	peak																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBµV/m)= Corr. (dB/m)+ Read Level (dBµV)</li> <li>3. Margin (dB) = Peak/AVG (dBµV/m)-Limit PK/AVG(dBµV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											



<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Horizontal																										
<b>Test Mode:</b>	TX 802.11ac(VHT80) Mode 5775MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1 *</td> <td>11550.000</td> <td>49.54</td> <td>8.82</td> <td>58.36</td> <td>68.30</td> <td>-9.94</td> <td>peak</td> </tr> <tr> <td>2</td> <td>11550.890</td> <td>34.72</td> <td>8.82</td> <td>43.54</td> <td>54.00</td> <td>-10.46</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11550.000	49.54	8.82	58.36	68.30	-9.94	peak	2	11550.890	34.72	8.82	43.54	54.00	-10.46	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1 *	11550.000	49.54	8.82	58.36	68.30	-9.94	peak																				
2	11550.890	34.72	8.82	43.54	54.00	-10.46	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

<b>Temperature:</b>	23.5°C	<b>Relative Humidity:</b>	54%																								
<b>Test Voltage:</b>	DC 5V																										
<b>Ant. Pol.</b>	Vertical																										
<b>Test Mode:</b>	TX 802.11ac(VHT80) Mode 5775MHz (U-NII-3)																										
<table border="1"> <thead> <tr> <th>No.</th> <th>Frequency (MHz)</th> <th>Reading (dBuV)</th> <th>Factor (dB/m)</th> <th>Level (dBuV/m)</th> <th>Limit (dBuV/m)</th> <th>Margin (dB)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>11510.578</td> <td>48.41</td> <td>8.95</td> <td>57.36</td> <td>68.30</td> <td>-10.94</td> <td>peak</td> </tr> <tr> <td>2 *</td> <td>11510.643</td> <td>37.88</td> <td>8.95</td> <td>46.83</td> <td>54.00</td> <td>-7.17</td> <td>AVG</td> </tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11510.578	48.41	8.95	57.36	68.30	-10.94	peak	2 *	11510.643	37.88	8.95	46.83	54.00	-7.17	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																				
1	11510.578	48.41	8.95	57.36	68.30	-10.94	peak																				
2 *	11510.643	37.88	8.95	46.83	54.00	-7.17	AVG																				
<p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)</li> <li>2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)</li> <li>3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)</li> <li>4. The tests evaluated1-40GHz,The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz.</li> <li>5. No report for the emission which more than 20dB below the prescribed limit.</li> </ol>																											

-----END OF REPORT-----

