



FCC PART 15B

TEST REPORT

For

3Dconnexion

3/5 Avenue des Citronniers, 98000, Monaco

FCC ID: 2AAHQ-SMW

Report Type: Original Report	Product Type: SpaceMouse Wireless
Test Engineer: Ares Liu	<i>Ares Liu</i>
Report Number: R2XM130719050-00B	
Report Date: 2013-08-01	
Reviewed By: RF Leader	Ivan Cao <i>Ivan Cao</i>
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.
* This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★" (Rev.2).
This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....3
 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....3
 OBJECTIVE3
 RELATED SUBMITTAL(S)/GRANT(S).....3
 TEST FACILITY3

SYSTEM TEST CONFIGURATION.....4
 JUSTIFICATION4
 EUT EXERCISE SOFTWARE4
 EQUIPMENT MODIFICATIONS4
 SUPPORT EQUIPMENT LIST AND DETAILS4
 EXTERNAL CABLE.....4
 BLOCK DIAGRAM OF TEST SETUP5

SUMMARY OF TEST RESULTS6

FCC §15.107 – AC LINE CONDUCTED EMISSIONS.....7
 MEASUREMENT UNCERTAINTY7
 EUT SETUP7
 EMI TEST RECEIVER SETUP.....8
 TEST PROCEDURE8
 CORRECTED AMPLITUDE & MARGIN CALCULATION8
 TEST EQUIPMENT LIST AND DETAILS.....9
 TEST RESULTS SUMMARY9
 TEST DATA9

FCC §15.109 - RADIATED EMISSIONS12
 MEASUREMENT UNCERTAINTY12
 EUT SETUP12
 EMI TEST RECEIVER SETUP.....13
 TEST PROCEDURE13
 CORRECTED AMPLITUDE & MARGIN CALCULATION13
 TEST EQUIPMENT LIST AND DETAILS.....14
 TEST RESULTS SUMMARY14
 TEST DATA14

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *3Dconnexion*'s product, model number: *SpaceMouse Wireless* (FCC ID: 2AAHQ-SMW) (the "EUT") in this report was a *SpaceMouse Wireless*, which was measured approximately: 7.8 cm (L) x 7.8 cm (W) x 5.2 cm (H), rated input voltage: DC 3.7 V from lithium battery or DC 5V from system.

* All measurement and test data in this report was gathered from production sample serial number: 130719050 (Assigned by BACL, Dongguan). The EUT was received on 2013-07-19.

Objective

This report is prepared on behalf of *3Dconnexion* in accordance with Part 2, Subpart J, Part 15, Subparts A and B of the Federal Communication Commissions rules.

The objective of the manufacturer is to determine compliance with FCC Part 15B, Class B.

Related Submittal(s)/Grant(s)

FCC Part 15C DXX submissions with FCC ID: 2AAHQ-SMW.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Dongguan) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 500069-0).



The current scope of accreditations can be found at <http://ts.nist.gov/standards/scopes/5000690.htm>

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in a typical fashion (as normally used by a typical user). The highest operating frequency is 96MHz.

EUT Exercise Software

No exercise software was used.

Equipment Modifications

No modification was made to the EUT tested.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
HP	Printer	C3941A	JPTVOB2337
SAST	Modem	AEM-2100	0293
DELL	Keyboard	L100	CNORH656658907BL05DC
DELL	Laptop	PP11L	QDS-BRCM1017

External Cable

Cable Description	Length (m)	From Port	To
Shielded Detachable Printer Cable	1.2	Parallel Port of Laptop	Printer
Shielded Detachable Serial Cable	1.2	Serial Port of Laptop	Modem
Shielded Detachable Keyboard Cable	1.5	Keyboard Port of Laptop	Keyboard
Shielded Detachable USB Cable	1.5	Laptop	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§15.107	AC Line Conducted Emissions	Compliance
§15.109	Radiated Emissions	Compliance

FCC §15.107 – AC LINE CONDUCTED EMISSIONS

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cispr}

Measurement	U_{cispr}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.107 Class B limits.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI TEST RECEIVER	ESCS 30	830245/006	2013-1-10	2014-1-9
R&S	L.I.S.N	ESH3-Z5	843331/015	2012-9-17	2013-9-16
R&S	L.I.S.N	ESH3-Z5	100113	2012-11-29	2013-11-28
BACL	Test Software	BACL-EMC	V1.0-2010	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.107, with the worst margin reading of:

8.53 dB at 0.310 MHz in the **Line** conducted mode.

Test Data


Environmental Conditions

Temperature:	27.6 °C
Relative Humidity:	61 %
ATM Pressure:	100.1 kPa

The testing was performed by Ares Liu on 2013-07-30.


Test mode: Operating

120 V, 60 Hz, Line:



Frequency (MHz)	Cord. Reading (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/AV/QP)
0.150	53.53	0.47	66.00	12.47	QP
0.150	35.73	0.47	56.00	20.27	AV
0.210	49.70	0.42	63.21	13.51	QP
0.210	38.26	0.42	53.21	14.95	AV
0.310	43.40	0.34	59.97	16.57	QP
0.310	41.44	0.34	49.97	8.53	AV
0.420	38.83	0.32	57.45	18.62	QP
0.420	25.30	0.32	47.45	22.15	AV
0.620	34.91	0.31	56.00	21.09	QP
0.620	29.01	0.31	46.00	16.99	AV
1.190	32.25	0.33	56.00	23.75	QP
1.190	32.09	0.33	46.00	13.91	AV

120 V, 60 Hz, Neutral:



Frequency (MHz)	Cord. Reading (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/AV/QP)
0.150	50.69	0.26	66.00	15.31	QP
0.150	41.27	0.26	56.00	14.73	AV
0.320	35.20	0.23	59.71	24.51	QP
0.320	34.67	0.23	49.71	15.04	AV
0.610	28.59	0.21	56.00	27.41	QP
0.610	23.56	0.21	46.00	22.44	AV
0.760	32.85	0.22	56.00	23.15	QP
0.760	27.00	0.22	46.00	19.00	AV
1.410	31.93	0.25	56.00	24.07	QP
1.410	26.30	0.25	46.00	19.70	AV
2.250	28.66	0.28	56.00	27.34	QP
2.250	22.33	0.28	46.00	23.67	AV

FCC §15.109 - RADIATED EMISSIONS

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:


- 30M~200MHz: 5.0 dB
- 200M~1GHz: 6.2 dB
- 1G~6GHz: 4.45 dB
- 6G~18GHz: 5.23 dB

Table 2 – Values of U_{cispr}

Measurement	U_{cispr}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1 GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC Part 15.109, Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

According to FCC 15.33 requirements, the system was measured from 30 MHz to 1 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz – 1000 MHz	120 kHz	300 kHz	120kHz	QP

Test Procedure

For the radiated emissions test, the adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The data was recorded in Quasi-peak detection mode for 30 MHz to 1 GHz, Peak and average detection mode above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI TEST RECEIVER	ESCI	100224	2013-5-6	2014-5-5
Sunol Sciences	Antenna	JB3	A060611-1	2012-9-6	2015-9-5
HP	HP AMPLIFIER	8447E	2434A02181	N/A	N/A
R&S	Spectrum analyzer	FSEM 30	849016/001	2012-9-4	2013-9-3
ETS LINDGREN	horn antenna	3115	000 527 35	2012-9-6	2015-9-5
Mini-Circuit	Amplifier	ZVA-213-S+	54201245	N/A	N/A
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.109, Class B, with the worst margin reading of:

5.10 dB at 555.7400 MHz in the Vertical polarization

Test Data

Environmental Conditions


Temperature:	25.2 °C
Relative Humidity:	60 %
ATM Pressure:	100 kPa

The testing was performed by Ares Liu on 2013-07-31.

Test mode: Operating

Horizontal:


80.0 dBuV/m



Frequency (MHz)	Receiver Reading (dBuV/m)	Detector (PK/QP/Ave)	Correction Factor (dB)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
135.7300	37.86	QP	-6.86	31.00	43.50	12.50
199.7500	38.95	QP	-7.75	31.20	43.50	12.30
243.4000	41.80	QP	-8.10	33.70	46.00	12.30
271.5300	40.06	QP	-6.56	33.50	46.00	12.50
565.4400	35.95	QP	-1.55	34.40	46.00	11.60
796.3000	33.12	QP	1.68	34.80	46.00	11.20

Vertical:

80.0 dBuV/m



Frequency (MHz)	Receiver Reading (dBuV/m)	Detector (PK/QP/Ave)	Correction Factor (dB)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
40.6700	40.03	QP	-6.93	33.10	40.00	6.90
199.7500	37.55	QP	-7.75	29.80	43.50	13.70
497.5400	36.18	QP	-2.28	33.90	46.00	12.10
555.7400	42.62	QP	-1.72	40.90	46.00	5.10*
632.3700	39.63	QP	-0.33	39.30	46.00	6.70
797.2700	32.49	QP	1.71	34.20	46.00	11.80

*Within measurement uncertainty!

***** END OF REPORT *****