Beijing TierTime Technology Co., Ltd. No.2 Nanyi Street, Yanqi Economic Development Zone, Huairou District, Beijing, 101407, P. R. China

Date: April 6, 2023

FCC ID: 2AAHW-AW869A

Software Operation Description

We, Beijing TierTime Technology Co., Ltd. hereby declare that requirements of WIFI MODULE have been met and shown on the following question.

	SOFTWARE SECURITY DESCRIPTION				
General Description	1.	Describe how any software/firmware updates for elements than can affect the device's RF parameters will be obtained, downloaded, validated and installed. For software that is accessed through manufacturer's website or device's management system, describe the different levels of security as appropriate.	Software/firmware will be obtained by the factory, downloaded from the ODM website, and installed by the end user. Software is accessed through Web UI when computer is connected.		
	2.	Describe the RF parameters that are modified by any software/firmware without any hardware changes. Are these parameters in some way limited such that any other software/firmware changes will not allow the device to exceed the authorized RF characteristics?	The RF parameters cannot be modified by software. All these parameters will not exceed the authorized parameters. The firmware has been complied as binary file. It couldn't change the setting RF parameter through this binary file. It is read-only without change.		
	3.	Describe in detail the authentication protocols that are in place to ensure that the source of the RF-related software/firmware is valid. Describe in detail how the RF-related software is protected against modification.	No any authentication protocol is used. The RF Parameters is put in read-only partition of EUT's flash and are only installed in the factory. RF parameters including frequency of operation, power setting, modulation type, antenna types or country code setting will be locked in this partition.		
	4.	Describe in detail any encryption methods used to support the use of legitimate RF-related software/firmware.	No encryption methods used.		

	5.			is a client device without lar detection.	
Third-Party Access Control	2.	Explain if any third parties have the capability to operate a U.Ssold device on any other regulatory domain, frequencies, or in any manner that ma allow the device to operate in violation of the device's authorization if activated in the U.S. Describe, if the device permits third-party software or firmware installation, what mechanisms are provided by the manufacturer to perm integration of such functions while	יy ז	 device on any other regulatory domain, frequencies, or in any manner that may allow the device to operate in violation of the device's authorization if activated in the U.S The RF Parameters is put in read-only partition of EUT's flash and are only installed in the 	
		integration of such functions while ensuring that the RF parameters of the device cannot be operated outside its authorization for operation in the U.S. In the description include what control and/or agreements are in place with providers of third-party functionality to ensure the devices' underlying RF parameters are unchanged and how the manufacturer verifies the functionality.	ls	setting, modulation type, antenna types or country code setting will be locked in this partition.	
	3.	For Certified Transmitter modular devices, describe how the module grantee ensures that host manufacturers fully comply with these software security requirements for U-NII devices. If the module is controlled through driver software loaded in the host, describe how the drivers are controlled and managed such that the modular transmitter RF parameters are not modified outside the grant of authorization.		User couldn't change channel for UI, so user has no way to break compliance on our device.	

SOFTWARE CONFIGURATION DESCRIPTION GUIDE

For devices which have "User Interfaces" (UI) to configure the device in a manner that may impact the operational RF parameters, the following questions shall be answered by the applicant and the information included in the operational description. The description must address if the device supports any of the country code configurations or peer-peer mode communications discussed in KDB 594280 Publication D01.

SOFTWARE CONFIGURATION DESCRIPTION				
USER CONFIGURATION GUIDE	 Describe the user configurations permitted through the UI. If different levels of access are permitted for professional installers, system integrators or end-users, describe the differences. 	Authorized channel, bandwidth, and modulation can be configured through the UI. There are no different levels of access.		
	a. What parameters are viewable and configurable by different parties?	Authorized channel, bandwidth, and modulation.		
	b. What parameters are accessible or modifiable by the professional installer or system integrators?	This is not professional install device.		
	(1) Are the parameters in some way limited, so that the installers will not enter parameters that exceed those authorized?	This is not professional install device.		
	(2) What controls exist that the user cannot operate the device outside its authorization in the U.S.?	The RF Parameters is put in read-only partition of EUT's flash and are only installed in the factory. RF parameters including frequency of operation, power setting, modulation type, antenna types or country code setting will be locked in this partition.		
	c. What parameters are accessible or modifiable by the end-user?	Authorized channel, bandwidth, and modulation.		
	(1) Are the parameters in some way limited, so that the user or installers will not enter parameters that exceed those authorized?	This is not professional install device.		
	(2) What controls exist so that the user cannot operate the device outside its authorization in the U.S.?	The RF Parameters is put in read-only partition of EUT's flash and are only installed in the factory. RF parameters including		

d. Is the country code factory set?	operation, power setting, modulation type, antenna types or country code setting will be locked in this partition. Yes, the country code is set
Can it be changed in the UI?	by factory. It cannot be changed in the UI.
(1) If it can be changed, what controls exist to ensure that the device can only operate within its authorization in the U.S.?	The country code cannot be changed in the UI.
e. What are the default parameters when the device is restarted?	Factory setting.
 Can the radio be configured in bridge or mesh mode? If yes, an attestation may be required. Further information is available in KDB Publication 905462 D02. 	No, this device cannot be configured in both bridge and mesh mode.
3. For a device that can be configured as a master and client (with active or passive scanning), if this is user configurable, describe what controls exist, within the UI, to ensure compliance for each mode. If the device acts as a master in some bands and client in others, how is this configured to ensure compliance?	User couldn't change channel for UI, so user has no way to break compliance on our device.
4. For a device that can be configured as different types of access points, such as point-to-point or point-to-multipoint, and use different types of antennas, describe what controls exist to ensure compliance with applicable limits and the proper antenna is used for each mode of operation. (See Section 15.407(a))	This device cannot be configured as different types of access points.

2023-04-06

Tangyuolin

Signature:

Name	Tangguo Lin
Position	Technology Manager
Company Name	Beijing TierTime Technology Co., Ltd.
Address	No.2 Nanyi Street, Yanqi Economic Development Zone, Huairou
	District, Beijing,101407, P. R. China
Tel	+86-010-51299667
Fax	+86-010-51299667
Email	Tgl@pp3dp.com