Test Report No. 9312312944

<u>Applicant</u>: Scientific Educational Systems Ltd.

Equipment Under Test:

NeuLog System WiFi communication module.

Model: WiFi-201 module. FCC ID: 2AAI3-SNP-2000

From The Standards Institution Of Israel Industry Division Electronics & Telematics Laboratory EMC Branch



ACLASS Accreditation Services Certificate Number: AT-1359



Test Report No.: 9312312944

Page 2 of 27 pages

<u>Title:</u> NeuLog System WiFi communication module. <u>Model:</u> WiFi-201 module.

FCC ID: 2AAI3-SNP-2000

Applicant:	Scientific Educational Systems Ltd.
Address:	6 Elhanan Street, Rishon Lezion 75151, POB 5340 Israel
Sample for test selected by:	The applicant.
The date of tests:	13 May, 8 June and 20, 21 August 2013

Description of Equipment Under Test (EUT):	NeuLog System WiFi communication module.
Model:	WiFi-201 module.
Software version of brain unit	0.4.0.1
Hardware version of brain unit	MAL-00021 rev.0B
Serial Number:	N/A
Manufactured by:	Scientific Educational Systems Ltd

Reference Documents:

 CFR 47 FCC: Rules and Regulations; Part 15. "Radio frequency devices"; <u>Subpart B:</u> "Unintentional radiators". Section 15.109. "Radiated emission limits". <u>Subpart C</u>: "Intentional radiators". Section 15.209. "Radiated emission limits, general requirements". "Radiated Emission Limits, Additional Provisions"; Section 15.249. "Operation within the bands 902 – 928 MHz, 2400 – 2483.5 MHz, 5725 – 5875 MHz and 24.0 - 24.25 GHz".

This Test Report contains 27 pages	This Test Report applies only to the specimen tested and may not
and may be used only in full.	be applied to other specimens of the same product.



Test Report No.: 9312312944	Page 3 of 27 pages
Title: NeuLog System WiFi communication module.	FCC ID. 24412 SND 2000
<u>woaei:</u> wifi-201 module.	FUU ID: 2AAI3-5NP-2000

Table of Contents

1.	EUT Description and operation	4
1.1.	General description:	4
2.	Test summary	6
2.1. 2.2.	Potential emission sources: EUT setup and operation:	8 8
3.	Measurements, examinations and derived results	8
3.1. 3.2. 3.3. 3.4. 3.5. 3.6. 3.7. 3.8.	Location of the Test Site: Test condition: Initial visual check and functional test: Radiated emission test. Test of field strength emission from intentional radiator. Test of occupied bandwidth per 15.215(c) Test of undesired radiated emissions. Test of conducted emission at main terminal.	8 8 9 10 17 18 19
4.	Appendix 1. Test equipment used	21
5.	Appendix 2: Antenna Factor and Cable Loss	22
6.	Appendix 3: Test setups photo.	27



Test Report No.: 9312312944

Page 4 of 27 pages

<u>Title:</u> NeuLog System WiFi communication module. **Model:** WiFi-201 module.

FCC ID: 2AAI3-SNP-2000

1. EUT Description and operation

1.1. General description:

* Note: the customer supplied all information in clause below.

The WiFi-201 wireless communication module is one of the most advanced and innovating elements of NeuLog System which is a set of independent computer based modules, complete with a data logger, flash memory and a sensor all in one single smart unit. Measurements and sending the data to PC, made through USB-200 or WIFI-201 modules. The RT5350 is a highly integrated MAC/BBP and 2.4 GHz RF/PA/ LNA single chip with 150 Mbps PHY rate supporting. It fully complies with IEEE 802.11 b/g feature rich wireless connectivity at high standards and delivers reliability of wireless communication. The interface is normal RJ45 signal ports for connection each other sensor modules and inner communication. The crystal oscillator provide 40 MHz basic frequency signal to processor. NeuLog System should be connected to a power supply or to a BAT-200 battery module.

Declare frequency band	2400 – 2483.5 MHz
Operating frequency.	2462 MHz only. Channel 11.
Type of multiplexing .	OFDM
Antenna type:	Internal on PCB

The EUT power source: AC to DC adaptor 120 VAC/5.0 VDC.

The EUT's block diagram is shown in figure 1.

The EUT external views are presented in photo # 1, 2.



Test Report No.: 9312312944	F
Title: Neul or System WiEi communication module	

Page 5 of 27 pages

- <u>**Title:**</u> NeuLog System WiFi communication module.
- Model: WiFi-201 module.

FCC ID: 2AAI3-SNP-2000

Neulog WIFI module block diagram



Figure 1. NeuLog system block diagram (No sensors included).



Test Report No.: 9312312944

Page 6 of 27 pages

- Title: NeuLog System WiFi communication module.
- Model: WiFi-201 module.

FCC ID: 2AAI3-SNP-2000

2. **Test summary**

Parameter	FCC Part 15 Reference paragraph	Verdict
Radiated emission test on unintentional radiator.	Subpart B Section 15.109	Comply
Test of field strength emission from intentional radiators	"Radiated Emission Limits, Additional Provisions"; Section 15.249.	Comply
Conducted emission test.	Subpart C Section 15.207	Comply

Name: Eng. Yuri Rozenberg

Position: Head of EMC Branch

Electronics & Telematics Laboratory

September 2013

Name: Michael Feldman Position: Test Technician

Measurement uncertainty.

Were relevant, the following measurement uncertainty level have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expended uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test description	Expanded uncertainty
Radiated emissions in the open field test site at 3 m measuring distance:	
30 MHz – 1.0 GHz 1.0 GHz – 18 GHz	2 Uc (E) = ± 4.32 dB 2 Uc (E) = ± 4.47 dB



Test Report No.: 9312312944

Page 7 of 27 pages

- <u>**Title:**</u> NeuLog System WiFi communication module.
- Model: WiFi-201 module.

FCC ID: 2AAI3-SNP-2000



Photo 1. WiFi-201 module front view.



Photo 2. WiFi-201 rear view



Test Report No.: 9312312944

Page 8 of 27 pages

<u>Title:</u> NeuLog System WiFi communication module.

Model: WiFi-201 module.

FCC ID: 2AAI3-SNP-2000

2.1. Potential emission sources:

The potential emission sources are detailed in Table 1.

Table 1. Potential em	nission sources
-----------------------	-----------------

Frequency	Location
8.0 MHz crystal	Microcontroller oscillator
40.0 MHz crystal	RF Lo oscillator
2462 MHz crystal	RF signal

2.2. EUT setup and operation:

RE tests were performed in transmission (Tx) mode on transmitter carrier frequency 2462 MHz in configuration included WiFi-201 (Tx) module and connected NeuLog sensors. RE test in 30 - 1000 MHz band was performed in follow configuration: WiFi -201+ (VIEW-200 + VIEW-101+ ROBO-206/5 + BAT-200)

CE test was performed in follow configuration: WiFi -201 + (NUL-217 + NUL-204 + NUL-224 + NUL-210)

Measurements of transmitter were performed in continue transmit mode and recorded on plots peak results were taken in SA max hold mode.

3. Measurements, examinations and derived results

3.1. Location of the Test Site:

Preliminary radiated test was conducted at the EMC laboratory of the Standards Institution of Israel in Tel-Aviv. Final tests were conducted in an Open Area Test Site located at Kibbutz Native Halamed Hai in Emek HaEla, Israel.

3.2. Test condition:

Temperature: 24 °C. Humidity: 56 %. Atmospheric pressure: 1011 mbar.

3.3. Initial visual check and functional test:

Initial visual check and brief built - in- test of the EUT was performed before testing. No external damages were found.



i	Test Report	No.:	9312312944
÷.			

Page 9 of 27 pages

<u>Title:</u> NeuLog System WiFi communication module. **Model:** WiFi-201 module.

FCC ID: 2AAI3-SNP-2000

3.4. Radiated emission test.

3.4.1. <u>General:</u>

Per FCC Part 15 Subpart C Sections 15.209, 15.249.

- Initial scans were made using a peak detector but still using the appropriate ANSI IF bandwidth.
- A tolerance limit was set 10 dB below the specification limit. Levels above the tolerance limit were retested using the Peak, QP and Average detectors.

3.4.2. Preliminary radiated emission tests:

Preliminary investigation was performed from the lowest radio frequency signal generated in the equipment up to ten harmonic of a carrier frequency. Test was conducted in a semianechoic chamber at distances 1 and 3 meters. The EUT was setup in its typical configuration and operated in its various modes. For each mode of operation the frequency spectrum was monitored. EUT configuration, cable configuration and mode of operation, which produced the maximum level of emission, were documented. A list of frequencies to be tested was prepared.

3.4.3. Final measurements:

The final radiated emission measurements were performed at the Open Area Test Site at the 3 m test distance. The EUT was operated as described above. The EUT was installed on a turn - table. Biconilog and Double Ridged Guide antennas were used. The measurements were performed at each frequency that founded previously at which the signal level was 10 dB below the limit or less. The levels were maximized by rotating turntable through 360°, changing antenna height and changing antenna-to-EUT polarization from vertical to horizontal. The worst case result was noted in tables.

3.4.4. Radiated emission test results:

Final result measurements in transmit mode are presented in tables and plots ## 1 - 8 in section 3.5.5.



Test Report No.: 9312312944	Page 10 of 27 pages
<u>Title:</u> NeuLog System WiFi communication module. <u>Model:</u> WiFi-201 module.	FCC ID: 2AAI3-SNP-2000

3.5. Test of field strength emission from intentional radiator.

3.5.1. <u>General:</u>

Per FCC Part 15 Subpart C clause 15.249.

3.5.2. Requirements:

The field strength emissions from intentional radiators operated according to section 15.249 (a) shall comply with the follow limits .

Table 2. Section 15.249 limit.

Specified field strength limit of	Specified field strength limit of
Fundamental	Harmonics
dBµV/m	dBµV/m
94.0	54.0

Note: The field strength of emissions radiated on any frequency outside of the specified band, except for harmonics shall be attenuated by at least 50 dB below the level of fundamental or to the general radiated emissions limits in section 15.209 whichever is lesser attenuation.

3.5.3. Test procedure:

The test was conducted according to clause 15.249.

3.5.4. Test summary:

The tested unit meets the standard requirement. Test results presented in section 3.5.5, results for 30 – 1000 MHz frequency band presented in section 3.7.



Test Report No.: 9312312944	Page 11 of 27 pages
<u>Title:</u> NeuLog System WiFi communication module. <u>Model:</u> WiFi-201 module.	FCC ID: 2AAI3-SNP-2000

3.5.5. <u>Test results:</u>

Table 3. Radiated emission result at carrier frequency.

Carrier frequency	Antenna polar.	Peak ampl.	*Avg. ampl.	Specified avg. limit.	Margin	Reference to plot #
	_	ασμν/π	ασμν/π	ασμν/π	uБ	
2462.0	Vertical	103.4	77.4	94.0	16.6	1

Freq. MHz	Antenna pol. V/H	Peak ampl dBµV/m	Peak ampl limit, dBμV/m	Margin dB	*Avg ampl. dBμV/m	Specified @3m limit, dBµV/m	Margin dB	Ref. to plot #
1200	Vertical	47.89	74.0	26.1	21.9	54.0	32.1	14
2483	Vertical	72.77	74.0	1.2	46.77	54.0	7.2	15
4927	Vertical	64.0	74.0	10.0	38.0	54.0	16.0	17

Table 4. Spurious emission result.

*Average amplitude result was calculated from measured Peak value – Average factor. Average factor = 20 Log Tx on/100msec = 20 Log [4.98 ms/100ms] = -26.0 dB. For transmitter average factor calculation see plot # 10.



Test Report No.: 9312312944

Page 12 of 27 pages

- <u>Title:</u> NeuLog System WiFi communication module.
- Model: WiFi-201 module.

FCC ID: 2AAI3-SNP-2000



Plot # 1. Fundamental frequency test.



Test Report No.: 9312312944

Page 13 of 27 pages

Title: NeuLog System WiFi communication module.

Model: WiFi-201 module.

FCC ID: 2AAI3-SNP-2000



Plot # 2. Spurious emissions scan 0.15 MHz – 30 MHz.



Test Report No.: 9312312944

Page 14 of 27 pages

- Title: NeuLog System WiFi communication module.
- Model: WiFi-201 module.

FCC ID: 2AAI3-SNP-2000

Spurious emissions result





Plot # 5.





Plot # 6.



Test Report No.: 9312312944

Page 15 of 27 pages

- Title: NeuLog System WiFi communication module.
- Model: WiFi-201 module.

FCC ID: 2AAI3-SNP-2000



Plot # 7. Test distance = 1m



Test Report No .: 9312312944

Page 16 of 27 pages

<u>Title:</u> NeuLog System WiFi communication module.

Model: WiFi-201 module.

FCC ID: 2AAI3-SNP-2000



Plot # 9. Sweep duration 100 msec.





Average factor was calculated from result on plot # 10. Average factor = 20 Log Tx on/100msec = 20 Log [4.98 ms/100ms] = -26.0 dB



Test Report No.: 9312312944	Page 17 of 27 pages
Title: NeuLog System WiFi communication module.	
Model: WiFi-201 module.	FCC ID: 2AAI3-SNP-2000

3.6. Test of occupied bandwidth per 15.215(c)

3.6.1. <u>Requirements:</u>

Intentional radiator must be designed to ensure that the 20 dB bandwidth of the emission is contained within the frequency band.

3.6.2. <u>Test results:</u>

Test result presented in plot below.





3.6.3. <u>Test summary:</u>

20 dB occupied bandwidth is less than 20 MHz. The tested unit meets the standard requirement.



Test Report No.: 9312312944

Page 18 of 27 pages

<u>Title:</u> NeuLog System WiFi communication module. **Model:** WiFi-201 module.

FCC ID: 2AAI3-SNP-2000

3.7. Test of undesired radiated emissions.

Per FCC Part 15 subpart B/C Section 15.109 and 15.209.

3.7.1. Test procedure:

The test setup included maximum allowed configuration - WiFi -201 module with four connected NeuLog sensors as worst case.

Final measurements were performed according to clause 3.4.3.

Freq. MHz	Antenna height m	Antenna pol. V/H	Turn table angle (°)	Emission level Note 1 dBµV/m	Specified @3m limit, dBµV/m	Margin. dB
240.0	3.0	Н	200	41.6	46.0	4.4
250.0	2.9	Н	39	33.3	46.0	12.7
300.6	3.0	Н	152	35.3	46.0	9.7
360.0	2.5	Н	170	43.8	46.0	2.2
600.0	1.6	Н	157	44.8	46.0	1.2

Table 5. Radiated emission test results.

Note 1: Emission level = E Reading $(dB\mu V)$ + Cable loss (dB) + Antenna Factor (dB/m)For Cable Loss and Antenna Factor refer to Appendix 2

3.7.2. Radiated emission test results:

All received emissions were found below FCC Parts 15.109 class B and 15.209 limits and presented in table # 5.



Test Report No.: 9312312944	Page 19 of 27 pages	
Title: NeuLog System WiFi communication module.		
Model: WiFi-201 module.	FCC ID: 2AAI3-SNP-2000	

3.8. Test of conducted emission at main terminal.

3.8.1. <u>General</u>

The conducted emission test was performed in normal operation mode in maximum allowed configuration included WiFi-201 (Tx) module and four connected NeuLog sensors. EUT was powered from 120 VAC via AC/DC adaptor.

3.8.2. Test results:

Subpart C clause 15.207 (a).



Table 6. Test result. Line Phase.

Frequency	QP Ampl.	QP Limit	Margin	Avg Ampl.	Average Limit	Margin
MHz	dBuV	dBuV	dB	dBuV	dBuV	dB
2.440	43.5	56.0	-12.5	37.4	46.0	8.6
4.885	41.9	56.0	-14.1	30.4	46.0	15.6
9.746	36.5	60.0	-23.5	23.8	50.0	26.2
12.191	44.5	60.0	-15.5	33.8	50.0	16.2
14.661	33.8	60.0	-26.2	15.3	50.0	34.7
19.520	37.5	60.0	-22.5	27.8	50.0	22.2



Test Report No.: 9312312944

Page 20 of 27 pages

Title: NeuLog System WiFi communication module.

Model: WiFi-201 module.

FCC ID: 2AAI3-SNP-2000



Table	? ? .	Test	result.	Line	Neutral	•

Freque ncy	QP Ampl.	QP Limit	Margin	Avg Ampl.	Average Limit	Margin
MHz	dBµV	dBuV	dB	dBµV	dBuV	dB
2.444	35.4	56.0	-20.6	25.7	46.0	20.3
4.885	41.4	56.0	-14.6	31.4	46.0	14.6
7.314	34.1	60.0	-25.9	23.3	50.0	26.7
12.214	33.9	60.0	-26.1	20.9	50.0	29.1
14.625	32.9	60.0	-27.1	22.1	50.0	27.9
19.529	32.1	60.0	-27.9	22.3	50.0	27.7



Test Report No.: 9312312944

Page 21 of 27 pages

<u>Title:</u> NeuLog System WiFi communication module.

Model: WiFi-201 module.

FCC ID: 2AAI3-SNP-2000

4. Appendix 1. Test equipment used

All measurements equipment is on SII calibration schedule with a recalibration interval not exceeding one year.

Instrument	MFR	Model	Serial No.	Due calibration date
EMI Receiver 9 kHz – 6.5 GHz	HP	8546A+ 85460A	SII 4068	May 2014
EMI Analyser 9 kHz - 26.5 GHz	HP	E7405A	SII 4944	April 2014
Biconilog Antenna 30 – 2000 MHz	Teseq GmbH	CBL 6112D	23181	December 2013
Antenna Double Ridged Guide, 1-18 GHz	EMCO	3115	SII4873	December 2013
Broadband Horn antenna, 15 – 40 GHz	Schwarzbeck Mess- Electronik	BBHA 9170	9170-341	December 2013
Active Loop antenna 10 kHz – 30 MHz	EMCO	6502	SII 4874	December 2013
LISN 9 kHz – 30 MHz	FCC	LISN 250-32-4-16	SII5023	Aug. 2014
Transient limiter 0.009-200 MHz	HP	11947A	3107105	Aug. 2014
Oscilloscope	HP	54610B	US37340682	May 2014
RF cable, 4m	Huber-Suhner	Sucoflex 104PE	21329/4PE	Oct 2013
Cable RF 0.5m	Huber-Suhner	Sucoflex 104PE	500448/4PE	Oct 2013
Cable RF 1m	ENP Connectivity Solutions	X116LCX10040	10-11-002	Oct 2013
Antenna Mast	Frankonia	FAM6	5952	N/A
Metallic turntable	Frankonia	FTM2-2	5952	N/A
Positioning controller	Frankonia	FCO2	5952	N/A



Test Report No.: 9312312944	
Title: Neul og System WiFi communication module	

Model: WiFi-201 module.

Page 22 of 27 pages

FCC ID: 2AAI3-SNP-2000

5. Appendix 2: Antenna Factor and Cable Loss

Point	Frequency (MHz)	Cable Loss (dB)	Point	Frequency (MHz)	Cable Loss (dB)
1	30	0.53	21	1000	3.68
2	50	0.75	22	1100	3.82
3	100	1.08	23	1200	4.07
4	150	1.39	24	1300	4.24
5	200	1.61	25	1400	4.43
6	250	1.752	26	1500	4.6
7	300	2.00	27	1600	4.7
8	350	2.15	28	1700	4.85
9	400	2.26	29	1800	4.98
10	450	2.383	30	1900	5.19
11	500	2.52	31	2000	5.34
12	550	2.606	32	2100	5.51
13	600	2.75	33	2200	5.69
14	650	2.856	34	2300	5.89
15	700	3.06	35	2400	6.07
16	750	3.20	36	2500	6.22
17	800	3.27	37	2600	6.28
18	850	3.38	38	2700	6.41
19	900	3.46	39	2800	6.53
20	950	3.55	40	2900	6.84

Cable Loss (10m cable + Mast)

42 Chaim Levanon St. Tel-Aviv 69977 Israel. Management: Tel: 972-3-6467800 Fax: 972-3-6467779 www.sii.org.il Electronics: Tel: 972-3-6465050 Fax: 972-3-7454026 - Alarms Systems Section: Tel: 972-3-6465370 Fax: 972-3-6467262



Test Report No.: 9312312944

Page 23 of 27 pages

<u>Title:</u> NeuLog System WiFi communication module. <u>Model:</u> WiFi-201 module.

FCC ID: 2AAI3-SNP-2000

Table 8. Antenna FactorFor Biconilog Antenna, Model Number: CBL 6112D, S/N: 23181

No.	f / MHz)	AF / dB/m						
1	30	17.90	170	9.40	530	17.70	1040	22.20
2	32	16.70	175	9.00	540	18.25	1060	22.50
3	34	15.55	180	8.50	550	18.60	1080	22.50
4	36	14.35	185	8.45	560	14.45	1100	22.40
5	38	13.30	190	8.60	570	18.40	1120	22.60
6	40	12.20	195	8.85	580	18.50	1140	22.45
7	42	11.05	200	8.95	590	18.60	1160	22.50
8	44	9.95	205	8.80	600	18.60	1180	22.40
9	46	8.90	210	8.50	610	18.80	1200	22.80
10	48	8.05	215	8.20	620	18.99	1220	22.95
11	50	7.30	220	8.50	630	19.05	1240	23.10
12	52	6.80	225	9.00	640	19.23	1260	23.40
13	54	6.45	230	9.65	650	19.10	1280	23.35
14	56	6.00	235	10.30	660	19.13	1300	23.62
15	58	5.70	240	11.00	670	19.04	1320	23.64
16	60	5.45	245	11.60	680	19.00	1340	23.86
17	62	5.30	250	12.00	690	19.17	1360	23.95
18	64	5.20	255	12.45	700	19.28	1380	23.90
19	66	5.30	260	12.85	710	19.25	1400	24.45
20	68	5.30	265	12.50	720	19.45	1420	24.74
21	70	5.35	270	12.45	730	19.75	1440	24.93
22	72	5.50	275	12.40	740	19.95	1460	25.03
23	74	5.80	280	12.55	750	20.07	1480	25.45
24	76	6.00	285	12.65	760	19.85	1500	25.30
25	78	6.60	290	12.75	770	19.80	1520	25.25
26	80	6.70	295	12.95	780	19.85	1540	25.36
27	82	7.15	300	13.00	790	19.95	1560	25.58
28	84	7.60	310	13.35	800	20.05	1580	25.50
29	86	8.10	320	13.75	810	20.10	1600	25.65
30	88	8.50	330	13.85	820	20.35	1620	25.60
31	90	8.90	340	14.10	830	20.40	1640	25.70
32	92	9.20	350	14.50	840	20.35	1660	25.83
33	94	9.75	360	14.70	850	20.46	1680	25.97
34	96	9.95	370	14.90	860	20.39	1700	26.10
35	98	10.20	380	15.10	870	20.29	1720	26.25
36	100	10.50	390	15.45	880	20.24	1740	26.04
37	105	11.25	400	16.00	890	20.35	1760	26.14
38	110	11.70	410	16.40	900	20.55	1780	26.20
39	115	11.70	420	16.70	910	20.45	1800	26.40
40	120	11.80	430	16.35	920	20.60	1820	26.64
41	125	11.80	440	16.30	930	20.60	1840	26.86
42	130	11.70	450	16.30	940	20.66	1860	27.12
43	135	11.35	460	16.70	950	20.88	1880	27.00
44	140	10.95	470	17.05	960	21.11	1900	27.25
45	145	10.35	480	17.20	970	20.93	1920	27.36
46	150	10.05	490	17.30	980	21.03	1940	27.68
47	155	9.70	500	17.40	990	21.05	1960	27.10
48	160	9.70	510	17.50	1000	21.10	1980	27.06
49	165	9.45	520	17.60	1020	21.40	2000	27.25



Test Report No.: 9312312944

Page 24 of 27 pages

<u>Title:</u> NeuLog System WiFi communication module. <u>Model:</u> WiFi-201 module.

FCC ID: 2AAI3-SNP-2000

Antenna factor Active Loop antenna mfr.EMCO mod. 6502 S/N 3424

Frequency (MHz)	Magnetic Antenna factor (dBS/m)	Electric Antenna factor (dB/m)
0.009	-31.46	20.07
0.010	-32.34	19.18
0.020	-36.15	15.38
0.050	-38.57	12.96
0.075	-38.78	12.75
0.100	-39.07	12.46
0.150	-39.07	12.45
0.250	-39.18	12.35
0.500	-39.29	12.24
0.750	-39.38	12.14
1.000	-39.57	11.95
2.000	-39.84	11.69
3.000	-40.09	11.44
4.000	-40.13	11.40
5.000	-40.24	11.28
10.000	-40.26	11.27
15.000	-40.70	10.83
20.000	-41.02	10.51
25.000	-41.94	9.59
30.000	-43.39	8.14



Test Report No.: 9312312944

Page 25 of 27 pages

- Title: NeuLog System WiFi communication module. Model: WiFi-201 module.
- FCC ID: 2AAI3-SNP-2000

Antenna Factor Double Ridged Guide Antenna mfr EMCO model 3115 1m calibration

Point	Frequency (MHz)	Antenna Factor (dB/m)
1	1000	23.9
2	2000	28.3
3	3000	31.0
4	4000	33.1
5	4500	32.5
6	5000	32.4
7	6000	53.7
8	6500	35.6
9	7000	36.4
10	7500	36.9
11	8000	37.0
12	8500	38.0
13	9000	38.6
14	9500	38.4
15	10000	38.4
16	10500	38.4
17	11000	38.9
18	11500	39.6
19	12000	39.4
20	12500	39.2
21	13000	40.3
22	13500	41.0
23	14000	41.2
24	14500	41.3
25	15000	40.0
26	15500	38.0
27	16000	38.1
28	16500	40.3
29	17000	42.2
30	17500	44.6
31	18000	46.2

<u>Cable Loss</u> <u>Type: Sucoflex 104PE; Ser.No.21329/4PE; 4 m length</u>

Point	Frequency (GHz)	Cable Loss (dB)
1	0.0-1.0	1.7
2	1.0-3.5	3.2
3	3.5– 5.5	4.0
4	5.5 – 7.5	4.7
5	7.5 – 9.5	5.3
6	9.5 – 10.5	5.6
7	10.5 – 12.5	6.2
8	12.5 – 14.5	6.8
9	14.5 – 16.5	7.5
10	16.5 - 18.0	8.1



Test Report No.: 9312312944

Page 26 of 27 pages

Title: NeuLog System WiFi communication module. Model: WiFi-201 module.

FCC ID: 2AAI3-SNP-2000

Antenna Factor Broadband Horn Antenna model BBHA 9170 1m calibration

Point	Frequency (GHz)	Antenna Factor (dB/m)
1	15.0	38.5
2	16.0	37.7
3	17.0	38.1
4	18.0	37.9
5	19.0	38.0
6	20.0	38.0
7	21.0	37.9
8	22.0	38.2
9	23.0	39.6
10	24.0	39.6
11	25.0	39.3
12	26.0	39.5
13	27.0	39.6
14	28.0	39.6
15	30.0	40.1
16	32.0	41.2
17	34.0	41.5
18	35.0	41.9
19	36.0	42.2
20	38.0	43.8
21	40.0	43.2

42 Chaim Levanon St. Tel-Aviv 69977 Israel. Management: Tel: 972-3-6467800 Fax: 972-3-6467779 www.sii.org.il Electronics: Tel: 972-3-6465050 Fax: 972-3-7454026 - Alarms Systems Section: Tel: 972-3-6465370 Fax: 972-3-6467262



Test Report No.: 9312312944

<u>Title:</u> NeuLog System WiFi communication module. <u>Model:</u> WiFi-201 module. Page 27 of 27 pages

FCC ID: 2AAI3-SNP-2000

6. Appendix 3: Test setups photo.



Photo 3. Radiated emissions test.

42 Chaim Levanon St. Tel-Aviv 69977 Israel. Management: Tel: 972-3-6467800 Fax: 972-3-6467779 www.sii.org.il Electronics: Tel: 972-3-6465050 Fax: 972-3-7454026 - Alarms Systems Section: Tel: 972-3-6465370 Fax: 972-3-6467262