



FCC Part 15B TEST REPORT

Report No: STS1803190E01

Issued for
Trackimo INC.

450 Seventh Avenue, Suite 1408, New York, United States

Product Name:	GPS Tracker
Brand Name:	trackimo
Model Name:	TRKM017-3G
Series Model:	N/A
FCC ID:	2AAI6-TRKM017-3G
Test Standard:	FCC Part 15B

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.





TEST RESULT CERTIFICATION

Applicant's name.....: Trackimo INC.

Address.....: 450 Seventh Avenue, Suite 1408, New York, United States

Manufacture's Name: HUIZHOU QIAOWEI INTELLIGENT OVERSEAS CO.,LTD

Address.....: B2 building, ELing phase 2, wuyi village, chenjiang street, gaoxin district, Huizhou city, Guangdong Province, China

Product description

Product name.....: GPS Tracker

Brand name.....: trackimo

Model Name: TRKM017-3G

Series Model N/A

Standards.....: FCC Part 15B

Test procedure ANSI C63.4-2014

This device described above has been tested by STS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test.....

Date of performance of tests 19 Mar. 2018~20 Mar. 2018

Date of Issue..... 21 Mar. 2018

Test Result Pass

Testing Engineer :

Kyle. Rao

(Kyle Rao)

Technical Manager :

Chopin. Xiao

(Chopin Xiao)

Authorized Signatory :

Vita Li


(Vita Li)





Table of Contents

1. SUMMARY OF TEST RESULTS	5
1.1 TEST FACTORY	5
1.2 MEASUREMENT UNCERTAINTY	5
2. GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	7
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	7
2.4 DESCRIPTION OF SUPPORT UNITS	8
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	9
3. EMC EMISSION TEST	10
3.1 CONDUCTED EMISSION MEASUREMENT	10
3.2 RADIATED EMISSION MEASUREMENT	14





Revision History

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	21 Mar. 2018	STS1803190E01	ALL	Initial Issue





1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

EMISSION			
Standard	Item	Result	Remarks
FCC 47 CFR Part 15 Subpart B	Conducted Emission	PASS	Meet Class B limit
	Radiated Emission	PASS	Meet Class B limit

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

1.1 TEST FACTORY

Company Name:	Shenzhen STS Test Services Co. Ltd.
Address:	1/F., Building B, Zhuoke Science Park, No.190, Chongqing Road, Fuyong Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	+86-755 3688 6288
Fax:	+86-755 3688 6277
Registration No.:	CNAS Registration No.: L7649; FCC Registration No.: 625569 IC Registration No.: 12108A; A2LA Certificate No.: 4338.01;

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$ where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$ providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission (9KHz-150KHz)	± 2.88 dB
2	Conducted Emission (150KHz-30MHz)	± 2.67 dB
3	All emissions,radiated(<30M) (9KHz-30MHz)	± 2.45 dB
4	All emissions,radiated(<1G) 30MHz-200MHz	± 3.73 dB
5	All emissions,radiated(<1G) 200MHz-1000MHz	± 3.92 dB
6	All emissions,radiated(>1G)	± 3.31 dB



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product Name	GPS Tracker	
Brand Name	trackimo	
Model Name	TRKM017-3G	
Series Model	N/A	
Model Difference	N/A	
Frequency Bands	GSM	850: 824.2~848.8MHz 1900: 1850.2~1909.8MHz
	WCDMA	Band II: 1852.4~1907.6MHz Band V: 826.4~846.6MHz
	WLAN	802.11b/g/n(HT20/40):2412~2462MHz
Modulation Mode	GSM	GMSK for GSM/GPRS
	WCDMA	QPSK; HSDPA:QPSK/16QAM; HSUPA:BPSK
	WLAN	802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM
Battery	Rated Voltage: 3.8V Capacity: 530mAh Charge Limit: 4.35V	
Hardware version number	CW01_V3.0_20171114	
Software version number	1.3	

Note: For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	USB port communication with PC

For Conducted Test	
Final Test Mode	Description
Mode 1	USB port communication with PC

For Radiated Test	
Final Test Mode	Description
Mode 1	USB port communication with PC

NOTE: The test modes were carried out for all operation modes. Only worst case will be show in this report.

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED





2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.
E-1	Adapter	N/A	N/A
E-2	PC	4CV428DQXR	500-320cx

Item	Shielded Type	Ferrite Core	Length
C-1	Shielded	NO	70cm
C-2	USB Cable (FTP)	NO	78cm

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.
- (4) PC is the FCC DOC is approved.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
EMI Test Receiver	R&S	ESCI	101427	2017.10.15	2018.10.14
Bilog Antenna	TESEQ	CBL6111D	34678	2017.10.30	2018.10.29
Horn Antenna	SCHWARZBECK	BBHA 9120D	1343	2017.10.27	2018.10.26
Spectrum Analyzer	Agilent	E4407B	MY50140340	2018.03.08	2019.03.07
Pre-mpplier(1G-18 G)	Agilent	8449B	60538	2017.10.28	2018.10.27
Spectrum Analyzer	Agilent	N9020A	MY49100060	2018.03.08	2019.03.07
Pre-mpplier(0.1M-3 GHz)	EM	EM330	--	2018.03.11	2019.03.10

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
EMI Test Receiver	R&S	ESPI	102086	2017.10.15	2018.10.14
LISN	R&S	ENV216	101242	2017.10.15	2018.10.14
LISN	EMCO	3810/2NM	23625	2017.10.15	2018.10.14
Absorbing clamp	R&S	MDS-21	100668	2017.10.19	2018.10.18



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Conducted Emission Limits (dBuV)			
	Class A		Class B	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- a. The EUT was 0.8 meters from the horizontal ground plane and 0.4 meters from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



- Note: 1.Support units were connected to second LISN.**
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




3.1.6 TEST RESULTS

Temperature:	23.5 °C	Relative Humidity:	59%
Phase:	L	Test Mode:	Mode 1
Test Voltage:	DC 5V From PC		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1740	51.18	9.81	60.99	64.77	-3.78	QP
2	0.1740	34.58	9.81	44.39	54.77	-10.38	AVG
3	0.2820	38.76	10.20	48.96	60.76	-11.80	QP
4	0.2820	24.47	10.20	34.67	50.76	-16.09	AVG
5	0.5180	29.08	9.97	39.05	56.00	-16.95	QP
6	0.5180	12.40	9.97	22.37	46.00	-23.63	AVG
7	3.5260	31.50	9.93	41.43	56.00	-14.57	QP
8	3.5260	14.52	9.93	24.45	46.00	-21.55	AVG
9	9.1340	36.14	9.91	46.05	60.00	-13.95	QP
10	9.1340	24.40	9.91	34.31	50.00	-15.69	AVG
11	24.7780	17.19	10.28	27.47	60.00	-32.53	QP
12	24.7780	3.86	10.28	14.14	50.00	-35.86	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor) – Limit
3. Factor = Cable Loss + Antenna Factor - Amplifier Gain






Temperature:	23.5 °C	Relative Humidity:	59%
Phase:	N	Test Mode:	Mode 1
Test Voltage:	DC 5V From PC		

No.	Frequency (MHz)	Reading (dBUV)	Correct Factor (dB)	Result (dBUV)	Limit (dBUV)	Margin (dB)	Detector
1	0.1700	51.89	9.80	61.69	64.96	-3.27	QP
2	0.1700	39.97	9.80	49.77	54.96	-5.19	AVG
3	0.2300	43.16	9.99	53.15	62.45	-9.30	QP
4	0.2300	27.72	9.99	37.71	52.45	-14.74	AVG
5	0.5180	29.11	9.97	39.08	56.00	-16.92	QP
6	0.5180	13.91	9.97	23.88	46.00	-22.12	AVG
7	3.6540	32.02	9.93	41.95	56.00	-14.05	QP
8	3.6540	14.90	9.93	24.83	46.00	-21.17	AVG
9	9.1860	35.47	9.92	45.39	60.00	-14.61	QP
10	9.1860	23.75	9.92	33.67	50.00	-16.33	AVG
11	16.4380	22.10	10.19	32.29	60.00	-27.71	QP
12	16.4380	10.10	10.19	20.29	50.00	-29.71	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor) – Limit
3. Factor= Cable Loss +Antenna Factor-Amplifier Gain

100.0 dBUV



Note: The test voltage is 100-240V, both of which have assessment tests, and the worst test data is in the report.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 Radiated Emission Limits

In case the emission fall within the restricted band specified on 15.105(a)&109(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microrvolts/meter)	Measurement Distance (meters)
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (dBuV/m) (at 3M)		Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80	60	74	54

Note:

- (1) The limit for radiated test was performed according to FCC PART 15B.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower



Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	5th harmonic (Peak/AV)
RB / VB (emission in restricted band)	30MHz to 1000MHz: 100 KHz / 300 KHz Above 1000MHz: 1 MHz / 3 MHz

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	30MHz to 1000MHz: 100 KHz / 300 KHz Above 1000MHz: 1 MHz / 3 MHz

3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz and above 1GHz.
The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter
- b. anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. the height of the antenna shall vary between 1m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
The initial step in collecting conducted emission data is a spectrum analyzer peak detector
- d. mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the
- e. EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.


Note: Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency 30MHz~1GHz



(B) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



3.2.6 TEST RESULTS


30MHz -1000MHz

Temperature:	22.1 °C	Relative Humidity:	56%
Phase:	Horizontal	Test Mode:	Mode 1
Test Voltage:	DC 5V From PC		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	46.6664	40.03	-19.77	20.26	40.00	-19.74	QP
2	77.3212	51.56	-23.07	28.49	40.00	-11.51	QP
3	108.6470	43.89	-18.46	25.43	43.50	-18.07	QP
4	191.7450	52.57	-20.24	32.33	43.50	-11.17	QP
5	239.9873	49.26	-17.76	31.50	46.00	-14.50	QP
6	326.7395	45.61	-14.12	31.49	46.00	-14.51	QP

Remark:

1. Margin = Result (Result =Reading + Factor)–Limit
2. Factor= Cable Loss +Antenna Factor–Amplifier Gain






Temperature:	22.1 °C	Relative Humidity:	56%
Phase:	Vertical	Test Mode:	Mode 1
Test Voltage:	DC 5V From PC		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	42.8997	50.02	-17.83	32.19	40.00	-7.81	QP
2	46.9947	52.64	-19.94	32.70	40.00	-7.30	QP
3	77.8653	54.40	-23.00	31.40	40.00	-8.60	QP
4	191.7450	54.65	-20.24	34.41	43.50	-9.09	QP
5	239.9873	46.44	-17.76	28.68	46.00	-17.32	QP
6	625.0780	39.45	-6.43	33.02	46.00	-12.98	QP

Remark:

- Margin = Result (Result = Reading + Factor) - Limit
- Factor = Cable Loss + Antenna Factor - Amplifier Gain





(1 GHz to 25GHz.)

Temperature:	26 °C	Relative Humidity:	54%
Phase:	Vertical/Horizontal	Test Mode:	Mode 1
Test Voltage:	DC 5V From PC		

PK

Freq.	Ant. Pol	Peak	Amplifier	Loss	Antenna Factor	Orrected Factor	Actual Fs	Peak	Peak
(MHz)	H/V	Reading (dBuV)	(dB)	(dB)	(dB/m)	(dB)	Peak (dBuV/m)	Limit (dBuV/m)	margin (dB)
2356.63	H	66.35	43.81	4.36	25.93	-12.54	52.83	74.00	-21.17
2542.39	H	57.46	44.47	6.32	27.64	-10.81	46.95	74.00	-27.05
3412.58	H	65.38	44.78	6.71	28.22	-9.82	55.53	74.00	-18.47
4635.85	H	54.23	44.35	8.42	30.44	-5.48	48.74	74.00	-25.26
2254.68	V	60.38	43.81	4.36	25.95	-12.54	46.88	74.00	-27.12
2457.59	V	55.22	44.47	6.32	27.69	-10.83	44.76	74.00	-29.24
3368.56	V	63.68	44.78	6.71	28.26	-9.85	53.87	74.00	-20.13
4542.68	V	56.39	44.35	8.42	30.45	-5.48	50.91	74.00	-23.09
5545.74	V	45.29	44.21	9.35	32.23	-2.59	42.66	74.00	-31.34

AV

Freq.	Ant. Pol	AV	Amplifier	Loss	Antenna Factor	Orrected Factor	AV	AV	AV
(MHz)	H/V	Reading (dBuV)	(dB)	(dB)	(dB/m)	(dB)	AV (dBuV/m)	Limit (dBuV/m)	margin (dB)
2356.63	H	56.35	43.81	4.36	25.93	-12.54	42.83	54.00	-11.17
2542.39	H	48.56	44.47	6.32	27.64	-10.81	38.05	54.00	-15.95
3412.58	H	51.29	44.78	6.71	28.22	-9.82	41.44	54.00	-12.56
4635.85	H	46.38	44.35	8.42	30.44	-5.48	40.89	54.00	-13.11
2254.68	V	55.29	43.81	4.36	25.95	-12.54	41.79	54.00	-12.21
2457.59	V	49.65	44.47	6.32	27.69	-10.83	39.19	54.00	-14.81
3368.56	V	56.38	44.78	6.71	28.26	-9.85	46.57	54.00	-7.43
4542.68	V	47.14	44.35	8.42	30.45	-5.48	41.66	54.00	-12.34
5545.74	V	38.39	44.21	9.35	32.23	-2.59	35.76	54.00	-18.24



Notes:

1. Measuring frequencies from 1 GHz to 25GHz.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode of the emission shown in Actual FS column.
3. The frequency that above 5.5GHz is mainly from the environment noise.

*****END OF THE REPORT*****

