

## MPE ESTIMATION

FCC ID: 2AAIN-MNPAMB283

### 1, Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm <sup>2</sup> )	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

### 2, Estimation Result

#### For 2.4G WIFI:

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )
BT	-3.74	-4±1(-3)	0.5	0	1	0.0001
$Pd = \frac{Pout * G}{4\pi r^2} :$						
Note:						
Note: The estimation distance is 20cm The device could not transmit simultaneously in BT.						
Note: PK Output power= conducted power. Conducted power see the test report HK2101050122-E. Gantenna gain=0dBi						

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.0001mW/cm<sup>2</sup> which is < 1.0mW/cm<sup>2</sup>, RF Exposure testing is not required.

-----The End-----