

FCC Part 15C Measurement and Test Report


For

ACOUSTMAX INTERNATIONAL Co., Ltd

Unit D16/F Cheuk Nang Plaza 250 Hennessy Road Wanchai HongKong.

FCC ID: 2AAINMNDECORA

FCC Rule(s):	<u>FCC Part 15.247</u>
Product Description:	<u>Monster Decora</u>
Tested Model:	<u>MNDECORA-HZL</u>
Report No.:	<u>STRD1804046E-2</u>
Sample Receipt Date:	<u>2018-04-16</u>
Tested Date:	<u>2018-04-17 to 2018-05-02</u>
Issued Date:	<u>2018-05-02</u>
Tested By:	<u>Ray Yang/ Engineer</u>
Reviewed By:	<u>Silin Chen / EMC Manager</u>
Approved & Authorized By:	<u>Jandy So / PSQ Manager</u>
Prepared By:	



Shenzhen SEM Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY.....	4
1.4 TEST FACILITY.....	4
1.5 EUT SETUP AND TEST MODE.....	5
1.6 MEASUREMENT UNCERTAINTY.....	5
1.7 TEST EQUIPMENT LIST AND DETAILS.....	6
2. SUMMARY OF TEST RESULTS.....	7
3. RF EXPOSURE.....	8
3.1 STANDARD APPLICABLE.....	8
3.2 TEST RESULT.....	8
4. ANTENNA REQUIREMENT.....	9
4.1 STANDARD APPLICABLE.....	9
4.2 EVALUATION INFORMATION.....	9
5. POWER SPECTRAL DENSITY.....	10
5.1 STANDARD APPLICABLE.....	10
5.2 TEST PROCEDURE.....	10
5.3 ENVIRONMENTAL CONDITIONS.....	10
5.4 SUMMARY OF TEST RESULTS/PLOTS.....	10
6. 6DB BANDWIDTH.....	13
6.1 STANDARD APPLICABLE.....	13
6.2 TEST PROCEDURE.....	13
6.3 ENVIRONMENTAL CONDITIONS.....	13
6.4 SUMMARY OF TEST RESULTS/PLOTS.....	13
7. RF OUTPUT POWER.....	16
7.1 STANDARD APPLICABLE.....	16
7.2 TEST PROCEDURE.....	16
7.3 ENVIRONMENTAL CONDITIONS.....	16
7.4 SUMMARY OF TEST RESULTS/PLOTS.....	16
8. FIELD STRENGTH OF SPURIOUS EMISSIONS.....	19
8.1 STANDARD APPLICABLE.....	19
8.2 TEST PROCEDURE.....	19
8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	20
8.4 ENVIRONMENTAL CONDITIONS.....	20
8.5 SUMMARY OF TEST RESULTS/PLOTS.....	21
9. OUT OF BAND EMISSIONS.....	28
9.1 STANDARD APPLICABLE.....	28
9.2 TEST PROCEDURE.....	28
9.3 ENVIRONMENTAL CONDITIONS.....	29
9.4 SUMMARY OF TEST RESULTS/PLOTS.....	29
10. CONDUCTED EMISSIONS.....	34
10.1 TEST PROCEDURE.....	34
10.2 BASIC TEST SETUP BLOCK DIAGRAM.....	34
10.3 ENVIRONMENTAL CONDITIONS.....	34
10.4 TEST RECEIVER SETUP.....	35
10.5 SUMMARY OF TEST RESULTS/PLOTS.....	35
10.6 CONDUCTED EMISSIONS TEST DATA.....	35

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: ACOUSTMAX INTERNATIONAL Co., Ltd
Address of applicant: Unit D16/F Cheuk Nang Plaza 250 Hennessy Road
Wanchai HongKong.

Manufacturer: Tech Pro plastic Hardware Dongguan products Co., Ltd.
Address of manufacturer: No.5 fengping road, xinzhongkeng village, sanzhang district, qingxi town, dongguan city, guangdong province

General Description of EUT	
Product Name:	Monster Decora
Brand Name:	MONSTER
Model No.:	MNDECORA-HZL
Adding Model(s):	Monster Decora, MNOECORAMT, MNDECORA-GR, MNDECORA-RD, MNDECORA-AX, MNDECORA-XL, MNDECORA-AV
Rated Voltage:	Adapter: DC 12V
Power Adapter:	Model : BI36-120300-AdU INPUT : AC100-240V~50/60Hz, 1.2A; OUTPUT : DC12V,3A
Software Version:	V0.2
Hardware Version:	V1.0
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model MNDECORA-HZL, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Bluetooth Version:	V4.0 (BLE mode)
Frequency Range:	2402-2480MHz
RF Output Power:	2.599dBm (Conducted)
Data Rate:	1Mbps
Modulation:	GFSK
Quantity of Channels:	40
Channel Separation:	2MHz
Type of Antenna:	PCB
Antenna Gain:	-0.5dBi
Lowest Internal Frequency of EUT:	26MHZ

1.2 Test Standards

The following report is prepared on behalf of the ACOUSTMAX INTERNATIONAL Co., Ltd in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide KDB 558074 D01 v04 for digital transmission systems shall be performed also.

1.4 Test Facility

FCC – Registration No.: 125990

Shenzhen SEM Test Technology Co., Ltd. Laboratory has been recognized to perform compliance testing on equipment subject to the Commissions Declaration Of Conformity (DOC). The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	GFSK(BLE)	2402MHz, 2440MHz, 2480MHz

Accessories Equipment List and Details			
Description	Manufacturer	Model No.	Serial Number
iPhone6 Plus	Apple	MGAJ2ZP/A	FK1PQ4JBG5QW
Earphone	PHILIPS	SHE6000	/
Accessories Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With Core/Without Core
/	/	/	/
EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With Core/Without Core
DC Power	2.0	Unshielded	Without Core

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2017-06-12	2018-06-11
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2017-06-12	2018-06-11
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2017-06-12	2018-06-11
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2017-06-12	2018-06-11
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2017-06-12	2018-06-11
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2017-06-08	2020-06-07
SEMT-1042	Horn Antenna	ETS	3117	00086197	2017-06-08	2020-06-07
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2017-06-08	2020-06-07
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2017-06-08	2020-06-07
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2017-06-12	2018-06-11
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2017-06-12	2018-06-11
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2017-06-12	2018-06-11
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2017-08-15	2018-08-14
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2017-08-15	2018-08-14
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2017-06-12	2018-06-11
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2018-03-19	2021-03-18

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.247(e)	Power Spectral Density	Compliant
§ 15.247(a)(2)	6 dB Bandwidth	Compliant
§ 15.247(b)(3)	RF Output Power	Compliant
§ 15.209(a)	Radiated Emission	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable



3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has a PCB antenna, fulfill the requirement of this section.

5. Power Spectral Density

5.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 Test Procedure

According to the KDB 558074 D01 v04, the test method of power spectral density as below:

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 Environmental Conditions


Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

5.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
GFSK(BLE)	2402	-16.74	8
	2440	-14.73	8
	2480	-12.62	8

Please refer to the following test plots:


Low Channel



Middle Channel



High Channel



6. 6dB Bandwidth

6.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 Environmental Conditions


Temperature:	25° C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

6.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	6 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz
GFSK(BLE)	2402	556.558	1091.3	≥ 500
	2440	555.467	1093.3	≥ 500
	2480	565.800	1102.2	≥ 500

Please refer to the following test plots:


For BLE
Low Channel:



Middle Channel:



High Channel:



7. RF Output Power

7.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

7.2 Test Procedure

According to section KDB-558074 D01 v04 section 9.1.1, this procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the RBW \geq DTS bandwidth.
- b) Set VBW $\geq 3 \times$ RBW.
- c) Set span $\geq 3 \times$ RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

7.3 Environmental Conditions


Temperature:	26° C
Relative Humidity:	57%
ATM Pressure:	1011 mbar

7.4 Summary of Test Results/Plots


Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
GFSK(BLE)	2402	1.011	1.262	1000
	2440	2.599	1.819	1000
	2480	1.995	1.583	1000

Note: the antenna gain of -0.5dBi less than 6dBi maximum permission antenna gain value based on 1 watt peak output power limit.


For BLE
Low Channel:



Middle Channel:



High Channel:



8. Field Strength of Spurious Emissions

8.1 Standard Applicable


According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz
 RBW=10KHz,
 VBW =30KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak

Frequency :30MHz-1GHz
 RBW=120KHz,
 VBW=300KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, QP

Frequency :Above 1GHz
 RBW=1MHz,
 VBW=3MHz(Peak), 10Hz(AV)
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, AV

8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of $-6\text{dB}\mu\text{V}$ means the emission is $6\text{dB}\mu\text{V}$ below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

8.5 Summary of Test Results/Plots


According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Plot of Radiated Emissions Test Data


EUT: *Monster Decora*
 Tested Model: *MNDECORA-HZL*
 Operating Condition: *Transmitting-Low channel (2402MHz)*
 Comment: *AC120V /60Hz*

Test Specification: *Horizontal*



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (*)	Height (cm)	Remark
1	48.5016	27.97	-10.67	17.30	40.00	-22.70	214	100	peak
2	98.4866	27.65	-11.73	15.92	43.50	-27.58	90	100	peak
3	202.8104	26.42	-11.72	14.70	43.50	-28.80	336	100	peak
4	292.0583	27.13	-9.66	17.47	46.00	-28.53	94	100	peak
5	480.5276	27.12	-5.36	21.76	46.00	-24.24	206	100	peak
6	790.6188	28.10	0.21	28.31	46.00	-17.69	292	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (*)	Height (cm)	Remark
1	44.7434	27.25	-10.44	16.81	40.00	-23.19	245	100	peak
2	100.9340	26.77	-11.51	15.26	43.50	-28.24	97	100	peak
3	200.6881	25.76	-11.63	14.13	43.50	-29.37	184	100	peak
4	271.3246	27.09	-9.76	17.33	46.00	-28.67	102	100	peak
5	494.1984	27.42	-5.95	21.47	46.00	-24.53	273	100	peak
6	929.0082	26.88	2.00	28.88	46.00	-17.12	219	100	peak

Operating Condition: Transmitting-Middle channel (2440MHz)


Comment: AC120V /60Hz

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (*)	Height (cm)	Remark
1	45.3755	28.42	-10.60	17.82	40.00	-22.18	83	100	peak
2	97.7983	27.99	-11.88	16.11	43.50	-27.39	315	100	peak
3	199.2855	26.53	-11.69	14.84	43.50	-28.66	50	100	peak
4	392.0951	26.89	-7.36	19.53	46.00	-26.47	284	100	peak
5	629.4772	27.64	-2.99	24.65	46.00	-21.35	326	100	peak
6	952.0937	26.84	1.85	28.69	46.00	-17.31	96	100	peak

Test Specification: Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (*)	Height (cm)	Remark
1	45.2166	28.02	-10.45	17.57	40.00	-22.43	263	100	peak
2	99.1797	26.66	-11.58	15.08	43.50	-28.42	267	100	peak
3	279.0436	25.96	-9.53	16.43	46.00	-29.57	65	100	peak
4	482.2156	27.27	-5.44	21.83	46.00	-24.17	151	100	peak
5	699.3046	28.34	-3.40	24.94	46.00	-21.06	67	100	peak
6	925.7563	26.54	1.90	28.44	46.00	-17.56	284	100	peak

Operating Condition: Transmitting-High channel (2480MHz)


Comment: AC120V /60Hz

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (*)	Height (cm)	Remark
1	46.9948	28.05	-10.64	17.41	40.00	-22.59	268	100	peak
2	99.1797	27.02	-11.58	15.44	43.50	-28.06	138	100	peak
3	214.5143	26.44	-12.24	14.20	43.50	-29.30	107	100	peak
4	393.4724	27.35	-7.41	19.94	46.00	-26.06	111	100	peak
5	631.6884	27.99	-3.03	24.96	46.00	-21.04	104	100	peak
6	938.8326	26.24	2.27	28.51	46.00	-17.49	268	100	peak

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (*)	Height (cm)	Remark
1	50.7637	29.32	-10.65	18.67	40.00	-21.33	90	100	peak
2	97.1148	27.33	-12.04	15.29	43.50	-28.21	154	100	peak
3	210.0482	26.57	-12.04	14.53	43.50	-28.97	104	100	peak
4	406.0880	26.90	-7.70	19.20	46.00	-26.80	103	100	peak
5	622.8900	27.99	-2.85	25.14	46.00	-20.86	153	100	peak
6	896.9965	27.02	1.41	28.43	46.00	-17.57	225	100	peak

Spurious Emissions Above 1GHz
Transmitting: BLE mode:

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2402MHz							
4804	56.38	-3.41	52.97	74	-21.03	H	PK
4804	46.35	-3.41	42.94	54	-11.06	H	AV
7206	55.84	-0.42	55.42	74	-18.58	H	PK
7206	42.36	-0.42	41.94	54	-12.06	H	AV
4804	57.41	-3.41	54	74	-20	V	PK
4804	43.25	-3.41	39.84	54	-14.16	V	AV
7206	56.38	-0.42	55.96	74	-18.04	V	PK
7206	42.58	-0.42	42.16	54	-11.84	V	AV
Middle Channel-2440MHz							
4880	57.41	-3.49	53.92	74	-20.08	H	PK
4880	46.35	-3.49	42.86	54	-11.14	H	AV
7320	56.36	-0.47	55.89	74	-18.11	H	PK
7320	45.18	-0.47	44.71	54	-9.29	H	AV
4880	54.21	-3.49	50.72	74	-23.28	V	PK
4880	44.21	-3.49	40.72	54	-13.28	V	AV
7320	53.25	-0.47	52.78	74	-21.22	V	PK
7320	41.01	-0.47	40.54	54	-13.46	V	AV
High Channel-2480MHz							
4960	57.24	-3.59	53.65	74	-20.35	H	PK
4960	43.25	-3.59	39.66	54	-14.34	H	AV
7440	56.39	-0.52	55.87	74	-18.13	H	PK
7440	42.18	-0.52	41.66	54	-12.34	H	AV
4960	55.24	-3.59	51.65	74	-22.35	V	PK
4960	42.58	-3.59	38.99	54	-15.01	V	AV
7440	56.58	-0.52	56.06	74	-17.94	V	PK
7440	46.35	-0.52	45.83	54	-8.17	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

9. Out of Band Emissions

9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

9.2 Test Procedure

According to the KDB 558074 D01 v04, the band-edge radiated test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

According to the KDB 558074 D01 v04, the conducted spurious emissions test method as follows:

1. Set start frequency to DTS channel edge frequency.
2. Set stop frequency so as to encompass the spectrum to be examined.
3. Set RBW = 100 kHz.
4. Set VBW \geq 300 kHz.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

9.3 Environmental Conditions


Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

9.4 Summary of Test Results/Plots

Restricted Bandedge (Radiated)


Lowest Bandedge-BLE

Horizontal (Worst case)





No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	37.86	-6.38	31.48	54.00	-22.52	Average Detector
	2310.000	50.85	-6.38	44.47	74.00	-29.53	Peak Detector
2	2390.000	37.89	-7.26	30.63	54.00	-23.37	Average Detector
	2390.000	62.13	-7.26	54.87	74.00	-19.13	Peak Detector
3	2401.741	81.10	-7.39	73.71	/	/	Average Detector
	2401.436	101.30	-7.38	93.92	/	/	Peak Detector

Highest Bandedge-BLE
Horizontal (Worst case)





No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.890	81.20	-7.28	73.92	/	/	Average Detector
	2480.010	99.96	-7.28	92.68	/	/	Peak Detector
2	2483.500	43.38	-7.28	36.10	54.00	-17.90	Average Detector
	2483.500	61.95	-7.28	54.67	74.00	-19.33	Peak Detector
3	2500.000	37.52	-7.25	30.27	54.00	-23.73	Average Detector
	2500.000	55.67	-7.25	48.42	74.00	-25.58	Peak Detector



Out of Bandedge and Spurious Emission (Conducted)
 Lowest



Middle Channel:



High Channel:




10. Conducted Emissions

10.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

10.2 Basic Test Setup Block Diagram



10.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

10.4 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency 150 kHz
Stop Frequency 30 MHz
Sweep Speed Auto
IF Bandwidth..... 10 kHz
Quasi-Peak Adapter Bandwidth 9 kHz
Quasi-Peak Adapter Mode Normal

10.5 Summary of Test Results/Plots

According to the data in section 10.6, the EUT complied with the FCC Part 15.207 Conducted margin for this device, with the *worst* margin reading of:


-3.48 dB at 0.4300 MHz in the **Neutral, AVG** detector, 0.15-30MHz

10.6 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data


EUT: *Monster Decora*
 Tested Model: *MNDECORA-HZL*
 Operating Condition: *Transmitting*
 Comment: *AC 120V/60Hz*

Test Specification: *Neutral*



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.4300	33.97	9.80	43.77	47.25	-3.48	AVG
2	0.4380	37.67	9.80	47.47	57.10	-9.63	QP
3	0.7620	25.62	9.78	35.40	56.00	-20.60	QP
4	0.7820	17.36	9.78	27.14	46.00	-18.86	AVG
5	8.4180	4.04	9.56	13.60	50.00	-36.40	AVG
6	9.9140	13.60	9.52	23.12	60.00	-36.88	QP

Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.4340	32.84	9.80	42.64	47.18	-4.54	AVG
2	0.4380	37.41	9.80	47.21	57.10	-9.89	QP
3	0.7500	23.68	9.78	33.46	56.00	-22.54	QP
4	0.7820	14.54	9.78	24.32	46.00	-21.68	AVG
5	25.6380	2.33	9.69	12.02	50.00	-37.98	AVG
6	25.7780	11.49	9.69	21.18	60.00	-38.82	QP

***** END OF REPORT *****