



# RF Exposure Report

**Test report  
On Behalf of  
ACOUSTMAX INTERNATIONAL CO., LTD  
For  
ROCKIN' ROLLER CHARGE SPEAKER  
Model No.: MNRRC**

**FCC ID: 2AAINYS1352**

**Prepared for :** ACOUSTMAX INTERNATIONAL CO., LTD  
Unit D16/F Cheuk Nang Plaza 250 Hennessy Road Wanchai HongKong

**Prepared By :** Shenzhen HUAKE Testing Technology Co., Ltd.  
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai  
Street, Bao'an District, Shenzhen City, China

**Date of Test:** Dec. 28, 2018 ~ Jan. 30, 2019

**Date of Report:** Jan. 30, 2019

**Report Number:** HK1901030021E01



### TEST RESULT CERTIFICATION

**Applicant's name** ..... : ACOUSTMAX INTERNATIONAL CO., LTD  
**Address** ..... : Unit D16/F Cheuk Nang Plaza 250 Hennessy Road Wanchai  
 HongKong  
**Manufacture's Name** ..... : Arts Electronics Co., Ltd.  
**Address** ..... : NO. 1, SHANGXING LU, SHANGJIAO COMMUNITY, CHANGAN  
 TOWN, DONGGUAN CITY, GUANGDONG PROVINCE, CHINA

#### Product description

**Trade Mark:** MONSTER  
**Product name** ..... : ROCKIN' ROLLER CHARGE SPEAKER  
**Model and/or type reference** : MNRRC  
**Series Model** ..... MNRRC2, MNRRC3, MNRRCSE

**Difference Description**..... All models covered in this report were identical with each other except different model no.and appearance(for color and silk-screen only)for trading purpose

**Standards** ..... : KDB 680106 D01 RF Exposure Wireless Charging Base App v03

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Date of Test** ..... :  
**Date (s) of performance of tests** ..... : Dec. 28, 2018 ~ Jan. 30, 2019  
**Date of Issue**..... : Jan. 30, 2019  
**Test Result**..... : **Pass**

**Testing Engineer** : Gary Qian  
 (Gary Qian)  
**Technical Manager** : Eden Hu  
 (Eden Hu)  
**Authorized Signatory** : Jason Zhou  
 (Jason Zhou)



<b>Table of Contents</b>	<b>Page</b>
1 . TEST SUMMARY	4
2. GENERAL INFORMATION	5
2.1. PRODUCT DESCRIPTION	5
2.2 OPERATION OF EUT DURING TESTING	6
2.3 DESCRIPTION OF TEST SETUP	6
5. TEST EQUIPMENT LIST	6
6. RADIO FREQUENCY (RF) EXPOSURE TEST	8
6.1. LIMITS	8
6.2. TEST SETUP	8
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	10



## 1. TEST SUMMARY

### 1.1 TEST PROCEDURES AND RESULTS

DESCRIPTION OF TEST	RESULT
E and H field strength measurements	Compliant

### 1.2 TEST FACILITY

Test Firm : Shenzhen HUAKE Testing Technology Co., Ltd.

Address : 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road,  
Heping Community, Fuhai Street, Bao'an District, Shenzhen,  
Guangdong, China

Designation Number: : CN1229

Test Firm Registration Number : 616276

### 1.3 MEASUREMENT UNCERTAINTY

Measurement Uncertainty

E-field strength = 0.2dB, k=2

H-field strength = 0.3dB, k=2



## 2. GENERAL INFORMATION

### 2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

<b>Operation Frequency</b>	110~148kHz
<b>Test Frequency</b>	146.6kHz
<b>Maximum field strength</b>	50.65dBuV/m(Peak)@3m
<b>Antenna Designation</b>	Integrated Antenna (Met 15.203 Antenna requirement)
<b>Hardware Version</b>	RV01
<b>Software Version</b>	V00
<b>Power Supply(by battery)</b>	DC 12V by battery
<b>Power Supply</b>	AC 100-240V 50/60Hz



## 2.2 OPERATION OF EUT DURING TESTING


NO.	TEST MODE DESCRIPTION
1	Wireless charging Mode(Full load)
2	Wireless charging Mode(half load)
3	Wireless charging Mode(Null load)

Note:

1. The mode 1 was the worst case and only the data of the worst case record in this report.

## 2.3 DESCRIPTION OF TEST SETUP

Configure :



Item	Equipment	Mfr/Brand	Model/Type No.	Remark
1	ROCKIN' ROLLER CHARGE SPEAKER	MONSTER	MNRRC	EUT
2	AC input Cable	N/A	2.0m unshielded	Accessory
3	Wireless electronic Load	--	Maximum power 5W	AE



### 3. TEST EQUIPMENT LIST


Description	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Broadband Field Meter	Narda Safety Test Solutions GmbH	NBM-550	J-0004	June 12, 2018	June 11, 2019
Probe FHP	Narda Safety Test Solutions GmbH	EHP-50F	J-0015	June 12, 2018	June 11, 2019

## 4. RADIO FREQUENCY (RF) EXPOSURE TEST

### 4.1. LIMITS

For devices designed for typical desktop applications, such as wireless charging pads, RF exposure evaluation should be conducted assuming a user separation distance of 15 cm. E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair, with the 15 cm measured from the center of the probe(s) to the edge of the device. Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m.

### 4.2. TEST SETUP



Note: Position A: Front of EUT; Position B: Left of EUT; Position C: back of EUT; Position D: Right of EUT; Position E: Top of EUT(20 cm measure distance);





### 4.3. TEST PROCEDURE

The EUT was placed on a non-conductive table top and the ancillary equipment (e.g. mobile phone) was placed on the EUT for charging.

Maximum E-field and H-field measurements were tested 15cm from each side of the EUT. For top side the measure distance is 15cm.

Along the side of the EUT to center of E-field probe and H-field probe were positioned at the location to search maximum field strength.

### 4.4. TEST RESULT

Test condition: Mode 1

E-field strength test result:

Frequency Range	Probe Position A (V/m)	Probe Position B (V/m)	Probe Position C (V/m)	Probe Position D (V/m)	Probe Position E (V/m)	Limit (V/m)
146.6kHz	0.16	0.16	0.16	0.16	2.42	614

H-field strength test result:

Frequency Range	Probe Position A (A/m)	Probe Position B (A/m)	Probe Position C (A/m)	Probe Position D (A/m)	Probe Position E (A/m)	Limit (A/m)
146.6kHz	0.18	0.18	0.18	0.18	0.41	1.63

Test condition: Mode 3

E-field strength test result:

Frequency Range	Probe Position A (V/m)	Probe Position B (V/m)	Probe Position C (V/m)	Probe Position D (V/m)	Probe Position E (V/m)	Limit (V/m)
110.4kHz	0.18	0.18	0.18	0.18	1.29	614

H-field strength test result:


Frequency Range	Probe Position A (A/m)	Probe Position B (A/m)	Probe Position C (A/m)	Probe Position D (A/m)	Probe Position E (A/m)	Limit (A/m)
110.4kHz	0.16	0.16	0.16	0.16	0.36	1.63

## APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Position E



Position A





Position B




Position C





Position D



----END OF REPORT----