



FCC 47 CFR PART 22 SUBPART H AND PART 24 SUBPART E

TEST REPORT

For

Product Name: Mobile Phone

Brand Name: FPXPHONE

Model No.: F9300

Series Model: N/A

Test Report Number:
C130703R01-RP1

Issued for

Etoway Technology Co.,Ltd

Room 1004-1005, Building A, Stars Plaza No.38 Hongli Road, Futian District, Shenzhen City, China

Issued by

Compliance Certification Services Inc.

Kun shan Laboratory

No.10 Weiye Rd., Innovation park, Eco&Tec,
Development Zone, Kunshan City, Jiangsu, China

TEL: 86-512-57355888

FAX: 86-512-57370818



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by A2LA or any government agencies. The test results in the report only apply to the tested sample.



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

REVISION HISTORY

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	July 12, 2013	Initial Issue	ALL	Hui.Li



TABLE OF CONTENTS

1	TEST RESULT CERTIFICATION	4
2	EUT DESCRIPTION	5
3	TEST METHODOLOGY	6
3.1.	EUT CONFIGURATION	6
3.2.	EUT EXERCISE	6
3.3.	GENERAL TEST PROCEDURES	6
3.4.	DESCRIPTION OF TEST MODES	6
4	INSTRUMENT CALIBRATION	7
4.1.	MEASURING INSTRUMENT CALIBRATION	7
4.2.	MEASUREMENT EQUIPMENT USED	7
4.3.	MEASUREMENT UNCERTAINTY	8
5	FACILITIES AND ACCREDITATIONS	9
5.1.	FACILITIES	9
5.2.	EQUIPMENT	9
5.3.	ACCREDITATIONS	9
6	SETUP OF EQUIPMENT UNDER TEST	10
6.1.	SETUP CONFIGURATION OF EUT	10
6.2.	SUPPORT EQUIPMENT	10
7	FCC PART 22 & 24 REQUIREMENTS	11
7.1.	PEAK POWER	11
7.2.	AVERAGE POWER	13
7.3.	ERP & EIRP MEASUREMENT	15
7.4.	OCCUPIED BANDWIDTH MEASUREMENT	19
7.5.	OUT OF BAND EMISSION AT ANTENNA TERMINALS	26
7.6.	FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT	39
7.7.	FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT	53
7.8.	REQUENCY STABILITY V.S. VOLTAGE MEASUREMENT	56
7.9.	POWERLINE CONDUCTED EMISSIONS	58



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

1 TEST RESULT CERTIFICATION

Product Name:	Mobile Phone
Trade Name:	FPXPHONE
Model Name.:	F9300
Series Model:	N/A
Applicant Discrepancy:	Initial
Devices supporting GPRS:	Class B
GPRS /EDGE Level:	Multi-Class 12
Multi-slot Class:	1 Uplink +4 Downlink
Device Category:	PORTABLE DEVICES
Exposure Category:	GENERAL POPULATION/UNCONTROLLED EXPOSURE
Date of Test:	July 9, 2013
Applicant:	Etoway Technology Co.,Ltd Room 1004-1005, Building A, Stars Plaza No.38 Hongli Road, Futian District, Shenzhen City, China
Manufacturer:	Etoway Technology Co.,Ltd Room 1004-1005, Building A, Stars Plaza No.38 Hongli Road, Futian District, Shenzhen City, China
Application Type:	Certification


APPLICABLE STANDARDS

STANDARD	TEST RESULT
FCC 47 CFR Part 22 Subpart H & Part 24 Subpart E	No non-compliance noted

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4: 2003 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rule FCC PART 22 Subpart H and PART 24 Subpart E.

The test results of this report relate only to the tested sample identified in this report.


Approved by:



Hui.Li

Hui.Li
RF Manager
Compliance Certification Service Inc.

Tested by:



Blent.Wang

Blent.Wang
Test Engineer
Compliance Certification Service Inc.



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

2 EUT DESCRIPTION

Product Name:	Mobile Phone
Brand Name:	FPXPHONE
Model Name:	F9300
Series Model:	N/A
Model Discrepancy:	N/A
Power Adapter Power Rating :	Power supply and ADP (rating): Brand: Class 2 power unit Model: SK01G-0500050U INPUT:AC100~240V 50/60Hz 0.2A OUTPUT:5V --- 0.5A Battery (rating): Model: BL-4U Capacitance: 3.7V 800mAh
Frequency Range:	GSM/GPRS 850: 824.20 ~ 848.80 MHz GSM/GPRS 1900: 1850.20 ~ 1909.80 MHz WIFI:2412~2462 MHz
Transmit Power:	GSM 850: 31.50 dBm GSM 1900: 27.06 dBm GPRS 850: 31.55 dBm GPRS 1900: 27.06 dBm
Modulation Technique:	GSM/GPRS: GMSK IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: DSSS /OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20/40 : OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Gain:	GSM/WCDMA : 2 dBi
Antenna Type:	GSM/WCDMA : PIFA Antenna BT,WIFI: PIFA Antenna

Remark:

1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.
2. This submittal(s) (test report) is intended for FCC ID: 2AAJDF9300 filing to comply with Part 22 and Part 24 of the FCC 47 CFR Rules.



3 TEST METHODOLOGY

Both conducted and radiated testing were performed according to the procedures document on chapter 13 of ANSI C63.4: 2003, TIA/EIA-603-C: 2004 and FCC CFR 47, Part 2, PART 22 SUBPART H AND PART 24 SUBPART E

3.1. EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2. EUT EXERCISE

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

3.3. GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4: 2003. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

RADIATED EMISSIONS

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4: 2003.

3.4. DESCRIPTION OF TEST MODES

The EUT (model: Gobi2) had been tested under operating condition.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz and power line conducted emissions below 30MHz, which worst case was in normal link mode only.

EUT staying in continuous transmitting mode was programmed.

GSM/GPRS / 850:

Channel Low (CH128), Channel Mid (CH190) and Channel High (CH251) were chosen for full testing.

GSM/GPRS / 1900:

Channel Low (CH512), Channel Mid (CH661) and Channel High (CH810) were chosen for full testing.



4 INSTRUMENT CALIBRATION

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

4.2. MEASUREMENT EQUIPMENT USED

Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	2014-5-11
DETECTOR NEGATIVE	Agilent	8473B	MY42240176	2014-5-11
OSCILLOSCOPE	Agilent	DSO6104A	MY44002585	2014-3-24
Peak and Avg Power Sensor	Agilent	E9327A	US40441788	2014-3-24
EPM-P Series Power Meter	Agilent	E4416A	GB41292714	2014-5-11
Power SPLITTER	Mini-Circuits	ZN2PD-9G	SF078500430	2014-5-11
DC POWER SUPPLY	GW instek	GPS-3303C	E903131	2014-5-11
Temp. / Humidity Chamber	Kingson	THS-M1	242	2014-3-12
Test Software			EZ-EMC	

977 Chamber

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	2014-5-11
EMI Test Receiver	R&S	ESPI3	101026	2014-3-15
Pre-Amplifier	MINI	ZFL-1000VH2	d041703	2014-6-29
Pre-Amplifier	Miteq	NSP4000-NF	870629	2014-6-29
Bilog Antenna	Sunol	JB1	A110204-2	2014-6-23
Horn-antenna	SCHWARZBECK	BBHA9120D	D:266	2014-5-11
Turn Table	CT	CT123	4165	N.C.R
Antenna Tower	CT	CTERG23	3256	N.C.R
Controller	CT	CT100	95637	N.C.R
Test Software			EZ-EMC	



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

Conducted Emission				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI TEST RECEIVER	R&S	ESCI3	100781	2014-3-15
V (V-LISN)	Schwarzbeck	NNLK 8129	8129-143	2014-3-15
LISN (EUT)	FCC	FCC-LISN-50/250-50-2-02	SN:05012	2014-3-15
TRANSIENT LIMITER	SCHAFFNER	CFL9206	1710	2014-4-8
Test Software		EZ-EMC		

Remark: Each piece of equipment is scheduled for calibration once a year.

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency		Uncertainty
Conducted emissions	0.15MHz~30MHz		± 3.43 dB
Measurement	Polarity	Frequency	Uncertainty
Radiated emissions (below 1GHz)	H	30MHz ~ 200MHz	+/- 4.72dB
		200MHz ~1000MHz	+/- 4.72dB
	V	30MHz ~ 200MHz	+/- 4.83dB
		200MHz ~1000MHz	+/- 4.70dB
Radiated emissions (above 1GHz)	H	1000MHz ~5000MHz	+/- 3.94dB
		5000MHz ~6000MHz	+/- 3.94dB
	V	1000MHz ~5000MHz	+/- 3.94dB
		5000MHz ~6000MHz	+/- 3.94dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



5 FACILITIES AND ACCREDITATIONS

5.1. FACILITIES

No.10Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22.

5.2. EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

USA	A2LA
China	CNAS

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada	Industry Canada
Japan	VCCI
Taiwan	BSMI
USA	FCC

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsrf.com>



6 SETUP OF EQUIPMENT UNDER TEST

6.1. SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix I for the actual connections between EUT and support equipment.

6.2. SUPPORT EQUIPMENT

No.	Device Type	Brand	Model	FCC ID	Series No.	Data Cable	Power Cord
N/A							

Remark:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.




7 FCC PART 22 & 24 REQUIREMENTS

7.1. PEAK POWER

LIMIT

According to FCC §2.1046.

Test Configuration



Remark: Measurement setup for testing on Antenna connector

TEST PROCEDURE

The transmitter output was connected to a calibrated attenuator, the other end of which was connected to a power meter. Transmitter output was read off the power meter in dBm. The power output at the transmitter antenna port was determined by adding the value of the attenuator to the power meter reading.

TEST RESULTS

No non-compliance noted.

Test Data

Test Mode	CH	Frequency (MHz)	Peak Power (dBm)
GSM 850	128	824.40	31.39
	190	836.60	31.50
	251	848.80	31.48
GSM 1900	512	1850.20	27.06
	661	1880.00	26.94
	810	1909.80	27.05



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

Test Mode		CH	Frequency (MHz)	Peak Power (dBm)
GSM850 (Class12)	1 Uplink +4 Downlink	128	824.40	31.36
		190	836.60	31.48
		251	848.80	31.55
	2 Uplink +3 Downlink	128	824.40	30.10
		190	836.60	30.21
		251	848.80	30.28
	3 Uplink +2 Downlink	128	824.40	28.26
		190	836.60	28.41
		251	848.80	28.51
	4 Uplink +1 Downlink	128	824.40	26.32
		190	836.60	26.50
		251	848.80	26.61

Test Mode		CH	Frequency (MHz)	Peak Power (dBm)
GSM19000 (Class12)	1 Uplink +4 Downlink	512	1850.20	27.02
		661	1880.00	26.92
		810	1909.80	27.06
	2 Uplink +3 Downlink	512	1850.20	25.00
		661	1880.00	24.87
		810	1909.80	24.86
	3 Uplink +2 Downlink	512	1850.20	23.07
		661	1880.00	23.14
		810	1909.80	23.25
	4 Uplink +1 Downlink	512	1850.20	21.11
		661	1880.00	21.14
		810	1909.80	21.31

Remark: The value of factor includes both the loss of cable and external attenuator




7.2. AVERAGE POWER

LIMIT

For reporting purposes only.

TEST CONFIGURATION



Remark: Measurement setup for testing on Antenna connector

TEST PROCEDURE

The transmitter output was connected to a calibrated attenuator, the other end of which was connected to a power meter. Transmitter output was read off the power meter in dBm. The power output at the transmitter antenna port was determined by adding the value of the attenuator to the power meter reading.

TEST RESULTS

No non-compliance noted.

Test Data

Test Mode	CH	Frequency (MHz)	Average Power (dBm)
GSM 850	128	824.40	31.36
	190	836.60	31.44
	251	848.80	31.43
GSM 1900	512	1850.20	27.05
	661	1880.00	26.94
	810	1909.80	27.04



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

Test Mode		CH	Frequency (MHz)	Average Power (dBm)
GSM850 (Class12)	1 Uplink +4 Downlink	128	824.40	31.26
		190	836.60	31.35
		251	848.80	31.42
	2 Uplink +3 Downlink	128	824.40	30.09
		190	836.60	30.20
		251	848.80	30.27
	3 Uplink +2 Downlink	128	824.40	28.25
		190	836.60	28.40
		251	848.80	28.47
	4 Uplink +1 Downlink	128	824.40	26.31
		190	836.60	26.48
		251	848.80	26.60

Test Mode		CH	Frequency (MHz)	Average Power (dBm)
GSM19000 (Class12)	1 Uplink +4 Downlink	512	1850.20	27.01
		661	1880.00	26.91
		810	1909.80	27.05
	2 Uplink +3 Downlink	512	1850.20	24.98
		661	1880.00	24.85
		810	1909.80	24.77
	3 Uplink +2 Downlink	512	1850.20	23.06
		661	1880.00	23.13
		810	1909.80	23.23
	4 Uplink +1 Downlink	512	1850.20	21.10
		661	1880.00	21.12
		810	1909.80	21.29

Remark: The value of factor includes both the loss of cable and external attenuator

7.3. ERP & EIRP MEASUREMENT

LIMIT


According to FCC §2.1046

FCC 22.913(a): The Effective Radiated Power (ERP) of mobile transmitters must not exceed 7 Watts.


FCC 24.232(b): The equivalent Isotropic Radiated Power (EIRP) must not exceed 2 Watts.

TEST CONFIGURATION

Below 1 GHz




Above 1 GHz





FOR SUBSTITUTED METHOD TEST SET-UP



TEST PROCEDURE

The EUT was placed on a non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer.

During the measurement of the EUT, the resolution bandwidth was set to 3MHz and the average bandwidth was set to 3MHz. The highest emission was recorded with the rotation of the turntable and the lowering of the test antenna. The reading was recorded and the field strength (E in dBuV/m) was calculated.

ERP in frequency band 824-849MHz, and EIRP in frequency band 1851.25 –1910MHz were measured using a substitution method. The EUT was replaced by half-wave dipole (824-849MHz) or horn antenna (1851.25-1910MHz) connected to a signal generator. The spectrum analyzer reading was recorded and ERP/EIRP was calculated as follows:

$$\text{ERP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable (dB)}$$

$$\text{EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable (dB)}$$

TEST RESULTS

No non-compliance noted.



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

GSM 850 TEST DATA

Channel	Frequency (MHz)	Antenna Pol.	Reading level (dB)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
128	824.18	V	-4.79	33.16	28.37	38.5	-10.13
	824.3	H	-9.92	33.13	23.21	38.5	-15.29
190	836.66	V	-5.06	33.15	28.09	38.5	-10.41
	836.78	H	-9.33	33.17	23.84	38.5	-14.66
251	848.84	V	-3.82	33.2	29.38	38.5	-9.12
	848.84	H	-7.79	33.18	25.39	38.5	-13.11

GSM 1900 TEST DATA

Channel	Frequency (MHz)	Antenna Pol.	Reading level (dB)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
512	1850.1	V	-26.19	40.48	14.29	33	-18.71
	1850	H	-29.56	48.5	18.94	33	-14.06
661	1880	V	-27.33	40.56	13.23	33	-19.77
	1879.8	H	-22.03	40.55	18.52	33	-14.48
810	1909.9	V	-28.28	40.7	12.42	33	-20.58
	1909.9	H	-22.57	40.71	18.14	33	-14.86

GPRS 850 TEST DATA

Channel	Frequency (MHz)	Antenna Pol.	Reading level (dB)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
128	824.18	V	-5.47	33.16	27.69	38.5	-10.81
	824.18	H	-10.06	33.13	23.07	38.5	-15.43
190	836.54	V	-5.8	33.15	27.35	38.5	-11.15
	836.54	H	-9.98	33.17	23.19	38.5	-15.31
251	848.78	V	-4.82	33.2	28.38	38.5	-10.12
	849.08	H	-7.97	33.18	25.21	38.5	-13.29



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

GPRS 1900 TEST DATA

Channel	Frequency (MHz)	Antenna Pol.	Reading level (dB)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
512	1850.2	V	-26.95	40.48	13.53	33	-19.47
	1850.2	H	-30.34	48.5	18.16	33	-14.84
661	1879.8	V	-27.44	40.56	13.12	33	-19.88
	1879.8	H	-22.09	40.55	18.46	33	-14.54
810	1909.7	V	-28.33	40.7	12.37	33	-20.63
	1909.7	H	-22.45	40.71	18.26	33	-14.74




7.4. OCCUPIED BANDWIDTH MEASUREMENT

LIMIT

According to §FCC 2.1049.

TEST CONFIGURATION



Remark: Measurement setup for testing on Antenna connector

TEST PROCEDURE

The EUT's output RF connector was connected with a short cable to the spectrum analyzer, RBW was set to about 1% of emission BW, VBW is set to 3 times the RBW, -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

TEST RESULTS

No non-compliance noted

Test Data

Test Mode	CH	Frequency (MHz)	99% Bandwidth (kHz)	26dB Bandwidth KHz
GPRS 850	128	824.40	244.1409	313.368
	190	836.60	247.8827	317.156
	251	848.80	240.9108	321.648
GSM 850	128	824.40	245.8230	323.096
	190	836.60	246.0681	324.267
	251	848.80	246.8855	321.323

Test Mode	CH	Frequency (MHz)	99% Bandwidth (kHz)	26dB Bandwidth KHz
GPRS 1900	512	1850.20	246.6260	317.142
	661	1880.00	245.7775	314.200
	810	1909.80	246.5600	322.255
GSM 1900	512	1850.20	244.7789	321.697
	661	1880.00	246.3067	321.212
	810	1909.80	244.3029	320.677



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300


Date of Issue :July 12, 2013

Test Plot

GSM 850 (CH Low)

Agilent

R L




Transmit Freq Error 1.480 kHz
x dB Bandwidth 323.096 kHz

GSM 850 (CH Mid)

Agilent

R L



Transmit Freq Error -310.511 Hz
x dB Bandwidth 324.267 kHz



Compliance Certification Services Inc.

Report No: C130703R01-RP1


FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

GSM 850(CH High)

Agilent

R L




Transmit Freq Error 49.821 Hz
x dB Bandwidth 321.323 kHz

GPRS 850 (CH Low)

Agilent

R T



Transmit Freq Error -314.164 Hz
x dB Bandwidth 313.368 kHz



Compliance Certification Services Inc.

Report No: C130703R01-RP1


FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

GPRS 850 (CH Mid)

Agilent

R T




Transmit Freq Error 416.122 Hz
x dB Bandwidth 317.156 kHz

GPRS 850(CH High)

Agilent

R T



Transmit Freq Error 1.859 kHz
x dB Bandwidth 321.648 kHz



Compliance Certification Services Inc.

Report No: C130703R01-RP1


FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

GPRS 1900 (CH Low)

Agilent

R T




Transmit Freq Error 1.095 kHz
x dB Bandwidth 317.142 kHz

GPRS 1900 (CH Mid)

Agilent

R T



Transmit Freq Error 713.885 Hz
x dB Bandwidth 314.200 kHz



Compliance Certification Services Inc.

Report No: C130703R01-RP1


FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

GPRS 1900 (CH High)

Agilent

R T




Transmit Freq Error 508.351 Hz
x dB Bandwidth 322.255 kHz

GSM 1900 (CH Low)

Agilent

R L



Transmit Freq Error 323.846 Hz
x dB Bandwidth 321.697 kHz



Compliance Certification Services Inc.

Report No: C130703R01-RP1


FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

GSM 1900 (CH Mid)

Agilent

R L




Transmit Freq Error -10.907 Hz
x dB Bandwidth 321.212 kHz

GSM 1900 (CH High)

Agilent

R L



Transmit Freq Error -980.934 Hz
x dB Bandwidth 320.677 kHz



7.5. OUT OF BAND EMISSION AT ANTENNA TERMINALS

LIMIT


According to FCC §2.1051, FCC §22.917, FCC §24.238(a).

Out of Band Emissions: The mean power of emission must be attenuated below the mean power of the non-modulated carrier (P) on any frequency twice or more than twice the fundamental frequency by at least $43 + 10 \log P$ dB.

Mobile Emissions in Base Frequency Range: The mean power of any emissions appearing in the base station frequency range from cellular mobile transmitters operated must be attenuated to a level not exceed -80 dBm at the transmit antenna connector.

Band Edge Requirements: In the 1MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1% of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the Out of band Emission

TEST CONFIGURATION



TEST PROCEDURE

The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz, sufficient scans were taken to show the out of band Emissions if any up to 10th harmonic.

For the out of band: Set the RBW, VBW = 1MHz, Start=30MHz, Stop= 10 th harmonic. Limit = -13dBm

Band Edge Requirements (824 MHz and 849 MHz /1850MHz and 1910MHz): In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions. Limit, -13dBm.

TEST RESULTS

No non-compliance noted.



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

Test Data

Mode	CH	Location	Description
GSM 850	128	Figure 3-1	Band Edge emissions
	251	Figure 3-2	Band Edge emissions

Mode	CH	Location	Description
GSM 1900	512	Figure 4-1	Band Edge emissions
	810	Figure 4-2	Band Edge emissions

Mode	CH	Location	Description
GSM 850	128	Figure 5-1	Conducted spurious emissions, 30MHz - 20GHz
	190	Figure 5-2	Conducted spurious emissions, 30MHz - 20GHz
	251	Figure 5-3	Conducted spurious emissions, 30MHz - 20GHz

Mode	CH	Location	Description
GSM 1900	512	Figure 6-1	Conducted spurious emissions, 30MHz - 20GHz
	661	Figure 6-2	Conducted spurious emissions, 30MHz - 20GHz
	810	Figure 6-3	Conducted spurious emissions, 30MHz - 20GHz

Mode	CH	Location	Description
GPRS 850	128	Figure 7-1	Conducted spurious emissions, 30MHz - 20GHz
	190	Figure 7-2	Conducted spurious emissions, 30MHz - 20GHz
	251	Figure 7-3	Conducted spurious emissions, 30MHz - 20GHz

Mode	CH	Location	Description
GPRS 1900	512	Figure 8-1	Conducted spurious emissions, 30MHz - 20GHz
	661	Figure 8-2	Conducted spurious emissions, 30MHz - 20GHz
	810	Figure 8-3	Conducted spurious emissions, 30MHz - 20GHz



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

Mode	CH	Location	Description
GPRS 850	128	Figure 9-1	Band Edge emissions
	251	Figure 9-2	Band Edge emissions

Mode	CH	Location	Description
GPRS 1900	512	Figure 10-1	Band Edge emissions
	810	Figure 10-2	Band Edge emissions



Test Plot

GSM 850

Figure 5-1: Out of Band emission at antenna terminals – GSM CH Low




Figure 5-2: Out of Band emission at antenna terminals – GSM CH Mid








Figure 5-3: Out of Band emission at antenna terminals – GSM CH High



GSM 1900

Figure 6-1: Out of Band emission at antenna terminals – GSM CH Low





Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

Figure 6-2: Out of Band emission at antenna terminals – GSM CH Mid





Figure 6-3: Out of Band emission at antenna terminals – GSM CH High





GSM 850

Figure 3-1: Band Edge emissions – GSM CH Low





Figure 3-2: Band Edge emissions –GSM CH High





GSM 1900

Figure 4-1: Band Edge emissions – GSM CH Low





Figure 4-2: Band Edge emissions – GSM CH High





GPRS 850

Figure 7-1: Out of Band emission at antenna terminals – GPRS CH Low




Figure 7-2: Out of Band emission at antenna terminals – GPRS CH Mid







Figure 7-3: Out of Band emission at antenna terminals – GPRS CH High



GPRS 1900

Figure 8-1: Out of Band emission at antenna terminals – GPRS CH Low






Figure 8-2: Out of Band emission at antenna terminals – GPRS CH Mid





Figure 8-3: Out of Band emission at antenna terminals – GPRS CH High





GPRS 850

Figure 9-1: Band Edge emissions – GPRS CH Low





Figure 9-2: Band Edge emissions –GPRS CH High





GPRS 1900

Figure 10-1: Band Edge emissions – GPRS CH Low





Figure 10-2: Band Edge emissions – GPRS CH High






7.6. FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT

LIMIT


According to FCC §2.1053

TEST CONFIGURATION

Below 1 GHz




Above 1 GHz





Substituted Method Test Set-up



TEST PROCEDURE

The EUT was placed on a non-conductive, the measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

The frequency range up to tenth harmonic was investigated for each of three fundamental frequency (low, middle and high channels). Once spurious emission were identified, the power of the emission was determined using the substitution method.

The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and the spurious emissions frequency.

$$\text{ERP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBd)} - \text{Cable (dB)}$$

$$\text{EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable (dB)}$$



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

TEST RESULTS

Refer to the attached tabular data sheets.

Radiated Spurious Emission Measurement Result / Below 1GHz

Operation Mode:	GPRS 850 / TX / CH 128	Test Date:	2013-7-10
Temperature:	23°C	Tested by:	Blent.Wang
Humidity:	51 % RH	Polarity:	Ver. / Hor.

Frequency (MHz)	Antenna Polarization	Reading (dBm)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
159.02	V	-73.87	24.38	-49.49	-13.00	-36.49
370.43	V	-73.45	27.03	-46.42	-13.00	-33.42
476.14	V	-73.88	29.22	-44.66	-13.00	-31.66
634.70	V	-74.37	31.44	-42.93	-13.00	-29.93
748.17	V	-73.81	32.78	-41.03	-13.00	-28.03
953.37	V	-73.75	34.38	-39.37	-13.00	-26.37
126.38	H	-74.48	27.37	-47.11	-13.00	-34.11
368.88	H	-73.97	26.92	-47.05	-13.00	-34.05
488.57	H	-73.90	29.38	-44.52	-13.00	-31.52
620.71	H	-73.61	31.18	-42.43	-13.00	-29.43
819.68	H	-74.04	33.16	-40.88	-13.00	-27.88
928.49	H	-73.85	34.62	-39.23	-13.00	-26.23



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

Operation Mode:	GPSR 850 / TX / CH 190	Test Date:	2013-7-10
Temperature:	23°C	Tested by:	Blent.Wang
Humidity:	51 % RH	Polarity:	Ver. / Hor.

Frequency (MHz)	Antenna Polarization	Reading (dBm)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
141.92	V	-74.19	24.41	-49.78	-13.00	-36.78
272.50	V	-73.91	25.48	-48.43	-13.00	-35.43
497.90	V	-73.34	29.28	-44.06	-13.00	-31.06
658.01	V	-73.52	31.39	-42.13	-13.00	-29.13
751.28	V	-73.72	32.85	-40.87	-13.00	-27.87
961.14	V	-73.41	34.49	-38.92	-13.00	-25.92
127.93	H	-74.35	27.55	-46.80	-13.00	-33.80
323.80	H	-72.94	26.08	-46.86	-13.00	-33.86
487.02	H	-74.20	29.35	-44.85	-13.00	-31.85
633.14	H	-74.34	31.35	-42.99	-13.00	-29.99
757.50	H	-73.94	32.61	-41.33	-13.00	-28.33
992.23	H	-73.18	34.98	-38.20	-13.00	-25.20

Remark:

1. The emission behaviour belongs to narrowband spurious emission.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

Operation Mode:	GPRS 850 / TX / CH 251	Test Date:	2013-7-10
Temperature:	23°C	Tested by:	Blent.Wang
Humidity:	51 % RH	Polarity:	Ver. / Hor.

Frequency (MHz)	Antenna Polarization	Reading (dBm)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
137.26	V	-74.28	24.30	-49.98	-13.00	-36.98
364.21	V	-73.62	26.84	-46.78	-13.00	-33.78
552.31	V	-73.38	29.94	-43.44	-13.00	-30.44
745.06	V	-73.86	32.64	-41.22	-13.00	-28.22
864.76	V	-74.01	33.70	-40.31	-13.00	-27.31
973.57	V	-73.65	34.69	-38.96	-13.00	-25.96
131.04	H	-74.54	27.67	-46.87	-13.00	-33.87
344.01	H	-73.30	26.04	-47.26	-13.00	-34.26
490.13	H	-73.92	29.41	-44.51	-13.00	-31.51
603.61	H	-73.74	30.76	-42.98	-13.00	-29.98
701.54	H	-73.76	32.01	-41.75	-13.00	-28.75
869.42	H	-73.08	33.73	-39.35	-13.00	-26.35

Remark:

1. The emission behaviour belongs to narrowband spurious emission.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

Operation Mode:	GPRS 1900 / TX / CH 512	Test Date:	2013-7-10
Temperature:	21°C	Tested by:	Blent.Wang
Humidity:	53 % RH	Polarity:	Ver. / Hor.

Frequency (MHz)	Antenna Polarization	Reading (dBm)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
182.34	V	-74.14	24.15	-49.99	-13.00	-36.99
306.70	V	-73.57	25.58	-47.99	-13.00	-34.99
522.77	V	-74.00	29.32	-44.68	-13.00	-31.68
706.20	V	-73.25	32.00	-41.25	-13.00	-28.25
869.42	V	-74.03	33.80	-40.23	-13.00	-27.23
978.24	V	-73.79	34.78	-39.01	-13.00	-26.01
127.93	H	-73.89	27.55	-46.34	-13.00	-33.34
280.27	H	-74.06	25.68	-48.38	-13.00	-35.38
483.91	H	-74.18	29.29	-44.89	-13.00	-31.89
675.11	H	-73.56	31.35	-42.21	-13.00	-29.21
821.23	H	-74.46	33.16	-41.30	-13.00	-28.30
951.81	H	-74.02	34.25	-39.77	-13.00	-26.77

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

Operation Mode:	GPRS 1900 / TX / CH 661	Test Date:	2013-7-10
Temperature:	21°C	Tested by:	Blent.Wang
Humidity:	53 % RH	Polarity:	Ver. / Hor.

Frequency (MHz)	Antenna Polarization	Reading (dBm)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
152.80	V	-74.55	24.54	-50.01	-13.00	-37.01
281.83	V	-73.38	25.46	-47.92	-13.00	-34.92
483.91	V	-73.97	29.28	-44.69	-13.00	-31.69
645.58	V	-74.09	31.41	-42.68	-13.00	-29.68
816.57	V	-74.27	33.21	-41.06	-13.00	-28.06
961.14	V	-73.50	34.49	-39.01	-13.00	-26.01
126.38	H	-74.07	27.37	-46.70	-13.00	-33.70
465.26	H	-73.67	28.90	-44.77	-13.00	-31.77
611.38	H	-73.49	31.00	-42.49	-13.00	-29.49
682.88	H	-73.12	31.67	-41.45	-13.00	-28.45
776.15	H	-74.12	32.69	-41.43	-13.00	-28.43
920.72	H	-73.83	34.38	-39.45	-13.00	-26.45

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

Operation Mode:	GPRS 1900 / TX / CH 810	Test Date:	2013-7-10
Temperature:	21°C	Tested by:	Blent.Wang
Humidity:	53 % RH	Polarity:	Ver. / Hor.

Frequency (MHz)	Antenna Polarization	Reading (dBm)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
129.49	V	-74.95	27.74	-47.21	-13.00	-34.21
267.84	V	-74.06	25.59	-48.47	-13.00	-35.47
502.56	V	-73.70	29.23	-44.47	-13.00	-31.47
645.58	V	-73.70	31.31	-42.39	-13.00	-29.39
801.03	V	-73.68	33.03	-40.65	-13.00	-27.65
975.13	V	-73.95	34.68	-39.27	-13.00	-26.27
141.92	H	-73.93	24.41	-49.52	-13.00	-36.52
270.95	H	-73.78	25.48	-48.30	-13.00	-35.30
469.92	H	-74.25	29.17	-45.08	-13.00	-32.08
623.81	H	-73.53	31.33	-42.20	-13.00	-29.20
774.60	H	-73.26	32.68	-40.58	-13.00	-27.58
912.95	H	-73.85	34.24	-39.61	-13.00	-26.61

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

Radiated Spurious Emission Measurement Result / Above 1GHz

Operation Mode:	GPRS 850 / TX / CH 128	Test Date:	2013-7-10
Temperature:	21°C	Tested by:	Blent.Wang
Humidity:	53 % RH	Polarity:	Ver. / Hor.

Frequency (MHz)	Antenna Polarization	Reading (dBm)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
1649.04	V	-39.15	-0.52	-39.67	-13.00	-26.67
2475.96	V	-38.50	2.32	-36.18	-13.00	-23.18
1649.04	H	-39.23	-0.71	-39.94	-13.00	-26.94
2471.15	H	-33.21	1.95	-31.26	-13.00	-18.26

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

Operation Mode:	GPRS 850 / TX / CH 190	Test Date:	2013-7-10
Temperature:	21°C	Tested by:	Blent.Wang
Humidity:	53 % RH	Polarity:	Ver. / Hor.

Frequency (MHz)	Antenna Polarization	Reading (dBm)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
1764.42	V	-43.76	-0.08	-43.84	-13.00	-30.84
3298.08	V	-47.17	4.77	-42.40	-13.00	-29.40
1860.58	H	-50.95	-0.51	-51.46	-13.00	-38.46
3298.08	H	-50.11	4.55	-45.56	-13.00	-32.56

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

Operation Mode:	GPRS 850 / TX / CH 251	Test Date:	2013-7-10
Temperature:	21°C	Tested by:	Blent.Wang
Humidity:	53 % RH	Polarity:	Ver. / Hor.

Frequency (MHz)	Antenna Polarization	Reading (dBm)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
1730.77	V	-34.91	-0.04	-34.95	-13.00	-21.95
3480.77	V	-55.57	4.97	-50.60	-13.00	-37.60
1860.58	H	-49.03	-0.51	-49.54	-13.00	-36.54
2427.89	H	-56.60	1.66	-54.94	-13.00	-41.94

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

Operation Mode:	GPRS 1900 / TX / CH 512	Test Date:	2013-7-10
Temperature:	21°C	Tested by:	Blent.Wang
Humidity:	53 % RH	Polarity:	Ver. / Hor.

Frequency (MHz)	Antenna Polarization	Reading (dBm)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3875.00	V	-51.86	7.39	-44.47	-13.00	-31.47
5551.28	V	-38.49	7.47	-31.02	-13.00	-18.02
3899.04	H	-56.85	7.02	-49.83	-13.00	-36.83
5551.28	H	-45.70	7.62	-38.08	-13.00	-25.08

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

Operation Mode:	GPRS 1900 / TX / CH 661	Test Date:	2013-7-10
Temperature:	21°C	Tested by:	Blent.Wang
Humidity:	53 % RH	Polarity:	Ver. / Hor.

Frequency (MHz)	Antenna Polarization	Reading (dBm)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3780.77	V	-53.21	7.12	-46.09	-13.00	-33.09
5640.49	V	-40.22	7.06	-33.16	-13.00	-20.16
3780.76	H	-52.16	7.10	-45.06	-13.00	-32.06
5640.50	H	-46.50	7.13	-39.37	-13.00	-26.37

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

Operation Mode:	GPRS 1900 / TX / CH 810	Test Date:	2013-7-10
Temperature:	21°C	Tested by:	Blent.Wang
Humidity:	53 % RH	Polarity:	Ver. / Hor.

Frequency (MHz)	Antenna Polarization	Reading (dBm)	Correction Factor (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
3822.12	V	-42.58	7.24	-35.34	-13.00	-22.34
5730.77	V	-44.42	6.88	-37.54	-13.00	-24.54
3822.12	H	-44.26	7.08	-37.18	-13.00	-24.18
5730.77	H	-46.77	6.79	-39.98	-13.00	-26.98

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.




7.7. FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT

LIMIT

According to FCC §2.1055, FCC §22.355, .FCC §24.235.

Frequency Tolerance: 2.5 ppm

TEST CONFIGURATION



Remark: Measurement setup for testing on Antenna connector

TEST PROCEDURE

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

TEST RESULTS

No non-compliance noted.

Reference Frequency: GSM Mid Channel 836.6 MHz @ 20°C

Limit: ± 2.5 ppm = 2091.5 Hz

Power Supply Vdc	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
3.7	55	836600125	125	2091.5
	50	836600125	125	
	40	836600126	126	
	30	836600126	126	
	20	836600128	128	
	10	836600130	130	
	0	836600134	134	
	-5	836600138	138	
	-10	836600140	140	

Reference Frequency: GSM Mid Channel 1880 MHz @ 20°C

Limit: ± 2.5 ppm = 4700 Hz

Power Supply Vdc	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
3.7	55	1879999894	106	4700
	50	1879999893	107	
	40	1879999893	107	
	30	1879999893	107	
	20	1879999892	108	
	10	1879999891	109	
	0	1879999887	113	
	-5	1879999882	118	
	-10	1879999878	122	



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

Reference Frequency: GPRS Mid Channel 836.6 MHz @ 20°C

Limit: +/- 2.5 ppm = 2090 Hz

Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
3.7	55	836600114	114	2090
	50	836600115	115	
	40	836600116	116	
	30	836600114	114	
	20	836600118	118	
	10	836600120	120	
	0	836600121	121	
	-5	836600120	120	
	-10	836600123	123	

Reference Frequency: GPRS Mid Channel 1880 MHz @ 20°C

Limit: ± 2.5 ppm = 4700 Hz

Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
3.7	55	1878999873	127	4700
	50	1878999871	129	
	40	1878999871	129	
	30	1878999872	128	
	20	1879999870	130	
	10	1878999869	131	
	0	1878999868	132	
	-5	1878999868	132	
	-10	1878999866	134	




7.8. FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT

LIMIT

According to FCC §2.1055, FCC §22.355, FCC §24.235,

TEST CONFIGURATION



Remark: Measurement setup for testing on Antenna connector.

TEST PROCEDURE

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and record the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 10\%$) and endpoint, record the maximum frequency change.



Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

TEST RESULTS

No non-compliance noted.

Reference Frequency: GPRS Mid Channel 836.6 MHz @ 20°C

Limit: ± 2.5 ppm = 2090Hz

Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
4.2	20	836599887	113	2090
3.7		836599885	115	
3.6 end		836599882	118	

Reference Frequency: GPRS Mid Channel 1880 MHz @ 20°C

Limit: ± 2.5 ppm = 4700 Hz

Power Supply Vac	Environment Temperature (°C)	Frequency (Hz)	Delta (Hz)	Limit (Hz)
4.2	20	1879999876	124	4700
3.7		1879999872	128	
3.6 end		1879999874	126	



7.9. POWERLINE CONDUCTED EMISSIONS

LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

TEST CONFIGURATION

See test photographs attached in Appendix I for the actual connections between EUT and support equipment.

TEST PROCEDURE


1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.



TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Operation Mode:	Normal Link	Test Date:	2013-7-10
Temperature:	23°C	Tested by:	Blent.Wang
Humidity:	50% RH		



No.	Frequency	QuasiPeak reading	Average reading	Correction factor	QuasiPeak result	Average result	QuasiPeak limit	Average limit	QuasiPeak margin	Average margin	Remark
	(MHz)	(dBuV)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dB)	(dB)	
1	0.3759	35.06	15.95	9.95	45.01	25.90	58.37	48.37	-13.36	-22.47	Pass
2	0.8498	27.80	16.37	9.99	37.79	26.36	56.00	46.00	-18.21	-19.64	Pass
3*	0.9915	30.53	17.31	9.98	40.51	27.29	56.00	46.00	-15.49	-18.71	Pass
4	1.6234	26.29	14.51	10.05	36.34	24.56	56.00	46.00	-19.66	-21.44	Pass
5	2.0142	26.34	14.61	10.09	36.43	24.70	56.00	46.00	-19.57	-21.30	Pass
6	2.7670	25.03	14.58	10.18	35.21	24.76	56.00	46.00	-20.79	-21.24	Pass

Remark:

1. Measuring frequencies from 0.15 MHz to 30MHz.
2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Quasi-peak detector and average detector.
3. The IF bandwidth of SPA between 0.15MHz to 30MHz was 10kHz; the IF bandwidth of Test Receiver between 0.15MHz to 30MHz was 9kHz;
4. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)

"—" means Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary




Compliance Certification Services Inc.

Report No: C130703R01-RP1

FCC ID: 2AAJDF9300

Date of Issue :July 12, 2013

L2



No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1	0.3776	41.73	21.31	9.98	51.71	31.29	58.33	48.33	-6.62	-17.04	Pass
2	0.9598	27.65	8.03	9.97	37.62	18.00	56.00	46.00	-18.38	-28.00	Pass
3	1.7866	31.17	11.59	10.09	41.26	21.68	56.00	46.00	-14.74	-24.32	Pass
4	2.1225	33.66	17.69	10.14	43.80	27.83	56.00	46.00	-12.20	-18.17	Pass
5*	2.7581	33.87	17.69	10.21	44.08	27.90	56.00	46.00	-11.92	-18.10	Pass
6	15.2489	24.69	9.48	10.74	35.43	20.22	60.00	50.00	-24.57	-29.78	Pass

Remark:

5. Measuring frequencies from 0.15 MHz to 30MHz.
6. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Quasi-peak detector and average detector.
7. The IF bandwidth of SPA between 0.15MHz to 30MHz was 10kHz; the IF bandwidth of Test Receiver between 0.15MHz to 30MHz was 9kHz;
8. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)

"-" means Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary

END OF REPORT