

**FCC PART 22/24 TEST REPORT****FCC Part 22 /Part 24****Report Reference No.....** : MWR151225102**FCC ID.....** : 2AAJDX5

Compiled by

( position+printed name+signature)... File administrators Martin Ao

Supervised by

( position+printed name+signature)... Test Engineer Yuchao Wang

Approved by

( position+printed name+signature)... Manager Dixon Hao

Date of issue.....: Jan. 14, 2016

**Representative Laboratory Name ..** **Maxwell International Co., Ltd.**

Address..... Room 509, Hongfa center building, Baoan District, Shenzhen, Guangdong, China

**Testing Laboratory Name .....****Shenzhen CTL Testing Technology Co., Ltd.**

Address..... Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, China 518055

**Applicant's name .....** **ETOWAY TECHNOLOGY CO.,LTD.**

Address..... Room 1005, Building A, Stars Plaza, #38 Hongli Road, Futian, Shenzhen, China

**Test specification .....** :**FCC Part 22: PUBLIC MOBILE SERVICES**

Standard .....

**FCC Part 24: PERSONAL COMMUNICATIONS SERVICES**

TRF Originator.....: Maxwell International Co., Ltd.

**MAXWELL INTERNATIONAL CO., LTD. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the MAXWELL INTERNATIONAL CO., LTD. as copyright owner and source of the material. MAXWELL INTERNATIONAL CO., LTD. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test item description .....** : Mobile Phone

Trade Mark .....

MOVILSER

**Manufacturer .....** **ETOWAY TECHNOLOGY CO.,LTD.**

Model/Type reference.....: X5

Listed Models .....

X51, X52, X53, X54, X55, X56, X57, X58, X59

Ratings.....: DC 3.70V

Modulation .....

QPSK

Hardware version .....

A825\_324\_AX\_LJ\_A9\_MOVILSER\_B2B5\_V1.01\_20151219

Software version .....

T825-A-V1.1

Frequency..... UMTS Band II/ UMTS Band V

Result.....: **PASS**

## TEST REPORT

<b>Test Report No. :</b>	<b>MWR151225102</b>	Jan. 14, 2016
		Date of issue

Equipment under Test : Mobile Phone

Model /Type : X5

Listed Models : X51, X52, X53, X54, X55, X56, X57, X58, X59

**Applicant** : **ETOWAY TECHNOLOGY CO.,LTD.**

Address : Room 1005, Building A, Stars Plaza, #38 Hongli Road, Futian, Shenzhen, China

**Manufacturer** : **ETOWAY TECHNOLOGY CO.,LTD.**

Address : Room 1005, Building A, Stars Plaza, #38 Hongli Road, Futian, Shenzhen, China

<b>Test Result:</b>	<b>PASS</b>
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Contents

<u>1</u>	<u>TEST STANDARDS .....</u>	<u>4</u>
<u>2</u>	<u>SUMMARY .....</u>	<u>5</u>
2.1	General Remarks	5
2.2	Product Description	5
2.3	Product Description	5
2.4	Equipment under Test	6
2.5	Short description of the Equipment under Test (EUT)	6
2.6	Internal Identification of AE used during the test	6
2.7	Normal Accessory setting	7
2.8	EUT configuration	7
2.9	Related Submittal(s) / Grant (s)	7
2.10	Modifications	7
2.11	General Test Conditions/Configurations	7
<u>3</u>	<u>TEST ENVIRONMENT .....</u>	<u>8</u>
3.1	Address of the test laboratory	8
3.2	Test Facility	8
3.3	Environmental conditions	8
3.4	Test Description	8
3.5	Equipments Used during the Test	9
<u>4</u>	<u>TEST CONDITIONS AND RESULTS .....</u>	<u>10</u>
4.1	Output Power	10
4.2	Radiated Spurious Emssion	14
4.3	Occupied Bandwidth and Emission Bandwith	17
4.4	Band Edge Compliance	20
4.5	Spurious Emission on Antenna Port	23
4.6	Frequency Stability Test	40
4.7	Peak-to-Average Ratio (PAR)	42
<u>5</u>	<u>TEST SETUP PHOTOS OF THE EUT .....</u>	<u>44</u>
<u>6</u>	<u>EXTERNAL PHOTOS OF THE EUT .....</u>	<u>44</u>
<u>7</u>	<u>INTERNAL PHOTOS OF THE EUT .....</u>	<u>44</u>

## 1 TEST STANDARDS

The tests were performed according to following standards:

[FCC Part 22 \(20-1-15 Edition\)](#): PRIVATE LAND MOBILE RADIO SERVICES.

[FCC Part 24\(20-1-15 Edition\)](#): PUBLIC MOBILE SERVICES

[TIA/EIA 603 D June 2010](#): Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

[47 CFR FCC Part 15 Subpart B](#): - Unintentional Radiators

[FCC Part 2](#): FREQUENCY ALLOCA-TIONS AND RADIO TREATY MAT-TERS; GENERAL RULES AND REG-ULATIONS

[ANSI C63.4:2009](#): Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

[FCC KDB971168D01](#) Power Meas License Digital Systems

## 2 SUMMARY

### 2.1 General Remarks

Date of receipt of test sample	:	Dec. 25, 2015
Testing commenced on	:	Jan. 12, 2016
Testing concluded on	:	Jan. 13, 2016

### 2.2 Product Description

### 2.3 Product Description

The **ETOWAY TECHNOLOGY CO.,LTD.**'s Model: X5 or the "EUT" as referred to in this report; more general information as follows, for more details, refer to the user's manual of the EUT.

Name of EUT	Mobile Phone
Model Number	X5
Modulation Type	GMSK for GSM/GPRS, 8-PSK for EDGE, QPSK for UMTS
Antenna Type	Internal
UMTS Operation Frequency Band	Device supported UMTS FDD Band II/V
WLAN FCC Operation frequency	IEEE 802.11b:2412-2462MHz IEEE 802.11g:2412-2462MHz IEEE 802.11n HT20:2412-2462MHz IEEE 802.11n HT40:2422-2452MHz
BT FCC Operation frequency	2402MHz-2480MHz
HSDPA Release Version	Release 10
HSUPA Release Version	Release 6
DC-HSUPA Release Version	Not Supported
WCDMA Release Version	R99
WLAN FCC Modulation Type	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK,BPSK)
BT Modulation Type	GFSK,8DPSK, $\pi/4$ DQPSK(BT 3.0+EDR)
Hardware version	A825_324_AX_LJ_A9_MOVILSER_B2B5_V1.01_20151219
Software version	T825-A-V1.1
Android version	Android 4.4.2
GPS function	Supported
WLAN	Supported 802.11b/802.11g/802.11n
Bluetooth	Supported BT 4.0/BT 3.0+EDR
GSM/EDGE/GPRS	Supported GSM/GPRS/EDGE
GSM/EDGE/GPRS Power Class	GSM850:Power Class 4/ PCS1900:Power Class 1
GSM/EDGE/GPRS Operation Frequency	GSM850 :824.2MHz-848.8MHz/PCS1900:1850.2MHz-1909.8MHz
GSM/EDGE/GPRS Operation Frequency Band	GSM850/PCS1900/GPRS850/GPRS1900/EDGE850/EDGE1900
GSM Release Version	R99
GPRS/EDGE Multislot Class	GPRS/EDGE: Multi-slot Class 12
Extreme temp. Tolerance	-30°C to +50°C
Extreme vol. Limits	3.15VDC to 4.25VDC (nominal: 3.70VDC)
GPRS operation mode	Class B

## 2.4 Equipment under Test

### Power supply system utilised

Power supply voltage	:	<input type="radio"/>	120V / 60 Hz	<input type="radio"/>	115V / 60Hz
		<input type="radio"/>	12 V DC	<input type="radio"/>	24 V DC
		<input checked="" type="radio"/>	Other (specified in blank below)		

DC 3.70V

### Test frequency list

Test Mode	TX/RX	RF Channel		
		Low(L)	Middle (M)	High (H)
WCDMA850	TX	Channel 4132	Channel 4182	Channel 4233
		826.4 MHz	836.4 MHz	846.6 MHz
	RX	Channel 4357	Channel 4407	Channel 4458
		871.4 MHz	881.4 MHz	891.6 MHz
Test Mode	TX/RX	RF Channel		
		Low(L)	Middle (M)	High (H)
WCDMA1900	TX	Channel 9262	Channel 9400	Channel 9538
		1852.4 MHz	1880.0 MHz	1907.6 MHz
	RX	Channel 9662	Channel 9800	Channel 9938
		1932.4 MHz	1960.0 MHz	1987.6 MHz

## 2.5 Short description of the Equipment under Test (EUT)

### 2.5.1 General Description

X5 is subscriber equipment in the WCDMA/GSM system. The HSPA/UMTS frequency band is Band I,Band II , Band Vand Band VIII; The GSM/GPRS/EDGE frequency band includes GSM850 and GSM900 and DCS1800 and PCS1900, but only Band II and Band V and GSM850 and PCS1900 bands test data included in this report. The Mobile Phone implements such functions as RF signal receiving/transmitting, HSPA/UMTS and GSM/GPRS/EDGE protocol processing, voice, video MMS service, GPS and WIFI etc. Externally it provides micro SD card interface, earphone port (to provide voice service) and SIM card interface. It also provides Bluetooth module to synchronize data between a PC and the phone, or to use the built-in modem of the phone to access the Internet with a PC, or to exchange data with other Bluetooth devices.

NOTE: Unless otherwise noted in the report, the functional boards installed in the units shall be selected from the below list, but not means all the functional boards listed below shall be installed in one unit.

## 2.6 Internal Identification of AE used during the test

AE ID*	Description
AE1	Battery
AE2	Charger

AE1

Model: X5

INPUT: AC180-240V~ 50/60Hz 0.12A

OUTPUT: DC 5.0V 1000mA

\*AE ID: is used to identify the test sample in the lab internally.

## 2.7 Normal Accessory setting

Fully charged battery was used during the test.

## 2.8 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

<input type="radio"/>	Power Cable	Length (m) :	/
		Shield :	/
		Detachable :	/
<input type="radio"/>	Multimeter	Manufacturer :	/
		Model No. :	/

## 2.9 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2AAJDX5** filing to comply with FCC Part 22 and Part 24 Rules

## 2.10 Modifications

No modifications were implemented to meet testing criteria.

## 2.11 General Test Conditions/Configurations

### 2.11.1 Test Modes

NOTE: The test mode(s) are selected according to relevant radio technology specifications.

Test Mode	Test Modes Description
UMTS/TM1	WCDMA system, QPSK modulation
UMTS/TM2	HSDPA system, QPSK modulation
UMTS/TM3	HSUPA system, QPSK modulation

Note:

1. This EUT owns two SIM cards, after we perform the pretest for these two SIM cards; we found the SIM 1 is the worst case, so its result is recorded in this report.
2. As WCDMA, HSDPA and HSUPA with the same emission designator, test result recorded in this report at the worst case UMTS/TM1 only after exploratory scan.

### 2.11.2 Test Environment

Environment Parameter	Selected Values During Tests	
Relative Humidity	Ambient	
Temperature	TN	Ambient
Voltage	VL	3.15V
	VN	3.70V
	VH	4.25V

NOTE: VL=lower extreme test voltage VN=nominal voltage  
 VH=upper extreme test voltage TN=normal temperature

### 3 TEST ENVIRONMENT

#### 3.1 Address of the test laboratory

##### Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 22/EN 55022 requirements.

#### 3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

The test facility is recognized, certified, or accredited by the following organizations:

##### IC Registration No.: 9618B

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 9618B on November 13, 2013.

##### FCC-Registration No.: 970318

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December 19, 2013.

#### 3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

(1) expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

#### 3.4 Test Description

##### 3.4.1 Cellular Band (824-849MHz paired with 869-894MHz)

Test Item	FCC Rule No.	Requirements	Verdict
Effective(Isotropic) Radiated Output Power	§2.1046, §22.913	FCC: ERP ≤ 7W.	Pass
Modulation Characteristics	§2.1047	Digital modulation	N/A
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Pass
Band Edges Compliance	§2.1051, §22.917	≤-13dBm/1%*EBW, in 1MHz bands immediately outside and adjacent to The frequency block.	Pass
Spurious Emission at Antenna Terminals	§2.1051, §22.917	FCC: ≤ -13dBm/100kHz, from 9kHz to 10th harmonics but outside authorized operating frequency ranges.	Pass
Field Strength of Spurious Radiation	§2.1053, §22.917	FCC: ≤ -13dBm/100kHz.	Pass
Frequency Stability	§2.1055, §22.355	≤ ±2.5ppm.	Pass

NOTE 1: For the verdict, the "N/A" denotes "not applicable", the "N/T" de notes "not tested".

### 3.4.2 PCS Band (1850-1915MHz paired with 1930-1995MHz)

Test Item	FCC Rule No.	Requirements	Verdict
Effective(Isotropic) Radiated Output Power	§2.1046, §24.232	EIRP ≤ 2W	Pass
Peak-Average Ratio	§2.1046, §24.232	FCC:Limit≤13dB	Pass
Modulation Characteristics	§2.1047	Digital modulation	N/A
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Pass
Band Edges Compliance	§2.1051, §24.238	≤ -13dBm/1%*EBW, In 1MHz bands immediately outside and adjacent to The frequency block.	Pass
Spurious Emission at Antenna Terminals	§2.1051, §24.238	≤-13dBm/1MHz, from 9kHz to10th harmonics but outside authorized Operating frequency ranges.	Pass
Field Strength of Spurious Radiation	§2.1053, §24.238	≤ -13dBm/1MHz.	Pass
Frequency Stability	§2.1055, §24.235	FCC: within authorized frequency block.	Pass

NOTE 1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".

Remark:

1. The measurement uncertainty is not included in the test result.

### 3.5 Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	3560.6550.12	2015/06/02	2016/06/01
LISN	R&S	ESH2-Z5	860014/010	2015/06/02	2016/06/01
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2015/06/02	2016/06/01
EMI Test Receiver	R&S	ESCI	103710	2015/06/02	2016/06/01
Spectrum Analyzer	Agilent	N9030A	MY49430428	2015/05/21	2016/05/20
Controller	EM Electronics	Controller EM 1000	N/A	2015/05/21	2016/05/20
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2015/05/19	2016/05/18
Active Loop Antenna	SCHWARZBECK	FMZB1519	1519-037	2015/05/19	2016/05/18
Amplifier	Agilent	8349B	3008A02306	2015/05/19	2016/05/18
Amplifier	Agilent	8447D	2944A10176	2015/05/19	2016/05/18
Temperature/ Humidity Meter	Gangxing	CTH-608	02	2015/05/20	2016/05/19
High-Pass Filter	K&L	9SH10-2700/X12750-O/O	N/A	2015/05/20	2016/05/19
High-Pass Filter	K&L	41H10-1375/U12750-O/O	N/A	2015/05/20	2016/05/19
Coaxial Cables	HUBER+SUHNER	SUCOFLEX 104PEA-10M	10m	2015/06/02	2016/06/01
Coaxial Cables	HUBER+SUHNER	SUCOFLEX 104PEA-3M	3m	2015/06/02	2016/06/01
Coaxial Cables	HUBER+SUHNER	SUCOFLEX 104PEA-3M	3m	2015/06/02	2016/06/01
RF Cable	Megalon	RF-A303	N/A	2015/06/02	2016/06/01
Power Sensor	R&S	NRP-Z4	823.3618.03	2015.06.02	2016.06.01
Power Meter	R&S	NRVS	1020.1809.02	2015.06.02	2016.06.01
System Simulator	R&S	CMU200	115419	2015.05.22	2016.05.21

## 4 TEST CONDITIONS AND RESULTS


### 4.1 Output Power

#### TEST APPLICABLE

During the process of testing, the EUT was controlled via R&S Digital Radio Communication tester (CMU200) to ensure max power transmission and proper modulation. This result contains output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

#### 4.1.1. Conducted Output Power

#### TEST CONFIGURATION



#### TEST PROCEDURE

##### **Conducted Power Measurement:**

- a) Place the EUT on a bench and set it in transmitting mode.
- b) Connect a low loss RF cable from the antenna port to a CMU200 by an Att.
- c) EUT Communicate with CMU200 then selects a channel for testing.
- d) Add a correction factor to the display CMU200, and then test.

#### TEST RESULTS

See next page

Test Mode	Test Channel	Burst Average Conducted power (dBm)	
		UMTS Band V	UMTS Band II
UMTS/TM1	LCH	23.68	23.71
	MCH	23.48	23.52
	HCH	23.73	23.56
UMTS/TM2	LCH_SubTest-1	22.81	22.73
	LCH_SubTest-2	22.05	22.14
	LCH_SubTest-3	22.09	22.13
	LCH_SubTest-4	21.98	21.95
	MCH_SubTest-1	22.54	22.49
	MCH_SubTest-2	21.76	21.77
	MCH_SubTest-3	21.72	21.78
	MCH_SubTest-4	21.67	21.78
	HCH_SubTest-1	22.78	22.64
	HCH_SubTest-2	22.04	21.88
	HCH_SubTest-3	22.05	21.85
	HCH_SubTest-4	21.97	21.85
	LCH_SubTest-1	20.59	21.86
	LCH_SubTest-2	20.53	21.07
	LCH_SubTest-3	21.64	21.03
UMTS/TM3	LCH_SubTest-4	19.99	21.98
	LCH_SubTest-5	19.49	21.66
	MCH_SubTest-1	20.29	22.38
	MCH_SubTest-2	20.24	21.01
	MCH_SubTest-3	21.28	20.69
	MCH_SubTest-4	19.72	21.89
	MCH_SubTest-5	21.83	21.56
	HCH_SubTest-1	20.60	22.16
	HCH_SubTest-2	20.51	21.53
	HCH_SubTest-3	21.63	21.22
	HCH_SubTest-4	19.87	21.98
	HCH_SubTest-5	19.95	21.28


### 4.1.1 Radiated Output Power

#### TEST DESCRIPTION

This is the test for the maximum radiated power from the EUT.

Rule Part 24.232(c) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(e) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 22.913(a) specifies "The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

#### TEST CONFIGURATION



#### TEST PROCEDURE

1. EUT was placed on a 1.50 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.50m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=10MHz, VBW=10MHz, And the maximum value of the receiver should be recorded as ( $P_r$ ).
4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver

reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss ( $P_{cl}$ ), the Substitution Antenna Gain ( $G_a$ ) and the Amplifier Gain ( $P_{Ag}$ ) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{Ag} - P_{cl} + G_a$$

We used SMF100A microwave signal generator which signal level can up to 33dBm, so we not used power Amplifier for substitution test; The measurement results are amend as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{cl} + G_a$$

6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.

7. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dBi}$ .

### TEST LIMIT

According to 22.913(a), 24.232(c) and 27.50(d) (4), the ERP(EIRP) should be not exceeding following table limits:

		Burst Average EIRP
UMTS Band II		33dBm (2W)
		Burst Average ERP
UMTS Band V		38.45dBm (7W)

### TEST RESULTS

Remark:

1. We were tested all Configuration refer 3GPP TS134 121.
2.  $EIRP = P_{Mea}(\text{dBm}) - P_{cl}(\text{dB}) + P_{Ag}(\text{dB}) + G_a(\text{dBi})$
3.  $ERP = EIRP - 2.15\text{dBi}$  as EIRP by subtracting the gain of the dipole.

#### UMTS/TM1/UMTS Band II

Frequency (MHz)	$P_{Mea}$ (dBm)	$P_{cl}$ (dB)	$G_a$ Antenna Gain(dB)	$P_{Ag}$ (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1852.4	-17.65	3.41	10.24	33.60	<b>22.78</b>	33.01	10.23	H
1880.0	-20.11	3.49	10.24	33.60	20.24	33.01	12.77	H
1907.6	-20.95	3.55	10.23	33.60	19.33	33.01	13.68	H

#### UMTS/TM1/UMTS Band V


Frequency (MHz)	$P_{Mea}$ (dBm)	$P_{cl}$ (dB)	$G_a$ Antenna Gain(dB)	Correction (dB)	$P_{Ag}$ (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
826.40	-19.96	2.42	8.45	2.15	36.82	<b>20.74</b>	38.45	17.71	V
836.60	-20.68	2.46	8.45	2.15	36.82	19.98	38.45	18.47	V
846.60	-22.29	2.53	8.36	2.15	36.82	18.21	38.45	20.24	V

## 4.2 Radiated Spurious Emission

### TEST APPLICABLE

According to the TIA/EIA 603D:2010 test method, The Receiver or Spectrum was scanned from 9 KHz to the 10<sup>th</sup> harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set as outlined in Part 24.238, Part 22.917. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of WCDMA Band II and WCDMA Band V.

### TEST CONFIGURATION



### TEST PROCEDURE

1. EUT was placed on a 1.50 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.50m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz,VBW=3MHz, And the maximum value of the receiver should be recorded as ( $P_r$ ).
4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss ( $P_{cl}$ ), the Substitution Antenna Gain ( $G_a$ ) and the Amplifier Gain ( $P_{Ag}$ ) should be recorded after test.  
The measurement results are obtained as described below:  
$$\text{Power(EIRP)} = P_{Mea} - P_{Ag} - P_{cl} + G_a$$
6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
7. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $\text{ERP} = \text{EIRP} - 2.15\text{dBi}$ .
8. In order to make sure test results more clearly, we set frequency range and sweep time for difference frequency range as follows table:

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
UMTS/TM1/ WCDMA Band V	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
UMTS/TM1/ WCDMA Band II	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2

### TEST LIMITS

According to 24.238, 22.917 and 27.54 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power ( $P$ ) by a factor of at least  $43 + 10 \log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power ( $P$ ) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Frequency	Channel	Frequency Range	Verdict
UMTS/TM1/ WCDMA Band V	Low	9KHz-10GHz	PASS
	Middle	9KHz -10GHz	PASS
	High	9KHz -10GHz	PASS
UMTS/TM1/ WCDMA Band II	Low	9KHz -20GHz	PASS
	Middle	9KHz -20GHz	PASS
	High	9KHz -20GHz	PASS

**TEST RESULTS***Remark:*

1. We were tested all Configuration refer 3GPP TS134 121.
2.  $EIRP = P_{Mea}(dBm) - P_{cl}(dB) + P_{Ag}(dB) + G_a(dBi)$
3.  $ERP = EIRP - 2.15dB$  as  $EIRP$  by subtracting the gain of the dipole.

***UMTS/TM1/ WCDMA Band II \_ Low Channel***

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3704.8	-43.82	4.39	3.00	12.34	-35.87	-13.00	22.87	H
5557.2	-46.16	5.31	3.00	13.52	-37.95	-13.00	24.95	H
3704.8	-41.36	4.39	3.00	12.34	-33.41	-13.00	20.41	V
5557.2	-43.63	5.31	3.00	13.52	-35.42	-13.00	22.42	V

***UMTS/TM1/ WCDMA Band II \_ Middle Channel***

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.0	-41.51	4.41	3.00	12.34	-33.58	-13.00	20.58	H
5640.0	-56.85	5.38	3.00	13.58	-48.65	-13.00	35.65	H
3760.0	-40.34	4.41	3.00	12.34	-32.41	-13.00	19.41	V
5640.0	-46.04	5.38	3.00	13.58	-37.84	-13.00	24.84	V

***UMTS/TM1/ WCDMA Band II \_ High Channel***

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3815.2	-43.36	4.45	3.00	12.45	-35.36	-13.00	22.36	H
5722.8	-45.04	5.47	3.00	13.66	-36.85	-13.00	23.85	H
3815.2	-42.42	4.45	3.00	12.45	-34.42	-13.00	21.42	V
5722.8	-44.50	5.48	3.00	13.66	-36.32	-13.00	23.32	V

***UMTS/TM1/ WCDMA Band V \_ Low Channel***

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	Diatance	Ga Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1652.8	-38.91	3.00	3.00	9.58	-32.33	-13.00	19.33	H
2479.2	-48.17	3.03	3.00	10.72	-40.48	-13.00	27.48	H
1652.8	-38.66	3.00	3.00	9.68	-31.98	-13.00	18.98	V
2479.2	-46.20	3.03	3.00	10.72	-38.51	-13.00	25.51	V

***UMTS/TM1/ WCDMA Band V \_ Middle Channel***

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1672.8	-39.24	3.00	3.00	9.58	-32.66	-13.00	19.66	H
2509.2	-47.47	3.03	3.00	10.72	-39.78	-13.00	26.78	H
1672.8	-36.20	3.00	3.00	9.68	-29.52	-13.00	16.52	V
2509.2	-42.95	3.03	3.00	10.72	-35.26	-13.00	22.26	V

***UMTS/TM1/ WCDMA Band V \_ High Channel***


Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	Diatance	Ga Antenna Gain(dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1693.2	-37.92	3.00	3.00	9.58	-31.34	-13.00	18.34	H
2539.8	-49.43	3.03	3.00	10.72	-41.74	-13.00	28.74	H
1693.2	-37.24	3.00	3.00	9.68	-30.56	-13.00	17.56	V
2539.8	-45.93	3.03	3.00	10.72	-38.24	-13.00	25.24	V

## 4.3 Occupied Bandwidth and Emission Bandwidth

### TEST APPLICABLE

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of WCDMA Band II, and WCDMA band V. The table below lists the measured 99% Bandwidth and -26dBc Bandwidth.

### TEST CONFIGURATION



### TEST PROCEDURE


1. The EUT was set up for the max output power with pseudo random data modulation;
2. The Occupied bandwidth and Emission Bandwidth were measured with Agilent Spectrum Analyzer N9020A (peak);
3. Set RBW=100KHz,VBW=300KHz,Span=10MHz,SWT=1ms;
4. Set SPA Max hold and View, Set 99% Occupied Bandwidth/ Set -26dBc Occupied Bandwidth
5. These measurements were done at 3 frequencies for WCDMA band II/V. (low, middle and high of operational frequency range).

### TEST RESULTS


UMTS/TM1/ WCDMA Band II				
Channel Number	Frequency (MHz)	Occupied Bandwidth (99% BW) (kHz)	Emission Bandwidth (26 dBc BW) (kHz)	Verdict
9262	1852.4	4177.8	4688	PASS
9400	1880.0	4182.5	4690	PASS
9538	1907.6	4187.7	4699	PASS

UMTS/TM1/ WCDMA Band V				
Channel Number	Frequency (MHz)	Occupied Bandwidth (99% BW) (kHz)	Emission Bandwidth (26 dBc BW) (kHz)	Verdict
4132	826.40	4149.9	4691	PASS
4183	836.60	4169.3	4707	PASS
4233	846.60	4155.8	4708	PASS


## UMTS/TM1/ WCDMA Band II



Channel 9262




Channel 9400




Channel 9538


## UMTS/TM1/ WCDMA Band V



Channel 4132



Channel 4132




Channel 4233

## 4.4 Band Edge Compliance

### TEST APPLICABLE

During the process of testing, the EUT was controlled via Agilent Digital Radio Communication tester (8960) to ensure max power transmission and proper modulation.

### TEST CONFIGURATION



### TEST PROCEDURE

1. The EUT was set up for the max output power with pseudo random data modulation;
2. The power was measured with Agilent Spectrum Analyzer N9020A;


3. Set RBW=51KHz,VBW=200KHz,Span=5MHz,SWT=1ms,Deator: RMS;

These measurements were done at 2 frequencies for WCDMA Band II/V. (low and high of operational frequency range).


### TEST RESULTS

UMTS/TM1/WCDMA Band II						
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Refer to Plot	Verdict
		Frequency (MHz)	Values (dBm)			
9262	1852.4	1849.986	-31.017	-13.00	Plot 4.4.1 A	PASS
9538	1907.6	1910.000	-30.950	-13.00	Plot 4.4.1 B	PASS


UMTS/TM1/WCDMA Band V						
Channel Number	Frequency (MHz)	Measurement Results		Limit (dBm)	Refer to Plot	Verdict
		Frequency (MHz)	Values (dBm)			
4132	826.40	824.000	-21.327	-13.00	Plot 4.4.2 A	PASS
4233	846.60	849.000	-16.626	-13.00	Plot 4.4.2 B	PASS




(Plot 4.5.1 A: Channel 9262: 1852.4MHz WCDMA Band II)



(Plot 4.5.1 B: Channel 9538: 1907.6MHz WCDMA Band II)



(Plot 4.5.2 A: Channel 4132: 826.4MHz @ WCDMA Band V)



(Plot 4.5.2 B: Channel 4233: 846.6MHz @ WCDMA Band V)


## 4.5 Spurious Emission on Antenna Port

### TEST APPLICABLE

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of WCDMA band II, this equates to a frequency range of 9 KHz to 20GHz, data taken from 9 KHz to 20 GHz. For WCDMA Band V, data taken from 9 KHz to 13.6 GHz.
2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; if the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give an optimal sweep time according the selected span and RBW.
3. The procedure to get the conducted spurious emission is as follows:  
The trace mode is set to MaxHold to get the highest signal at each frequency;  
Wait 25 seconds;  
Get the result.
4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

### TEST CONFIGURATION



### TEST PROCEDURE

1. The EUT was set up for the max output power with pseudo random data modulation;
2. The power was measured with Agilent Spectrum Analyzer N9030A (peak);
3. These measurements were done at 3 frequencies for WCDMA band II/V. (low, middle and high of operational frequency range).

### TEST LIMIT

Part 24.238, Part 22.917 and Part 22.54 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

### TEST RESULTS

### 4.5.1 For UMTS/TM1/WCDMA Band II Test Results


#### A. Test Verdict

Test Mode/ Channel	Frequency (MHz)	Frequency Range	Refer to Plot	Limit (dBm)	Verdict
UMTS/TM1/WCDMA Band II/9262	1852.40	9KHz-150KHz	Plot 4.5.1 A1	-13.00	PASS
		150KHz-30MHz	Plot 4.5.1 A2	-13.00	PASS
		30MHz-1GHz	Plot 4.5.1 A3	-13.00	PASS
		1GHz-7GHz	Plot 4.5.1 A4	-13.00	PASS
		7GHz-13.6GHz	Plot 4.5.1 A5	-13.00	PASS
		13.6GHz-25GHz	Plot 4.5.1 A6	-13.00	PASS
UMTS/TM1/WCDMA Band II/9400	1880.00	9KHz-150KHz	Plot 4.5.1 B1	-13.00	PASS
		150KHz-30MHz	Plot 4.5.1 B2	-13.00	PASS
		30MHz-1GHz	Plot 4.5.1 B3	-13.00	PASS
		1GHz-7GHz	Plot 4.5.1 B4	-13.00	PASS
		7GHz-13.6GHz	Plot 4.5.1 B5	-13.00	PASS
		13.6GHz-25GHz	Plot 4.5.1 B6	-13.00	PASS
UMTS/TM1/WCDMA Band II/9538	1907.60	9KHz-150KHz	Plot 4.5.1 C1	-13.00	PASS
		150KHz-30MHz	Plot 4.5.1 C2	-13.00	PASS
		30MHz-1GHz	Plot 4.5.1 C3	-13.00	PASS
		1GHz-7GHz	Plot 4.5.1 C4	-13.00	PASS
		7GHz-13.6GHz	Plot 4.5.1 C5	-13.00	PASS
		13.6GHz-25GHz	Plot 4.5.1 C6	-13.00	PASS


Note:

1. In general, the worse case attenuation requirement shown above was applied.
2. \*\*\* means that the emission level is too low to be measured or at least 20 dB down than the limit.


#### B. Test Plots




(Plot 4.5.1 A1: Channel 9262: 1852.4MHz @ Traffic WCDMA Band II)




(Plot 4.5.1 A2: Channel 9262: 1852.4MHz @ Traffic WCDMA Band II)




(Plot 4.5.1 A3: Channel 9262: 1852.4MHz @ Traffic WCDMA Band II)




(Plot 4.5.1 A4: Channel 9262: 1852.4MHz @ Traffic WCDMA Band II)




(Plot 4.5.1 A5: Channel 9262: 1852.4MHz @ Traffic WCDMA Band II)




(Plot 4.5.1 A6: Channel 9262: 1852.4MHz @ Traffic WCDMA Band II)




(Plot 4.5.1 B1: Channel 9400: 1880.0MHz @ Traffic WCDMA Band II)




(Plot 4.5.1 B2: Channel 9400: 1880.0MHz @ Traffic WCDMA Band II)





(Plot 4.5.1 B3: Channel 9400: 1880.0MHz @ Traffic WCDMA Band II)




(Plot 4.5.1 B4: Channel 9400: 1880.0MHz @ Traffic WCDMA Band II)




(Plot 4.5.1 B5: Channel 9400: 1880.0MHz @ Traffic WCDMA Band II)







(Plot 4.5.1 C2: Channel 9538: 1907.6MHz @ Traffic WCDMA Band II)




(Plot 4.5.1 C3: Channel 9538: 1907.6MHz @ Traffic WCDMA Band II)



(Plot 4.5.1 C4: Channel 9538: 1907.6MHz @ Traffic WCDMA Band II)



(Plot 4.5.1 C5: Channel 9538: 1907.6MHz @ Traffic WCDMA Band II)



(Plot 4.5.1 C6: Channel 9538: 1907.6MHz @ Traffic WCDMA Band II)

#### 4.5.2 For UMTS/TM1/WCDMA Band V Test Results


##### A. Test Verdict

Test Mode/ Channel	Frequency (MHz)	Frequency Range	Refer to Plot	Limit (dBm)	Verdict
UMTS/TM1/WCDMA Band V/4132	826.40	9KHz-150KHz	Plot 4.5.2 A1	-13.00	PASS
		150KHz-30MHz	Plot 4.5.2 A2	-13.00	PASS
		30MHz-1GHz	Plot 4.5.2 A3	-13.00	PASS
		1GHz-9GHz	Plot 4.5.2 A4	-13.00	PASS
UMTS/TM1/WCDMA Band V/4183	836.60	9KHz-150KHz	Plot 4.5.2 B1	-13.00	PASS
		150KHz-30MHz	Plot 4.5.2 B2	-13.00	PASS
		30MHz-1GHz	Plot 4.5.2 B3	-13.00	PASS
		1GHz-9GHz	Plot 4.5.2 B4	-13.00	PASS
UMTS/TM1/WCDMA Band V/4233	846.60	9KHz-150KHz	Plot 4.5.2 C1	-13.00	PASS
		150KHz-30MHz	Plot 4.5.2 C2	-13.00	PASS
		30MHz-1GHz	Plot 4.5.2 C3	-13.00	PASS
		1GHz-9GHz	Plot 4.5.2 C4	-13.00	PASS


##### Note:

1. In general, the worse case attenuation requirement shown above was applied.
2. "----" means that the emission level is too low to be measured or at least 20 dB down than the limit.


##### B. Test Plots




(Plot 4.5.2 A1: Channel 4132: 826.40 MHz @ WCDMA Band V)




(Plot 4.5.2 A2: Channel 4132: 826.40 MHz @ WCDMA Band V)




(Plot 4.5.2 A3: Channel 4132: 826.40 MHz @ WCDMA Band V)





(Plot 4.5.2 A4: Channel 4132: 826.40 MHz @ WCDMA Band V)






(Plot 4.5.2 B1: Channel 4183: 836.60 MHz @ WCDMA Band V)




(Plot 4.5.2 B2: Channel 4183: 836.60 MHz @ WCDMA Band V)







(Plot 4.5.2 C3: Channel 4233: 846.60 MHz @ WCDMA Band V)



(Plot 4.5.2 C4: Channel 4233: 846.60 MHz @ WCDMA Band V)

## 4.6 Frequency Stability Test

### TEST APPLICABLE


1. According to FCC Part 2 Section 2.1055 (a)(1), the frequency stability shall be measured with variation of ambient temperature from -30°C to +50°C centigrade.
2. According to FCC Part 2 Section 2.1055 (E) (2), for battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacturer.
3. Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried voltage equipment and the end voltage point was 3.15V.

### TEST PROCEDURE

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature;
2. Subject the EUT to overnight soak at -30°C;
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on middle channel of WCDMA Band II/IV/V, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming;
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 0.5 hours at each temperature, unpowered, before making measurements;
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1 Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 0.5 hours unpowered, to allow any self-heating to stabilize, before continuing;
6. Subject the EUT to overnight soak at +50°C;
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming;
8. Repeat the above measurements at 10°C increments from +50°C to -30°C. Allow at least 0.5 hours at each temperature, unpowered, before making measurements;
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure;

### TEST CONFIGURATION



### TEST LIMITS

#### **For Hand carried battery powered equipment**

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the

manufacturer. This transceiver is specified to operate with an input voltage of between 3.40VDC and 4.20VDC, with a nominal voltage of 3.70DC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

***For equipment powered by primary supply voltage***

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

**TEST RESULTS**

UMTS/TM1/WCDMA Band II					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.15	20	-2.72	0.00	2.50	PASS
3.70	20	2.88	0.00	2.50	PASS
4.25	20	1.36	0.00	2.50	PASS
3.70	-30	0.46	0.00	2.50	PASS
3.70	-20	3.78	0.00	2.50	PASS
3.70	-10	0.79	0.00	2.50	PASS
3.70	0	-2.44	0.00	2.50	PASS
3.70	10	0.79	0.00	2.50	PASS
3.70	20	-3.16	0.00	2.50	PASS
3.70	30	2.53	0.00	2.50	PASS
3.70	40	3.98	0.00	2.50	PASS
3.70	50	3.57	0.00	2.50	PASS


UMTS/TM1/WCDMA Band V					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.15	20	-8.39	-0.01	2.50	PASS
3.70	20	-7.83	-0.01	2.50	PASS
4.25	20	-6.33	-0.01	2.50	PASS
3.70	-30	-2.93	0.00	2.50	PASS
3.70	-20	-2.75	0.00	2.50	PASS
3.70	-10	-3.10	0.00	2.50	PASS
3.70	0	-5.20	-0.01	2.50	PASS
3.70	10	-6.23	-0.01	2.50	PASS
3.70	20	-6.27	-0.01	2.50	PASS
3.70	30	-1.42	0.00	2.50	PASS
3.70	40	2.09	0.00	2.50	PASS
3.70	50	-6.24	-0.01	2.50	PASS

## 4.7 Peak-to-Average Ratio (PAR)

### LIMIT

The Peak-to-Average Ratio (PAR) of the transmission may not exceed 13 dB.

### TEST CONFIGURATION




### TEST PROCEDURE

1. Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
2. Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
3. Set the number of counts to a value that stabilizes the measured CCDF curve;
4. Set the measurement interval as follows:
  - 1). for continuous transmissions, set to 1 ms,
  - 2). for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
5. Record the maximum PAPR level associated with a probability of 0.1%.


### TEST RESULTS

UMTS/TM1/ WCDMA Band II		
Channel Number	Frequency (MHz)	Measured (dB)
9262	1852.4	3.29
9400	1880.0	3.42
9538	1907.6	3.35


## UMTS/TM1/ WCDMA Band II



Channel 9262



Channel 9400



Channel 9538

## **5 Test Setup Photos of the EUT**

Please refer to separated files for Test Setup Photos of the EUT.

## **6 External Photos of the EUT**

Please refer to separated files for External Photos of the EUT.

## **7 Internal Photos of the EUT**

Please refer to separated files for Internal Photos of the EUT.

.....End of Report.....