



TESTING LABORATORY
CERTIFICATE #4820.01



FCC PART 15.247

TEST REPORT

For

Guangzhou Robustel LTD

ROOM F315, NO.95 DAGUAN MIDDLE ROAD, TIANHE DISTRICT, GUANGZHOU, China

FCC ID: 2AAJGR2000S

Report Type: Original Report	Product Type: Industrial Dual SIM Cellular VPN Router
Report Number: RDG190214005-00A	
Report Date: 2019-04-11	
Jerry Zhang	
Reviewed By:	EMC Manager
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	9
SUPPORT EQUIPMENT LIST AND DETAILS	9
SUPPORT CABLE LIST AND DETAILS	9
BLOCK DIAGRAM OF TEST SETUP	10
SUMMARY OF TEST RESULTS	11
FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	12
APPLICABLE STANDARD	12
FCC §15.203 - ANTENNA REQUIREMENT.....	14
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	14
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	15
APPLICABLE STANDARD	15
EUT SETUP	15
EMI TEST RECEIVER SETUP.....	15
TEST PROCEDURE	16
CORRECTED AMPLITUDE & MARGIN CALCULATION	16
TEST EQUIPMENT LIST AND DETAILS.....	16
TEST DATA	16
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	21
APPLICABLE STANDARD	21
EUT SETUP	21
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	22
TEST PROCEDURE	22
CORRECTED AMPLITUDE & MARGIN CALCULATION	22
TEST EQUIPMENT LIST AND DETAILS.....	23
TEST DATA	23
FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH.....	42
APPLICABLE STANDARD	42
TEST PROCEDURE	42
TEST EQUIPMENT LIST AND DETAILS.....	42
TEST DATA	42
FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER.....	50
APPLICABLE STANDARD	50
TEST PROCEDURE	50
TEST EQUIPMENT LIST AND DETAILS.....	50

TEST DATA	50
FCC §15.247(d)– 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	52
APPLICABLE STANDARD	52
TEST PROCEDURE	52
TEST EQUIPMENT LIST AND DETAILS.....	52
TEST DATA	53
FCC §15.247(e) - POWER SPECTRAL DENSITY	62
APPLICABLE STANDARD	62
TEST PROCEDURE	62
TEST EQUIPMENT LIST AND DETAILS.....	62
TEST DATA	62

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Type:		Industrial Dual SIM Cellular VPN Router
EUT Model:		R2000-4L
Multiple Models:		R2000-3P, R2000-4M
Operation Frequency:		2412-2462MHz(802.11b/g/n ht20) 2422-2452 MHz(802.11 n ht40)
Maximum Peak Output Power (Conducted):		20.95dBm
Modulation Type:		DSSS, OFDM
Rated Input Voltage:		DC 12V from Adapter or DC 12V from PoE
Adapter Information	Model:	NBS18C120150D5
	Input:	AC 100-240V 50/60Hz 0.6A
	Output:	DC 12V 1.5A
External Dimension:		127.5mm(L)* 82.5mm(W)*29.5 mm(H)
Serial Number:		190214005-1(Without PoE Funtion) 190214005-2(With PoE Funtion)
EUT Received Date:		2019/3/18

Note:

The series products models R2000-3P, R2000-4M are electrically identical with R2000-4L, we selected R2000-4L for fully testing, each model have two configuration, we seleted the device with PoE funtion for full test, and two configuration device for AC line conducted test and radiation emissions test, the details of the difference between them were explained in the attached declaration letter.

The device contains RF module, FCC ID: XMR201605EC25A

Objective

This report is prepared on behalf of **Guangzhou Robustel LTD** in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the compliance of the EUT with FCC Rules Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No Related submittal

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And 558074 D01 15.247 Meas Guidance v05r01.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB, 1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in Engineering Mode, which was provided by the manufacturer. The device have two type antennas may sold with EUT, both type was tested.

For 2.4GHz band, total 11 channels are provided:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were test with channel 1,6,11.

For 802.11n ht40 modes were test with channel 3,6,9.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations. The device supports SISO in all modes, and MIMO in 802.11n modes, per pretest, MIMO 2TX mode was the worst mode and reported for 802.11n modes.

EUT Exercise Software


The software “Engineering Mode” was used for testing, which was provided by manufacturer. The maximum power was configured as below table, that provided by the manufacturer:

Mode	Channel	Frequency (MHz)	Data rate	Power level
802.11b	Low	2412	1 Mbps	18
	Middle	2437	1 Mbps	17
	High	2462	1 Mbps	20
802.11g	Low	2412	6 Mbps	18
	Middle	2437	6 Mbps	20
	High	2462	6 Mbps	20
802.11n ht20	Low	2412	MCS0	17.5
	Middle	2437	MCS0	15
	High	2462	MCS0	20.5
802.11n ht40	Low	2422	MCS0	14
	Middle	2437	MCS0	14
	High	2452	MCS0	16

The maximum duty cycle as following table:


Test mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
802.11b	100	100	100
802.11g	100	100	100
802.11n ht20	100	100	100
802.11n ht40	100	100	100

802.11b




Date: 8.MAR.2019 20:42:53

802.11g




Date: 8.MAR.2019 20:43:20

802.11n ht20



Date: 8.MAR.2019 20:43:51

802.11n ht40



Date: 8.MAR.2019 20:44:29

Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	Laptop	PP11L	QDS-BRCM1017
DELL	Laptop	PP11L	QDS-BRCR123
ToTolink	PoE Adapter	PoE12	/
SAST	modem	AEM-2100	90200213
DELL	Keyboard	SK-8115	CN-0J4628-71616-52H-0RT6
HP	Printer	C3941A	JPTV013237

Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Power Cable	yes	No	0.5	Adapter	EUT
RJ45 Cable	No	No	10	EUT	Laptop
RJ45 Cable	No	No	1.0	PoE adapter	EUT
Serial Cable	yes	No	1.2	Serial Port of Laptop	Modem
Parallel Cable	yes	No	1.2	Parallel Port of Laptop	Printer
Keyboard Cable	yes	No	1.8	USB Port of Laptop	Keyboard

Block Diagram of Test Setup

Adapter Mode:



PoE Mode:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure(MPE)	Compliance
§15.203	Antenna Requirement	Compliance
FCC §15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Calculated Data:

Mode	Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
WLAN	2412-2462	5	2.51	21	316.23	20.00	0.16	1.0
WCDMA band 2	1850-1910	3.0	2.00	23.5	224	20.00	0.09	1.0
WCDMA Band 5	824-849	1.1	1.29	23.5	223.87	20.00	0.06	0.55
LTE band 2	1850-1910	3.0	2.00	24	251.19	20.00	0.10	1.0
LTE band 4	1710-1755	2.7	1.86	24	251.19	20.00	0.09	1.0
LTE band 12	699-716	1.0	1.26	24	251.19	20.00	0.06	0.47

The device contains a WWAN RF module, FCC ID: XMR201605EC25A, The WLAN and WWAN can transmit simultaneously:

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

$$=S_{WLAN}/S_{limit-WLAN}+S_{WWAN}/S_{limit-WWAN}$$

$$=0.16/1+0.06/0.47$$

$$=0.29$$

$$< 1.0$$

Result: The device meet FCC MPE at 20 cm distance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has two type antennas for WLAN radio use a unique type of connector to attach to the EUT, fulfill the requirement of this section. Please refer to the EUT photos.

Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range
Stubby	50	5.0 dBi/2.4~2.5GHz
Magnet	50	3.0 dBi/2.4~2.5GHz

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a).

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main lisn with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2018-12-10	2019-12-10
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-01	2018-09-05	2019-09-05
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
R&S	Two-line V-network	ENV 216	101614	2018-12-10	2019-12-10

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	26.5 °C
Relative Humidity:	60%
ATM Pressure:	100.3 kPa

The testing was performed by Lily Xie on 2019-03-23

Test Mode: Transmitting(EUT with PoE function was the worst)


Apdater mode:

AC120 V, 60 Hz, Line:




Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	49.1	9.000	L1	11.2	16.9	66.0
0.256712	36.7	9.000	L1	10.3	24.8	61.5
0.397728	44.5	9.000	L1	10.0	13.4	57.9
10.296163	33.4	9.000	L1	9.8	26.6	60.0
16.111546	40.1	9.000	L1	10.0	19.9	60.0
21.933090	24.2	9.000	L1	10.1	35.8	60.0

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.164053	35.4	9.000	L1	11.0	19.9	55.3
0.397728	39.3	9.000	L1	10.0	8.6	47.9
0.520311	26.3	9.000	L1	9.9	19.7	46.0
1.248947	23.2	9.000	L1	9.8	22.8	46.0
8.868595	29.7	9.000	L1	9.8	20.3	50.0
15.482879	34.2	9.000	L1	9.9	15.8	50.0

AC120 V, 60 Hz, Neutral:


Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	48.6	9.000	N	11.2	17.4	66.0
0.393790	39.9	9.000	N	10.0	18.1	58.0
10.194221	34.4	9.000	N	9.8	25.6	60.0
11.260762	34.7	9.000	N	9.8	25.3	60.0
15.952026	41.8	9.000	N	9.9	18.2	60.0
23.987897	30.9	9.000	N	10.1	29.1	60.0

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.157652	31.8	9.000	N	11.1	23.8	55.6
0.397728	34.8	9.000	N	10.0	13.1	47.9
8.868595	29.1	9.000	N	9.8	20.9	50.0
10.608147	29.4	9.000	N	9.8	20.6	50.0
15.952026	35.9	9.000	N	9.9	14.1	50.0
18.154894	28.1	9.000	N	10.0	21.9	50.0

PoE mode:**AC120 V, 60 Hz, Line:**

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	43.9	9.000	L1	11.2	22.1	66.0
0.259279	50.1	9.000	L1	10.3	11.4	61.5
0.500009	30.9	9.000	L1	9.9	25.1	56.0
0.557844	30.8	9.000	L1	9.8	25.2	56.0
10.929584	36.1	9.000	L1	9.8	23.9	60.0
15.952026	35.8	9.000	L1	9.9	24.2	60.0

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.256712	46.0	9.000	L1	10.3	5.5	51.5
0.628593	29.9	9.000	L1	9.8	16.1	46.0
0.945248	31.3	9.000	L1	9.8	14.7	46.0
1.176565	30.7	9.000	L1	9.8	15.3	46.0
1.435633	30.1	9.000	L1	9.8	15.9	46.0
15.952026	29.2	9.000	L1	9.9	20.8	50.0

AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	43.4	9.000	N	11.2	22.6	66.0
0.254170	50.6	9.000	N	10.3	11.0	61.6
0.256712	50.9	9.000	N	10.3	10.6	61.5
10.296163	35.7	9.000	N	9.8	24.3	60.0
10.608147	36.9	9.000	N	9.8	23.1	60.0
16.272662	35.9	9.000	N	9.9	24.1	60.0

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.234722	37.7	9.000	N	10.4	14.6	52.3
0.254170	47.5	9.000	N	10.3	4.1	51.6
0.256712	45.5	9.000	N	10.3	6.0	51.5
0.628593	30.4	9.000	N	9.8	15.6	46.0
0.945248	31.1	9.000	N	9.8	14.9	46.0
1.176565	30.8	9.000	N	9.8	15.2	46.0


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission Below 1GHz tests were performed in the 3 meters chamber A, above 1GHz tests were performed in the 3 meters chamber B, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2018-12-10	2019-12-10
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2018-05-06	2019-05-06
HP	Amplifier	8447D	2727A05902	2018-09-05	2019-09-05
Agilent	Spectrum Analyzer	E4440A	SG43360054	2019-01-04	2020-01-04
ETS-Lindgren	Horn Antenna	3115	000 527 35	2018-10-12	2021-10-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2016-11-18	2019-11-18
MICRO-COAX	Coaxial Cable	UFA147-1-2362- 100100	64639 231029- 001	2019-02-24	2020-02-24
MITEQ	Amplifier	AFS42-00101800- 25-S-42	2001271	2018-09-05	2019-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2018-06-27	2019-06-27
E-Microwave	Band-stop Filters	OBSF-2400-2483.5- S	OE01601525	2018-06-16	2019-06-16
Micro-tronics	High Pass Filter	HPM50111	S/N-G217	2018-06-16	2019-06-16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data**Environmental Conditions**

Temperature:	23~26.5 °C
Relative Humidity:	45~69%
ATM Pressure:	100.4 kPa


* The testing was performed by Neil Liao on 2019-03-23

Test Result: Compliance, please Refer to the following data

Test Mode: Transmitting(EUT with PoE function+ Magnet Antenna was the worst)

1) 30MHz-1GHz:**Adapter Mode:****Horizontal:**


Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
54.2500	43.69	peak	-12.06	31.63	40.00	8.37
138.6400	36.92	peak	-5.56	31.36	43.50	12.14
296.7500	46.40	QP	-3.90	42.50	46.00	3.50
334.5800	45.35	QP	-3.35	42.00	46.00	4.00
399.5700	39.93	QP	-2.03	37.90	46.00	8.10
600.3600	37.69	peak	1.03	38.72	46.00	7.28

Vertical:


Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
37.7600	37.02	QP	-4.22	32.80	40.00	7.20
51.3400	41.99	QP	-11.59	30.40	40.00	9.60
302.5700	36.76	peak	-3.75	33.01	46.00	12.99
334.5800	38.67	peak	-3.35	35.32	46.00	10.68
399.5700	40.45	peak	-2.03	38.42	46.00	7.58
600.3600	41.77	QP	1.03	42.80	46.00	3.20

PoE Mode:

Horizontal:



Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
30.9700	30.79	QP	0.91	31.70	40.00	8.30
131.8500	40.69	QP	-4.89	35.80	43.50	7.70
159.9800	45.36	QP	-5.86	39.50	43.50	4.00
258.9200	47.93	QP	-5.43	42.50	46.00	3.50
600.3600	40.37	QP	1.03	41.40	46.00	4.60
800.1800	36.07	QP	4.43	40.50	46.00	5.50

Vertical:

Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
30.9700	32.59	QP	0.91	33.50	40.00	6.50
62.0100	47.41	QP	-12.01	35.40	40.00	4.60
159.9800	41.26	QP	-5.86	35.40	43.50	8.10
299.6600	41.38	peak	-3.83	37.55	46.00	8.45
600.3600	39.37	QP	1.03	40.40	46.00	5.60
800.1800	36.37	QP	4.43	40.80	46.00	5.20

2) 1-25GHz(Adapter mode was the worst):**Magnet Antenna:****802.11b Mode, Chain 0:**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	63.26	PK	H	28.12	1.81	0.00	93.19	N/A	N/A
2412.00	60.38	AV	H	28.12	1.81	0.00	90.31	N/A	N/A
2412.00	67.51	PK	V	28.12	1.81	0.00	97.44	N/A	N/A
2412.00	64.38	AV	V	28.12	1.81	0.00	94.31	N/A	N/A
2390.00	30.47	PK	V	28.08	1.80	0.00	60.35	74.00	13.65
2390.00	22.46	AV	V	28.08	1.80	0.00	52.34	54.00	1.66
4824.00	55.83	PK	V	32.95	3.19	37.20	54.77	74.00	19.23
4824.00	51.07	AV	V	32.95	3.19	37.20	50.01	54.00	3.99
7236.00	46.47	PK	V	35.81	4.77	37.27	49.78	74.00	24.22
7236.00	33.61	AV	V	35.81	4.77	37.27	36.92	54.00	17.08
Middle Channel: 2437 MHz									
2437.00	63.79	PK	H	28.17	1.82	0.00	93.78	N/A	N/A
2437.00	60.52	AV	H	28.17	1.82	0.00	90.51	N/A	N/A
2437.00	67.15	PK	V	28.17	1.82	0.00	97.14	N/A	N/A
2437.00	64.23	AV	V	28.17	1.82	0.00	94.22	N/A	N/A
4874.00	55.88	PK	V	33.05	3.26	37.21	54.98	74.00	19.02
4874.00	51.78	AV	V	33.05	3.26	37.21	50.88	54.00	3.12
7311.00	47.71	PK	V	36.01	4.64	37.36	51.00	74.00	23.00
7311.00	34.12	AV	V	36.01	4.64	37.36	37.41	54.00	16.59
High Channel: 2462 MHz									
2462.00	63.65	PK	H	28.22	1.83	0.00	93.70	N/A	N/A
2462.00	60.47	AV	H	28.22	1.83	0.00	90.52	N/A	N/A
2462.00	67.00	PK	V	28.22	1.83	0.00	97.05	N/A	N/A
2462.00	63.12	AV	V	28.22	1.83	0.00	93.17	N/A	N/A
2483.50	28.59	PK	V	28.27	1.84	0.00	58.70	74.00	15.30
2483.50	20.47	AV	V	28.27	1.84	0.00	50.58	54.00	3.42
4924.00	54.52	PK	V	33.15	3.27	37.22	53.72	74.00	20.28
4924.00	51.15	AV	V	33.15	3.27	37.22	50.35	54.00	3.65
7386.00	49.87	PK	V	36.20	4.51	37.46	53.12	74.00	20.88
7386.00	40.74	AV	V	36.20	4.51	37.46	43.99	54.00	10.01

Chain 1:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	56.35	PK	H	28.12	1.81	0.00	86.28	N/A	N/A
2412.00	51.56	AV	H	28.12	1.81	0.00	81.49	N/A	N/A
2412.00	68.08	PK	V	28.12	1.81	0.00	98.01	N/A	N/A
2412.00	63.74	AV	V	28.12	1.81	0.00	93.67	N/A	N/A
2390.00	28.97	PK	V	28.08	1.80	0.00	58.85	74.00	15.15
2390.00	20.30	AV	V	28.08	1.80	0.00	50.18	54.00	3.82
4824.00	56.87	PK	V	32.95	3.19	37.20	55.81	74.00	18.19
4824.00	51.58	AV	V	32.95	3.19	37.20	50.52	54.00	3.48
7236.00	46.47	PK	V	35.81	4.77	37.27	49.78	74.00	24.22
7236.00	33.31	AV	V	35.81	4.77	37.27	36.62	54.00	17.38
Middle Channel: 2437 MHz									
2437.00	55.49	PK	H	28.17	1.82	0.00	85.48	N/A	N/A
2437.00	50.34	AV	H	28.17	1.82	0.00	80.33	N/A	N/A
2437.00	67.80	PK	V	28.17	1.82	0.00	97.79	N/A	N/A
2437.00	62.54	AV	V	28.17	1.82	0.00	92.53	N/A	N/A
4874.00	54.59	PK	V	33.05	3.26	37.21	53.69	74.00	20.31
4874.00	51.37	AV	V	33.05	3.26	37.21	50.47	54.00	3.53
7311.00	46.46	PK	V	36.01	4.64	37.36	49.75	74.00	24.25
7311.00	33.20	AV	V	36.01	4.64	37.36	36.49	54.00	17.51
High Channel: 2462 MHz									
2462.00	57.45	PK	H	28.22	1.83	0.00	87.50	N/A	N/A
2462.00	52.64	AV	H	28.22	1.83	0.00	82.69	N/A	N/A
2462.00	69.50	PK	V	28.22	1.83	0.00	99.55	N/A	N/A
2462.00	64.94	AV	V	28.22	1.83	0.00	94.99	N/A	N/A
2483.50	27.75	PK	V	28.27	1.84	0.00	57.86	74.00	16.14
2483.50	16.73	AV	V	28.27	1.84	0.00	46.84	54.00	7.16
4924.00	55.12	PK	V	33.15	3.27	37.22	54.32	74.00	19.68
4924.00	51.52	AV	V	33.15	3.27	37.22	50.72	54.00	3.28
7386.00	46.40	PK	V	36.20	4.51	37.46	49.65	74.00	24.35
7386.00	33.25	AV	V	36.20	4.51	37.46	36.50	54.00	17.50

802.11g Mode, Chain 0:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	58.37	PK	H	28.12	1.81	0.00	88.30	N/A	N/A
2412.00	45.68	AV	H	28.12	1.81	0.00	75.61	N/A	N/A
2412.00	67.05	PK	V	28.12	1.81	0.00	96.98	N/A	N/A
2412.00	54.57	AV	V	28.12	1.81	0.00	84.50	N/A	N/A
2390.00	36.45	PK	V	28.08	1.80	0.00	66.33	74.00	7.67
2390.00	16.47	AV	V	28.08	1.80	0.00	46.35	54.00	7.65
4824.00	54.70	PK	V	32.95	3.19	37.20	53.64	74.00	20.36
4824.00	39.18	AV	V	32.95	3.19	37.20	38.12	54.00	15.88
7236.00	46.13	PK	V	35.81	4.77	37.27	49.44	74.00	24.56
7236.00	33.50	AV	V	35.81	4.77	37.27	36.81	54.00	17.19
Middle Channel: 2437 MHz									
2437.00	59.30	PK	H	28.17	1.82	0.00	89.29	N/A	N/A
2437.00	46.85	AV	H	28.17	1.82	0.00	76.84	N/A	N/A
2437.00	68.28	PK	V	28.17	1.82	0.00	98.27	N/A	N/A
2437.00	55.64	AV	V	28.17	1.82	0.00	85.63	N/A	N/A
4874.00	54.16	PK	V	33.05	3.26	37.21	53.26	74.00	20.74
4874.00	38.49	AV	V	33.05	3.26	37.21	37.59	54.00	16.41
7311.00	46.47	PK	V	36.01	4.64	37.36	49.76	74.00	24.24
7311.00	33.02	AV	V	36.01	4.64	37.36	36.31	54.00	17.69
High Channel: 2462 MHz									
2462.00	58.20	PK	H	28.22	1.83	0.00	88.25	N/A	N/A
2462.00	46.07	AV	H	28.22	1.83	0.00	76.12	N/A	N/A
2462.00	68.10	PK	V	28.22	1.83	0.00	98.15	N/A	N/A
2462.00	56.08	AV	V	28.22	1.83	0.00	86.13	N/A	N/A
2483.50	41.89	PK	V	28.27	1.84	0.00	72.00	74.00	2.00
2483.50	20.00	AV	V	28.27	1.84	0.00	50.11	54.00	3.89
4924.00	54.15	PK	V	33.15	3.27	37.22	53.35	74.00	20.65
4924.00	38.89	AV	V	33.15	3.27	37.22	38.09	54.00	15.91
7386.00	46.93	PK	V	36.20	4.51	37.46	50.18	74.00	23.82
7386.00	33.58	AV	V	36.20	4.51	37.46	36.83	54.00	17.17

Chain 1:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	63.51	PK	H	28.12	1.81	0.00	93.44	N/A	N/A
2412.00	51.47	AV	H	28.12	1.81	0.00	81.40	N/A	N/A
2412.00	68.49	PK	V	28.12	1.81	0.00	98.42	N/A	N/A
2412.00	56.97	AV	V	28.12	1.81	0.00	86.90	N/A	N/A
2390.00	39.68	PK	V	28.08	1.80	0.00	69.56	74.00	4.44
2390.00	20.29	AV	V	28.08	1.80	0.00	50.17	54.00	3.83
4824.00	46.58	PK	V	32.95	3.19	37.20	45.52	74.00	28.48
4824.00	33.24	AV	V	32.95	3.19	37.20	32.18	54.00	21.82
7236.00	46.35	PK	V	35.81	4.77	37.27	49.66	74.00	24.34
7236.00	33.17	AV	V	35.81	4.77	37.27	36.48	54.00	17.52
Middle Channel: 2437 MHz									
2437.00	63.24	PK	H	28.17	1.82	0.00	93.23	N/A	N/A
2437.00	51.37	AV	H	28.17	1.82	0.00	81.36	N/A	N/A
2437.00	68.09	PK	V	28.17	1.82	0.00	98.08	N/A	N/A
2437.00	56.81	AV	V	28.17	1.82	0.00	86.80	N/A	N/A
4874.00	46.89	PK	V	33.05	3.26	37.21	45.99	74.00	28.01
4874.00	33.61	AV	V	33.05	3.26	37.21	32.71	54.00	21.29
7311.00	45.94	PK	V	36.01	4.64	37.36	49.23	74.00	24.77
7311.00	32.68	AV	V	36.01	4.64	37.36	35.97	54.00	18.03
High Channel: 2462 MHz									
2462.00	63.48	PK	H	28.22	1.83	0.00	93.53	N/A	N/A
2462.00	51.72	AV	H	28.22	1.83	0.00	81.77	N/A	N/A
2462.00	68.41	PK	V	28.22	1.83	0.00	98.46	N/A	N/A
2462.00	56.46	AV	V	28.22	1.83	0.00	86.51	N/A	N/A
2483.50	33.45	PK	V	28.27	1.84	0.00	63.56	74.00	10.44
2483.50	19.37	AV	V	28.27	1.84	0.00	49.48	54.00	4.52
4924.00	46.88	PK	V	33.15	3.27	37.22	46.08	74.00	27.92
4924.00	33.64	AV	V	33.15	3.27	37.22	32.84	54.00	21.16
7386.00	46.18	PK	V	36.20	4.51	37.46	49.43	74.00	24.57
7386.00	33.06	AV	V	36.20	4.51	37.46	36.31	54.00	17.69

802.11n ht20 Mode(MIMO mode was the worst):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	63.51	PK	H	28.12	1.81	0.00	93.44	N/A	N/A
2412.00	51.47	AV	H	28.12	1.81	0.00	81.40	N/A	N/A
2412.00	68.49	PK	V	28.12	1.81	0.00	98.42	N/A	N/A
2412.00	56.97	AV	V	28.12	1.81	0.00	86.90	N/A	N/A
2390.00	39.68	PK	V	28.08	1.80	0.00	69.56	74.00	4.44
2390.00	20.29	AV	V	28.08	1.80	0.00	50.17	54.00	3.83
4824.00	46.58	PK	V	32.95	3.19	37.20	45.52	74.00	28.48
4824.00	33.24	AV	V	32.95	3.19	37.20	32.18	54.00	21.82
7236.00	46.35	PK	V	35.81	4.77	37.27	49.66	74.00	24.34
7236.00	33.17	AV	V	35.81	4.77	37.27	36.48	54.00	17.52
Middle Channel: 2437 MHz									
2437.00	63.24	PK	H	28.17	1.82	0.00	93.23	N/A	N/A
2437.00	51.37	AV	H	28.17	1.82	0.00	81.36	N/A	N/A
2437.00	68.09	PK	V	28.17	1.82	0.00	98.08	N/A	N/A
2437.00	56.81	AV	V	28.17	1.82	0.00	86.80	N/A	N/A
4874.00	46.89	PK	V	33.05	3.26	37.21	45.99	74.00	28.01
4874.00	33.61	AV	V	33.05	3.26	37.21	32.71	54.00	21.29
7311.00	45.94	PK	V	36.01	4.64	37.36	49.23	74.00	24.77
7311.00	32.68	AV	V	36.01	4.64	37.36	35.97	54.00	18.03
High Channel: 2462 MHz									
2462.00	63.48	PK	H	28.22	1.83	0.00	93.53	N/A	N/A
2462.00	51.72	AV	H	28.22	1.83	0.00	81.77	N/A	N/A
2462.00	68.41	PK	V	28.22	1.83	0.00	98.46	N/A	N/A
2462.00	56.46	AV	V	28.22	1.83	0.00	86.51	N/A	N/A
2483.50	33.45	PK	V	28.27	1.84	0.00	63.56	74.00	10.44
2483.50	19.37	AV	V	28.27	1.84	0.00	49.48	54.00	4.52
4924.00	46.88	PK	V	33.15	3.27	37.22	46.08	74.00	27.92
4924.00	33.64	AV	V	33.15	3.27	37.22	32.84	54.00	21.16
7386.00	46.18	PK	V	36.20	4.51	37.46	49.43	74.00	24.57
7386.00	33.06	AV	V	36.20	4.51	37.46	36.31	54.00	17.69

802.11n ht40 Mode(MIMO mode was the worst):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2422 MHz									
2422.00	57.61	PK	H	28.14	1.81	0.00	87.56	N/A	N/A
2422.00	46.38	AV	H	28.14	1.81	0.00	76.33	N/A	N/A
2422.00	62.39	PK	V	28.14	1.81	0.00	92.34	N/A	N/A
2422.00	51.75	AV	V	28.14	1.81	0.00	81.70	N/A	N/A
2390.00	28.75	PK	V	28.08	1.80	0.00	58.63	74.00	15.37
2390.00	16.84	AV	V	28.08	1.80	0.00	46.72	54.00	7.28
4844.00	46.63	PK	V	32.99	3.22	37.20	45.64	74.00	28.36
4844.00	33.94	AV	V	32.99	3.22	37.20	32.95	54.00	21.05
7266.00	46.41	PK	V	35.89	4.72	37.31	49.71	74.00	24.29
7266.00	33.12	AV	V	35.89	4.72	37.31	36.42	54.00	17.58
Middle Channel: 2437 MHz									
2437.00	57.69	PK	H	28.17	1.82	0.00	87.68	N/A	N/A
2437.00	46.85	AV	H	28.17	1.82	0.00	76.84	N/A	N/A
2437.00	62.28	PK	V	28.17	1.82	0.00	92.27	N/A	N/A
2437.00	51.34	AV	V	28.17	1.82	0.00	81.33	N/A	N/A
4874.00	46.47	PK	V	33.05	3.26	37.21	45.57	74.00	28.43
4874.00	33.26	AV	V	33.05	3.26	37.21	32.36	54.00	21.64
7311.00	46.44	PK	V	36.01	4.64	37.36	49.73	74.00	24.27
7311.00	33.25	AV	V	36.01	4.64	37.36	36.54	54.00	17.46
High Channel: 2452 MHz									
2452.00	56.42	PK	H	28.20	1.83	0.00	86.45	N/A	N/A
2452.00	45.89	AV	H	28.20	1.83	0.00	75.92	N/A	N/A
2452.00	61.78	PK	V	28.20	1.83	0.00	91.81	N/A	N/A
2452.00	50.42	AV	V	28.20	1.83	0.00	80.45	N/A	N/A
2483.50	31.74	PK	V	28.27	1.84	0.00	61.85	74.00	12.15
2483.50	16.47	AV	V	28.27	1.84	0.00	46.58	54.00	7.42
4904.00	46.51	PK	V	33.11	3.30	37.21	45.71	74.00	28.29
4904.00	33.27	AV	V	33.11	3.30	37.21	32.47	54.00	21.53
7356.00	45.69	PK	V	36.13	4.56	37.42	48.96	74.00	25.04
7356.00	32.54	AV	V	36.13	4.56	37.42	35.81	54.00	18.19

**Stubby Antenna:
802.11b Mode, Chain 0:**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	62.67	PK	H	28.12	1.81	0.00	92.60	N/A	N/A
2412.00	59.58	AV	H	28.12	1.81	0.00	89.51	N/A	N/A
2412.00	78.52	PK	V	28.12	1.81	0.00	108.45	N/A	N/A
2412.00	75.55	AV	V	28.12	1.81	0.00	105.48	N/A	N/A
2390.00	29.60	PK	V	28.08	1.80	0.00	59.48	74.00	14.52
2390.00	19.88	AV	V	28.08	1.80	0.00	49.76	54.00	4.24
4824.00	54.10	PK	V	32.95	3.19	37.20	53.04	74.00	20.96
4824.00	50.55	AV	V	32.95	3.19	37.20	49.49	54.00	4.51
7236.00	46.41	PK	V	35.81	4.77	37.27	49.72	74.00	24.28
7236.00	33.76	AV	V	35.81	4.77	37.27	37.07	54.00	16.93
Middle Channel: 2437 MHz									
2437.00	62.41	PK	H	28.17	1.82	0.00	92.40	N/A	N/A
2437.00	59.35	AV	H	28.17	1.82	0.00	89.34	N/A	N/A
2437.00	78.42	PK	V	28.17	1.82	0.00	108.41	N/A	N/A
2437.00	75.34	AV	V	28.17	1.82	0.00	105.33	N/A	N/A
4874.00	53.87	PK	V	33.05	3.26	37.21	52.97	74.00	21.03
4874.00	50.21	AV	V	33.05	3.26	37.21	49.31	54.00	4.69
7311.00	46.37	PK	V	36.01	4.64	37.36	49.66	74.00	24.34
7311.00	33.79	AV	V	36.01	4.64	37.36	37.08	54.00	16.92
High Channel: 2462 MHz									
2462.00	61.82	PK	H	28.22	1.83	0.00	91.87	N/A	N/A
2462.00	58.77	AV	H	28.22	1.83	0.00	88.82	N/A	N/A
2462.00	77.41	PK	V	28.22	1.83	0.00	107.46	N/A	N/A
2462.00	74.35	AV	V	28.22	1.83	0.00	104.40	N/A	N/A
2483.50	29.36	PK	V	28.27	1.84	0.00	59.47	74.00	14.53
2483.50	19.50	AV	V	28.27	1.84	0.00	49.61	54.00	4.39
4924.00	53.45	PK	V	33.15	3.27	37.22	52.65	74.00	21.35
4924.00	49.88	AV	V	33.15	3.27	37.22	49.08	54.00	4.92
7386.00	45.76	PK	V	36.20	4.51	37.46	49.01	74.00	24.99
7386.00	33.30	AV	V	36.20	4.51	37.46	36.55	54.00	17.45

Chain 1:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	63.10	PK	H	28.12	1.81	0.00	93.03	N/A	N/A
2412.00	60.12	AV	H	28.12	1.81	0.00	90.05	N/A	N/A
2412.00	78.83	PK	V	28.12	1.81	0.00	108.76	N/A	N/A
2412.00	75.87	AV	V	28.12	1.81	0.00	105.80	N/A	N/A
2390.00	28.84	PK	V	28.08	1.80	0.00	58.72	74.00	15.28
2390.00	20.33	AV	V	28.08	1.80	0.00	50.21	54.00	3.79
4824.00	53.10	PK	V	32.95	3.19	37.20	52.04	74.00	21.96
4824.00	49.63	AV	V	32.95	3.19	37.20	48.57	54.00	5.43
7236.00	46.73	PK	V	35.81	4.77	37.27	50.04	74.00	23.96
7236.00	34.24	AV	V	35.81	4.77	37.27	37.55	54.00	16.45
Middle Channel: 2437 MHz									
2437.00	63.34	PK	H	28.17	1.82	0.00	93.33	N/A	N/A
2437.00	60.29	AV	H	28.17	1.82	0.00	90.28	N/A	N/A
2437.00	79.61	PK	V	28.17	1.82	0.00	109.60	N/A	N/A
2437.00	66.58	AV	V	28.17	1.82	0.00	96.57	N/A	N/A
4874.00	53.44	PK	V	33.05	3.26	37.21	52.54	74.00	21.46
4874.00	50.10	AV	V	33.05	3.26	37.21	49.20	54.00	4.80
7311.00	46.39	PK	V	36.01	4.64	37.36	49.68	74.00	24.32
7311.00	33.80	AV	V	36.01	4.64	37.36	37.09	54.00	16.91
High Channel: 2462 MHz									
2462.00	62.99	PK	H	28.22	1.83	0.00	93.04	N/A	N/A
2462.00	59.87	AV	H	28.22	1.83	0.00	89.92	N/A	N/A
2462.00	78.46	PK	V	28.22	1.83	0.00	108.51	N/A	N/A
2462.00	75.41	AV	V	28.22	1.83	0.00	105.46	N/A	N/A
2483.50	29.29	PK	V	28.27	1.84	0.00	59.40	74.00	14.60
2483.50	20.21	AV	V	28.27	1.84	0.00	50.32	54.00	3.68
4924.00	52.93	PK	V	33.15	3.27	37.22	52.13	74.00	21.87
4924.00	49.44	AV	V	33.15	3.27	37.22	48.64	54.00	5.36
7386.00	45.98	PK	V	36.20	4.51	37.46	49.23	74.00	24.77
7386.00	33.54	AV	V	36.20	4.51	37.46	36.79	54.00	17.21

802.11g Mode, Chain 0:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	61.58	PK	H	28.12	1.81	0.00	91.51	N/A	N/A
2412.00	51.60	AV	H	28.12	1.81	0.00	81.53	N/A	N/A
2412.00	77.07	PK	V	28.12	1.81	0.00	107.00	N/A	N/A
2412.00	67.20	AV	V	28.12	1.81	0.00	97.13	N/A	N/A
2390.00	41.06	PK	V	28.08	1.80	0.00	70.94	74.00	3.06
2390.00	22.45	AV	V	28.08	1.80	0.00	52.33	54.00	1.67
4824.00	48.11	PK	V	32.95	3.19	37.20	47.05	74.00	26.95
4824.00	35.77	AV	V	32.95	3.19	37.20	34.71	54.00	19.29
7236.00	45.96	PK	V	35.81	4.77	37.27	49.27	74.00	24.73
7236.00	33.52	AV	V	35.81	4.77	37.27	36.83	54.00	17.17
Middle Channel: 2437 MHz									
2437.00	61.95	PK	H	28.17	1.82	0.00	91.94	N/A	N/A
2437.00	52.07	AV	H	28.17	1.82	0.00	82.06	N/A	N/A
2437.00	77.41	PK	V	28.17	1.82	0.00	107.40	N/A	N/A
2437.00	67.54	AV	V	28.17	1.82	0.00	97.53	N/A	N/A
4874.00	48.35	PK	V	33.05	3.26	37.21	47.45	74.00	26.55
4874.00	35.86	AV	V	33.05	3.26	37.21	34.96	54.00	19.04
7311.00	46.24	PK	V	36.01	4.64	37.36	49.53	74.00	24.47
7311.00	33.74	AV	V	36.01	4.64	37.36	37.03	54.00	16.97
High Channel: 2462 MHz									
2462.00	58.93	PK	H	28.22	1.83	0.00	88.98	N/A	N/A
2462.00	49.10	AV	H	28.22	1.83	0.00	79.15	N/A	N/A
2462.00	75.80	PK	V	28.22	1.83	0.00	105.85	N/A	N/A
2462.00	65.73	AV	V	28.22	1.83	0.00	95.78	N/A	N/A
2483.50	38.18	PK	V	28.27	1.84	0.00	68.29	74.00	5.71
2483.50	21.99	AV	V	28.27	1.84	0.00	52.10	54.00	1.90
4924.00	47.56	PK	V	33.15	3.27	37.22	46.76	74.00	27.24
4924.00	35.07	AV	V	33.15	3.27	37.22	34.27	54.00	19.73
7386.00	46.39	PK	V	36.20	4.51	37.46	49.64	74.00	24.36
7386.00	33.87	AV	V	36.20	4.51	37.46	37.12	54.00	16.88

Chain 1:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	61.50	PK	H	28.12	1.81	0.00	91.43	N/A	N/A
2412.00	51.63	AV	H	28.12	1.81	0.00	81.56	N/A	N/A
2412.00	76.92	PK	V	28.12	1.81	0.00	106.85	N/A	N/A
2412.00	67.25	AV	V	28.12	1.81	0.00	97.18	N/A	N/A
2390.00	40.83	PK	V	28.08	1.80	0.00	70.71	74.00	3.29
2390.00	21.70	AV	V	28.08	1.80	0.00	51.58	54.00	2.42
4824.00	47.87	PK	V	32.95	3.19	37.20	46.81	74.00	27.19
4824.00	35.43	AV	V	32.95	3.19	37.20	34.37	54.00	19.63
7236.00	46.71	PK	V	35.81	4.77	37.27	50.02	74.00	23.98
7236.00	34.21	AV	V	35.81	4.77	37.27	37.52	54.00	16.48
Middle Channel: 2437 MHz									
2437.00	61.75	PK	H	28.17	1.82	0.00	91.74	N/A	N/A
2437.00	51.80	AV	H	28.17	1.82	0.00	81.79	N/A	N/A
2437.00	77.26	PK	V	28.17	1.82	0.00	107.25	N/A	N/A
2437.00	67.30	AV	V	28.17	1.82	0.00	97.29	N/A	N/A
4874.00	47.18	PK	V	33.05	3.26	37.21	46.28	74.00	27.72
4874.00	34.77	AV	V	33.05	3.26	37.21	33.87	54.00	20.13
7311.00	45.96	PK	V	36.01	4.64	37.36	49.25	74.00	24.75
7311.00	33.54	AV	V	36.01	4.64	37.36	36.83	54.00	17.17
High Channel: 2462 MHz									
2462.00	60.99	PK	H	28.22	1.83	0.00	91.04	N/A	N/A
2462.00	51.07	AV	H	28.22	1.83	0.00	81.12	N/A	N/A
2462.00	75.30	PK	V	28.22	1.83	0.00	105.35	N/A	N/A
2462.00	65.49	AV	V	28.22	1.83	0.00	95.54	N/A	N/A
2483.50	40.15	PK	V	28.27	1.84	0.00	70.26	74.00	3.74
2483.50	21.69	AV	V	28.27	1.84	0.00	51.80	54.00	2.20
4924.00	47.06	PK	V	33.15	3.27	37.22	46.26	74.00	27.74
4924.00	34.71	AV	V	33.15	3.27	37.22	33.91	54.00	20.09
7386.00	45.87	PK	V	36.20	4.51	37.46	49.12	74.00	24.88
7386.00	33.40	AV	V	36.20	4.51	37.46	36.65	54.00	17.35

802.11n ht20 Mode(MIMO was the worst):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	62.31	PK	H	28.12	1.81	0.00	92.24	N/A	N/A
2412.00	52.40	AV	H	28.12	1.81	0.00	82.33	N/A	N/A
2412.00	77.98	PK	V	28.12	1.81	0.00	107.91	N/A	N/A
2412.00	68.07	AV	V	28.12	1.81	0.00	98.00	N/A	N/A
2390.00	42.13	PK	V	28.08	1.80	0.00	72.01	74.00	1.99
2390.00	22.54	AV	V	28.08	1.80	0.00	52.42	54.00	1.58
4824.00	48.59	PK	V	32.95	3.19	37.20	47.53	74.00	26.47
4824.00	36.04	AV	V	32.95	3.19	37.20	34.98	54.00	19.02
7236.00	46.47	PK	V	35.81	4.77	37.27	49.78	74.00	24.22
7236.00	34.10	AV	V	35.81	4.77	37.27	37.41	54.00	16.59
Middle Channel: 2437 MHz									
2437.00	62.10	PK	H	28.17	1.82	0.00	92.09	N/A	N/A
2437.00	52.21	AV	H	28.17	1.82	0.00	82.20	N/A	N/A
2437.00	77.94	PK	V	28.17	1.82	0.00	107.93	N/A	N/A
2437.00	68.09	AV	V	28.17	1.82	0.00	98.08	N/A	N/A
4874.00	48.50	PK	V	33.05	3.26	37.21	47.60	74.00	26.40
4874.00	34.98	AV	V	33.05	3.26	37.21	34.08	54.00	19.92
7311.00	45.77	PK	V	36.01	4.64	37.36	49.06	74.00	24.94
7311.00	32.24	AV	V	36.01	4.64	37.36	35.53	54.00	18.47
High Channel: 2462 MHz									
2462.00	61.78	PK	H	28.22	1.83	0.00	91.83	N/A	N/A
2462.00	51.80	AV	H	28.22	1.83	0.00	81.85	N/A	N/A
2462.00	77.57	PK	V	28.22	1.83	0.00	107.62	N/A	N/A
2462.00	67.78	AV	V	28.22	1.83	0.00	97.83	N/A	N/A
2483.50	40.83	PK	V	28.27	1.84	0.00	70.94	74.00	3.06
2483.50	21.30	AV	V	28.27	1.84	0.00	51.41	54.00	2.59
4924.00	48.33	PK	V	33.15	3.27	37.22	47.53	74.00	26.47
4924.00	35.71	AV	V	33.15	3.27	37.22	34.91	54.00	19.09
7386.00	46.22	PK	V	36.20	4.51	37.46	49.47	74.00	24.53
7386.00	34.74	AV	V	36.20	4.51	37.46	37.99	54.00	16.01




802.11n ht40 Mode(MIMO was the worst):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2422 MHz									
2422.00	58.55	PK	H	28.14	1.81	0.00	88.50	N/A	N/A
2422.00	48.60	AV	H	28.14	1.81	0.00	78.55	N/A	N/A
2422.00	72.50	PK	V	28.14	1.81	0.00	102.45	N/A	N/A
2422.00	62.45	AV	V	28.14	1.81	0.00	92.40	N/A	N/A
2390.00	40.60	PK	V	28.08	1.80	0.00	70.48	74.00	3.52
2390.00	22.07	AV	V	28.08	1.80	0.00	51.95	54.00	2.05
4844.00	46.98	PK	V	32.99	3.22	37.20	45.99	74.00	28.01
4844.00	34.40	AV	V	32.99	3.22	37.20	33.41	54.00	20.59
7266.00	45.40	PK	V	35.89	4.72	37.31	48.70	74.00	25.30
7266.00	33.71	AV	V	35.89	4.72	37.31	37.01	54.00	16.99
Middle Channel: 2437 MHz									
2437.00	58.96	PK	H	28.17	1.82	0.00	88.95	N/A	N/A
2437.00	49.10	AV	H	28.17	1.82	0.00	79.09	N/A	N/A
2437.00	73.16	PK	V	28.17	1.82	0.00	103.15	N/A	N/A
2437.00	63.22	AV	V	28.17	1.82	0.00	93.21	N/A	N/A
4874.00	46.82	PK	V	33.05	3.26	37.21	45.92	74.00	28.08
4874.00	34.26	AV	V	33.05	3.26	37.21	33.36	54.00	20.64
7311.00	46.04	PK	V	36.01	4.64	37.36	49.33	74.00	24.67
7311.00	33.54	AV	V	36.01	4.64	37.36	36.83	54.00	17.17
High Channel: 2452 MHz									
2452.00	57.22	PK	H	28.20	1.83	0.00	87.25	N/A	N/A
2452.00	47.30	AV	H	28.20	1.83	0.00	77.33	N/A	N/A
2452.00	71.99	PK	V	28.20	1.83	0.00	102.02	N/A	N/A
2452.00	62.14	AV	V	28.20	1.83	0.00	92.17	N/A	N/A
2483.50	41.09	PK	V	28.27	1.84	0.00	71.20	74.00	2.80
2483.50	20.75	AV	V	28.27	1.84	0.00	50.86	54.00	3.14
4904.00	46.52	PK	V	33.11	3.30	37.21	45.72	74.00	28.28
4904.00	34.10	AV	V	33.11	3.30	37.21	33.30	54.00	20.70
7356.00	45.55	PK	V	36.13	4.56	37.42	48.82	74.00	25.18
7356.00	33.10	AV	V	36.13	4.56	37.42	36.37	54.00	17.63

Test plots(Magnet Antenna 802.11b middle channel was the worst)




Horizontal:

Fundamental
Test with Band
Rejection Filter



Vertical:

Fundamental
Test with Band
Rejection Filter



FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH


Applicable Standard

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2018-08-03	2019-08-03
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.4 °C
Relative Humidity:	63%
ATM Pressure:	100.5kPa


* The testing was performed by Vern Shen .Kami Zhou, on 2019-03-06

Test Mode: Transmitting(Test only performed at Chain 0)


Test Result: Compliance. Please refer to the following table and plots.

Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	11.142	≥ 0.5
	Middle	2437	10.180	≥ 0.5
	High	2462	10.180	≥ 0.5
802.11g	Low	2412	16.433	≥ 0.5
	Middle	2437	16.673	≥ 0.5
	High	2462	16.433	≥ 0.5
802.11n ht20	Low	2412	17.475	≥ 0.5
	Middle	2437	17.475	≥ 0.5
	High	2462	17.315	≥ 0.5
802.11n ht40	Low	2422	36.553	≥ 0.5
	Middle	2437	36.553	≥ 0.5
	High	2452	36.553	≥ 0.5


802.11b Low Channel




802.11b Middle Channel




802.11b High Channel




802.11g Low Channel




802.11g Middle Channel




802.11n ht20 Middle Channel




802.11n ht20 High Channel




802.11n ht40 Low Channel



802.11n ht40 Middle Channel



802.11n ht40 High Channel




FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.
4. Set the power meter to test average output power, record the result as average power.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	USB Wideband Power Sensor	U2022XA	MY5417006	2018-12-10	2019-12-10
yzjingcheng	Coaxial Cable	KTRFBU-141-50	41005012	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.4 °C
Relative Humidity:	63%
ATM Pressure:	100.5kPa

* The testing was performed by Vern Shen ,Kami Zhou on 2019-03-06

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table.

Test mode	Channel	Frequency (MHz)	Max Peak Conducted Output Power (dBm)			Limit (dBm)
			Chain 0	Chain 1	Total	
802.11b	Low	2412	16.41	16.55	/	30
	Middle	2437	16.79	16.50	/	30
	High	2462	17.14	17.66	/	30
802.11g	Low	2412	16.71	17.13	/	30
	Middle	2437	17.63	17.42	/	30
	High	2462	17.91	18.50	/	30
802.11n ht20	Low	2412	16.50	16.82	19.67	30
	Middle	2437	17.41	17.19	20.31	30
	High	2462	17.69	18.18	20.95	30
802.11n ht40	Low	2422	15.14	15.41	18.29	30
	Middle	2437	15.33	15.50	18.43	30
	High	2452	15.55	15.71	18.64	30

Note:

The maximum antenna gain is 5.0 dBi. The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices:

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

So:

Directional gain = $G_{ANT} + \text{Array Gain} = 5.0 \text{ dBi} < 6 \text{ dBi}$

FCC §15.247(d)– 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**Applicable Standard**

According to FCC§15.247(d):In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.


Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2018-08-03	2019-08-03
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A



* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

802.11b: Band Edge, Right Side

Date: 6.MAR.2019 22:07:31

802.11g: Band Edge, Left Side

Date: 6.MAR.2019 22:11:30

802.11g: Band Edge, Right Side**802.11n ht20 Band Edge, Left Side**

[illegible]

Ref Lvl 20 dBm

Marker 2 [T1] -33.99 dBm

2.39955912 GHz

RBW 100 kHz

RF Att 30 dB

VBW 300 kHz

SWT 22 ms

Unit dBm

1 dB Offset

1MAX

28.01 dBm

2 [T1] -33.99 dBm

2.39955912 GHz


2.40573146 GHz

Center 2.4 GHz


8.8 MHz/



Span 88 MHz



Date: 6.MAR.2019 22:33:46




Chain 1:




802.11b: Band Edge, Right Side**802.11g: Band Edge, Left Side**

802.11g: Band Edge, Right Side**802.11n ht20 Band Edge, Left Side**


802.11n ht20 Band Edge, Right Side



802.11n ht40: Band Edge, Left Side



802.11n ht40 Band Edge, Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the RBW = 3 kHz, VBW = 10 kHz, Set the span to 1.5 times the DTS bandwidth.
4. Use the peak marker function to determine the maximum amplitude level.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2018-08-03	2019-08-03
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	26.4 °C
Relative Humidity:	63%
ATM Pressure:	100.5kPa

* The testing was performed by Andy Huang on 2019-03-24

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table and plots


Test mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)			Limit (dBm/3kHz)
			Chain 0	Chain 1	Total	
802.11b	Low	2412	-7.83	-7.52	/	≤8
	Middle	2437	-8.02	-7.74	/	≤8
	High	2462	-8.74	-8.30	/	≤8
802.11g	Low	2412	-11.56	-12.56	/	≤8
	Middle	2437	-12.09	-12.89	/	≤8
	High	2462	-12.76	-12.51	/	≤8
802.11n ht20	Low	2412	-12.87	-13.55	-10.19	≤6
	Middle	2437	-13.25	-13.43	-10.33	≤6
	High	2462	-13.24	-14.06	-10.62	≤6
802.11n ht40	Low	2422	-21.30	-21.06	-18.17	≤6
	Middle	2437	-22.11	-21.71	-18.90	≤6
	High	2452	-21.58	-22.28	-18.91	≤6

Note 1: The maximum antenna gain is 5.0 dBi. The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices:


$$\text{Array Gain} = 10 \log(N_{\text{ANT}}/N_{\text{SS}}) \text{ dB.}$$

So:


$$\text{Directional gain} = G_{\text{ANT}} + \text{Array Gain} = 5.0 \text{ dBi} + 10 * \log(2/1) = 8.0 \text{ dBi}$$




802.11b_Low_Chain 1




802.11b_Middle_Chain 0




802.11b_Middle_Chain 1




802.11b_High_Chain 0




802.11b_High_Chain 1




802.11g_Low_Chain 0




802.11g_Low_Chain 1




802.11g_Middle_Chain 0




802.11g_Middle_Chain 1




802.11g_High_Chain 0




802.11g_High_Chain 1




802.11n20_Low_Chain 0




802.11n20_Low_Chain 1




802.11n20_Middle_Chain 0




802.11n20_Middle_Chain 1




802.11n20_High_Chain 0




802.11n20_High_Chain 1




802.11n40_Low_Chain 0




802.11n40_Low_Chain 1




802.11n40_Middle_Chain 0




802.11n40_Middle_Chain 1



802.11n40_High_Chain 0



802.11n40_High_Chain 1



***** END OF REPORT *****