

INTERTEK TESTING SERVICES

RF Exposure

The Equipment under Test (EUT) is a Control unit for DRONE DX 2INCH NANO model: HD16A operating at 2.4GHz band. It is powered by DC 3.0V (2 x 1.5V AAA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -14.0dBm (tolerance: +/- 3dB).

The normal conducted output power is: -14.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 80.3dB μ V/m at 3m in the frequency 2405MHz

The EIRP = [(FS*D) ^2 / 30] mW = -14.93dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 78.4dB μ V/m at 3m in the frequency 2475MHz

The EIRP = [(FS*D) ^2 / 30] mW = -16.83dBm

which is within the production variation.

The maximum conducted output power specified is -11.0dBm = 0.08mW

The source- based time-averaging conducted output power

= 0.08* Duty Cycle mW < 0.1mW (Duty Cycle<100%)

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 * 5 / sqrt (2.477) mW

= 9.5mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duration of one cycle = 3.68ms

Effective period of the cycle = 0.4ms

DC = 0.4ms / 3.68ms = 0.1087 or 10.87%