





Test Report



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS

Report No	ER1112-1
Client	Ideal Industries, Inc.
Address	Becker Place Sycamore, IL 60178
Phone	815-895-1295
Items tested	SCDMET277
FCC ID	2AAMXSCDMET1000
IC ID	11250A-SCDMET1000
FRN	0002862225
Equipment Type	Digital Transmission System
Equipment Code	DTS
Emission Designator	755KG1D
FCC/IC Rule Parts	CFR Title 47 FCC Part 15.247, ISED Canada RSS-247 Issue 1
Test Dates	4/20/2017 -5/8/2017
Results	As detailed within this report
Prepared by	 Zachary Johnson – Test Engineer
Authorized by	 Yunus Faziloglu – Sr. Engineer
Issue Date	<u>7/26/2017</u>
Conditions of Issue	This Test Report is issued subject to the conditions stated in the 'Conditions of Testing' section on page 14 of this report.

Curtis-Straus LLC is accredited by the American Association for Laboratory Accreditation for the specific scope of accreditation under Certificate Number 1627-01. This report may contain data which is not covered by the A2LA accreditation.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Contents

Contents.....2
Summary.....3
Test Methodology.....3
Product Tested - Configuration Documentation.....4
Statement of Conformity.....5
Modifications Required for Compliance.....5
Test Results.....6
 Radiated Spurious Emissions.....6
 AC Line Conducted Emissions.....9
 Measurement Uncertainty.....13
Conditions of Testing.....14

Form Final Report REV 12-07-15



Summary

This test report supports a Class II Permissive Change certification application for a transmitter operating pursuant to:

CFR Title 47 FCC Part 15.247 and ISED Canada RSS-247 Issue 1.

SCDMET277 printed circuit board is identical to the previously certified model SCDMET1000.

The only difference is the power supply module between the two models.

Below are the different power supply modules for each variant.

Model Number	Ref Des	Manufacturer	Mfg Part Number
SCDMET1000	PS1	Recom	RAC02-12SC/277
SCDMET277	PS1	Recom	RAC02-12SE/277

SCDMET277 operates in the 902-928MHz frequency range and has a permanently installed wire antenna with 3dBi gain. It is powered by 120-277VAC at 60Hz.

We found that the product met the above requirements without modification. Test sample was received in good condition.

Test Methodology

All testing was performed according to the following rules/procedures/documents;

CFR Title 47 FCC Part 15.247, RSS-247 Issue 1, RSS-Gen Issue 4, FCC KDB 558074 D01

DTS Measurement Guidance v04 and ANSI C63.10-2013.

Radiated emissions were maximized by rotating the device around 3 orthogonal planes (X, Y and Z) as well as varying the test antenna's height and polarity. AC line conducted emissions testing was performed with a 50Ω/50μH LISN.

The following bandwidths were used during radiated spurious emissions testing.

Frequency	RBW	VBW
150kHz-30MHz	9kHz	30kHz
30-1000MHz	120kHz	1MHz
1-10GHz	1MHz	3MHz

Product Tested - Configuration Documentation

EUT Configuration										
Work Order:	R1112									
Company:	Ideal Industries									
Company Address:	Becker Place Sycamore, IL 60178									
Contact:	Dan Harrist									
EUT:	MN SCDMET277			PN RAC02-12SE/277			SN Sample 1			
EUT Description:	CFL Luminaire Controller - Metal Box									
EUT Tx Frequency:	902.7MHz - 927.3 MHz									
EUT Components	MN					SN				
Radiated Sample	--					--				
Conducted Sample	--					--				
Port Label	Port Type	# ports	# populated	cable type	shielded	ferrites	length (m)	in/out	under test	comment
AC Mains	Power AC	1	1	Power AC	No	No	1.5	in	yes	
Antenna	other	1	1	other	No	No	0.1	in	yes	
Load	other	1	1	other	No	No	0.1	in	yes	Power output from Smart Connector
Dim	other	1	1	other	No	No	1	in	yes	0-10Vdc Dimming control
Software Operating Mode Description:										
The EUT provides AC power and a 0-10V dimming control to an electronic ballast. The EUT will be mounted to a light fixture during normal operation. The EUT was set to transmit at Low(902.7MHz), Mid(915MHz), and High(927.3MHz) channels.										

Statement of Conformity

The SCDMET-277 has been found to conform to the following parts of 47 CFR and RSS 247 as detailed below:

RSS-GEN	RSP-100	RSS 247	Part 15	Comments
6.3			15.15(b)	There are no controls accessible to the user that varies the output power to operate in violation of the regulatory requirements.
	3.1		15.19	The label is shown in the label exhibit.
	3.2		15.21	Information to the user is shown in the instruction manual exhibit.
			15.27	No special accessories are required for compliance.
3, 6.1, 6.5			15.31	The EUT was tested in accordance with the measurement standards in this section.
6.13			15.33	Frequency range was investigated according to this section, unless noted in specific rule section under which the equipment operates.
8.1			15.35	The EUT emissions were measured using the measurement detector and bandwidth specified in this section, unless noted in specific rule section under which the equipment operates.
8.3			15.203	The antenna for this device is a permanently installed PCB antenna.
8.10			15.205 15.209	The fundamental is not in a Restricted band and the spurious and harmonic emissions in the Restricted bands comply with the general emission limits of 15.209 or RSS-Gen as applicable
8.8			15.207	EUT meets the AC Line conducted emissions requirements of this section.

Modifications Required for Compliance

None

Test Results

Radiated Spurious Emissions

Limits: Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). [15.247(d)]

As part of this Class II permissive change filing, for all radiated emissions tests, only the low channel (902.7MHz) that passed with the lowest margin in original certification filing has been tested.

MEASUREMENTS / RESULTS

Curtis Straus - a Bureau Veritas Company
 Radiated Emissions Electric Field 3m Distance
 Top Peaks Horizontal 30-1000MHz
 Operator: Nirak So
 Client Present:
 Company:

Work Order - R1112
 EUT Power Input - 120Vac 60Hz
 Test Site - Chamber#2
 Temp; Humid; Pres - 25°C; 29%RH; 1011mBar

Req. 1; Req. 2 - FCC Part 15.247

Frequency	Delta to Marginal Level	Peak Reading	Preamplifier Factor	Antenna Factor	Cable Factor	Adjusted Peak Level	Requirement 1 Limit	Requirement 1 Margin	Requirement 1 Results	Antenna Height	EUT Azimuth	Worst Margin Limit 1
MHz	dB	dBµV	dB	dB/m	dB	dBµV/m	dBµV/m	dB	Pass/Fail	centimeters	degrees	dB
319.933	-0.3	49.5	25	14	1.2	39.7	46	-6.3	PASS	100	135	
324.832	-0.6	49.2	25	14	1.2	39.4	46	-6.6	PASS	100	135	
328.081	-0.4	49.4	24.9	13.9	1.2	39.7	46	-6.4	PASS	100	135	
908.99	1.7	42.8	25.4	22.3	2.1	41.7	46	-4.3	PASS	100	0	-4.3
920.994	-0.3	40.4	25.1	22.4	2.1	39.8	46	-6.3	PASS	150	180	

EUT in Y Orientation. 902MHz TX channel is used.

Curtis Straus - a Bureau Veritas Company
 Radiated Emissions Electric Field 3m Distance
 30-1000MHz Vertical Tabular Data
 Operator: Nirak So
 Client Present:
 Company:

Work Order - R1112
 EUT Power Input - 120Va 60Hz
 Test Site - Chamber#2
 Temp; Humid; Pres - 25°C; 29%RH; 1011mBar

Req. 1; Req. 2 - FCC Part 15.247

Frequency	QP Reading	Preamplifier Gain	Antenna Factor	Cable Loss	QP Amplitude	Limit Req. 1	Margin Req. 1	Results Req. 1	Antenna Height	Turntable Azimuth	Worst Margin Limit 1
MHz	dBµV	dB	dB/m	dB	dBµV/m	dBµV/m	dB	pass/fail	centimeters	degrees	dB
30.513	39.6	25.2	21	0.4	35.7	40	-4.3	PASS	125	155	-4.3
39.024	42.7	25.2	13.9	0.4	31.8	40	-8.2	PASS	113	44	
45.746	47.9	25.2	9.7	0.4	32.8	40	-7.2	PASS	125	19	
323.894	48.2	25	14	1.2	38.4	46	-7.6	PASS	128	305	
326.078	47.2	24.9	14	1.2	37.5	46	-8.6	PASS	184	336	

EUT in Y Orientation. 902MHz TX channel is used.

30-1000MHz



Rev. 4/17/2017

Spectrum Analyzers / Receivers / Preselectors Rental MXE EMI Receiver(1170725)	Range 20Hz-26.5GHz	MN N9038A	Mfr Agilent	SN MY51210151	Asset 1170725	Cat I	Calibration Due 12/22/2017	Calibrated on 12/22/2016
Radiated Emissions Sites EMI Chamber 2	FCC Code 719150	IC Code 2762A-7	VCCI Code A-0015	Range 1-18GHz	Asset 1686	Cat I	Calibration Due 12/21/2018	Calibrated on 12/21/2016
Preamps/Couplers Attenuators / Filters Red	Range 0.009-2000MHz	MN ZFL-1000-LN	Mfr CS	SN N/A	Asset 798	Cat II	Calibration Due 1/28/2018	Calibrated on 1/28/2017
Antennas Red-Brown Bilog	Range 30-2000MHz	MN JB1	Mfr Sunol	SN A0032406	Asset 1218	Cat I	Calibration Due 1/13/2019	Calibrated on 1/13/2017
Meteorological Meters Weather Clock (Pressure Only) TH A#2078		MN BA928 HTC-1	Mfr Oregon Scientific HDE	SN C3166-1	Asset 831 2078	Cat I II	Calibration Due 4/28/2018 3/23/2018	Calibrated on 3/5/2017 3/23/2017
Cables Asset #2052 Asset #2053	Range 9kHz - 18GHz 9kHz - 18GHz		Mfr Florida RF Florida RF			Cat II II	Calibration Due 3/5/2018 10/1/3017	Calibrated on 3/5/2017 10/30/2016

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.

Date: 23-Apr-17		Company: Powercast Corporation				Work Order: R1112									
Engineer: Nirak So		EUT Desc: SCDMET277				EUT Operating Voltage/Frequency: 120Vac, 60Hz									
Temp: 25C		Humidity: 26%				Pressure: 1009mBar									
Frequency Range: 1 to 6GHz						Measurement Distance: 3 m									
Notes: EUT is in Y position with 902.7MHz channel.						EUT Max Freq: 927.3MHz									
Antenna Polarization (H/V)	Frequency (MHz)	Peak Reading (dBuV)	Average Reading (dBuV)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Peak Reading (dBuV/m)	Adjusted Avg Reading (dBuV/m)	FCC Class B High Frequency - Peak			FCC Class B High Frequency - Average			
									Limit (dBuV/m)	Margin (dB)	Result (Pass/Fail)	Limit (dBuV/m)	Margin (dB)	Result (Pass/Fail)	
H	1805.4	32.2	32.2	17.8	27.4	3.3	45.1	45.1	74.0	-28.9	Pass	54.0	-8.9	Pass	
H	2708.1	30.1	30.1	19.2	28.8	3.7	43.4	43.4	74.0	-30.6	Pass	54.0	-10.6	Pass	
V	1805.4	32.1	32.1	17.8	27.4	3.3	45.0	45.0	74.0	-29.0	Pass	54.0	-9.0	Pass	
V	2708.1	30.1	30.1	19.2	28.8	3.7	43.4	43.4	74.0	-30.6	Pass	54.0	-10.6	Pass	
Table Result:		Pass by -8.9 dB						Worst Freq: 1805.4 MHz							
Test Site: EMI Chamber 1		Cable 1: Asset #2052				Cable 2: Asset #2054				Cable 3: ---					
Analyzer: Rental SA#5		Preamp: Brown				Antenna: Orange Horn				Preselector: ---					
CSsoft Radiated Emissions Calculator v 1.017.186										Copyright Curtis-Straus LLC 2000					
Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor															

1GHz-6GHz

Date: 23-Apr-17		Company: Powercast Corporation				Work Order: R1112									
Engineer: Nirak So		EUT Desc: SCDMET277				EUT Operating Voltage/Frequency: 120Vac, 60Hz									
Temp: 25C		Humidity: 26%				Pressure: 1009mBar									
Frequency Range: 6 to 10GHz						Measurement Distance: 1 m									
Notes: EUT is in Y position with 902.7MHz channel.						EUT Max Freq: 927.3MHz									
Antenna Polarization (H/V)	Frequency (MHz)	Peak Reading (dBuV)	Average Reading (dBuV)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Peak Reading (dBuV/m)	Adjusted Avg Reading (dBuV/m)	FCC Class B High Frequency - Peak			FCC Class B High Frequency - Average			
									Limit (dBuV/m)	Margin (dB)	Result (Pass/Fail)	Limit (dBuV/m)	Margin (dB)	Result (Pass/Fail)	
No emissions found.															
Table Result:		by dB						Worst Freq: MHz							
Test Site: EMI Chamber 1		Cable 1: Asset #2052				Cable 2: Asset #2054				Cable 3: ---					
Analyzer: Rental SA#5		Preamp: Brown				Antenna: Orange Horn				Preselector: ---					
CSsoft Radiated Emissions Calculator v 1.017.186										Copyright Curtis-Straus LLC 2000					
Adjusted Reading = Reading - Preamp Factor + Antenna Factor + Cable Factor															

6GHz-10GHz



BUREAU VERITAS

Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Rev. 4/17/2017

Spectrum Analyzers / Receivers/Preselectors		Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
2093 MXE EMI Receiver		20Hz-26.5GHz	N9038A	Agilent	MY51210181	2093	I	8/9/2017	8/9/2016
Radiated Emissions Sites		FCC Code	IC Code	VCCI Code	Range	Asset	Cat	Calibration Due	Calibrated on
EMI Chamber 1		719150	2762A-6	A-0015	30-1000MHz	1685	II	12/21/2018	12/21/2016
Preamps/Couplers Attenuators / Filters		Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Brown		1-10GHz	CS	CS	N/A	1523	II	9/25/2017	9/25/2016
High Pass Filter		0.03-9 GHz	VHP-16	Mini-Circuits	NA	1288	II	1/7/2018	1/7/2017
Antennas		Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Orange Horn		1-18GHz	3115	EMCO	0004-6123	390	I	10/13/2018	10/13/2016
Meteorological Meters			MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Weather Clock (Pressure Only)			BA928	Oregon Scientific	C3166-1	831	I	4/28/2018	4/28/2016
TH A#2080			HTC-1	HDE		2080	II	3/23/2018	3/23/2017
Cables		Range		Mfr			Cat	Calibration Due	Calibrated on
Asset #2052		9kHz - 18GHz		Florida RF			II	3/5/2018	3/5/2017
Asset #2054		9kHz - 18GHz		Florida RF			II	10/1/3017	10/30/2016

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.



AC Line Conducted Emissions

Limits:

Frequency of emission (MHz)	Quasi-peak limit (dBµV)	Average limit (dBµV)
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

[47 CFR 15.207(a)]

MEASUREMENTS / RESULTS

Curtis Straus - a Bureau Veritas Company					Work Order # - R1112		
Conducted Emissions per CISPR 16-2-1					EUT Power Input - 120VAC/60 Hz		
Peak Detector Tabular Data - Voltage Measurement					Test Site - CEMI-5		
Operator: Michael Mehrmann					Temp; Humid; Pres - 21.4°C;32 %RH; 999mBar		
					EUT Line tested:120VAC/60Hz; Neutral		
					EUT Maximum Freq - MHz		
					Requirement - FCC/CISPR Class B		
Frequency	Raw Peak Rea	Correction Fa	Adjusted Pea	Quasi-peak L	Margin to th	Peak to QP	Worst Margin
MHz	dBµV	dB	dBµV	dBµV	dB	Pass/Fail	dB
0.204	26.2	20.7	46.9	63.4	-16.6	PASS	
0.371	21.6	20.7	42.2	58.5	-16.2	PASS	
0.419	24.4	20.7	45	57.5	-12.4	PASS	-12.4
0.454	20.8	20.7	41.5	56.8	-15.3	PASS	
19.688	22.5	21	43.5	60	-16.5	PASS	
28.263	22.4	21	43.4	60	-16.6	PASS	

120V Neutral Peak

Curtis Straus - a Bureau Veritas Company					Work Order # - R1112		
Conductor: CISPR Average Detector					EUT Power Input - 120VAC/60 Hz		
Quick Average Detector Tabular Data - Voltage Measurement					Test Site - CEMI-5		
Operator: Michael Mehrmann					Temp; Humid; Pres - 21.4°C;32 %RH; 999m		
					EUT Line tested:120VAC/60Hz; Neutral		
					EUT Maximum Freq - MHz		
					Requirement - FCC/CISPR Class B		
Frequency	Raw Aver	Correctio	Adjusted	Average L	Average M	Average R	Worst Average Margin
MHz	dBµV	dB	dBµV	dBµV	dB	Pass/Fail	dB
0.154	24.5	20.7	45.2	55.8	-10.6	PASS	
0.204	22.3	20.7	43	53.5	-10.5	PASS	
0.417	19.2	20.7	39.9	47.5	-7.6	PASS	-7.6
0.454	17.5	20.7	38.2	46.8	-8.6	PASS	
19.727	15.2	21	36.1	50	-13.9	PASS	
28.862	16.5	21	37.5	50	-12.5	PASS	

120V Neutral Average



Curtis Straus - a Bureau Veritas Company			Work Order # - R1112				
Conducted Emissions per CISPR 16-2-1			EUT Power Input - 120VAC/60 Hz				
Peak Detector Tabular Data - Voltage Measurement			Test Site - CEMI-5				
Operator: Michael Mehrmann			Temp; Humid; Pres - 21.4°C;32 %RH; 999mBar				
EUT Line tested:120VAC/60Hz; Phase			EUT Maximum Freq - MHz				
EUT Mode of Operation:			Requirement - FCC/CISPR Class B				
Frequency	Raw Peak	Re Correction	Adjusted Pea	Quasi-peak L	Margin to the	Peak to QP Li	Worst Margin
MHz	dBµV	dB	dBµV	dBµV	dB	Pass/Fail	dB
0.423	27.1	20.7	47.8	57.4	-9.6	PASS	-9.6
0.452	24.7	20.7	45.4	56.8	-11.4	PASS	
0.858	22.8	20.7	43.5	56	-12.5	PASS	
11.524	23.7	20.9	44.5	60	-15.5	PASS	
14.25	23.3	20.9	44.2	60	-15.8	PASS	
19.764	23.4	21	44.4	60	-15.6	PASS	

120V Hot Peak

Curtis Straus - a Bureau Veritas Company			Work Order # - R1112				
Conducted CISPR Average Detector			EUT Power Input - 120VAC/60 Hz				
Quick Average Detector Tabular Data - Voltage Measurement			Test Site - CEMI-5				
Operator: Michael Mehrmann			Temp; Humid; Pres - 21.4°C;32 %RH; 999mBar				
			EUT Line tested:120VAC/60Hz; Phase				
			EUT Maximum Freq - MHz				
			Requirement - FCC/CISPR Class B				
Frequency	Raw Average	Correction	Adjusted Average	Average L	Average R	Worst Average	Margin
MHz	dBµV	dB	dBµV	dBµV	dB	Pass/Fail	dB
0.411	21.7	20.7	42.4	47.6	-5.2	PASS	-5.2
0.451	20.1	20.7	40.7	46.9	-6.1	PASS	
0.864	13.2	20.7	33.9	46	-12.1	PASS	
10.749	15.6	20.9	36.5	50	-13.5	PASS	
18.244	15.9	21	36.9	50	-13.1	PASS	
28.88	15.7	21	36.7	50	-13.3	PASS	

120V Hot Average



Curtis Straus - a Bureau Veritas Company					Work Order # - R1112			
Conducted Emissions per CISPR 16-2-1					EUT Power Input - 277VAC/50 Hz			
Peak Detector Tabular Data - Voltage Measurement					Test Site - CEMI-5			
Operator: Michael Mehrmann					Temp; Humid; Pres - 21.4°C;32 %RH; 999mBar			
					EUT Line tested:277VAC/50Hz; Neutral			
					EUT Maximum Freq - MHz			
					Requirement - FCC/CISPR Class B			
Frequency	Raw Peak	Correctio	Adjusted	Quasi-pea	Margin to	Peak to Q	Worst Margin	
MHz	dBµV	dB	dBµV	dBµV	dB	Pass/Fail	dB	
0.445	31.8	20.7	52.5	57	-4.5	PASS	-4.5	
0.625	25.7	20.7	46.3	56	-9.7	PASS		
0.719	22.2	20.7	42.9	56	-13.1	PASS		
0.747	22.9	20.7	43.6	56	-12.4	PASS		
10.345	26	20.9	46.9	60	-13.1	PASS		
10.393	26.4	20.9	47.3	60	-12.7	PASS		

277V Neutral Peak

Curtis Straus - a Bureau Veritas Company					Work Order # - R1112			
Conductor: CISPR Average Detector					EUT Power Input - 277VAC/50 Hz			
Final Average Detector Tabular Data - Voltage Measurement					Test Site - CEMI-5			
Operator: Michael Mehrmann					Temp; Humid; Pres - 21.4°C;32 %RH; 999mBar			
					EUT Line tested:277VAC/50Hz; Neutral			
					EUT Maximum Freq - MHz			
					Requirement - FCC/CISPR Class B			
Frequency	Raw Aver	Correctio	Adjusted	Average L	Average M	Average R	Worst Average Margin	
MHz	dBµV	dB	dBµV	dBµV	dB	Pass/Fail	dB	
0.154	2.2	20.7	22.9	55.8	-32.9	PASS		
0.155	2.1	20.7	22.8	55.8	-32.9	PASS		
0.44	12	20.7	32.6	47.1	-14.4	PASS	-14.4	
10.244	11.1	20.9	32	50	-18	PASS		
10.387	10.9	20.9	31.8	50	-18.2	PASS		
10.477	10.8	20.9	31.6	50	-18.4	PASS		

277V Neutral Average



Curtis Straus - a Bureau Veritas Company				Work Order # - R1112			
Conducted Emissions per CISPR 16-2-1				EUT Power Input - 277VAC/50 Hz			
Peak Detector Tabular Data - Voltage Measurement				Test Site - CEMI-5			
Operator: Michael Mehrmann				Temp; Humid; Pres - 21.4°C;32 %RH; 999mBar			
				EUT Line tested:277VAC/50Hz; Phase			
				EUT Maximum Freq - MHz			
				Requirement - FCC/CISPR Class B			
Frequency	Raw Peak R	Correction Fact	Adjusted Pea	Quasi-peak Lir	Margin to the	Peak to QP L	Worst Margin
MHz	dBµV	dB	dBµV	dBµV	dB	Pass/Fail	dB
0.431	28.2	20.7	48.9	57.2	-8.4	PASS	-8.4
0.622	26.3	20.7	47	56	-9	PASS	
0.651	25.9	20.7	46.6	56	-9.4	PASS	
0.814	26.9	20.7	47.6	56	-8.4	PASS	
10.106	28.1	20.9	49	60	-11	PASS	
10.306	28.3	20.9	49.2	60	-10.8	PASS	

277V Hot Peak

Curtis Straus - a Bureau Veritas Company				Work Order # - R1112			
Conductor: CISPR Average Detector				EUT Power Input - 277VAC/50 Hz			
Quick Average Detector Tabular Data - Voltage Measurement				Test Site - CEMI-5			
Operator: Michael Mehrmann				Temp; Humid; Pres - 21.4°C;32 %RH; 999m			
				EUT Line tested:277VAC/50Hz; Phase			
				EUT Maximum Freq - MHz			
				Requirement - FCC/CISPR Class B			
Frequency	Raw Aver	Correctior	Adjusted	Average L	Average N	Average R	Worst Average Margin
MHz	dBµV	dB	dBµV	dBµV	dB	Pass/Fail	dB
0.427	21.2	20.7	41.9	47.3	-5.4	PASS	-5.4
0.801	17.1	20.7	37.7	46	-8.3	PASS	
0.837	17.1	20.7	37.8	46	-8.2	PASS	
10.136	19.9	20.9	40.8	50	-9.2	PASS	
10.425	20	20.9	40.9	50	-9.1	PASS	
11.384	19.9	20.9	40.7	50	-9.3	PASS	

277V Hot Average



Measurement Uncertainty

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement	Expanded Uncertainty k=2	Maximum allowable uncertainty
Radiated Emissions (30-1000MHz)		
NIST	5.6dB	N/A
CISPR	4.6dB	5.2dB (Ucisprr)
Radiated Emissions (1-26.5GHz)	4.6dB	N/A
Radiated Emissions (above 26.5GHz)	4.9dB	N/A
Magnetic Radiated Emissions	5.6dB	N/A
Conducted Emissions		
NIST	3.9dB	N/A
CISPR	3.6dB	3.6dB (Ucisprr)
Telco Conducted Emissions (Current)	2.9dB	N/A
Telco Conducted Emissions (Voltage)	4.4dB	N/A
Electrostatic Discharge	11.5%	N/A
Radiated RF Immunity (Uniform Field)	1.6dB	N/A
Electrical Fast Transients	23.1%	N/A
Surge	23.1%	N/A
Conducted RF Immunity	3dB	N/A
Magnetic Immunity	12.8%	N/A
Dips and Interrupts	2.3V	N/A
Harmonics	3.5%	N/A
Flicker	3.5%	N/A
Radio frequency (@ 2.4GHz)	3.23×10^{-8}	1×10^{-7}
RF power, conducted	0.40dB	0.75dB
Maximum frequency deviation:		
• Within 300Hz and 6kHz of audio frequency / Within 6kHz and 25kHz of audio frequency	3.4%	5%
Adjacent channel power	0.3dB	3dB
Conducted spurious emission of transmitter, valid up to 12.75GHz	1.9dB	3dB
Conducted emission of receivers	2.39dB	3dB
Radiated emission of transmitter, valid up to 26.5GHz	1.3dB	3dB
Radiated emission of transmitter, valid up to 80GHz	3.9dB	6dB
Radiated emission of receiver, valid up to 26.5GHz	3.3dB	6dB
Radiated emission of receiver, valid up to 80GHz	3.9dB	6dB
Humidity	3.3dB	6dB
Temperature	2.37%	5%
Time	0.7°C	1.0°C
RF Power Density, Conducted	4.1%	10%
DC and low frequency voltages	0.4dB	3dB
Voltage (AC, <10kHz)	1.3%	3%
Voltage (DC)	1.3%	2%
Voltage (DC)	0.62%	1%

The above reflects a 95% confidence level



Conditions of Testing

[Bureau Veritas Consumer Products Services, Inc., a Massachusetts corporation], and/or its affiliates (collectively, the "Company") will conduct, at the request of the Submitter ("Client"), the tests specified on the submitted Test Request Form or equivalent in accordance with, and subject to, the following terms and conditions (collectively, "Conditions"):

1. All orders for tests are subject to acceptance by the Company, and no order will constitute a binding commitment of the Company unless and until such order is accepted by it, as evidenced by the issuance of a written report ("Test Report") by the Company. The Test Report is issued solely by the Company, is intended for the exclusive use of Client and shall not be published, used for advertising purposes, copied or replicated for distribution to any other person or entity or otherwise publicly disclosed without the prior written consent of the Company. By submitting a request for services to the Company, Client consents to the disclosure to accreditation bodies of those records of Client relevant to the accreditation body's assessment of the Company's competence and compliance with relevant accreditation criteria. The Company shall not be liable for any loss or damage whatsoever resulting from the failure of the Company to provide its services within any time period for completion estimated by the Company. If Client anticipates using the Test Report in any legal proceeding, arbitration, dispute resolution forum or other proceeding, it shall so notify the Company prior to submitting the Test Report in such proceeding. The Company has no obligation to provide a fact or expert witness at such proceeding unless the Company agrees in advance to do so for a separate and additional fee.
2. The Test Report will set forth the findings of the Company solely with respect to the test samples identified therein. Unless specifically and expressly indicated in the Test Report, the results set forth in such Test Report are not intended to be indicative or representative of the quality or characteristics of the lot from which a test sample is taken, and Client shall not rely upon the Test Report as being so indicative or representative of the lot or of the tested product in general. The Test Report will reflect the findings of the Company at the time of testing only, and the Company shall have no obligation to update the Test Report after its issuance. The Test Report will set forth the results of the tests performed by the Company based upon the written information provided to the Company. The Test Report will be based solely on the samples and written information submitted to the Company by Client, and the Company shall not be obligated to conduct any independent investigation or inquiry with respect thereto.
3. The Company may, in its sole discretion, destroy samples which have been furnished to the Company for testing and which have not been destroyed in the course of testing. The Company may delegate the performance of all or a portion of the services contemplated hereunder to an affiliate, agent or subcontractor of the Company, and Client consents to such delegation.
4. These Conditions and the Test Report represent the entire understanding of the parties hereto with respect to the subject matter hereof and of the Test Report, and no modification, variance or extrapolation with respect thereto shall be permitted without the prior written consent of the Company.
5. The names, service marks, trademarks and copyrights of the Company and its affiliates, including the names "BUREAU VERITAS," "BUREAU VERITAS CONSUMER PRODUCTS SERVICES," "BVCPS," "MTL," "ACTS," "MTL-ACTS" and CURTIS-STRAUS (collectively, the "Marks") are and shall remain the sole property of the Company or its affiliates and shall not be used by Client except solely to the extent that Client obtains the prior written approval of the Company and then only in the manner prescribed by the Company. Client shall not contest the validity of the Marks or take any action that might impair the value or goodwill associated with the Marks or the image or reputation of the Company or its affiliates.
6. Payment in full shall be due 30 days after the date of invoice. Interest shall be due on overdue amounts from the due date until paid at an interest rate of 1.5% per month or, if less, the maximum rate permitted by law. The Company reserves the right, at any time and from time to time, to revoke any credit extended to Client. Client shall reimburse the Company for any costs it incurs in collecting past due amounts, including court costs and fees and expenses of attorneys and collection agencies. The Test Report may not be used or relied upon by Client if and for so long as Client fails to pay when due any invoice issued by the Company or any affiliate of it to Client or any affiliate or subsidiary of Client together with interest and penalties, if any, accrued thereon.
7. The Company disclaims any and all responsibility or liability arising out of or in connection with e-mail transmissions of such information.
8. Client understands and agrees that the Company is neither an insurer nor a guarantor, that the Company does not take the place of Client or any designer, manufacturer, agent, buyer, distributor or transportation or shipping company, and that the Company disclaims all liability in such capacities. Client further understands that if it seeks assurance against loss or damage, it should obtain appropriate insurance.
9. Client agrees that the Company, by providing the services, does not take the place of Client nor any third party, nor does the Company release them from any of their obligations, nor does the Company otherwise assume, abridge, abrogate or undertake to discharge any duty of any third party to Client or any duty of Client or any third party to any other third party, and Client will not release any third party from its obligations and duties with respect to the tested goods.
10. Client shall, on a timely basis, (a) provide adequate instructions to the Company in order to enable the Company to perform properly its services, (b) provide, or cause Client's suppliers and contractors to provide, the Company with all documents necessary to enable the Company to perform its services, (c) furnish the Company with all relevant information regarding Client's intended use and purposes of the tested goods, (d) advise the Company of essential dates and deadlines relevant to the tested goods and (e) fully exercise all rights and remedies available to Client against third parties in respect of the tested goods.
11. The Company shall undertake due care and ordinary skill in the performance of its services to Client, and the Company shall accept responsibility only where such skill has not been exercised and, even in such event, only to the extent of the limitation of liability set forth herein.
12. If Client desires to assert a claim arising from or relating to (i) the performance, purported performance or non-performance of any services by the Company or (ii) the sale, resale, manufacture, distribution or use of any tested goods, it must submit that claim to the Company in a writing that sets forth with particularity the basis for such claim within 60 days from discovery of the potential claim and not more than six months after the date of issuance of the Test Report to Client. Client waives any and all such claims including, without limitation, claims that the Test Report is inaccurate, incomplete or misleading or that additional or different testing is required, unless and then only to the extent that Client submits a written claim to the Company within both such time periods.
13. CLIENT SHALL, EXCEPT TO THE EXTENT OF COMPANY'S LIABILITY TO CLIENT HEREUNDER (WHICH IN NO EVENT SHALL EXCEED THE LIMITATION OF LIABILITY HEREIN), HOLD HARMLESS AND INDEMNIFY THE COMPANY, ITS AFFILIATES AND THEIR RESPECTIVE DIRECTORS, OFFICERS, EMPLOYEES, AGENTS AND SUBCONTRACTORS AGAINST ALL ACTUAL OR ALLEGED THIRD PARTY CLAIMS FOR LOSS, DAMAGE OR EXPENSE OF WHATSOEVER NATURE AND HOWSOEVER ARISING FROM OR RELATING TO (i) THE PERFORMANCE, PURPORTED PERFORMANCE OR NON-PERFORMANCE OF ANY SERVICES BY THE COMPANY OR (ii) THE SALE, RESALE, MANUFACTURE, DISTRIBUTION OR USE OF ANY TESTED GOODS.
14. EXCEPT AS MAY OTHERWISE BE EXPRESSLY AGREED TO IN WRITING BY THE COMPANY AND NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN OR IN ANY TEST REPORT, NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR USE, IS MADE.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS

One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



15. (A) IN NO EVENT WHATSOEVER SHALL THE COMPANY BE LIABLE FOR ANY CONSEQUENTIAL, SPECIAL, INCIDENTAL, EXEMPLARY OR PUNITIVE DAMAGES IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE TEST REPORT OR THE SERVICES PROVIDED BY THE COMPANY HEREUNDER, INCLUDING WITHOUT LIMITATION LOSS OF OR DAMAGE TO PROPERTY; LOSS OF INCOME, PROFIT OR USE; OR ANY CLAIMS OR DEMANDS MADE AGAINST CLIENT OR ANY OTHER PERSON BY ANY THIRD PARTY IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE SERVICES PROVIDED BY THE COMPANY HEREUNDER.

(B) NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN, AND IN RECOGNITION OF THE RELATIVE RISKS AND BENEFITS TO CLIENT AND THE COMPANY ASSOCIATED WITH THE TESTING SERVICES CONTEMPLATED HEREBY, THE RISKS HAVE BEEN ALLOCATED SUCH THAT UNDER NO CIRCUMSTANCES WHATSOEVER SHALL THE LIABILITY OF THE COMPANY TO CLIENT OR ANY THIRD PARTY IN RESPECT OF ANY CLAIM FOR LOSS, DAMAGE OR EXPENSE, OF WHATSOEVER NATURE OR MAGNITUDE, AND HOWSOEVER ARISING, EXCEED AN AMOUNT EQUAL TO FIVE (5) TIMES THE AMOUNT OF THE FEES PAID TO THE COMPANY FOR THE SPECIFIC SERVICES WHICH GAVE RISE TO SUCH CLAIM OR U.S.\$10,000, WHICHEVER IS THE LESSER AMOUNT.

16. The Company shall not be liable for any loss or damage resulting from any delay or failure in performance of its obligations hereunder resulting directly or indirectly from any event of force majeure or any event outside the control of the Company. If any such event occurs, the Company may immediately cancel or suspend its performance hereunder without incurring any liability whatsoever to Client.

17. Company's services, including these Conditions, shall be governed by, and construed in accordance with, the local laws of the country where the Company performs the tests or, in the case of tests performed in the United States of America, the laws of Massachusetts without regard to conflicts of laws principles. If any aspect(s) of these Conditions is found to be illegal or unenforceable, the validity, legality and enforceability of all remaining aspects of these Conditions shall not in any way be affected or impaired thereby. Any proceeding related to the subject matter hereof shall be brought, if at all, in the courts of the country where the Company performs the tests or, in the case of tests performed in the United States of America, in the courts of Massachusetts. Client waives the right to interpose any counterclaim or setoffs of any nature in any litigation arising hereunder.

The complete list of the Approved Subcontractors Curtis-Straus may use to delegate the performance of work can be provided upon request.
Rev.160009121(2)_#684340 v14CS



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS

One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828

