



No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan  
District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053  
Fax: +86 (0) 755 2671 0594  
Email: ee.shenzhen@sgs.com

Report No.: SZEM160400289103  
Page: 1 of 7

## RF Exposure Evaluation Report

Application No.:	SZEM1604002891CR
Applicant:	S.E.M. INDUSTRIES
Manufacturer:	S.E.M. INDUSTRIES
Factory	S.E.M. INDUSTRIES
Product Name:	Bluetooth Turntable
Model No.(EUT):	TT-9311
Add Model No.:	TT-9311-BTM3EJ, TT-9311-BTM3, TT-9511, TT-9511-BTM3EJ, TT-9511-BTM3, TTT601, TTT601-BK, TTT601-BL, TTT601-RD, TTT601-TN, TTT601S, TTT603, TTT603-BK
Trade Mark:	S.E.M., S-LOGO, NIL, S-DIGITAL, SDIGITAL, S.E.M. AUDIO LABORATORIES, TYLER
FCC ID:	2AANA-SEM-TT9311
Standards:	47 CFR Part 1.1307 (2015) 47 CFR Part 1.1310 (2015)
Date of Receipt:	2016-04-28
Date of Test:	2016-05-18 to 2016-05-19
Date of Issue:	2016-06-07
Test Result :	PASS*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang  
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

## 2 Version

<b>Revision Record</b>				
<b>Version</b>	<b>Chapter</b>	<b>Date</b>	<b>Modifier</b>	<b>Remark</b>
00		2016-06-07		Original

<b>Authorized for issue by:</b>			
<b>Tested By</b>		 (Bill Chen) /Project Engineer	2016-05-19
<b>Prepared By</b>		 (Iris Zhou) /Clerk	2016-06-07
<b>Checked By</b>		 (Eric Fu) /Reviewer	2016-06-07

### **3 Contents**

	Page
<b>1 COVER PAGE</b>	<b>1</b>
<b>2 VERSION</b>	<b>2</b>
<b>3 CONTENTS</b>	<b>3</b>
<b>4 GENERAL INFORMATION</b>	<b>4</b>
4.1 CLIENT INFORMATION	4
4.2 GENERAL DESCRIPTION OF EUT	4
4.3 TEST LOCATION	5
4.4 TEST FACILITY	5
4.5 DEVIATION FROM STANDARDS	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	5
<b>5 RF EXPOSURE EVALUATION</b>	<b>6</b>
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
5.1.1 <i>Limits</i>	6
5.1.2 <i>Test Procedure</i>	6
4.1.3 EUT RF EXPOSURE EVALUATION	7

## 4 General Information

### 4.1 Client Information

Applicant:	S.E.M. INDUSTRIES
Address of Applicant:	35/F., Tower A, Billion Centre, No.1 Wang Kwong Road, Kowloon Bay, Hong Kong
Manufacturer:	S.E.M. INDUSTRIES
Address of Manufacturer:	35/F., Tower A, Billion Centre, No.1 Wang Kwong Road, Kowloon Bay, Hong Kong
Factory:	S.E.M. INDUSTRIES
Address of Factory:	35/F., Tower A, Billion Centre, No.1 Wang Kwong Road, Kowloon Bay, Hong Kong

### 4.2 General Description of EUT

Product Name:	Bluetooth Turntable
Model No.:	TT-9311
Trade Mark:	S.E.M., S-LOGO, NIL, S-DIGITAL, SDIGITAL, S.E.M. AUDIO LABORATORIES, TYLER
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V2.1+EDR
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Antenna Type:	Integral
Antenna Gain:	1.2dBi
Power Supply:	Adapter MODEL:S24W-090200USD INPUT:100-240V50/60Hz 0.8A OUTPUT:9.0V 2A
Test Voltage:	120V 60Hz

Remark:

Model No.: TT-9311, TT-9311-BTM3EJ, TT-9311-BTM3, TT-9511, TT-9511-BTM3EJ, TT-9511-BTM3, TTT601, TTT601-BK, TTT601-BL, TTT601-RD, TTT601-TN, TTT601S, TTT603, TTT603-BK

Only the model TT-9311 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for all above models, only different on model No., trade name, color, cosmetic outlook and silkscreen.

## 4.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch E&E Lab  
No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China  
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

## 4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

## 4.5 Deviation from Standards

None.

## 4.6 Abnormalities from Standard Conditions

None.

## 4.7 Other Information Requested by the Customer

None.

## 5 RF Exposure Evaluation

### 5.1 RF Exposure Compliance Requirement

#### 5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

#### 5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

#### **4.1.3 EUT RF Exposure Evaluation**

Antenna Gain: 1.2dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.318 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

<b>Channel</b>	<b>Frequency (MHz)</b>	<b>Max Conducted Peak Output Power (dBm)</b>	<b>Output Power to Antenna (mW)</b>	<b>Power Density at R = 20 cm (mW/cm<sup>2</sup>)</b>	<b>Limit</b>	<b>Result</b>
Lowest	2402	-0.20	0.955	0.00023	1.0	PASS

Note: Refer to report No. SZEM160400289102 for EUT test Max Conducted Peak Output Power value.

The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.