Applicar	Applicant/Grantee Long Ben(Dong Guan)Elec. Tech. Co., Ltd.					
FCC ID: 2AANL-ZB0C						
Section 15.212 Modular Transmitters						
Request	for Modular Approval Requ	est for Limited Modular Approval				
_	Requirements	EUT Conditions	Comply (Y/N)			
	_	Approval Requirements				
1	The radio elements of the modular	There is no shielding on the module, so				
	transmitter must have their own	this is a LMA submission. Please refer to				
	shielding. The physical crystal and	User Manual for the restricted condition	N			
	tuning capacitors may be located	to the OEM integrator.				
	external to the shielded radio elements.					
2	The modular transmitter must have	Buffered Data input stage has been				
	buffered modulation/data inputs (if such	integrated in chip(88MZ100).				
	inputs are provided) to ensure that the	_	Y			
	module will comply with Part 15					
	requirements under conditions of					
	excessive data rates or over-modulation.					
3	The modular transmitter must have its	DC 3.3V power supply regulated by	Y			
	own power supply regulation.	chipset(88MZ100)				
4	The modular transmitter must comply	EUT is equipped with a PCB antenna,				
	with the antenna and transmission	Detail pleas reference internal photo.				
	system requirements of Sections 15.203,					
	15.204(b) and 15.204(c). The antenna					
	must either be permanently attached or					
	employ a "unique" antenna coupler (at		<b>X</b> 7			
	all connections between the module and		Y			
	the antenna, including the cable). The					
	"professional installation" provision of Section 15.203 is not applicable to					
	modules but can apply to limited					
	modular approvals under paragraph (b)					
	of this section.					
5	The modular transmitter must be tested	Pleas reference exhibition test setup				
	in a stand-alone configuration, <i>i.e.</i> , the	photo for the stand-alone test				
	module must not be inside another	configuration.				
	device during testing for compliance					
	with Part 15 requirements. Unless the					
	transmitter module will be battery					
	powered, it must comply with the AC					
	line conducted requirements found in		Y			
	Section 15.207. AC or DC power lines					
	and data input/output lines connected to					
	the module must not contain ferrites,					
	unless they will be marketed with the					
	module (see Section 15.27(a)). The					
	length of these lines shall be the length					
	typical of actual use or, if that length is					
	unknown, at least 10 centimeters to					
	insure that there is no coupling between					
	the case of the module and supporting					

	equipment. Any accessories, peripherals,		
	or support equipment connected to the		
	module during testing shall be		
	unmodified and commercially available		
	(see Section 15.31(i)).		
6	The modular transmitter must be	The instruction on the labeling rule of	
	equipped with either a permanently	the end product has been stated in the	
	affixed label or must be capable of	user manual of this module, please also	
	electronically displaying its FCC	see the exhibition label sample.	
	identification number.	see the exhibition facer sample.	
	(A) If using a permanently affixed label, the		
	modular transmitter must be labeled with its own		Y
	FCC identification number, and, if the FCC		1
	identification number is not visible when the		
	module is installed inside another device, then		
	the outside of the device into which the module is		
	installed must also display a label referring to the enclosed module. This exterior label can use		
	wording such as the following: "Contains		
	Transmitter Module		
	FCC ID: "2AANL-ZB0C" or "Contains FCC		
	ID: "2AANL-ZB0C" Any similar wording		
	that expresses the same meaning may be used.		
	The Grantee may either provide such a label, an example of which must be included in the		
	application for equipment		
	authorization, or, must provide adequate		
	instructions along with the module which explain		
	this requirement. In the latter case, a copy of		
	these instructions must be included in the		
	application for equipment authorization. (B) If the modular transmitter uses an electronic		
	display of the FCC identification number, the		
	information must be readily accessible and		
	visible on the modular transmitter or on the		
	device in which it is installed. If the module is		
	installed inside another device, then the outside		
	of the device into which the module is installed must display a label referring to the enclosed		
	module. This exterior label can use wording such		
	as the following:		
	"Contains FCC certified transmitter module(s)."		
	Any similar wording that expresses the same		
	meaning may be used. The user manual must include instructions on how to access the		
	electronic display. A copy of these instructions		
	must be included in the application for		
	equipment authorization.		
7	The modular transmitter must comply	The required FCC rule has been fulfilled	
	with any specific rules or operating	and all the instruction for maintaining	
	requirements that	compliance has been clearly stated in the	
	ordinarily apply to a complete	user manual.	
	transmitter and the manufacturer must		Y
	provide adequate instructions along with		
	the module to explain any such		
	requirements. A copy of these		
	instructions must be included in the		
	application for equipment authorization.		

8 [	The modular transmitter must comply	The maximum conducted output power	
•	with any applicable RF exposure	of this module is 10.5dBm with antenna	Y
1	requirements in its final configuration.	gain 2.0dBi only, and the module is	
		designed for end product which at least	
		20cm from human body as normal use.	
		therefore this module comply with FCC	
		§1.1310 and §2.1091 RF exposure	

A **limited modular approval** may be granted for single or split modular transmitters that do not comply with all of the above requirements, *e.g.*, shielding, minimum signaling amplitude, buffered modulation/data inputs, or power supply regulation, if the manufacturer can demonstrate by alternative means in the application for equipment authorization that the modular transmitter meets all the applicable Part 15 requirements under the operating conditions in which the transmitter will be used. Limited modular approval also may be granted in those instances where compliance with RF exposure rules is demonstrated only for particular product configurations. The applicant for certification must state how control of the end product into which the module will be installed will be maintained such that full compliance of the end product is always ensured.

Sincerely,

Client's name / title : Sui Xiong Diao / General Manager

Sui Xion 9 Diao

Contact information / address : No.19, Jian She Road, Shi Ma Village, Tang Xia Town, Dongguan, China

Tel: +86-139 2292 7321 Fax: +86-769 8781 9239

E-Mail: pdc@long-ben.com