

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057

 Telephone:
 +86 (0) 755 2601 2053

 Fax:
 +86 (0) 755 2671 0594

 Email:
 ee.shenzhen@sgs.com

Report No.: SZEM150200070402 Page: 1 of 48

# FCC REPORT

Application No:	SZEM1502000704CR (SGS GZ No.:GZEM1501000533CR )
Applicant:	WOOX Innovations Ltd.
Manufacturer:	WOOX Innovations Ltd.
Factory:	Arts Electronics Co., Ltd
Product Name:	Smart Home Window / Door Sensor
Model No.(EUT):	AEH2120/37
Add Model No.:	AEH2120/zz,wherezz=00-99(different exported countries)
Trade Mark:	PHILIPS
FCC ID:	2AANUAEH2120
Standards:	47 CFR Part 15, Subpart C (2014)
Date of Receipt:	2015-02-10
Date of Test:	2015-02-11 to 2015-03-05
Date of Issue:	2015-03-27
Test Result:	PASS *

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.



Report No.: SZEM150200070402 Page: 2 of 48

# 2 Version

Revision Record					
Version	Chapter	Date	Modifier	Remark	
00		2015-03-27		Original	

Authorized for issue by:		
Tested By	Eric Fu	2015-03-05
	(Erick Fu) /Project Engineer	Date
Prepared By	Jorde Chen	2015-03-27
	(Jade Chen) /Clerk	Date
Checked By	Emen-Li	2015-03-27
	(Emen Li) /Reviewer	Date

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM150200070402 Page: 3 of 48

# 3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2009	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	KDB558074 D01 v03r02	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	KDB558074 D01 v03r02	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	KDB558074 D01 v03r02	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	KDB558074 D01 v03r02	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	KDB558074 D01 v03r02	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS

Remark:

Model No.: AEH2120/zz, where zz=00-99 (different exported countries)

Only the model AEH2120/37 was tested, since the circuitry design, PCB layout, electrical components used, internal wiring and functions were identical for all above models. Only different on model No. and exported countries.





Report No.: SZEM150200070402 Page: 4 of 48

# 4 Contents

1	CC	OVER PAGE	1
2	VE	RSION	2
3	TE	ST SUMMARY	3
4		ONTENTS	-
-			
5	GE	ENERAL INFORMATION	5
	5.1	CLIENT INFORMATION	
	5.2	GENERAL DESCRIPTION OF EUT	
	5.3		
	5.4 5.5	DESCRIPTION OF SUPPORT UNITS	
	5.6	Test Facility	
	5.7	DEVIATION FROM STANDARDS	
	5.8	ABNORMALITIES FROM STANDARD CONDITIONS	
	5.9	OTHER INFORMATION REQUESTED BY THE CUSTOMER	
	5.10	EQUIPMENT LIST	
6	TE	ST RESULTS AND MEASUREMENT DATA	11
	6.1	ANTENNA REQUIREMENT	11
	6.2	CONDUCTED PEAK OUTPUT POWER	
	6.3	6DB OCCUPY BANDWIDTH	
	6.4	Power Spectral Density	
	6.5 6.6	BAND-EDGE FOR RF CONDUCTED EMISSIONS	
	6.7	RADIATED SPURIOUS EMISSION	-
	••••	7.1 Radiated Spurious Emissions	
	6.8	RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	38
7	PH	IOTOGRAPHS - EUT TEST SETUP	48
	7.1	RADIATED EMISSION	48
	7.2	RADIATED SPURIOUS EMISSION	48
8	PH	IOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	48



Report No.: SZEM150200070402 Page: 5 of 48

# 5 General Information

### 5.1 Client Information

Applicant:	WOOX Innovations Ltd.			
Address of Applicant:	5/F.,Philips Electronics Building,5 Science Park East Avenue, Hong Kong Science Park, Shatin, New Territories, Hong Kong			
Manufacturer:	WOOX Innovations Ltd.			
Address of Manufacturer:	5/F.,Philips Electronics Building,5 Science Park East Avenue, Hong Kong Science Park, Shatin, New Territories, Hong Kong			
Factory:	Arts Electronics Co., Ltd			
Address of Factory:	No.1, SHANGXING LU, SHANGJIAO COMMUNITY, CHANGAN TOWN, DONGGUAN CITY, GUANGDONG, PROVINCE, CHINA			

### 5.2 General Description of EUT

Product Name:	Smart Home Window / Door Sensor
Model No.:	AEH2120/37
Trade Mark:	PHILIPS
Operation Frequency:	2405MHz~2475MHz
Wireless technology:	Zigbee
Modulation Type:	DSSS(OQPSK)
Number of Channel:	15
Test Power Grade:	ClassII (manufacturer declare)
Test Software of EUT:	Hyperterminal (manufacturer declare)
Sample Type:	Portable production
Antenna Type:	Integral
Antenna Gain:	0.5dbi
Battery:	DC 3.0V(1.5V x 2"AAA" Size battery)

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM150200070402 Page: 6 of 48

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2405MHz	5	2425MHz	9	2445MHz	13	2465MHz
2	2410MHz	6	2430MHz	10	2450MHz	14	2470MHz
3	2415MHz	7	2435MHz	11	2455MHz	15	2475MHz
4	2420MHz	8	2440MHz	12	2460MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2405MHz
The Middle channel	2440MHz
The Highest channel	2475MHz

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM150200070402 Page: 7 of 48

### 5.3 Test Environment

Operating Environment:		
Temperature:	24.0 °C	
Humidity:	50 % RH	
Atmospheric Pressure:	1020mbar	

### 5.4 Description of Support Units

The EUT has been tested independent unit.

### 5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594 No tests were sub-contracted.



Report No.: SZEM150200070402 Page: 8 of 48

### 5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### • CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• VCCI

The 10m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

#### • FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

#### • Industry Canada (IC)

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.

### 5.7 Deviation from Standards

None.

### 5.8 Abnormalities from Standard Conditions

None.

### 5.9 Other Information Requested by the Customer

None.



Report No.: SZEM150200070402 Page: 9 of 48

# 5.10Equipment List

	RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)	
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2015-06-10	
2	EMI Test Receiver	Agilent Technologies	N9038A	SEL0312	2015-09-16	
3	EMI Test software	AUDIX	E3	SEL0050	N/A	
4	Coaxial cable	SGS	N/A	SEL0028	2015-05-29	
5	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0014	2015-10-24	
6	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2015-05-16	
7	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2015-10-24	
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2015-10-24	
9	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2015-10-24	
10	Band filter	Amindeon	Asi 3314	SEL0094	2015-05-16	
11	Active Loop Antenna	Beijing Daze	ZN30900A	SEL0097	2015-10-24	



Report No.: SZEM150200070402 Page: 10 of 48

	RF connected test				
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2015-10-24
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2015-10-24
4	Coaxial cable	SGS	N/A	SEL0178	2015-05-29
5	Coaxial cable	SGS	N/A	SEL0179	2015-05-29
6	Barometer	ChangChun	DYM3	SEL0088	2015-05-16
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2015-05-16
8	Band filter	amideon	82346	SEL0094	2015-05-16
9	POWER METER	R & S	NRVS	SEL0144	2015-10-24
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2015-05-16
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2015-10-24

Note: The calibration interval is one year, all the instruments are valid.

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM150200070402 Page: 11 of 48

# 6 Test results and Measurement Data

### 6.1 Antenna Requirement

Standard requirement: 47 CFR Part 15C Section 15.203 /247(c)


#### 15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### EUT Antenna:



The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0.5dBi.



Report No.: SZEM150200070402 Page: 12 of 48

### 6.2 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)				
Test Method:	KDB558074 D01 v03r02				
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table				
	Ground Reference Plane				
	Remark:				
	Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.				
Limit:	30dBm				
Test Mode:	Transmitting with DSSS(O-QPSK) modulation				
Instruments Used:	Refer to section 5.10 for details				
Test Results:	Pass				


#### **Measurement Data**

OQPSK mode								
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result					
Lowest	2.89	30.00	Pass					
Middle	2.12	30.00	Pass					
Highest	1.28	30.00	Pass					

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM150200070402 Page: 13 of 48





Report No.: SZEM150200070402 Page: 14 of 48





Report No.: SZEM150200070402 Page: 15 of 48

#### Test Requirement: 47 CFR Part 15C Section 15.247 (a)(2) **Test Method:** KDB558074 D01 v03r02 Test Setup: Spectrum Analyzer E.U.T C Non-Conducted Table **Ground Reference Plane** Limit: ≥ 500 kHz Test Mode: transmitting with DSSS(O-QPSK) modulation Instruments Used: Refer to section 5.10 for details **Test Results:** Pass

### 6.3 6dB Occupy Bandwidth


#### Measurement Data

Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	1.410	≥500	Pass
Middle	1.595	≥500	Pass
Highest	1.595	≥500	Pass

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM150200070402 Page: 16 of 48





Report No.: SZEM150200070402 Page: 17 of 48





Report No.: SZEM150200070402 Page: 18 of 48

Test Requirement:	47 CFR Part 15C Section 15.247 (e)				
Test Method:	KDB558074 D01 v03r02				
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane				
Limit:	≤8.00dBm/3kHz				
Exploratory Test Mode:	transmitting with DSSS(O-QPSK) modulation				
Instruments Used:	Refer to section 5.10 for details				
Test Results:	Pass				

### 6.4 Power Spectral Density


#### **Measurement Data**

DSSS(O-QPSK) mode								
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result					
Lowest	-0.48	≤8.00	Pass					
Middle	0.59	≤8.00	Pass					
Highest	-1.49	≤8.00	Pass					

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM150200070402 Page: 19 of 48





Report No.: SZEM150200070402 Page: 20 of 48





Report No.: SZEM150200070402 Page: 21 of 48


### 6.5 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	KDB558074 D01 v03r02
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	transmitting with DSSS(O-QPSK) modulation
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM150200070402 Page: 22 of 48





Report No.: SZEM150200070402 Page: 23 of 48


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	KDB558074 D01 v03r02
Test Setup:	Spectrum Analyzer E-U.T Non-Conducted Table
	Ground Reference Plane Remark:
	Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	transmitting with DSSS(O-QPSK) modulation
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

### 6.6 Spurious RF Conducted Emissions






Report No.: SZEM150200070402 Page: 24 of 48











Report No.: SZEM150200070402 Page: 26 of 48












Report No.: SZEM150200070402 Page: 28 of 48











#### Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM150200070402 Page: 31 of 48

### 6.7 Radiated Spurious Emission

6.7.1 Radiated Spurious Emissions									
Test Requirement:	47 CFR Part 15C Secti	on 1	5.209 and 15	.205					
Test Method:	ANSI C63.10 2009								
Test Site:	Measurement Distance	: 3m	(Semi-Anech	noic Cham	ber)				
Receiver Setup:	Frequency Detector RBW			V	BW	Remark			
	0.009MHz-0.090MHz		Peak	10kHz	30	)kHz	Peak		
	0.009MHz-0.090MHz		Average	10kHz	30	)kHz	Average		
	0.090MHz-0.110MH	z	Quasi-peak	10kHz	30	)kHz	Quasi-peak		
	0.110MHz-0.490MH	z	Peak	10kHz	30	)kHz	Peak		
	0.110MHz-0.490MH	Average	10kHz	30	)kHz	Average			
	0.490MHz -30MHz		Quasi-peak	10kHz	30	)kHz	Quasi-peak		
	30MHz-1GHz		Quasi-peak	100 kH	z 30	0kHz	Quasi-peak		
	Above 1GHz		Peak	1MHz	31	MHz	Peak		
	Above IGHZ		Peak	1MHz	1	0Hz	Average		
Limit:	Frequency		eld strength rovolt/meter)	Limit (dBuV/m)	Rer	nark	Measureme distance (r		
	0.009MHz-0.490MHz	24	100/F(kHz)			300			
	0.490MHz-1.705MHz	24	000/F(kHz)	-			30		
	1.705MHz-30MHz		30	-		-	30		
	30MHz-88MHz		100	40.0	Quas	i-peak	3		
	88MHz-216MHz		150	43.5	Quas	i-peak	3		
	216MHz-960MHz		200	46.0	Quas	i-peak	3		
	960MHz-1GHz	500		54.0	Quas	i-peak	3		
	Above 1GHz	ove 1GHz 500		54.0	Ave	rage	3		
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.								
Test Setup:									



Report No.: SZEM150200070402 Page: 32 of 48



<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM150200070402 Page: 33 of 48


	case. i. Repeat above procedures until all frequencies measured was complete.
Test Mode:	Transmitting with DSSS(O-QPSK) modulation Transmitting mode For below 1GHz part, through pre-scan, the worst case is the lowest channel. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass





Report No.: SZEM150200070402 Page: 34 of 48






Condition: 47 CFR PART 15.209 3m 3142C Vertical Job No. : 0704CR

Test	mode: TX Freq	Cable		Preamp Factor	Read Level		Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	31.95	0.60	17.61	27.35	23.17	14.03	40.00	-25.97
2	100.93	1.20	9.05	27.19	24.81	7.87	43.50	-35.63
3	311.09	1.94	14.30	26.48	23.19	12.95	46.00	-33.05
4	463.97	2.47	17.40	27.52	23.56	15.91	46.00	-30.09
5	545.18	2.65	18.82	27.63	25.30	19.14	46.00	-26.86
6	776.88	3.14	22.01	27.32	24.83	22.66	46.00	-23.34



Report No.: SZEM150200070402 Page: 35 of 48



Condition: 47 CFR PART 15.209 3m 3142C Horizontal Job No. : 0704CR Test mode: TX mode

	Freq			Preamp Factor				Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 2 3 4 5 6	36.77 155.91 314.38 413.27 668.14 893.86	1.33 1.95 2.26 2.84	9.35 14.42 16.35 21.18	27.33 26.88 26.50 27.21 27.45 26.82	25.10 23.11 24.82 25.01	8.90 12.98 16.22 21.58	43.50 46.00 46.00 46.00	-34.60 -33.02 -29.78 -24.42



Report No.: SZEM150200070402 Page: 36 of 48

Transmitter Emission above 1GHz								
Test mo	de:	Transmitti	ng Tes	t channel:	Lowest	Lowest Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3719.627	6.84	33.09	38.84	47.40	48.49	74	-25.51	Vertical
4810.000	6.43	34.71	39.24	46.85	48.75	74	-25.25	Vertical
7215.000	8.93	35.62	39.07	47.60	53.08	74	-20.92	Vertical
9620.000	9.98	37.36	37.93	44.40	53.81	74	-20.19	Vertical
12333.390	11.11	39.12	38.98	42.27	53.52	74	-20.48	Vertical
16755.080	17.23	40.57	41.55	37.60	53.85	74	-20.15	Vertical
3773.328	6.81	33.13	38.86	47.95	49.03	74	-24.97	Horizontal
4810.000	6.43	34.71	39.24	48.26	50.16	74	-23.84	Horizontal
7215.000	8.93	35.62	39.07	47.49	52.97	74	-21.03	Horizontal
9620.000	9.98	37.36	37.93	43.91	53.32	74	-20.68	Horizontal
13513.510	11.33	39.13	39.92	42.49	53.03	74	-20.97	Horizontal
17027.460	16.70	41.09	41.63	37.56	53.72	74	-20.28	Horizontal

Test mode:		Transmitting Tes		est channel:	Middle	e Re	emark:	Peak
Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	ο Reading Level (dBμV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Over limit (dB)	Polarization
3499.792	6.97	32.89	38.74	47.58	48.70	74	-25.30	Vertical
4880.000	6.58	34.78	39.26	48.10	50.20	74	-23.80	Vertical
7320.000	9.07	35.51	39.06	47.14	52.66	74	-21.34	Vertical
9760.000	9.90	37.80	37.84	43.63	53.49	74	-20.51	Vertical
12245.320	10.98	39.01	38.91	41.92	53.00	74	-21.00	Vertical
16516.620	16.26	40.04	41.48	38.56	53.38	74	-20.62	Vertical
3627.482	6.89	33.02	38.80	46.76	47.87	74	-26.13	Horizontal
4880.000	6.58	34.78	39.26	47.75	49.85	74	-24.15	Horizontal
7320.000	9.07	35.51	39.06	47.49	53.01	74	-20.99	Horizontal
9760.000	9.90	37.80	37.84	43.49	53.35	74	-20.65	Horizontal
12692.090	10.55	39.27	39.28	42.65	53.19	74	-20.81	Horizontal
16635.420	16.76	40.30	41.51	38.12	53.67	74	-20.33	Horizontal



Report No.: SZEM150200070402 Page: 37 of 48

Test mode:		Transmitti	ng Tes	t channel:	Highest		Remark:		Peak
Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)		Over limit (dB)	Polarization
3679.853	6.86	33.06	38.82	46.44	47.54	74		-26.46	Vertical
4950.000	6.76	34.86	39.29	47.45	49.78	74		-24.22	Vertical
7425.000	9.23	35.43	39.05	47.71	53.32	74		-20.68	Vertical
9900.000	9.79	38.38	37.72	43.27	53.72	74		-20.28	Vertical
12245.320	10.98	39.01	38.91	42.72	53.80	74		-20.20	Vertical
16223.320	15.02	40.16	41.39	39.71	53.50	74		-20.50	Vertical
3569.455	6.93	32.97	38.77	46.57	47.70	74		-26.30	Horizontal
4950.000	6.76	34.86	39.29	47.77	50.10	7	4	-23.90	Horizontal
7425.000	9.23	35.43	39.05	47.04	52.65	74		-21.35	Horizontal
9990.000	9.81	38.27	37.75	42.96	53.29	74		-20.71	Horizontal
13202.380	10.92	39.22	39.68	43.19	53.65	74		-20.35	Horizontal
17242.370	16.30	41.00	41.69	38.00	53.61	7	4	-20.39	Horizontal

#### Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

- 2) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sqs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sqs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."





Report No.: SZEM150200070402 Page: 38 of 48

## 6.8 Restricted bands around fundamental frequency

Test Require	47 CFR Part 15C Section 15.209 and 15.205							
Test Method	ANSI C63.10 2009							
Test Site:	easurement Distance: 3m (Semi-Anechoic Chamber)							
Limit:	Limit (dBuV/m @3m) Remark							
	40.0 Quasi-peak Value							
	43.5 Quasi-peak Value							
	46.0 Quasi-peak Value							
	54.0 Quasi-peak Value							
	54.0 Average Value							
	74.0 Peak Value							
Test Setup:								
Test Setup:         Image: Setup:         Image: Setup: Set								
"This document is issued	otatal syst idth v t the cy to restri powe							




Report No.: SZEM150200070402 Page: 39 of 48

	<ul> <li>g. Test the EUT in the lowest channel , the Highest channel</li> <li>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case.</li> <li>i. Repeat above procedures until all frequencies measured was complete.</li> </ul>
Test Mode:	Transmitting with DSSS(O-QPSK) modulation Transmitting mode
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass




Report No.: SZEM150200070402 Page: 40 of 48






Report No.: SZEM150200070402 Page: 41 of 48






Report No.: SZEM150200070402 Page: 42 of 48






Report No.: SZEM150200070402 Page: 43 of 48








Report No.: SZEM150200070402 Page: 44 of 48






Report No.: SZEM150200070402 Page: 45 of 48

Test mode: Transmitting	Test channel:	Highest	Remark:	Peak	Horizontal
-------------------------	---------------	---------	---------	------	------------






Report No.: SZEM150200070402 Page: 46 of 48





Report No.: SZEM150200070402 Page: 47 of 48



Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor



Report No.: SZEM150200070402 Page: 48 of 48

# 7 Photographs - EUT Test Setup

Test model No.: AEH2120/37

#### 7.1 Radiated Emission



# 7.2 Radiated Spurious Emission



# 8 Photographs - EUT Constructional Details

The detailed internal and external Photo see:

Appendix A - Photographs of EUT Constructional Details for SZEM1502000704CR.