

Report No.: SZEM150800505502

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com Page: 1 of 52

### FCC REPORT

Application No: SZEM1508005055CR

Applicant: Gibson Innovations Limited
Manufacturer: Gibson Innovations Limited
Factory: Arts Electronics Co.,Ltd.
Product Name: Wireless portable speaker

Trade Mark: PHILIPS

Model No.(EUT): BT6000B/37

Add Model No.: BT6000X/zz, BT6050X/zz, BT6060X/zz, where X=A - Z or NIL, zz=00 -

99(different plug portion and exported countries.)

FCC ID: 2AANUBT6000X

Standards: 47 CFR Part 15, Subpart C (2014)

**Date of Receipt:** 2015-08-18

**Date of Test:** 2015-08-18 to 2015-08-25

**Date of Issue:** 2015-09-01

Test Result: PASS \*

#### Authorized Signature:



Jack Zhang

#### **EMC Laboratory Manager**

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

<sup>\*</sup> In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEM150800505502

Page: 2 of 52

### 2 Version

Revision Record								
Version	Version Chapter Date Modifier Remark							
00		2015-09-01		Original				

Authorized for issue by:		
Tested By	Orien Zhon	2015-08-25
	(Owen Zhou) /Project Engineer	Date
Prepared By	Dovis Chen	2015-09-01
	(Doris Chen) /Clerk	Date
Checked By	Eric Fu	2015-09-01
	(Eric Fu) /Reviewer	Date



Report No.: SZEM150800505502

Page: 3 of 52

### 3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2009	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207 ANSI C63.10 20		PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2009	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2009	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2009	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2009	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2009	PASS
Radiated Spurious Emissions	-		PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS

Remark:

Model No.: BT6000B/37, BT6000X/zz, BT6050X/zz, BT6060X/zz, where X=A-Z or NIL, zz=00-99(different plug portion and exported countries.)

Only the Model BT6000B/37 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for all above models. Only the Item number and colour of cabinet are different.



Report No.: SZEM150800505502

Page: 4 of 52

### 4 Contents

			Page
1	CC	OVER PAGE	1
2	VE	ERSION	2
		ST SUMMARY	
3			
4		ONTENTS	
5	GE	ENERAL INFORMATION	5
	5.1	CLIENT INFORMATION	5
	5.2	GENERAL DESCRIPTION OF EUT	5
	5.3	TEST ENVIRONMENT	
	5.4	DESCRIPTION OF SUPPORT UNITS	7
	5.5	TEST LOCATION	
	5.6	TEST FACILITY	
	5.7	DEVIATION FROM STANDARDS	
	5.8	ABNORMALITIES FROM STANDARD CONDITIONS	
	5.9	OTHER INFORMATION REQUESTED BY THE CUSTOMER	
	5.10	EQUIPMENT LIST	9
6	TE	EST RESULTS AND MEASUREMENT DATA	12
	6.1	Antenna Requirement	12
	6.2	CONDUCTED EMISSIONS	13
	6.3	CONDUCTED PEAK OUTPUT POWER	17
	6.4	6DB OCCUPY BANDWIDTH	20
	6.5	Power Spectral Density	
	6.6	BAND-EDGE FOR RF CONDUCTED EMISSIONS	
	6.7	Spurious RF Conducted Emissions	
	6.8	RADIATED SPURIOUS EMISSION	
		8.1 Spurious Emissions	
	6.9	RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	
7	PH	HOTOGRAPHS - EUT TEST SETUP	51
	7.1	CONDUCTED EMISSION	51
	7.2	RADIATED EMISSION	
	7.3	RADIATED SPURIOUS EMISSION	52
Q	DH	ACTOCRADUS - ELIT CONSTRUCTIONAL DETAILS	52



Report No.: SZEM150800505502

Page: 5 of 52

### 5 General Information

#### 5.1 Client Information

Applicant:	Gibson Innovations Limited				
Address of Applicant:	5/F., Philips Electronics Building,5 Science Park East Avenue ,Ho Kong Science Park, Shatin, New Territories, Hong Kong				
Manufacturer:	Gibson Innovations Limited				
Address of Manufacturer:	5/F., Philips Electronics Building,5 Science Park East Avenue ,Hong Kong Science Park, Shatin, New Territories, Hong Kong				
Factory:	Arts Electronics Co.,Ltd.				
Address of Factory:	NO.1, SHANGXING LU, SHANGJIAO COMMUNITY, CHANGAN TOWN, DONGGUAN CITY, GUANGDONG PROVINCE, CHINA				

### 5.2 General Description of EUT

Product Name:	Wireless portable speaker
Trade Mark:	PHILIPS
Model No.(EUT):	BT6000B/37
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.0 dual mode
	This test report is for BLE mode.
Modulation Type:	GFSK
Number of Channel:	40
Sample Type:	Portable production
Antenna Type:	Integral
Antenna Gain:	2.12dBi
Rechargeable battery:	DC 3.7V 4400mAh (charge by USB)
Adapter:	Model: GME10C-050200FUu Input: AC 100-240V 50-60Hz 0.28A Output: DC 5.0V 2.0A
Test Voltage:	AC 120V 60Hz



Report No.: SZEM150800505502

Page: 6 of 52

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	11	2422MHz	21	2442MHz	31	2462MHz
2	2404MHz	12	2424MHz	22	2444MHz	32	2464MHz
3	2406MHz	13	2426MHz	23	2446MHz	33	2466MHz
4	2408MHz	14	2428MHz	24	2448MHz	34	2468MHz
5	2410MHz	15	2430MHz	25	2450MHz	35	2470MHz
6	2412MHz	16	2432MHz	26	2452MHz	36	2472MHz
7	2414MHz	17	2434MHz	27	2454MHz	37	2474MHz
8	2416MHz	18	2436MHz	28	2456MHz	38	2476MHz
9	2418MHz	19	2438MHz	29	2458MHz	39	2478MHz
10	2420MHz	20	2440MHz	30	2460MHz	40	2480MHz

#### Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency		
The Lowest channel	2402MHz		
The Middle channel	2440MHz		
The Highest channel	2480MHz		



Report No.: SZEM150800505502

Page: 7 of 52

#### 5.3 Test Environment

Operating Environment:			
Temperature:	25.0 °C		
Humidity:	53 % RH		
Atmospheric Pressure:	1010mbar		

### 5.4 Description of Support Units

The EUT has been tested independent unit.

#### 5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



Report No.: SZEM150800505502

Page: 8 of 52

### 5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### • CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

#### VCCI

The 10m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

#### • FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

#### Industry Canada (IC)

The 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-2.

#### 5.7 Deviation from Standards

None.

#### 5.8 Abnormalities from Standard Conditions

None.

### 5.9 Other Information Requested by the Customer

None.



Report No.: SZEM150800505502

Page: 9 of 52

### 5.10 Equipment List

	Conducted Emission								
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)			
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	2015-05-13	2016-05-13			
2	LISN	Rohde & Schwarz	ENV216	SEL0152	2014-10-24	2015-10-24			
3	LISN	ETS-LINDGREN	3816/2	SEL0021	2015-05-13	2016-05-13			
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLIS N-T8-02	SEL0162	2015-08-30	2016-08-30			
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLIS N-T4-02	SEL0163	2015-08-30	2016-08-30			
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLIS N-T2-02	SEL0164	2015-08-30	2016-08-30			
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	2015-05-13	2016-05-13			
8	Coaxial Cable	SGS	N/A	SEL0025	2015-05-13	2016-05-13			
9	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2014-10-24	2015-10-24			
10	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2014-10-24	2015-10-24			
11	Barometer	Chang Chun	DYM3	SEL0088	2015-05-13	2016-05-13			





Report No.: SZEM150800505502

Page: 10 of 52

	RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2015-05-13	2016-05-13
2	EMI Test Receiver	Agilent Technologies	N9038A	SEL0312	2014-09-16	2015-09-16
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2014-10-24	2015-10-24
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2014-10-24	2015-10-24
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2014-11-24	2015-11-24
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2015-05-13	2016-05-13
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2014-10-24	2015-10-24
9	Coaxial cable	SGS	N/A	SEL0027	2015-05-13	2016-05-13
10	Coaxial cable	SGS	N/A	SEL0189	2015-05-13	2016-05-13
11	Coaxial cable	SGS	N/A	SEL0121	2015-05-13	2016-05-13
12	Coaxial cable	SGS	N/A	SEL0178	2015-05-13	2016-05-13
13	Band filter	Amindeon	82346	SEL0094	2015-05-13	2016-05-13
14	Barometer	Chang Chun	DYM3	SEL0088	2015-05-13	2016-05-13
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2014-10-24	2015-10-24
16	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2014-10-24	2015-10-24
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2015-05-13	2016-05-13
18	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2014-10-24	2015-10-24
19	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2015-05-13	2016-05-13



Report No.: SZEM150800505502

Page: 11 of 52

RF connected test							
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)	
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2014-10-24	2015-10-24	
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2014-10-24	2015-10-24	
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2014-10-24	2015-10-24	
4	Coaxial cable	SGS	N/A	SEL0178	2015-05-13	2016-05-13	
5	Coaxial cable	SGS	N/A	SEL0179	2015-05-13	2016-05-13	
6	Barometer	ChangChun	DYM3	SEL0088	2015-05-13	2016-05-13	
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2015-04-25	2016-04-25	
8	Band filter	amideon	82346	SEL0094	2015-05-13	2016-05-13	
9	POWER METER	R&S	NRVS	SEL0144	2014-10-24	2015-10-24	
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2015-04-25	2016-04-25	
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2014-10-24	2015-10-24	



Report No.: SZEM150800505502

Page: 12 of 52

### 6 Test results and Measurement Data

### 6.1 Antenna Requirement

Standard requirement: 47 CFR Part 15C Section 15.203 /247(c)


15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **EUT Antenna:**



The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.12dBi.



Report No.: SZEM150800505502

Page: 13 of 52


#### 6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207			
Test Method:	ANSI C63.10: 2009			
Test Frequency Range:	150kHz to 30MHz			
Limit:	Limit (dBu\		dBuV)	
	Frequency range (MHz)	Quasi-peak	Average	
	0.15-0.5	66 to 56*	56 to 46*	
	0.5-5	56	46	
	5-30	60	50	
	* Decreases with the logarithm	n of the frequency.		_
Test Procedure:	The mains terminal disturbance voltage test was conducted in a shielded room.			elded
	<ul> <li>room.</li> <li>2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.</li> <li>3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,</li> <li>4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.</li> <li>5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to</li> </ul>			he was ear ne he



Report No.: SZEM150800505502

Page: 14 of 52





Report No.: SZEM150800505502


Page: 15 of 52

#### **Measurement Data**

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

#### Live line:



Site : Shielding Room

Condition : 47 CFR PART15C QP CE LINE

Job No. : 5055CR Test Mode : charge+TX

			LISN			Limit		
	Freq	Loss	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1 @	0.17866	0.02	9.83	36.52	46.37	64.55	-18.18	QP
2	0.17866	0.02	9.83	22.79	32.63	54.55	-21.91	AVERAGE
3	0.21167	0.02	9.83	31.14	40.99	63.14	-22.15	QP
4	0.21167	0.02	9.83	19.16	29.01	53.14	-24.13	AVERAGE
5	0.24682	0.02	9.84	27.85	37.70	61.86	-24.16	QP
6	0.24682	0.02	9.84	13.14	23.00	51.86	-28.87	AVERAGE
7	0.28782	0.01	9.84	25.85	35.71	60.59	-24.88	QP
8	0.28782	0.01	9.84	10.77	20.62	50.59	-29.97	AVERAGE
9	0.56111	0.01	9.87	18.66	28.54	56.00	-27.46	QP
10	0.56111	0.01	9.87	5.51	15.39	46.00	-30.61	AVERAGE
11	18.920	0.02	10.27	9.31	19.60	60.00	-40.40	QP
12	18.920	0.02	10.27	-3.44	6.85	50.00	-43.15	AVERAGE


<sup>&</sup>quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM150800505502

Page: 16 of 52

#### Neutral line:



Site : Shielding Room

Condition : 47 CFR PART15C QP CE NEUTRAL

Job No. : 5055CR Test Mode : charge+TX

	Freq	Cable	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1 @	0.16765	0.02	9.81	34.92	44.75	65.08	-20.32	QP
2	0.16765	0.02	9.81	12.40	22.23	55.08	-32.85	AVERAGE
3	0.18346	0.02	9.83	33.68	43.53	64.33	-20.80	QP
4	0.18346	0.02	9.83	18.94	28.79	54.33	-25.54	AVERAGE
5	0.25211	0.02	9.86	27.41	37.28	61.69	-24.41	QP
6	0.25211	0.02	9.86	13.05	22.92	51.69	-28.77	AVERAGE
7	0.28178	0.01	9.86	24.21	34.09	60.76	-26.68	QP
8	0.28178	0.01	9.86	8.30	18.18	50.76	-32.59	AVERAGE
9	0.54355	0.01	9.90	22.27	32.18	56.00	-23.82	QP
10	0.54355	0.01	9.90	11.91	21.82	46.00	-24.18	AVERAGE
11	0.60431	0.02	9.93	18.76	28.70	56.00	-27.30	QP
12	0.60431	0.02	9.93	8.28	18.22	46.00	-27.78	AVERAGE

#### Notes:


- 1. The following Quasi-Peak and Average measurements were performed on the EUT:
- 2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.



Report No.: SZEM150800505502

Page: 17 of 52

### 6.3 Conducted Peak Output Power



#### **Measurement Data**

mododiomont Bata			
	GFSK mod	de	
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	-4.75	30.00	Pass
Middle	0.10	30.00	Pass
Highest	0.90	30.00	Pass




Report No.: SZEM150800505502


Page: 18 of 52

#### Test plot as follows:

Test mode: GFSK Test channel: Lowest










Report No.: SZEM150800505502

Page: 19 of 52










Report No.: SZEM150800505502

Page: 20 of 52

### 6.4 6dB Occupy Bandwidth



#### **Measurement Data**

Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	0.702	≥500	Pass
Middle	0.708	≥500	Pass
Highest	0.702	≥500	Pass




Report No.: SZEM150800505502


Page: 21 of 52

#### Test plot as follows:

Test mode: GFSK Test channel: Lowest










Report No.: SZEM150800505502

Page: 22 of 52








Report No.: SZEM150800505502

Page: 23 of 52

### 6.5 Power Spectral Density



#### **Measurement Data**

	GFSK mode		
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-21.01	≤8.00	Pass
Middle	-15.88	≤8.00	Pass
Highest	-15.23	≤8.00	Pass




Report No.: SZEM150800505502


Page: 24 of 52

Test plot as follows:

Test mode: GFSK Test channel: Lowest










Report No.: SZEM150800505502

Page: 25 of 52

Test mode: GFSK Test channel: Highest






Report No.: SZEM150800505502

Page: 26 of 52

### 6.6 Band-edge for RF Conducted Emissions






Report No.: SZEM150800505502


Page: 27 of 52

#### Test plot as follows:

Test mode: GFSK Test channel: Lowest



Test mode: GFSK Test channel: Highest





Report No.: SZEM150800505502

Page: 28 of 52

### 6.7 Spurious RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)	
Test Method:	ANSI C63.10 2009	
Test Setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane  Remark:	
	Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.	
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.	
Test Mode:	Transmitting with GFSK modulation	
Instruments Used:	Refer to section 5.10 for details	
Test Results:	Pass	




Report No.: SZEM150800505502

Page: 29 of 52


Test mode: GFSK Test channel: Lowest








Report No.: SZEM150800505502









Report No.: SZEM150800505502

Page: 31 of 52









Report No.: SZEM150800505502

Page: 32 of 52

Test mode: GFSK Test channel: Middle









Report No.: SZEM150800505502


Page: 33 of 52








Report No.: SZEM150800505502









Report No.: SZEM150800505502

Page: 35 of 52











Report No.: SZEM150800505502

Page: 36 of 52









Report No.: SZEM150800505502

Page: 37 of 52





#### Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.



Report No.: SZEM150800505502

Page: 38 of 52


#### 6.8 Radiated Spurious Emission

6.8.1 Spurious Emissi	ions								
Test Requirement:	47 CFR Part 15C Section	on 1	5.209 and 15	.205					
Test Method:	ANSI C63.10 2009							-	
Test Site:	Measurement Distance	Measurement Distance: 3m (Semi-Anechoic Chamber)							
Receiver Setup:	Frequency		Detector	RBW		VBW	Remark		
	0.009MHz-0.090MH	Z	Peak	10kHz	7	30kHz	Peak		
	0.009MHz-0.090MHz		Average	10kHz	<u> </u>	30kHz	Average		
	0.090MHz-0.110MH	Z	Quasi-peak	10kHz	<u> </u>	30kHz	Quasi-peak		
	0.110MHz-0.490MH	Z	Peak	10kHz	<u> </u>	30kHz	Peak		
	0.110MHz-0.490MH	Z	Average	10kHz	<u> </u>	30kHz	Average		
	0.490MHz -30MHz		Quasi-peak	10kHz	z 30kHz		Quasi-peak		
	30MHz-1GHz		Quasi-peak	100 k⊢	lz	300kHz	Quasi-peak		
	Above 1GHz		Peak	1MHz		3MHz	Peak		
	Above IGHZ		Peak	1MHz	1MHz		Average		
Limit:	Frequency		eld strength crovolt/meter)	Limit (dBuV/m)	Remark		Measureme distance (r		
	0.009MHz-0.490MHz	2	400/F(kHz)	-		-	300		
	0.490MHz-1.705MHz	24	1000/F(kHz)	-	-		30		
	1.705MHz-30MHz		30	-		-	30		
	30MHz-88MHz		100	40.0	Q	uasi-peak	3		
	88MHz-216MHz		150	43.5	Q	uasi-peak	3		
	216MHz-960MHz		200	46.0	Q	uasi-peak	3		
	960MHz-1GHz		500	54.0	Q	uasi-peak	3		
	Above 1GHz		500	54.0		Average	3		
	Note: 15.35(b), frequency emissions is limit applicable to the epeak emission level race	20d quip	IB above the roment under to	maximum est. This p	pe	rmitted ave	erage emissio	n	
Test Setup:			•						



Report No.: SZEM150800505502

Page: 39 of 52






Figure 1. Below 30MHz

Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

#### Test Procedure:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel (2402MHz),the middle channel (2440MHz),the Highest channel (2480MHz)
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the



Report No.: SZEM150800505502

Page: 40 of 52


	worst case. i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with GFSK modulation Transmitting mode, Charge + Transmitting mode
Final Test Mode:	Transmitting with GFSK modulation  Pretest the EUT at Transmitting mode and Charge + Transmitting mode, found the Charge + Transmitting mode which it is worse case  For below 1GHz part, through pre-scan, the worst case is the lowest channel.  Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass



Report No.: SZEM150800505502

Page: 41 of 52

Radiated Emission below 1GHz				
30MHz~1GHz (QP)				
Test mode:	Charge +Transmitting	Vertical		



Condition: FCC PART 15 C 3m 3142C VERTICAL

Job No. : 5055CR

Test Mode: AC Charge+TX


Fr	Cable eq Loss	Antenna Factor			Level		Over Limit
	Hz dB	dB/m	dB	dBuV	$\overline{\text{dBuV/m}}$	$\overline{\text{dBuV/m}}$	dB
1 49. 2 101. 3 139. 4 153. 5 184. 6 552.	64 1.45 85 1.79 74 1.83 49 2.04	6.83 8.60 9.50 6.70	25. 45 25. 26 24. 81	41. 86 45. 11 42. 30 42. 98 44. 86 37. 40		43.50 43.50 43.50 43.50	



Report No.: SZEM150800505502

Page: 42 of 52

Test mode: Charge +Transmitting Horizontal



Condition: FCC PART 15 C 3m 3142C HORIZONTAL

Job No. : 5055CR

Test Mode: AC Charge+TX

	Freq			Preamp Factor			Limit Line	Over Limit
	MHz	d₿	dB/m	dB	dBuV	dBuV/m	dBuV/m	<del></del>
1 2 3 4 5 6	114.11 146.89 172.60 181.92 219.08 504.71	1.54 1.79 1.97 2.04 2.30 3.75	7.52 9.10 8.45 6.70 7.14 13.58	24. 94 25. 17 25. 24 25. 22	46. 49 43. 53 49. 07 50. 50 44. 10 37. 47	34.32 34.00	46.00	-14.02 -9.18 -9.50



Report No.: SZEM150800505502

Page: 43 of 52

Transmitter E	Emission	above 1GHz	2					
Test mode:	(	GFSK	Test	channel:	Lowest	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3585.000	-31.20	32.40	0.00	39.50	40.70	74	-33.30	Vertical
4804.000	-30.40	34.30	0.00	45.70	49.60	74	-24.40	Vertical
6000.000	-28.80	34.90	0.00	39.40	45.50	74	-28.50	Vertical
7206.000	-27.90	35.80	0.00	47.70	53.60	74	-20.40	Vertical
9608.000	-25.10	37.20	0.00	35.70	47.80	74	-26.20	Vertical
12630.000	-23.00	38.10	0.00	34.00	49.10	74	-24.90	Vertical
3870.000	-31.30	33.30	0.00	39.20	41.20	74	-32.80	Horizontal
4804.000	-30.40	34.30	0.00	44.10	48.00	74	-26.00	Horizontal
5985.000	-28.90	34.80	0.00	40.30	46.20	74	-27.80	Horizontal
7206.000	-27.90	35.80	0.00	44.30	52.20	74	-21.80	Horizontal
9608.000	-25.10	37.20	0.00	33.00	45.10	74	-28.90	Horizontal
12345.000	-22.70	37.90	0.00	32.60	47.80	74	-26.20	Horizontal

Test mode:	(	GFSK	Tes	t channel:	Middle	Rem	ark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3795.000	-31.20	33.10	0.00	38.80	40.70	74	-33.30	Vertical
4880.000	-30.30	34.50	0.00	46.60	50.80	74	-23.20	Vertical
6000.000	-28.80	34.90	0.00	39.70	45.80	74	-28.20	Vertical
7320.000	-27.90	35.70	0.00	47.90	53.70	74	-20.30	Vertical
9760.000	-24.90	37.30	0.00	34.90	47.30	74	-26.70	Vertical
12300.000	-22.50	37.90	0.00	33.30	48.70	74	-25.30	Vertical
3930.000	-31.20	33.20	0.00	40.20	42.20	74	-31.80	Horizontal
4880.000	-30.30	34.50	0.00	46.50	50.70	74	-23.30	Horizontal
6120.000	-29.20	35.00	0.00	39.90	45.70	74	-28.30	Horizontal
7320.000	-27.90	35.70	0.00	46.40	53.20	74	-20.80	Horizontal
9760.000	-24.90	37.30	0.00	34.80	47.20	74	-26.80	Horizontal
12525.000	-22.90	38.00	0.00	33.60	48.70	74	-25.30	Horizontal



Report No.: SZEM150800505502

Page: 44 of 52

Test mode:		GFSK	Tes	t channel:	Highest	Rem	ark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3990.000	-30.90	33.20	0.00	41.20	43.50	74	-30.50	Vertical
4960.000	-30.30	34.60	0.00	48.30	52.60	74	-21.40	Vertical
6000.000	-28.80	34.90	0.00	39.90	46.00	74	-28.00	Vertical
7440.000	-27.90	35.80	0.00	46.10	54.00	74	-20.00	Vertical
9920.000	-23.80	37.30	0.00	33.80	47.30	74	-26.70	Vertical
12630.000	-23.00	38.10	0.00	34.50	49.60	74	-24.40	Vertical
3825.000	-31.20	33.20	0.00	39.30	41.30	74	-32.70	Horizontal
4960.000	-30.30	34.60	0.00	47.20	51.50	74	-22.50	Horizontal
5925.000	-29.10	34.70	0.00	39.70	45.30	74	-28.70	Horizontal
7440.000	-27.90	35.80	0.00	44.40	52.30	74	-21.70	Horizontal
9920.000	-23.80	37.30	0.00	33.70	47.20	74	-26.80	Horizontal
12510.000	-23.00	38.00	0.00	33.90	48.90	74	-25.10	Horizontal

#### Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
  - Final Test Level = Receiver Reading + Antenna Factor + Cable Factor Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.




Report No.: SZEM150800505502

Page: 45 of 52

#### 6.9 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15	47 CFR Part 15C Section 15.209 and 15.205							
Test Method:	ANSI C63.10 2009								
Test Site:	Measurement Distance: 3m	Measurement Distance: 3m (Semi-Anechoic Chamber)							
Limit:	Frequency	Limit (dBuV/m @3m)	Remark						
	30MHz-88MHz	40.0	Quasi-peak Value						
	88MHz-216MHz	43.5	Quasi-peak Value						
	216MHz-960MHz	46.0	Quasi-peak Value						
	960MHz-1GHz	54.0	Quasi-peak Value						
	Above 1GHz	54.0	Average Value						
	Above IGHZ	74.0	Peak Value						
Test Setup:									






Figure 1. 30MHz to 1GHz

Figure 2. Above 1 GHz

#### Test Procedure:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel.



Report No.: SZEM150800505502

Page: 46 of 52

	<ul> <li>g. Test the EUT in the lowest channel , the Highest channel .</li> <li>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</li> <li>i. Repeat above procedures until all frequencies measured was complete.</li> </ul>					
Exploratory Test Mode:	Transmitting with GFSK modulation					
	Transmitting mode, Charge + Transmitting mode					
Final Test Mode:	Transmitting with GFSK modulation					
	Pretest the EUT at Transmitting mode and Charge + Transmitting mode,					
	found the Charge + Transmitting mode which it is worse case					
	Only the worst case is recorded in the report.					
Instruments Used:	Refer to section 5.10 for details.					
Test Results:	Pass					




Report No.: SZEM150800505502

Page: 47 of 52

#### Test plot as follows:

Test mode:	GFSK	Test channel:	Lowest	Remark:	Vertical	ı
------------	------	---------------	--------	---------	----------	---




Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dBuV/m)	Margin(dB)	Ant.F.(dB/m)	Amp.G.(dB)	Cbl.L.(dB)	Pol.
Peak:								
1	2390	44.9	74.0	29.1	32.5	0.0	-19.3	V
3	2402.245	97.7	74.0	-23.7	32.5	0.0	-19.3	V
Avg								
2	2390	32.2	54.0	21.8	32.5	0.0	-19.3	V
4	2402.245	74.1	54.0	-20.1	32.6	0.0	-19.3	٧



Report No.: SZEM150800505502

Page: 48 of 52






Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dBuV/m)	Margin(dB)	Ant.F.(dB/m)	Amp.G.(dB)	Cbl.L.(dB)	Pol.
Peak:								
1	2390	45.1	74.0	28.9	32.5	0.0	-19.3	Н
4	2402.245	96.0	74.0	-22.0	32.6	0.0	-19.3	Н
Avg								
2	2390	32.2	54.0	21.8	32.5	0.0	-19.3	Н
3	2402.245	73.2	54.0	-19.2	32.6	0.0	-19.3	Н



Report No.: SZEM150800505502

Page: 49 of 52

Test mode:	GFSK	Test channel:	Highest	Remark:	Vertical
------------	------	---------------	---------	---------	----------



Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dBuV/m)	Margin(dB)	Ant.F.(dB/m)	Amp.G.(dB)	Cbl.L.(dB)	Pol.
Peak:								
1	2479.675	98.9	74.0	-24.9	32.5	0.0	-19.1	V
3	2483.5	49.4	74.0	24.6	32.5	0.0	-19.1	V
Avg								
2	2479.675	74.6	54.0	-20.6	32.5	0.0	-19.1	V
4	2483.5	36.1	54.0	17.9	32.5	0.0	-19.1	V






Report No.: SZEM150800505502

Page: 50 of 52

Test mode: GFSK Test channel: Highest Remark: Horizontal



Mk.	Freq.(MHz)	Level(dBuV/m)	Limit(dBuV/m)	Margin(dB)	Ant.F.(dB/m)	Amp.G.(dB)	Cbl.L.(dB)	Pol.
Peak:								
1	2479.900	95.2	74.0	-21.2	32.5	0.0	-19.1	Н
3	2483.5	48.2	74.0	25.8	32.5	0.0	-19.1	Н
Avg								
2	2479.900	73.1	54.0	-19.1	32.5	0.0	-19.1	Н
4	2483.5	34.7	54.0	19.3	32.5	0.0	-19.1	Н

#### Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor



Report No.: SZEM150800505502

Page: 51 of 52


#### 7 Photographs - EUT Test Setup

Test model No.: BT6000B/37

#### 7.1 Conducted Emission



#### 7.2 Radiated Emission






Report No.: SZEM150800505502

Page: 52 of 52

#### 7.3 Radiated Spurious Emission



#### 8 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1508005055CR.