

RF exposure Estimation

1. Introduction

SHB4000, SHB4000/XX, SHB4000YY/XX, SHB4100, SHB4100/XX, SHB4100YY/XX SHK4000, SHK4000/XX, SHK4000YY/XX (XX=00 to 99 for marketing purpose representing different countries, YY=AA to ZZ for different color) are Bluetooth Headset operated at 2.4G, which are SRD devices.

SHB4000, SHB4000/XX, SHB4000YY/XX, SHB4100, SHB4100/XX, SHB4100YY/XX, SHK4000, SHK4000/XX, SHK4000YY/XX (XX=00 to 99 for marketing purpose representing different countries, YY=AA to ZZ for different color) have the same technical construction including software design, RF module, circuit design and PCB layout.

The only difference is the size of SHB4000, SHB4000/XX, SHB4000YY/XX, SHB4100, SHB4100/XX, SHB4100YY/XX is larger than SHK4000, SHK4000/XX, SHK4000YY/XX (XX=00 to 99 for marketing purpose representing different countries, YY=AA to ZZ for different color), SHK4000, SHK4000/XX, SHK4000YY are designed for kids version, which will not affect its electromagnetic emissions, radio-frequency output signal characteristics and output power level. Therefore full test was applied on SHB4000, the other model is deemed to fulfill relevant EMC requirement without further testing.

2. Limit and Guidelines on Exposure to Electromagnetic Fields

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 Mobile Portable RF Exposure v05r02, no SAR required if power is lower than the flowing threshold:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

3. Calculation method

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0$$

Conducted Power + tune up tolerance = 2.42mW

Distance = 5 mm

$f = 2.480$ GHz

$$\left[\frac{2.42}{5} \right] \cdot \text{SQRT}(2.480) = 0.76$$

$0.76 \leq 3.0$



Product Service

Therefore, excluded from SAR testing.

TUV SUD China, Shenzhen Branch

Reviewed by:

A handwritten signature in blue ink, appearing to read 'Phoebe Hu'.

Phoebe Hu/EMC Project Manager
Date: 2015-05-29

Prepared By:

A handwritten signature in blue ink, appearing to read 'Calvin Weng'.

Calvin Weng/EMC Project Engineer
Date: 2015-05-29