SGS

SGS-CSTC Standards Technical Services Co., Ltd.

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 Telephone: +86 (0) 755 2601 2053

 Fax:
 +86 (0) 755 2671 0594

 Email:
 ee.shenzhen@sgs.com

Report No.: SZEM141100603202 Page: 1 of 8

RF Exposure Evaluation Report

Application No.:	SZEM1411006032CR		
Applicant:	WOOX Innovations Ltd.		
Manufacturer: WOOX Innovations Ltd.			
Factory	Arts Electronics Co., Ltd.		
Product Name:	Spotify Connect Multiroom Speaker		
Model No.(EUT):	SW750M/zz, where zz=07, 17, 27, 37, 85 (different exported countries.)		
Add Model No.:	SW700M/zz, where zz=07, 17, 27, 37, 85 (different exported countries.)		
Trade Mark: PHILIPS			
FCC ID:	2AANUSW7X0M		
Standards:	47 CFR Part 1.1307(2013)		
	47 CFR Part 1.1310(2013)		
Date of Receipt:	2014-11-04		
Date of Test:	2014-11-06 to 2014-11-17		
Date of Issue:	2014-11-29		
Test Result :	PASS*		

In the configuration tested, the EUT complied with the standards specified above.



Authorized Signature: Jack Zhang

EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.



Report No.: SZEM141100603202 Page: 2 of 8

Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2014-11-19		Original

Authorized for issue by:		
Tested By	Eric Fu	2014-11-17
	(Eric Fu) /Project Engineer	Date
Prepared By	Link Liong	2014-11-19
	(Link Liang) /Clerk	Date
Checked By	Dermfer	2014-11-20
	(Kevin Feng) /Reviewer	Date



Report No.: SZEM141100603202 Page: 3 of 8

2 Contents

Page
Page

1	С	OVER PAGE	.1
V	ERSI	ON	.2
۷	ERSI	ON	.2
2	С	CONTENTS	.3
3	G	ENERAL INFORMATION	.4
	3.1 3.2 3.3 3.4 3.5 3.6 3.7	CLIENT INFORMATION GENERAL DESCRIPTION OF EUT TEST LOCATION TEST FACILITY DEVIATION FROM STANDARDS ABNORMALITIES FROM STANDARD CONDITIONS OTHER INFORMATION REQUESTED BY THE CUSTOMER	.4 .5 .6 .6 .6
4		RF EXPOSURE EVALUATION	
	4 4	RF Exposure Compliance Requirement 1.1 Limits 1.2 Test Procedure	.7 .7



Report No.: SZEM141100603202 Page: 4 of 8

3 General Information

3.1 Client Information

Applicant:	WOOX Innovations Ltd.
Address of Applicant:	5/F., Philips Electronics Building, 5 Science Park East Avenue, Hong Kong Science Park, Shatin, New Territorries, Hong Kong
Manufacturer:	WOOX Innovations Ltd.
Address of Manufacturer:	5/F., Philips Electronics Building, 5 Science Park East Avenue, Hong Kong Science Park, Shatin, New Territorries, Hong Kong
Factory:	Arts Electronics Co., Ltd.
Address of Factory:	NO. 1, SHANGXING LU, SHANGJIAO COMMUNITY, CHANGAN TOWN, DONGGUAN CITY, GUANGDONG PROVINCE, CHINA

3.2 General Description of EUT

Product Name:	Spotify Connect Multiroom Speaker
Model No.:	SW700M/zz, where zz=07, 17, 27, 37, 85 (different exported countries.) SW750M/zz, where zz=07, 17, 27, 37, 85 (different exported countries.)
Trade Mark:	PHILIPS
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(T20) : OFDM (64QAM, 16QAM, QPSK,BPSK)
Sample Type:	Fixed production
Test Power Grade:	13 provided by manufacturer
Test Software of EUT:	DOS command provided by manufacturer
Antenna Type and Gain:	Type : Integral Gain : 0dBi
AC adapter:	Model:S018KU1500100
(For SW700M/ZZ)	INPUT:AC 100-240V~50/60Hz 500mA
	OUTPUT:DC 15V=1000mA
AC adapter:	Model:S032BU1500200 INPUT:AC 100-240V~50/60Hz 900mA
(For SW750M/ZZ)	OUTPUT:DC 15V=2000mA
DC Cable:	175cm

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM141100603202 Page: 5 of 8

3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch E&E Lab

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.



Report No.: SZEM141100603202 Page: 6 of 8

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• VCCI

The 3m Semi-anechoic chamber, Full-anechoic Chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197, G-416, T-1153 and C-2383 respectively.

• FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

• Industry Canada (IC)

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.

3.5 Deviation from Standards

None.

3.6 Abnormalities from Standard Conditions

None.

3.7 Other Information Requested by the Customer

None.



Report No.: SZEM141100603202 Page: 7 of 8

4 **RF Exposure Evaluation**

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Lim	its for Occupational	/Controlled Exposu	res	
0.3–3.0 3.0–30 30–300 300–1500 1500–100,000	614 1842/f 61.4	1.63 4.89/f 0.163	*(100) *(900/f2) 1.0 f/300 5	6 6 6 6
(B) Limits	for General Populati	on/Uncontrolled Exp	oosure	
0.3–1.34 1.34–30 30–300 300–1500 1500–100,000	614 824/f 27.5	1.63 2.19/f 0.073	*(100) *(180/f ²) 0.2 f/1500 1.0	30 30 30 30 30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

F= Frequency in MHz

Friis Formula

Friis transmission formula: Pd = (Pout*G)/(4* Pi * R 2)

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



Report No.: SZEM141100603202 Page: 8 of 8

4.1.3 EUT RF Exposure Evaluation

Antenna Gain: 0dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1 in linear scale. Output Power Into Antenna & RF Exposure Evaluation Distance:

802.11b

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
Highest	2462	18.88	77.268	0.015	1.0	PASS

802.11g

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
Highest	2462	19.38	86.696	0.017	1.0	PASS

802.11n(HT20)

Channel	Frequency (MHz)	Max Conducted Peak Output	Output Power to Antenna	Power Density at R = 20 cm	Limit	Result
		Power (dBm)	(mW)	(mW/cm²)		
Highest	2462	19.18	82.794	0.016	1.0	PASS

Remark:

Refer to report No. SZEM141100603201 for EUT test Max Conducted Peak Output Power value. The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.

Model No.: SW700M/zz, SW750M/zz, where zz=07, 17, 27, 37, 85 (different exported countries.) Since the electrical circuit design, layout and RF full module (stand-alone configuration) were identical for all above models. With particular emphasis RF module had the radio frequency circuitry shielded and contain power supply regulation on the module.

Only different on the model number, external AC-DC adapter, and output of audio amplifier (non-RF circuitry, controlled by software).

AC adapter:	Model:S018KU1500100
(For SW700M/zz)	INPUT:AC 100-240V~50/60Hz 500mA OUTPUT:DC15V ==1000mA
AC adapter:	Model:S032BU1500200
(For SW750M/zz)	INPUT:AC 100-240V~50/60Hz 900mA OUTPUT:DC15V ==2000mA

So only the Model SW750M/37 was tested Max Conducted Peak Output Power and recorded in the report.