

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057

 Telephone:
 +86 (0) 755 2601 2053

 Fax:
 +86 (0) 755 2671 0594

 Email:
 ee.shenzhen@sgs.com

Report No.: SZEM150100010801 Page: 1 of 98

FCC REPORT

Application No:	SZEM1501000108CR (SGS GZ No.: GZEM1501000048CR)
Applicant:	WOOX Innovations Limited
Manufacturer:	WOOX Innovations Limited
Factory:	Foshan City Nanhai Commtech Technology Co., Ltd
Product Name:	Bluetooth Headset Trainer TH100
Model No.(EUT):	TH100
Add Model No.:	TH100/XX, TH100YY/XX (XX=00 to 99 & YY=AA to ZZ.)
Trade Mark:	Trainer
FCC ID:	2AANUTH100
Standards:	47 CFR Part 15, Subpart C (2014)
Date of Receipt:	2015-01-09
Date of Test:	2015-01-13 to 2015-01-15
Date of Issue:	2015-02-11
Test Result:	PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.



Report No.: SZEM150100010801 Page: 2 of 98

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2015-02-11		Original

Authorized for issue by:		
	Eric Fu	2015-01-15
Tested By	(Eric Fu) /Project Engineer	Date
Dress out d Dec	Medy Wen	2015-02-11
Prepared By	(Hedy Wen) /Clerk	Date
	Owen Zhou	2015-02-11
Checked By	(Owen Zhou) /Reviewer	Date





Report No.: SZEM150100010801 Page: 3 of 98

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 (2009)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2009)	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(1)	ANSI C63.10 (2009)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Carrier Frequencies Separation	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Hopping Channel Number	47 CFR Part 15, Subpart C Section 15.247 (b)	ANSI C63.10 (2009)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 15.247(b)(4)&TCB Exclusion List (7 July 2002)	ANSI C63.10 (2009)	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2009)	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2009)	PASS
Radiated Spurious emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2009)	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2009)	PASS

Remark:

Model No.: TH100, TH100/XX, TH100YY/XX (XX=00 to 99 & YY=AA to ZZ.)

Only the model TH100 was tested, since the circuit, PCB layout electrical parts and the architecture were identical for all above models. Only different on the model numbers indicate. Being sold to different countries. And XX just represent 00~99 to indicate the country version. YY (Y=A~Z) just represent the color version.



Report No.: SZEM150100010801 Page: 4 of 98

4 Contents

1	co	VER PAGE	1
2	VE	RSION	2
3	TE	ST SUMMARY	3
4	со	NTENTS	4
5			
Ŭ	5.1	CLIENT INFORMATION.	-
	5.1 5.2	GENERAL DESCRIPTION OF EUT	-
	5.3	Test Environment	
	5.4	DESCRIPTION OF SUPPORT UNITS	
	5.5	TEST LOCATION	
	5.6	TEST FACILITY	
	5.7	DEVIATION FROM STANDARDS.	
	5.8 5.9	Abnormalities from Standard Conditions Other Information Requested by the Customer	
	5.9 5.10	EQUIPMENT LIST	
c		ST RESULTS AND MEASUREMENT DATA	
6	IE		
	6.1		
	6.2	CONDUCTED EMISSIONS	
	6.3 6.4	CONDUCTED PEAK OUTPUT POWER	
	6.5	CARRIER FREQUENCIES SEPARATION	
	6.6	HOPPING CHANNEL NUMBER	
	6.7	DWELL TIME	
	6.8	BAND-EDGE FOR RF CONDUCTED EMISSIONS	
	6.9	SPURIOUS RF CONDUCTED EMISSIONS	
	6.10	OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM	
	6.11	RADIATED SPURIOUS EMISSION	
		1.2 Transmitter Emission above 1GHz	
		RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	
7	PH	OTOGRAPHS - EUT TEST SETUP	96
	7.1	CONDUCTED EMISSION	96
	7.2	RADIATED EMISSION	
	7.3	RADIATED Spurious Emission	
8	РН	OTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	98
-			



Report No.: SZEM150100010801 Page: 5 of 98

5 General Information

5.1 Client Information

Applicant:	WOOX Innovations Limited
Address of Applicant:	5/F, Philips Electronics Building, No.5 Science Park East Avenue, Hong Kong Science Park, Shatin, N.T., HONG KONG.
Manufacturer:	WOOX Innovations Limited
Address of Manufacturer:	5/F, Philips Electronics Building, No.5 Science Park East Avenue, Hong Kong Science Park, Shatin, N.T., HONG KONG.
Factory:	Foshan City Nanhai Commtech Technology Co., Ltd
Address of Factory:	Yi Zhong, DaZhen, Da Li, Nan Hai District, FoShan City, Guangdong Province, P.R.C

5.2 General Description of EUT

Product Name:	Bluetooth Headset Trainer TH100
Model No.:	TH100
Trade Mark:	Trainer
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.0
	This test report is for classic mode.
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, π/4DQPSK, 8DPSK
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	Portable production
EUT Function:	Bluetooth Headphone
Test Power Grade:	ClassII (manufacturer declare)
Test Software of EUT:	Blue test 3 (manufacturer declare)
Antenna Type:	Integral
Antenna Gain:	0dBi
Power Supply:	USB Charge DC 5V 0.5A
Battery:	DC 3.7V 190mAh Lithium ion Polymer Battery
USB Cable:	Unshielded 50cm



Report No.: SZEM150100010801 Page: 6 of 98

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2441MHz
The Highest channel	2480MHz

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM150100010801 Page: 7 of 98

5.3 Test Environment

Operating Environment:	
Temperature:	24.0 °C
Humidity:	52 % RH
Atmospheric Pressure:	1020 mbar

5.4 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.
RF test board	Supply by SGS	NONE
Adapter	Supply by SGS	R01100

5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594 No tests were sub-contracted.

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM150100010801 Page: 8 of 98

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• VCCI

The 10m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

• FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

Industry Canada (IC)

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.

5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.



Report No.: SZEM150100010801 Page: 9 of 98

5.10Equipment List

	Conducted Emission				
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	2015-06-10
2	LISN	Rohde & Schwarz	ENV216	SEL0152	2015-10-24
3	LISN	ETS-LINDGREN	3816/2	SEL0021	2015-05-16
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN- T8-02	SEL0162	2015-08-30
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN- T4-02	SEL0163	2015-08-30
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN- T2-02	SEL0164	2015-08-30
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	2015-05-16
8	Coaxial Cable	SGS	N/A	SEL0025	2015-05-29
9	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
10	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2015-10-24
11	Barometer	Chang Chun	DYM3	SEL0088	2015-05-16



Report No.: SZEM150100010801 Page: 10 of 98

	RE in Chamber				
ltem	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2015-06-10
2	EMI Test Receiver	Agilent Technologies	N9038A	SEL0312	2015-09-16
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2015-10-24
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2015-10-24
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2015-10-24
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2015-05-16
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2015-10-24
9	Coaxial cable	SGS	N/A	SEL0027	2015-05-29
10	Coaxial cable	SGS	N/A	SEL0189	2015-05-29
11	Coaxial cable	SGS	N/A	SEL0121	2015-05-29
12	Coaxial cable	SGS	N/A	SEL0178	2015-05-29
13	Band filter	Amindeon	82346	SEL0094	2015-05-16
14	Barometer	Chang Chun	DYM3	SEL0088	2015-05-16
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
16	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2015-10-24
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2015-05-16
18	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2015-10-24
19	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2015-06-04

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM150100010801 Page: 11 of 98

	RF connected test					
ltem	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)	
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24	
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2015-10-24	
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2015-10-24	
4	Coaxial cable	SGS	N/A	SEL0178	2015-05-29	
5	Coaxial cable	SGS	N/A	SEL0179	2015-05-29	
6	Barometer	ChangChun	DYM3	SEL0088	2015-05-16	
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2015-05-16	
8	Band filter	amideon	82346	SEL0094	2015-05-16	
9	POWER METER	R & S	NRVS	SEL0144	2015-10-24	
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2015-05-16	
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2015-10-24	

Note: The calibration interval is one year, all the instruments are valid.

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM150100010801 Page: 12 of 98

6 Test results and Measurement Data

6.1 Antenna Requirement

Standard requirement: 47 CFR Part 15C Section 15.203 /247(c)


15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:



The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.





Report No.: SZEM150100010801 Page: 13 of 98

Test Requirement:	47 CFR Part 15C Section 15.207			
Test Method:	ANSI C63.10: 2009			
Test Frequency Range:	150kHz to 30MHz			
Limit:		Limit (dBuV)		
	Frequency range (MHz)	Quasi-peak	Average	
	0.15-0.5	66 to 56*	56 to 46*	
	0.5-5	56	46	
	5-30	60	50	
	* Decreases with the logarithn	n of the frequency.		
Test Procedure:	0.5-5 56 46		ine 5Ω ere and ing ple not the UT of the Ns vas of	

6.2 Conducted Emissions



Report No.: SZEM150100010801 Page: 14 of 98

Test Setup:	Shielding Room Test Receiver Test Receiver Test Receiver Test Receiver Test Receiver Test Receiver Test Receiver Test Receiver Test Receiver Ground Reference Plane		
Exploratory Test Mode:	 Non-hopping transmitting mode with all kind of modulation and all kind of data type. AC charge + Transmitting mode. 		
Final Test Mode:	 Through Pre-scan, find the DH1 of data type and GFSK modulation is the worst case. AC charge + Transmitting mode. Only the worst case is recorded in the report. 		
Instruments Used:	Refer to section 5.10 for details		
Test Results:	Pass		




Report No.: SZEM150100010801 Page: 15 of 98

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live line:





Neutral line:

SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEM150100010801 Page: 16 of 98

Level (dBuV) 80 RSS-210 QP RSS-210 AV 40 WHALAMA NWAMANA MAN 0 .15 .2 .5 2 5 10 20 30 1 Frequency (MHz) Site : Shielding Room : RSS-210 AV CE NEUTRAL Condition Job.No :0108CR : AC charge +TX mode Mode Over Cable LISN Read Limit Freq Loss Factor Level Level Line Limit Remark MHz dB dB dBuV dBuV dBuV dB 1 0.16854 0.02 9.70 30.84 40.56 55.03 -14.48 Peak 27.50 2 37.31 46.80 -9.49 Peak 0.45395 0.01 9.80 0.02 9.80 27.72 37.54 46.00 -8.46 Peak 3 1.016 9.83 28.27 4 2.707 0.02 38.13 46.00 -7.87 Peak 4.746 0.01 9.89 23.05 32.95 46.00 -13.05 Peak 5 0.01 10.00 23.22 33.24 50.00 -16.76 Peak 12.318 6

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:

2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.



Report No.: SZEM150100010801 Page: 17 of 98

47 CFR Part 15C Section 15.247 (b)(1) **Test Requirement:** Test Method: ANSI C63.10:2009 Test Setup: Spectrum Analyzer E.U.T Non-Conducted Table **Ground Reference Plane** Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer. Limit: 30dBm Exploratory Test Mode: Non-hopping transmitting with all kind of modulation and all kind of data type. Final Test Mode: Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4DQPSK$ modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type. Instruments Used: Refer to section 5.10 for details Test Results: Pass

6.3 Conducted Peak Output Power




Report No.: SZEM150100010801 Page: 18 of 98

Measurement Data GFSK mode Test channel Peak Output Power (dBm) Limit (dBm) Result Lowest -2.03 30.00 Pass Middle 2.25 30.00 Pass 2.87 30.00 Highest Pass π/4DQPSK mode Test channel Peak Output Power (dBm) Limit (dBm) Result Pass Lowest -4.29 30.00 Middle -0.30 Pass 30.00 0.43 Highest 30.00 Pass 8DPSK mode Peak Output Power (dBm) Test channel Limit (dBm) Result Lowest -3.85 30.00 Pass Middle 0.46 30.00 Pass Highest 1.06 30.00 Pass





Report No.: SZEM150100010801 Page: 19 of 98






Report No.: SZEM150100010801 Page: 20 of 98









Report No.: SZEM150100010801 Page: 21 of 98







Report No.: SZEM150100010801 Page: 22 of 98




 Ref
 21.5 dBm
 *Att
 30 dB
 SWT 2.5 ms
 2.440959936 GHz

 20
 Offset
 1.1 dB
 Image: Construction of the second se





Report No.: SZEM150100010801 Page: 23 of 98





Report No.: SZEM150100010801 Page: 24 of 98

6.4 20dB Occupy Bandwidth


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)		
Test Method:	ANSI C63.10:2009		
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane		
Limit:	NA		
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type.		
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4DQPSK$ modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.		
Instruments Used:	Refer to section 5.10 for details		
Test Results:	Pass		

Measurement Data

Test channel	20dB Occupy Bandwidth (kHz)		
rest channel	GFSK	π/4DQPSK	8DPSK
Lowest	932.692	1225.962	1221.154
Middle	903.846	1225.962	1221.154
Highest	903.846	1225.962	1221.154





Report No.: SZEM150100010801 Page: 25 of 98






Report No.: SZEM150100010801 Page: 26 of 98









Report No.: SZEM150100010801 Page: 27 of 98









Report No.: SZEM150100010801 Page: 28 of 98







Report No.: SZEM150100010801 Page: 29 of 98





Report No.: SZEM150100010801 Page: 30 of 98

6.5 Carrier Frequencies Separation

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)		
Test Method:	ANSI C63.10:2009		
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table		
	Ground Reference Plane		
Limit:	2/3 of the 20dB bandwidth.		
	Remark: the transmission power is less than 0.125W.		
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.		
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4DQPSK$ modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.		
Instruments Used:	Refer to section 5.10 for details		
Test Results:	Pass		



Report No.: SZEM150100010801 Page: 31 of 98

Measurement Data


	GFSK mode				
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result		
Lowest	1002	≥622	Pass		
Middle	1002	≥622	Pass		
Highest	1002	≥622	Pass		
	π/4DQPSK m	node			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result		
Lowest	1002	≥817	Pass		
Middle	1002	≥817	Pass		
Highest	1002	≥817	Pass		
	8DPSK mode				
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result		
Lowest	1002	≥814	Pass		
Middle	1002	≥814	Pass		
Highest	1002	≥814	Pass		

Note: According to section 6.4,

Mode	20dB bandwidth (kHz)	Limit (kHz)
NIOUE	(worse case)	(Carrier Frequencies Separation)
GFSK	932.692	622
π/4DQPSK	1225.962	817
8DPSK	1221.154	814





Report No.: SZEM150100010801 Page: 32 of 98






Report No.: SZEM150100010801 Page: 33 of 98








Report No.: SZEM150100010801 Page: 34 of 98




Center 2.4795 GHz 250 kHz/ Span 2.5 MHz




Report No.: SZEM150100010801 Page: 35 of 98







Report No.: SZEM150100010801 Page: 36 of 98





Report No.: SZEM150100010801 Page: 37 of 98

6.6 Hopping Channel Number

Test Requirement:	47 CFR Part 15C Section 15.247 (b)
Test Method:	ANSI C63.10:2009
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane
Limit:	At least 15 channels.
Test Mode:	Hopping transmitting with all kind of modulation.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass


Measurement Data

Test mode	Hopping channel numbers	Limit	Results
GFSK	79	15	Pass
π/4DQPSK	79	15	Pass
8DPSK	79	15	Pass

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM150100010801 Page: 38 of 98





Report No.: SZEM150100010801 Page: 39 of 98





Report No.: SZEM150100010801 Page: 40 of 98

6.7 Dwell Time

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)	
Test Method:	ANSI C63.10:2009	
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table	
	Ground Reference Plane	
Instruments Used:	Refer to section 5.10 for details.	
Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.	
Limit:	0.4 Second	
Test Results:	Pass	



Report No.: SZEM150100010801 41 of 98 Page:

Mode	Packet	Dwell time (second)	Limit (second)
GFSK	DH1	0.13	≤0.4
	DH3	0.27	≤0.4
	DH5	0.32	≤0.4
π/4DQPSK	2-DH1	0.13	≤0.4
	2-DH3	0.27	≤0.4
	2-DH5	0.32	≤0.4
8DPSK	3-DH1	0.13	≤0.4
	3-DH3	0.26	≤0.4
	3-DH5	0.32	≤0.4

Measurement Data

Remark:

The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s


On (ms)*total number=dwell time (ms)

The middle channel (2441MHz), as below:

DH1 time slot=0.393(ms)*total number=125.76(ms) DH3 time slot=1.659(ms)* total number =265.44(ms) DH5 time slot=2.897(ms)* total number =318.67(ms) 2-DH1 time slot=0.409(ms)*total number=130.88(ms) 2-DH3 time slot=1.667(ms)* total number =266.72(ms) 2-DH5 time slot=2.929(ms)* total number =322.19(ms) 3-DH1 time slot=0.409(ms)*total number=130.88(ms) 3-DH3 time slot=1.651(ms)* total number =264.16(ms) 3-DH5 time slot=2.913(ms)* total number =320.43(ms)




Report No.: SZEM150100010801 Page: 42 of 98






Report No.: SZEM150100010801 Page: 43 of 98






Report No.: SZEM150100010801 Page: 44 of 98






Report No.: SZEM150100010801 Page: 45 of 98






Report No.: SZEM150100010801 Page: 46 of 98






Report No.: SZEM150100010801 Page: 47 of 98






Report No.: SZEM150100010801 Page: 48 of 98






Report No.: SZEM150100010801 Page: 49 of 98





Report No.: SZEM150100010801 Page: 50 of 98





Report No.: SZEM150100010801 Page: 51 of 98


6.8 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)	
Test Method:	ANSI C63.10:2009	
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane	
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.	
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.	
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type.	
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4DQPSK$ modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.	
Instruments Used:	Refer to section 5.10 for details	
Test Results:	Pass	

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM150100010801 Page: 52 of 98






Report No.: SZEM150100010801 Page: 53 of 98






Report No.: SZEM150100010801 Page: 54 of 98






Report No.: SZEM150100010801 Page: 55 of 98






Report No.: SZEM150100010801 Page: 56 of 98





Report No.: SZEM150100010801 Page: 57 of 98






Report No.: SZEM150100010801 Page: 58 of 98

6.9 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)	
Test Method:	ANSI C63.10:2009	
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane	
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.	
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.	
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type.	
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4DQPSK$ modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.	
Instruments Used:	Refer to section 5.10 for details	
Test Results:	Pass	




Report No.: SZEM150100010801 Page: 59 of 98






Report No.: SZEM150100010801 Page: 60 of 98






Report No.: SZEM150100010801 Page: 61 of 98






Report No.: SZEM150100010801 Page: 62 of 98








Report No.: SZEM150100010801 Page: 63 of 98






Report No.: SZEM150100010801 Page: 64 of 98






Report No.: SZEM150100010801 Page: 65 of 98






Report No.: SZEM150100010801 Page: 66 of 98






Report No.: SZEM150100010801 Page: 67 of 98






Report No.: SZEM150100010801 Page: 68 of 98






Report No.: SZEM150100010801 Page: 69 of 98






Report No.: SZEM150100010801 Page: 70 of 98






Report No.: SZEM150100010801 Page: 71 of 98






Report No.: SZEM150100010801 Page: 72 of 98








Report No.: SZEM150100010801 Page: 73 of 98






Report No.: SZEM150100010801 Page: 74 of 98






Report No.: SZEM150100010801 Page: 75 of 98





Report No.: SZEM150100010801 Page: 76 of 98



Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.



Report No.: SZEM150100010801 Page: 77 of 98

6.10Other requirements Frequency Hopping Spread Spectrum System

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1), (h) requirement:						
rate from a Pseudorandom of on the average by each trans	nnel frequencies that are selected at the system hopping ordered list of hopping frequencies. Each frequency must be used equally smitter. The system receivers shall have input bandwidths that match the s of their corresponding transmitters and shall shift frequencies in asmitted signals.						
channels during each transn receiver, must be designed t transmitter be presented with employing short transmission	spectrum systems are not required to employ all available hopping nission. However, the system, consisting of both the transmitter and the to comply with all of the regulations in this section should the h a continuous data (or information) stream. In addition, a system n bursts must comply with the definition of a frequency hopping system missions over the minimum number of hopping channels specified in						
the system to recognize othe independently chooses and The coordination of frequence	The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is						
Compliance for section 15.	.247(a)(1)						
stage shift register whose 5tl outputs are added in a modu	alo-two addition stage. And the result is fed back to the input of the first with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized ages: 9 sequence: $2^9 - 1 = 511$ bits						
Linear Feedback S	hift Register for Generation of the PRBS sequence						
An example of Pseudorando 20 62 46 77	m Frequency Hopping Sequence as follow: 7 64 8 73 16 75 1						
	y on the average by each transmitter.						
bandwidths that match the	e Specification, Bluetooth receivers are designed to have input and IF hopping channel bandwidths of any Bluetooth transmitters and shift on with the transmitted signals.						



Report No.: SZEM150100010801 Page: 78 of 98

Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM150100010801 Page: 79 of 98

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205						
Test Method:	ANSI C63.10: 2009						
Test Site:	Measurement Distance	: 3n	n (Semi-Anech	oic Cham	ber)		
Receiver Setup:	Frequency		Detector	RBW	VBW	Remark	
	0.009MHz-0.090MH	z	Peak	10kHz	z 30kHz	Peak	
	0.009MHz-0.090MH	z	Average	10kHz	z 30kHz	Average	
	0.090MHz-0.110MH	z	Quasi-peak	10kHz	z 30kHz	Quasi-peak	
	0.110MHz-0.490MH	z	Peak	10kHz	z 30kHz	Peak	
	0.110MHz-0.490MH	z	Average	10kHz	z 30kHz	Average	
	0.490MHz -30MHz		Quasi-peak	10kHz	z 30kHz	Quasi-peak	
	30MHz-1GHz		Quasi-peak	100 kH	lz 300kHz	Quasi-peak	
	Above 1GHz		Peak	1MHz	z 3MHz	Peak	
	Above IGH2		Peak	1MHz	z 10Hz	Average	
Limit:	Frequency		eld strength crovolt/meter)	Limit (dBuV/m)	Remark	Measureme distance (m	
	0.009MHz-0.490MHz	2	400/F(kHz)	-	-	300	
	0.490MHz-1.705MHz	24	1000/F(kHz)	-	-	30	
	1.705MHz-30MHz		30	-	-	30	
	30MHz-88MHz		100	40.0	Quasi-peak	3	
	88MHz-216MHz		150	43.5	Quasi-peak	3	
	216MHz-960MHz		200	46.0	Quasi-peak	3	
	960MHz-1GHz		500	54.0	Quasi-peak	3	
	Above 1GHz 500 54.0 Average 3				3		
	Note: 15.35(b), Unless emissions is 200 applicable to the peak emission le	dB a equ	bove the max	test. This	mitted average	ge emission li	mit

6.11 Radiated Spurious Emission



Report No.: SZEM150100010801 Page: 80 of 98





Report No.: SZEM150100010801 Page: 81 of 98

	 method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel (2402MHz),the middle channel (2441MHz),the Highest channel (2480MHz) h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. 			
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type. Transmitting mode.			
Final Test Mode:	Through Pre-scan, find the DH1 of data type and GFSK modulation is the worst case. Transmitting mode. For below 1GHz part, through pre-scan, the worst case is the lowest channel. Only the worst case is recorded in the report.			
Instruments Used:	Refer to section 5.10 for details			
Test Results:	Pass			


[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM150100010801 Page: 82 of 98

6.11.1 Radiated Emission below 1GHz

30MHz~1GHz (QP)		
Test mode:	Transmitting	Vertical



Condition: 47 CFR PART 15.209 3m 3142C Vertical Job No. : 0108CR Test mode: TX mode


	Freq			Preamp Factor				Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	33.92	0.60	16.51	27.34	30.13	19.90	40.00	-20.10
2	44.59	0.70	11.08	27.31	32.89	17.36	40.00	-22.64
3	56.20	0.80	7.77	27.27	37.31	18.61	40.00	-21.39
4	67.91	0.80	6.96	27.25	32.76	13.27	40.00	-26.73
5	149.49	1.32	8.95	26.91	24.36	7.72	43.50	-35.78
6	857.02	3.44	22.57	26.99	22.30	21.32	46.00	-24.68





Report No.: SZEM150100010801 Page: 83 of 98

Test mode:	Transmitting	Horizontal
------------	--------------	------------



Condition: 47 CFR PART 15.209 3m 3142C Horizontal Job No. : 0108CR Test mode: TX mode

	Freq			Preamp Factor				Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 2 3 4 5 6	30.00 423.54 530.10 670.49 782.35 909.67	2.30 2.63 2.85 3.15	16.39 18.58 21.26 22.03	27.36 27.27 27.65 27.45 27.32 26.71	24.69 22.91 22.54 26.60	16.11 16.47 19.20 24.46	46.00 46.00 46.00 46.00	-29.89 -29.53 -26.80 -21.54



Report No.: SZEM150100010801 Page: 84 of 98

Test mode:		GFSK(DH1)	Test	channel:	Lowest	Rema	rk:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3684.279	6.86	33.06	38.82	47.95	49.05	74	-24.95	Vertical
4804.000	6.42	34.70	39.24	48.72	50.60	74	-23.40	Vertical
5913.378	7.95	36.13	39.19	47.44	52.33	74	-21.67	Vertical
7206.000	8.92	35.63	39.07	44.63	50.11	74	-23.89	Vertical
9608.000	9.99	37.33	37.93	42.38	51.77	74	-22.23	Vertical
11455.380	10.38	38.19	38.45	43.30	53.42	74	-20.58	Vertical
3548.251	6.94	32.94	38.76	47.75	48.87	74	-25.13	Horizontal
4804.000	6.42	34.70	39.24	48.65	50.53	74	-23.47	Horizontal
5896.291	7.92	36.10	39.19	47.55	52.38	74	-21.62	Horizontal
7206.000	8.92	35.63	39.07	45.08	50.56	74	-23.44	Horizontal
9608.000	9.99	37.33	37.93	43.05	52.44	74	-21.56	Horizontal
11405.760	10.37	38.15	38.42	43.19	53.29	74	-20.71	Horizontal

6.11.2 Transmitter Emission above 1GHz

Test mode:		GFSK(DH1)	Test	channel:	Middle	Rema	rk:	Peak
Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Over limit (dB)	Polarization
3620.861	6.90	33.02	38.79	47.35	48.48	74	-25.52	Vertical
4882.000	6.59	34.78	39.26	48.07	50.18	74	-23.82	Vertical
6025.661	8.07	36.27	39.18	47.60	52.76	74	-21.24	Vertical
7323.000	9.08	35.50	39.06	44.79	50.31	74	-23.69	Vertical
9764.000	9.90	37.81	37.84	42.42	52.29	74	-21.71	Vertical
11438.810	10.38	38.18	38.44	43.08	53.20	74	-20.80	Vertical
3652.432	6.88	33.04	38.81	47.58	48.69	74	-25.31	Horizontal
4882.000	6.59	34.78	39.26	47.60	49.71	74	-24.29	Horizontal
5711.555	7.63	35.70	39.22	49.04	53.15	74	-20.85	Horizontal
7323.000	9.08	35.50	39.06	46.63	52.15	74	-21.85	Horizontal
9764.000	9.90	37.81	37.84	42.65	52.52	74	-21.48	Horizontal
11389.270	10.37	38.15	38.41	43.05	53.16	74	-20.84	Horizontal



Report No.: SZEM150100010801 Page: 85 of 98

Test mode:		GFSK(DH1)	Test	channel:	Highest	Rema	rk:	Peak
Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Over limit (dB)	Polarization
3310.181	7.34	32.55	38.65	47.49	48.73	74	-25.27	Vertical
4960.000	6.76	34.86	39.29	48.01	50.34	74	-23.66	Vertical
6104.642	8.06	36.18	39.17	50.00	52.80	74	-21.20	Vertical
7440.000	9.23	35.43	39.05	44.87	50.48	74	-23.52	Vertical
9920.000	9.81	38.27	37.75	42.19	52.52	74	-21.48	Vertical
11389.270	10.37	38.15	38.41	43.05	53.16	74	-20.84	Vertical
3427.149	7.11	32.81	38.71	47.24	48.45	74	-25.55	Horizontal
4960.000	6.76	34.86	39.29	48.64	50.97	74	-23.03	Horizontal
5964.939	8.03	36.23	39.19	48.22	53.29	74	-20.71	Horizontal
7440.000	9.23	35.43	39.05	46.76	52.37	74	-21.63	Horizontal
9920.000	9.81	38.27	37.75	42.19	52.52	74	-21.48	Horizontal
11455.380	10.38	38.19	38.45	43.30	53.42	74	-20.58	Horizontal

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

- 2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM150100010801 Page: 86 of 98

6.12Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205					
Test Method:	ANSI C63.10: 2009					
Test Site:	Measurement Distance: 3	m (Semi-Anechoic Chambe	r)			
Limit:	Frequency	Limit (dBuV/m@3m)	Remark			
	30MHz-88MHz	40.0	Quasi-peak Value			
	88MHz-216MHz	43.5	Quasi-peak Value			
	216MHz-960MHz	46.0	Quasi-peak Value			
	960MHz-1GHz	54.0	Quasi-peak Value			
	Above 1GHz	54.0	Average Value			
	Above IGH2	74.0	Peak Value			
Test Setup:						
AE EUT Ground Reference Pla Test Receiver		AE EUT (Turntable) Ground Reference Pic Test Receiver	Hom Anlenna Tower			
Figure 1. 30MHz	to 1GHz	Figure 2. Above	1 GHz			



Report No.: SZEM150100010801 Page: 87 of 98

Test Procedure:	 a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel. g. Test the EUT in the lowest channel , the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. 			
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type. Transmitting mode.			
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation is the worst case. Transmitting mode. Only the worst case is recorded in the report.			
Instruments Used:	Refer to section 5.10 for details			
Test Results:	Pass			



Test plot as follows: Worse case mode:

GFSK (DH5)

SGS-CSTC Standards Technical Services Ltd.

Remark:

Lowest

Report No.: SZEM150100010801 Page: 88 of 98

Peak

Vertical


	.evel (dBuV/									
110										
90										
70									FCC PART C	247 <u></u> řk
50	montan	ununu	Humm	enanna	www.ww	umunum	den an	Part and a start of the	me Annon	-
30										
10										
0	310 23	20		-	2350					2
2	510 25	20				ncy (MHz)				2
ite onditi	: cha on: FCC		247 F	°K 3mr ∿	/ertica	1				
ob No:						-				
	- 240	2 Band	edge E				Limit	0∨er		
lode:	: 240	Cable	Ant	D						

Test channel:



Report No.: SZEM150100010801 Page: 89 of 98


Worse case mode: GFSK (DH) Test channel:	Lowest	Remark:	Peak	Horizontal
---------------------------	-----------------	--------	---------	------	------------





Report No.: SZEM150100010801 Page: 90 of 98


Worse case mode: 0	GFSK (DH5)	Test channel:	Lowest	Remark:	Average	Vertical
--------------------	------------	---------------	--------	---------	---------	----------





Report No.: SZEM150100010801 Page: 91 of 98


Worse case mode: GFSK (DF	i) Test channel:	Lowest	Remark:	Average	Horizontal
---------------------------	------------------	--------	---------	---------	------------





Report No.: SZEM150100010801 Page: 92 of 98

Worse case mode:	GFSK (DH5)	Test channel:	Highest	Remark:	Peak	Vertical
------------------	------------	---------------	---------	---------	------	----------




Site Condit	: cha ion: FCC:		C 247	PK 3m \	/ertica	1		
Job Na	: : 010	8CR						
Mode:	: 248	0 Band	edge	вт				
		Cable	Ant	Preamp	Read		Limit	0∨er
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 2	2479.86 2483.50			38.47 38.47	84.14 48.54		74.00 74.00	9.13 -26.46





Report No.: SZEM150100010801 Page: 93 of 98

Worse case mode: GFSK (DH5)	Test channel:	Highest	Remark:	Peak	Horizontal
-----------------------------	---------------	---------	---------	------	------------




Job Na	ion: FCC : : 010 : : 248	8CR			Horizor	ıtal		
		Cable	Ant	Preamp	Read Level	Level	Limit Line	0∨er Limit
-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 2	2479.86 2483.50				91.76 53.77			



Report No.: SZEM150100010801 Page: 94 of 98

Worse case mode: GFSK (DH5)	Test channel:	Highest	Remark:	Average	Vertical
-----------------------------	---------------	---------	---------	---------	----------




Site	: 0	namber						
Conditi	ion: F	CC PAR	TC 247	AV 3m	Vertica	al		
Job No	: : 0	0108CR						
Mode:	: 2	480 Bai	nd edge	BT				
		Cab]	.e An	t Preamp	Read		Limit	0∨er
	Fr	eq Los	s Facto	r Factor	Level	Level	Line	Limit
_								
	М	Hz o	lB dB∕	m dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2480.	06 5.6	<i>3</i> 2.4	4 38.47	73.31	72.30	54.00	18.30
2	2483.	50 5.0	93 32.4	4 38.47	37.06	36.06	54.00	-17.94



Report No.: SZEM150100010801 Page: 95 of 98

Worse case mode: GFSK (DH5	Test channel:	Highest	Remark:	Average	Horizontal
----------------------------	---------------	---------	---------	---------	------------



Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor



Report No.: SZEM150100010801 Page: 96 of 98

7 Photographs - EUT Test Setup

Test model No.: TH100

7.1 Conducted Emission




7.2 Radiated Emission





Report No.: SZEM150100010801 Page: 97 of 98

7.3 Radiated Spurious Emission





Report No.: SZEM150100010801 Page: 98 of 98

8 Photographs - EUT Constructional Details

Test model No.: TH100

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1501000108CR