

TEST REPORT

Report No.: SRTC2024-9003(F)-0022
Product Name: Cellular Router
Model Name: CR202-NAC6
Applicant: Beijing InHand Networks Technology Co., Ltd.
Manufacturer: Beijing InHand Networks Technology Co., Ltd.
Specification: FCC Part15B (Certification)
(2023 edition)
ANSI C63.4-2014
FCC ID 2AANY-CR202NAC6

The State Radio_monitoring_center Testing Center (SRTC)
15th Building, No.30 Shixing Street, Shijingshan District,
Beijing, China

Tel: 86-10-57996183 Fax: 86-10-57996388

CONTENTS

1. General information	3
1.1 Notes of the test report.....	3
1.2 Information about the testing laboratory	3
1.3 Applicant's details.....	3
1.4 Manufacturer's details	3
1.5 Application details.....	3
1.6 Reference specification	4
1.7 Information of EUT	4
1.7.1 General information	4
1.7.2 EUT details.....	4
1.7.3 Auxiliary equipment details.....	4
1.7.4 Test mode.....	5
2. Test information	6
2.1 Summary of the test results	6
2.2 Test result	7
2.2.1 Conducted Emissions-FCC Part15.107.....	7
2.2.2 Radiated Emissions-FCC Part15.109.....	11
2.3. List of test equipments	15

1. General information

1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio_monitoring_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested.

1.2 Information about the testing laboratory

Company: The State Radio_monitoring_center Testing Center (SRTC)
Test Site 1: 15th Building, No.30 Shixing Street, Shijingshan District
Test Site 2: No.80, Zhaojiachang, Beizang, Daxing District
City: Beijing
Country or Region: P.R.China
Contacted person: Liu Jia
Tel: +86 10 57996183
Fax: +86 10 57996388
Email: liujiaf@srtc.org.cn
Designation Number: CN1267
Registration number: 239125

1.3 Applicant's details

Company: Beijing InHand Networks Technology Co., Ltd.
Address: Room 501, floor 5, building 3, yard 18, ziyue road, chaoyang district, Beijing
City: Beijing
Country or Region: China
Contacted person: Gujichi
Tel: 15281366255
Email: gujc@inhand.com.cn

1.4 Manufacturer's details

Company: Beijing InHand Networks Technology Co., Ltd.
Address: Room 501, floor 5, building 3, yard 18, ziyue road, chaoyang district, Beijing
City: Beijing
Country or Region: China
Contacted person: Gujichi
Tel: 15281366255
Email: gujc@inhand.com.cn

1.5 Application details

Date of reception of test sample: 24th May 2024

Date of test: 24th May 2024 to 7th June 2024

1.6 Reference specification

FCC Part 15B, 2023 (Certification)
ANSI C63.4-2014

1.7 Information of EUT

1.7.1 General information

Name of EUT	Cellular Router
Model Name of EUT	CR202-NAC6
FCC ID	2AANY-CR202NAC6
Frequency Range	LTE: FDD 2/ FDD 4/ FDD 5/ FDD 7/ FDD 12/ FDD 13/FDD 14/ FDD 25/FDD 26 FDD 30/ FDD 66/ FDD 71 /TDD 41/ TDD 48 WiFi: 2.412GHz~2.462 GHz
Input Rated Voltage	5VDC
Extreme Temperature	Lowest: -10°C Highest: +50°C
HW Version	V1.6
SW Version	V1.0

1.7.2 EUT details

No.	Model Name	IMEI
EUT1	CR202-NAC6	/

Note: Test model No. CR202-NAC6 series model No. CR212-NAC6, CR252-NAC6, CR292-NAC6. These models are the same in these: appearance, PCB layout and basic software function; The only difference is that the products are used in different markets.

1.7.3 Auxiliary equipment details

AE (Auxiliary Equipment) 1#: Adapter

Equipment	Adapter Power
Manufacturer	Shenzhen Fushigang Technology Co., Ltd
Model Number	AS1201A-0502000USL


1.7.4 Test mode

Mode No.	Description of test mode
Mode 1:	Charging mode

2. Test information

2.1 Summary of the test results

No.	Test case	FCC reference	Verdict
1	Conducted emissions	15.107	Pass
2	Radiated emissions	15.109	Pass

Approved By: Mr.LiuWei Director of the test department 	Checked By: Mr.Guoyu Vice director of the test department 
Tested By: Mr.Wu Chengwang 	Issued date: 2024.06.07

2.2 Test result

2.2.1 Conducted Emissions-FCC Part15.107

Ambient condition:

Temperature	Relative humidity	Pressure
25.2°C	38.1%	100.8kPa

Test Setup with charger:




Figure 1

Test Procedure:

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The EUT is connected with LISN via the charger. The LISN is connected to the reference ground.

The test set-up and the test methods are performed according to ANSI C63.4:2014.

Then start the test software EMC32. Sweep the whole frequency band through the range from 150 KHz to 30 MHz with RBW 9kHz, VBW 30kHz. The measurement should be done for both L line and N line. During pre-test, the receiver uses both peak detector and average detector. And the final test, the receiver uses both average detector and Quasi-peak detector.

The data of cable loss has been calibrated in full testing frequency range before the testing.

A “reference path loss” Corr.(dB) is established and the $L_{\text{cable}} + \text{ATT} + \text{VDF}$ is the attenuation of “reference path loss”, and including the cable loss, the attenuation of the attenuator, the voltage division factor of AMN.

The measurement results are obtained as described below:

$$P_{\text{result}} = P_{\text{mea}} + \text{Corr. (dB)}$$

Sample calculation: $(60.84 \text{ dB}\mu\text{V}) = (31.14 \text{ dB}\mu\text{V}) + (29.7 \text{ dB})$, the corresponding frequency is 0.150000MHz.

Limit:

Frequency of Emission(MHz)	Limits(dBμV)	
	Quasi-peak	Average
0.15~0.5	66 to 56*	56 to 46*
0.5~5	56	46
5~30	60	50

Note: * Decreases with the logarithm of the frequency


Uncertainty

Quasi-peak: 3.92dB

Average: 3.92dB


Test result:

Noise Level of the Measuring Instrument



Pic1. Conducted emission L and N Line

EUT1 + AE#1: Adapter:




Comment

Pic2. Conducted emission L&N Line 120V AC

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)	Pmea QuasiPeak (dBμV)	Pmea Average (dBμV)
0.150000	60.84	---	66.00	5.16	N	29.7	31.14	---
0.179850	---	36.57	54.49	17.92	L1	29.8	---	6.77
0.179850	54.90	---	64.49	9.59	L1	29.8	25.1	---
0.218229	---	35.16	52.89	17.73	L1	29.8	---	5.36
0.218229	51.81	---	62.89	11.08	L1	29.8	22.01	---
0.256607	50.54	---	61.54	11.00	L1	29.8	20.74	---
0.256607	---	33.53	51.54	18.01	L1	29.8	---	3.73
0.294986	49.12	---	60.38	11.27	N	29.7	19.42	---
0.329100	46.15	---	59.47	13.32	L1	29.8	16.35	---
0.665979	---	28.16	46.00	17.84	L1	29.8	---	-1.64
18.742286	---	28.30	50.00	21.70	N	30.1	---	-1.8
20.183614	---	30.17	50.00	19.83	L1	30.1	---	0.07

EUT1 + AE#1: Adapter:



Pic3. Conducted emission L&N Line 240V AC

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)	Pmea QuasiPeak (dBμV)	Pmea Average (dBμV)
0.154264	56.78	---	65.77	8.99	N	29.7	27.08	---
0.196907	---	33.00	53.74	20.74	N	29.7	---	3.3
0.235286	---	28.54	52.26	23.72	N	29.7	---	-1.16
0.363214	42.14	---	58.66	16.52	N	29.7	12.44	---
0.674507	---	26.36	46.00	19.64	N	29.7	---	-3.34
0.704357	33.40	---	56.00	22.60	N	29.7	3.7	---
1.028443	33.27	---	56.00	22.73	N	29.7	3.57	---
1.425021	32.28	---	56.00	23.72	N	29.7	2.58	---
2.674457	29.53	---	56.00	26.47	N	29.7	-0.17	---
3.693621	---	22.55	46.00	23.45	N	29.8	---	-7.25
18.742286	---	26.05	50.00	23.95	L1	30.0	---	-3.95
20.187879	---	28.47	50.00	21.53	N	30.1	---	-1.63

2.2.2 Radiated Emissions-FCC Part15.109

Ambient condition:

Temperature	Relative humidity	Pressure
25.3°C	37.2%	100.8kPa

Test Setup:




Figure 2

Test Procedure:

EUT+Charger:

The EUT should be placed on a non-metallic table 80cm above the ground plane. The receive antennas shall be moved from 1 to 4 meters. The distance between EUT and receive antenna should be 3 meters.

The EUT should work in idle mode. The test set-up and the test methods are performed according to ANSI C63.4:2014.

Then start the test software EMC32. Sweep the whole frequency band through the range from 30MHz to 1GHz, using receive log period antenna VULB 9163.

During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with orthogonal polarization of the test antenna. The EUT is laid in two modes as follow: 1. put the EUT in horizontal direction; 2. put the EUT in vertical direction.

The data of cable loss and antenna factor have been calibrated in full testing frequency range before the testing. All test results are performed with max hold at the horizontal and vertical polarity.

RBW=120kHz, VBW=300kHz, when the test frequency: 30MHz<f<1GHz

RBW=1MHz, VBW=3MHz, when the test frequency: f>1GHz

A “reference path loss” is established and the A_{Rpl} is the attenuation of “reference path loss”,

and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{mea}} + A_{\text{Rpl}}$$

Sample calculation: $(28.37 \text{ dB}\mu\text{V/m}) = (47.57 \text{ dB}\mu\text{V}) + (-19.2\text{dB/m})$, the corresponding frequency is 39.806000MHz.

Limit:

Frequency of Emission(MHz)	Limits	
	Detector	Unit (dB μ V/m)
30~88	Quasi-peak	40
88~216	Quasi-peak	43.5
216~960	Quasi-peak	46
960~1000	Quasi-peak	54
1000~5th harmonic of the highest frequency or 40GHz, whichever is lower	Average Peak	54 74

Uncertainty

30MHz~1000MHz 4.73dB


1000MHz~26000MHz 4.58dB

Test result:

EUT1 + AE#1: Adapter:


Frequency (MHz)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	ARpl (dB/m)	Pmea (dB μ V)	Polarity
39.806000	28.37	40.00	11.63	-19.2	47.57	V
83.612500	29.49	40.00	10.51	-21.4	50.89	V
132.574500	32.77	43.50	10.73	-22.0	54.77	V
195.995500	21.72	43.50	21.78	-20.2	41.92	V
436.732500	22.40	46.00	23.60	-13.5	35.90	V
584.906000	14.07	46.00	31.93	-10.4	24.47	V

EUT1 + AE#1: Adapter: refer to Pic4 to Pic6




Pic4. Radiated emission (30MHz – 1GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical



Pic5. Radiated emission (1GHz –6GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical



Pic6. Radiated emission (6GHz –18GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical

2.3. List of test equipments

No.	Name/Model	Manufacturer	S/N	Calibration Due Date	Calibration Date
1	23.18m×16.88m×9.60m Semi-Anechoic Chamber	FRANKONIA	-----	2028.09.05	2023.09.05
2	ESW EMI test receiver	R&S	101574	2025.03.06	2024.03.06
3	ESR3 EMI test receiver	R&S	102361	2025.03.06	2024.03.06
4	9.080m×5.255m×3.525m Shielding room	FRANKONIA	-----	2027.03.25	2022.03.25
5	VULB 9163 Ultra log test antenna	schwarzbeck	727	2025.05.28	2023.05.28
6	HF 907 Double-Ridged Waveguide Horn Antenna	R&S	100512	2025.07.20	2023.07.20
7	SAS-574 Horn Antenna	schwarzbeck	535	2025.05.12	2023.05.12
8	ENV216 AMN	R&S	101881	2024.06.21	2023.06.21
9	EMC32EMI test software	R&S	V10	-----	-----

-----The end-----