

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	HOVER-1 - SELF-BALANCING SCOOTER
Model Name	DSA-200
Series Model	H1-200-21B, H1-200-BLK-21B, H1-200-BLU-21B, H1-200-PNK-21B, H1-200-CAMO-21B, H1-200-GLX-21B, H1-200-GMT-21B, H1-200-IRD-21B, H1-200-XXX-21B, DSA-200-21B, DSA-200-BLK-21B, DSA-200-BLU-21B, DSA-200-PNK-21B, DSA-200-CAMO-21B, DSA-200-GLX-21B, DSA-200-GMT-21B, DSA-200-IRD-21B, DSA-200-XXX-21B, DSA-200-BF21, DSA-200-BF21-XXX, DSA-AH-200-21B, DSA-AH-200-BLK-21B, DSA-AH-200-BLU-21B, DSA-AH-200-PNK-21B, DSA-AH-200-CAMO-21B, DSA-AH-200-GLX-21B, DSA-AH-200-GMT-21B, DSA-AH-200-IRD-21B, DSA-AH-200-XXX-21B, DSA-AH-200-BF21-21B
FCC ID	2AANZ200B

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

$$P_t = -1.111 \text{ dBm} = 0.77 \text{ mW}$$

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation $\text{SAR} = (0.77 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.441 \text{ GHz}}] = 0.24 < 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

4. CONCLUSION

The SAR evaluation is not required.