

# RF EXPOSURE EVALUATION

## 1. PRODUCT INFORMATION

Product Description	Stereo Wireless Headphones
Test Model	DG-985BT-ASST
Series Model	DG-985BT-XXX, DG-985BT
FCC ID	2AANZ985BTL

## 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR.

Where f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

## 3. CALCULATION

P<sub>t</sub>=1.010dBm=1.26mW

The value of the Maximum output power  $P_t$  is referred to the test report of the CFR47  $\S15.247$ .

The result for RF exposure evaluation SAR= $(1.26 \text{mW} / 5 \text{mm}) \cdot [\sqrt{2.402 \text{GHz}}] = 0.39 < 3.0 \text{ for } 1-\text{g SAR}$  and  $\leq 7.5$  for 10-g extremity SAR.

## 4. CONCLUSION

The SAR evaluation is not required.