

# **FCC Test Report**

Report No.: AGC01559221103FE10

FCC ID	:	2AANZDFNL
APPLICATION PURPOSE		Original Equipment
PRODUCT DESIGNATION	:	3-IN-1 Fan Lamp Led Light
BRAND NAME	:	SARINA
MODEL NAME	:	SA-DFNL-BLK, SA-DFNL, SA-DFNL-XXX
APPLICANT	:	DGL Group LTD.
DATE OF ISSUE	:	Nov. 21, 2022
STANDARD(S)	:	FCC Part 15 Subpart C
<b>REPORT VERSION</b>	:	V 1.0
		opa Compliance (Shendhen)

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance (Shenzhen) Co., Ltd





## **REPORT REVISE RECORD**

Report Version	Revise Time	Issued Date Valid Version Note		Notes
V1.0	/	Nov. 21, 2022	Valid	Initial Release



# **TABLE OF CONTENTS**

1. GENERAL INFORMATION	5
2. PRODUCT INFORMATION	6
2.1 PRODUCT TECHNICAL DESCRIPTION	6
2.2 TEST FREQUENCY LIST	6
2.3 RELATED SUBMITTAL(S) / GRANT (S)	7
2.4 TEST METHODOLOGY	7
2.5 SPECIAL ACCESSORIES	7
2.6 EQUIPMENT MODIFICATIONS	7
2.7 ANTENNA REQUIREMENT	7
3. TEST ENVIRONMENT	8
3.1 ADDRESS OF THE TEST LABORATORY	8
3.2 TEST FACILITY	8
3.3 ENVIRONMENTAL CONDITIONS	9
3.4 MEASUREMENT UNCERTAINTY	9
3.5 LIST OF EQUIPMENTS USED	10
4.SYSTEM TEST CONFIGURATION	11
4.1 EUT CONFIGURATION	11
4.2 EUT EXERCISE	11
4.3 CONFIGURATION OF TESTED SYSTEM	11
4.4 EQUIPMENT USED IN TESTED SYSTEM	11
4.5 SUMMARY OF TEST RESULTS	12
5. DESCRIPTION OF TEST MODES	13
6. FIELD STRENGTH OF FUNDAMENTAL	14
6.1 PROVISIONS APPLICABLE	14
6.3 FIELD STRENGTH CALCULATION	16
6.4 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	
6.5 MEASUREMENT RESULTS	18
7. 20 dB BANDWIDTH	24
7.1 PROVISIONS APPLICABLE	24
7.2 MEASUREMENT PROCEDURE	24
7.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	24
7.4 MEASUREMENT RESULTS	25
8. AC POWER LINE CONDUCTED EMISSION TEST	26
8.1 LIMITS OF LINE CONDUCTED EMISSION TEST	26
8.2 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	26



AP	PENDIX B: PHOTOGRAPHS OF TEST EUT	. 30
AP	PENDIX A: PHOTOGRAPHS OF TEST SETUP	. 30
	8.5 MEASUREMENT RESULTS	. 28
	8.4 FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	. 27
	8.3 PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	. 27



# **1. GENERAL INFORMATION**

Applicant	DGL Group LTD.	
Address	2045 Lincoln Highway, 3rd Floor, Edison, NJ 08817, United States	
Manufacturer	DGL Group LTD.	
Address	2045 Lincoln Highway, 3rd Floor, Edison, NJ 08817, United States	
Product Designation	3-IN-1 Fan Lamp Led Light	
Brand Name	SARINA	
Test Model	SA-DFNL-BLK	
Series Model	SA-DFNL, SA-DFNL-XXX	
Declaration Difference	All the same except for the appearance color, X is just a letter	
Date of receipt of test item Nov. 09, 2022		
Date of test	Nov. 09, 2022 to Nov. 21, 2022	
Deviation from Standard	No any deviation from the test method	
Test Result	Pass	
Test Report Form No	AGCTR-ER-FCC-WPTV1.0	

Prepared By

Alan Duan

Alan Duan (Project Engineer)

Nov. 21, 2022

Reviewed By

Ln in .

Calvin Liu (Reviewer)

Nov. 21, 2022

Approved By

Max Ina

Max Zhang (Authorized Officer)

Nov. 21, 2022

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



# 2. PRODUCT INFORMATION

## 2.1 PRODUCT TECHNICAL DESCRIPTION

Hardware Version	V0.1
Software Version	V1.0
Operation Frequency	110.8KHz-205KHz
Modulation Type	Backscatter
Number of channels	1
Field Strength of Fundamental	65.42dBuV/m (Max)
Antenna Designation	Coil Antenna
Antenna Gain	0dBi
Power Supply	DC 5V 2A, DC 9V 2A
Wireless Charging Output Power	5W, 10W

## 2.2 TEST FREQUENCY LIST

Frequency Band	Channel Number	Frequency
110.8KHz-205KHz	01	124.6 KHz



## 2.3 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2AANZDFNL** filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

## 2.4 TEST METHODOLOGY

The tests were performed according to following standards:

No.	Identity	Document Title	
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulation	
2	FCC 47 CFR Part 15	Radio Frequency Devices	
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices	

#### **2.5 SPECIAL ACCESSORIES**

Not available for this EUT intended for grant.

#### 2.6 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

#### 2.7 ANTENNA REQUIREMENT

#### **Standard Requirement**

#### 15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antennathat uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a brokenantenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

#### EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 0 dBi.



# **3. TEST ENVIRONMENT**

## **3.1 ADDRESS OF THE TEST LABORATORY**

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

## **3.2 TEST FACILITY**

The test facility is recognized, certified, or accredited by the following organizations:

#### CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

#### A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

#### FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

#### IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



## **3.3 ENVIRONMENTAL CONDITIONS**

	NORMAL CONDITIONS	EXTREME CONDITIONS		
Temperature range (°C)	15 - 35	-20 - 50		
Relative humidty range	20 % - 75 %	20 % - 75 %		
Pressure range (kPa)	86 - 106	86 - 106		
Power supply				
Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.				

## **3.4 MEASUREMENT UNCERTAINTY**

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard

uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 150kHz	$U_c = \pm 4.2 \text{ dB}$
Uncertainty of Radiated Emission below 30MHz	$U_c = \pm 3.8 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 4.0 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_{c} = \pm 2.7 \%$
Uncertainty of Occupied Channel Bandwidth	U <sub>c</sub> = ±2 %



## 3.5 LIST OF EQUIPMENTS USED

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESPI	101206	Mar. 28, 2022	Mar. 27, 2023
Artificial power network	R&S	ESH2-Z5	100086	Jun. 08, 2022	Jun. 07, 2023
Test Software	FARA	EZ-EMC	Ver. AGC-CON03A1	N/A	N/A
Test Receiver	R&S	ESCI	10096	Mar. 28, 2022	Mar. 27, 2023
EXA Signal Analyzer	Agilent	N9010A	MY53470504	Aug. 04, 2022	Aug. 03, 2023
Active Loop Antenna (9K-30Mhz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 11, 2024
Wideband Antenna	SCHWARZBECK	VULB9168	VULB9168-494	Jan. 08, 2021	Jan. 07, 2023
Test Software	FARA	EZ-EMC	Ver.RA-03A	N/A	N/A



# **4.SYSTEM TEST CONFIGURATION**

## **4.1 EUT CONFIGURATION**


The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

## 4.2 EUT EXERCISE


The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

## **4.3 CONFIGURATION OF TESTED SYSTEM**

Radiated Emission Configure:



Conducted Emission Configure:



#### 4.4 EQUIPMENT USED IN TESTED SYSTEM

The Following Peripheral Devices And Interface Cables Were Connected During The Measurement: Test Accessories Come From The Laboratory

Item	Equipment	Model No.	Identifier	Note
1	Charger line	N/A	0.8m unshielded	Accessories
2	Wireless charging load	N/A	N/A	Accessories
3	Adapter	HW-200325CP0	DC 5V	Accessories

I Test Accessories Come From The Manufacturer

Item	Equipment	Model No.	Identifier	Note
1	3-IN-1 Fan Lamp Led Light	SA-DFNL-BLK	2AANZDFNL	EUT

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd



#### **4.5 SUMMARY OF TEST RESULTS**

ltem	FCC Rules	Description Of Test	Result
1	§15.203	Antenna Equipment	Pass
2	§15.209(a)(f)	Radiated Spurious Emission	Pass
3	§15.215(c)	20dB Bandwidth	Pass
4	§15.205(a)	Restricted Bands of Operation	Pass
5	§15.207	AC Power Line Conducted Emission	Pass



# **5. DESCRIPTION OF TEST MODES**

	Summary table of Test Cases
Test Item	Equipment type / Modulation
Test tient	WPT_(TX:124.6KHz)/ Backscatter
Radiated&Conducted Test Cases	Mode 1: DUT+ Wireless load (10W Full load mode) Mode 2: DUT + Wireless load (5W Half load mode) Mode 3: DUT + Wireless load (Null load mode)
AC Conducted Emission	Mode 1: DUT+ Wireless load (10W Full load mode) Mode 5: DUT + Wireless load (5W Half load mode) Mode 6: DUT + Wireless load (Null load mode)
-	rst case was recorded in the report, if no other cases. Baxis were chosen for testing for each applicable mode.



# 6. FIELD STRENGTH OF FUNDAMENTAL

## 6.1 PROVISIONS APPLICABLE

Test Requirement:	FCC Part15 C Sec	FCC Part15 C Section 15.209						
Test Method:	ANSI C63.10:2013	ANSI C63.10:2013						
Test Frequency Range:	9kHz to 1GHz	9kHz to 1GHz						
Test site:	Measurement Dist	ance: 3m						
	Frequency	Detector	RBW	VBW	Value			
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak			
Receiver setup:	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak			
Receiver setup.	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak			
	Above 1CL	Peak	1MHz	3MHz	Peak			
	Above 1GHz	Peak	1MHz	10Hz	Average			
		1 Call		10112	Twerage			

#### Limits for frequency below 30MHz

Frequency	Limit (uV/m)	Measurement Distance(m)	Remark
0.009-0.490	2400/F(kHz)	300	Quasi-peak Value
0.490-1.705	24000/F(kHz)	30	Quasi-peak Value
1.705-30	30	30	Quasi-peak Value

#### Limits for frequency Above 30MHz

Frequency	Limit (dBuV/m @3m)	Remark
30MHz-88MHz	40.00	Quasi-peak Value
88MHz-216MHz	43.50	Quasi-peak Value
216MHz-960MHz	46.00	Quasi-peak Value
960MHz-1GHz	54.00	Quasi-peak Value
Above 1GHz	54.00	Average Value
Above IGHZ	74.00	Peak Value

Remark: (1) Emission level dB  $\mu$  V = 20 log Emission level  $\mu$  V/m

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.



## 6.2 MEASUREMENT PROCEDURE

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



## 6.3 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CF - AG - AV

where FS = Field Strength in  $dB\mu V/m$ 

RA = Receiver Amplitude (including preamplifier) in dBµV

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB/m

AG = Amplifier Gain in dB

AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

FS = RR + LF

where  $FS = Field Strength in dB\mu V/m$ RR = RA - AG - AV in dB $\mu$ V LF = CF + AF in dB

Assume a receiver reading of 52.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB/m and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB $\mu$ V/m.

This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

 $\begin{array}{ll} {\sf RA} = 52.0 \; d{\sf B}\mu{\sf V}/{\sf m} & \\ {\sf AF} = 7.4 \; d{\sf B}/{\sf m} & {\sf RR} = 18.0 \; d{\sf B}\mu{\sf V} \\ {\sf CF} = 1.6 \; d{\sf B} & {\sf LF} = 9.0 \; d{\sf B} \\ {\sf AG} = 29.0 \; d{\sf B} & \\ {\sf AV} = 5.0 \; d{\sf B} & \\ {\sf FS} = {\sf RR} + {\sf LF} \\ {\sf FS} = 18 + 9 = 27 \; d{\sf B}\mu{\sf V}/{\sf m} & \\ \end{array}$ 

Level in  $\mu$ V/m = Common Antilogarithm [(27 dB $\mu$ V/m)/20] = 22.4  $\mu$ V/m

Magnetic field strength calculation (9 kHz – 30 MHz)

When the limit is in terms of magnetic field, the following equation applies: U(dP(x)/m) = V(dP(x)/n) + U(dP(x)/m) = 0

```
H[dB(\mu A/m)] = V[dB(\mu V)] + LC [dB] - GPA [dB] + AFH [dB(S/m)]
```

#### Where,

H is the magnetic field strength (to be compared with the limit), V is the voltage level measured by the receiver or spectrum analyzer, LC is the cable loss, GPA is the gain of the preamplifier (if used), and AFH is the magnetic antenna factor.

If the "electrical" antenna factor is used instead, the above equation becomes:

 $H[dB(\mu A/m)] = V[dB(\mu V)] + LC [dB] - GPA [dB] + AFE [dB(m-1)] - 51.5 [dB\Omega]$ 


where AFE is the "electric" antenna factor, as provided by the antenna calibration laboratory.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



## 6.4 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)

RADIATED EMISSION TEST SETUP 9KHz-30MHz




The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.205 limits.



#### **6.5 MEASUREMENT RESULTS**

#### **ELECTRIC FIELD TEST IN THE FREQUENCY RANGE 9KHz-150KHz**



## RESULT: PASS



						1	
EUT	1 3			Model Name		SA-DFNL	BLK
Temperature				Relative Hum	nidity	52%	
Pressure	985hPa			Test Voltage		Normal V	oltage
Test Mode	Mode 1		Antenna			Side	
130.0 dBuV/	m						
70	1 3						
porter	and warden	Makanaphraha	man why	A had	Marilanderin	mumhrow	me lam
10.0	Mar Mark	all all and a special here			My America	muhanthanto	
		Reading Level	(MHz) Correct Factor	Measure- ment	Limit	Over	WW (44%) 0.150
10.0		Reading	(MHz) Correct	Measure-			
10.0	k. Freq.	Reading Level	(MH2) Correct Factor	Measure- ment	Limit	Over	0.150
10.0 0.009 No. Mi	k. Freq. MHz	Reading Level dBuV	(MH2) Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over	0.150 Detector
10.0 0.009 No. Mi	k. Freq. MHz 0.0117	Reading Level dBuV 10.90	(MHz) Correct Factor dB 28.21	Measure- ment dBuV/m 39.11	Limit dB/m 125.4	Over dB -86.33	0.150 Detector peak
10.0 0.009 No. Mi 1 2	k. Freq. MHz 0.0117 0.0155	Reading Level dBuV 10.90 12.52	(MHz) Correct Factor dB 28.21 27.93	Measure- ment dBuV/m 39.11 40.45	Limit dB/m 125.4 123.1	Over dB -86.33 -82.72	0.150 Detector peak peak
10.0 0.009 No. Mi 1 2 3	k. Freq. MHz 0.0117 0.0155 0.0352	Reading Level dBuV 10.90 12.52 29.49	(мнz) Correct Factor dB 28.21 27.93 26.46	Measure- ment dBuV/m 39.11 40.45 55.95	Limit dB/m 125.4 123.1 116.5	Over dB -86.33 -82.72 -60.58	0.150 Detector peak peak peak

## ELECTRIC FIELD TEST IN THE FREQUENCY RANGE 9KHz-150KHz

## **RESULT: PASS**



EUT	3-IN-1 Fan L	amp Led Lig	ht	Model Name		SA-DFNL	BLK
Temperature	21°C			Relative Hum	idity	52%	
Pressure	985hPa			Test Voltage		Normal Voltage	
Test Mode						Face	
120.0 dBu∀/m							
60 1 0.0							in:
0.150	0.5	i	(MHz)	5			30.000
No. Mk.	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
	MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	0.1737	17.80	21.48	39.28	103.4	-64.15	peak
2	0.2575	16.98	21.33	38.31	99.77	-61.46	peak
3	0.4761	18.86	20.92	39.78	94.07	-54.29	peak
4	3.1899	17.26	22.47	39.73	69.54	-29.81	peak
5	8.1483	18.65	23.88	42.53	69.54	-27.01	peak
6 *	26.9832	19.64	24.41	44.05	69.54	-25.49	peak

## ELECTRIC FIELD TEST IN THE FREQUENCY RANGE 150KHz-30MHz

## **RESULT: PASS**



							SA-DFNL-BLK	
EUT		3-IN-1 Fan L	amp Led Lig	ht	Model Name		SA-DFNL	BLK
Temperature		21°C			Relative Hum	idity	52%	
Pressure		985hPa			Test Voltage		Normal Voltage	
Test Mode Mode 1					Antenna		Side	
120.0 d	lBuV/m						Linit	
60	2					52	Marg	5
0.0	hillenijterer		ndi mangula yaka na saday					
0.0	What is a second se	0.5		(MHz)	Measure-			30.000
0.150	Mk.				Measure- ment	Limit	Over	30.000
0.150	Mk.	0.5	Reading	(MHz) Correct	Measure-		Over	30.000
0.150	Mk.	0.5 Freq.	Reading	(MHz) Correct Factor	Measure- ment	Limit		
0.150 No.	Mk.	0.5 Freq. MHz	Reading Level dBuV	(MHz) Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	dB	Detector
0.150 No.	Mk.	0.5 Freq. MHz 0.1766	Reading Level dBuV 16.79	(MHz) Correct Factor dB 21.48	Measure- ment dBuV/m 38.27	Limit dB/m 103.2	dB -65.01	Detector peak
0.150 No. 1 2 3	*	0.1766 0.2584	Reading Level dBuV 16.79 18.71	(MHz) Correct Factor dB 21.48 21.33	Measure- ment dBuV/m 38.27 40.04	Limit dB/m 103.2 99.74	dB -65.01 -59.70	Detector peak peak
0.150 No. 1 2 3	*	0.1766 0.2584 0.5045	Reading Level dBuV 16.79 18.71 17.21	(MHz) Correct Factor dB 21.48 21.33 20.88	Measure- ment dBuV/m 38.27 40.04 38.09	Limit dB/m 103.2 99.74 73.54	dB -65.01 -59.70 -35.45	Detector peak peak peak

## ELECTRIC FIELD TEST IN THE FREQUENCY RANGE 150KHz-30MHz

#### RESULT: PASS NOTES:

- 1. Quasi-Peak detector is used for frequency below 30MHz.
- 2. Negative value in the margin column shows emission below limit.
- 3. All measurements were made with 0.6m loop antenna at 3m distance. All emissions are below the QP limit.
- 4. Corr. Factor= Antenna Factor (dB/m) + Cable Loss (dB)
- 5. Loop antenna is used for the emission under 30MHz.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



			RAD						
EUT		3-IN-	1 Fan La	amp Le	d Light	Model Na	ime	SA-DF	NL-BLK
Temperature	perature 22°C			Relative	Relative Humidity				
Pressure		985hPa		Test Volta	Test Voltage		Normal Voltage		
Test Mode	Mode 1		Antenna	Antenna		Horizontal			
72.0 dBuV/i					mt Muur				
-8	AN AN	why			J <sup>M</sup> , twi.				
-8	40 50		70 80		(MHz)	300	400 5	500 600 700	) 1000.000
-8	40 50			ding	(MHz) Correct Factor	300 Measure- ment	400 5 Limit	500 600 700 Over	) 1000.000
-8 30.000	40 50  k. F	60	70 80 Read	ding	Correct	Measure-			0 1000.000 Detector
-8 30.000	40 50  k. F	60 Freq. MHz	<sup>70 80</sup> Read	ding	Correct Factor	Measure- ment	Limit	Over	
-8 30.000 No. M	40 50  k. F	<sup>60</sup> Freq. MHz 9169	70 80 Read Lev	ding vel IV 83	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
-8 30.000 No. M	40 50 lk. F 114.9	60 Freq. MHz 9169 9909	70 80 Read Lev dBu 13.8	ding vel vv 83 08	Correct Factor dB 20.96	Measure- ment dBuV/m 34.79	Limit dB/m 43.50	Over dB -8.71	Detector QP
-8 30.000 No. M	40 50 k. F 114.9 234.9	60 Freq. MHz 9169 9909 9509	<sup>70</sup> 80 Read Lev dBu 13.8 21.0 16.1	ding vel JV 83 08 19	Correct Factor dB 20.96 21.65	Measure- ment dBuV/m 34.79 42.73	Limit dB/m 43.50 46.00	Over dB -8.71 -3.27	Detector QP peak
-8 30.000 No. M 1 2 * 3	40 50 k. F 114.9 234.9 245.9	60 Freq. MHz 9169 9909 9509 1886	<sup>70</sup> 80 Read Lev dBu 13.8 21.0 16.1 15.0	ding rel IV 83 08 19 03	Correct Factor dB 20.96 21.65 21.92	Measure- ment dBuV/m 34.79 42.73 38.11 41.16	Limit dB/m 43.50 46.00 46.00	Over dB -8.71 -3.27 -7.89	Detector QP peak QP

# DADIATED EMICCION DEL OW 401-

## **RESULT: PASS**



		AISSION BELOW 1GHz	
EUT	3-IN-1 Fan Lamp Led L	ight Model Name	SA-DFNL-BLK
Temperature	22°C	Relative Hum	idity 52%
Pressure	essure 985hPa		Normal Voltage
Test Mode	Mode 1	Antenna	Vertical
72.0 dBuV/m		When the web and	Limit: — Margin: —
-8		W MWWWWWW "	
		(MHz) 300 4	
-8 30.000 40 50	Reading Co	(MHz) 300 4	
-8 30.000 40 50 No. Mk.	Reading Co	(MHz) 300 A prrect Measure- actor ment Li	400 500 600 700 1000.000
-8 30.000 40 50 No. Mk.	Reading Co Freq. Level F MHz dBuV	(MHz) 300 d orrect Measure- actor ment Li dB dBuV/m d	400 500 600 700 1000.000
-8 30.000 40 50 No. Mk.	Reading Co Freq. Level F MHz dBuV 7019 18.65 1	(MHz) 300 d prrect Measure- actor ment Li dB dBuV/m d 5.50 34.15 40	400 500 600 700 1000.000 imit Over B/m dB Detector
-8 30.000 40 50 No. Mk. 1 ! 84. 2 387.	Reading     Control       Freq.     Level     F       MHz     dBuV     7019     18.65     1       9920     16.61     2     2	(MHz) 300 d orrect Measure- actor ment Li dB dBuV/m d 5.50 34.15 40 1.72 38.33 46	400 500 600 700 1000.000 imit Over B/m dB Detector 0.00 -5.85 peak
-8 30.000 40 50 No. Mk. 1 ! 84. 2 387. 3 443.	Reading     Cd       Freq.     Level     F       MHz     dBuV     7019     18.65     1       9920     16.61     2     2       2943     13.44     2	(MHz) 300 d orrect Measure- actor ment Li dB dBuV/m d 5.50 34.15 40 1.72 38.33 46 3.95 37.39 46	400   500   600   700   1000.000     400   500   600   700   1000.000     imit   Over     B/m   dB   Detector     0.00   -5.85   peak     0.00   -7.67   QP
-8 30.000 40 50 No. Mk. 1 ! 84. 2 387. 3 443. 4 537.	Reading     Cd       Freq.     Level     F       MHz     dBuV     7019     18.65     1       9920     16.61     2     2     2943     13.44     2       5891     13.09     2     1     1     1     1     1	(MHz) 300 4 orrect Measure- actor ment Li dB dBuV/m d 5.50 34.15 40 1.72 38.33 46 3.95 37.39 46 4.52 37.61 46	400   500   600   700   1000.000     400   500   600   700   1000.000     imit   Over     B/m   dB   Detector     0.00   -5.85   peak     0.00   -7.67   QP     0.00   -8.61   QP

## DADIATED EMICCION DEL OW 401-

## **RESULT: PASS**

Note: 1. Factor=Antenna Factor + Cable loss, Over=Measurement-Limit.

2. All test modes had been pre-tested. The mode 1 is the worst case and recorded in the report.

3. The "Factor" value can be calculated automatically by software of measurement system.



# 7. 20 dB BANDWIDTH

## 7.1 PROVISIONS APPLICABLE

N/A

## 7.2 MEASUREMENT PROCEDURE

Set the parameters of SPA as below:

- 1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
- 2. Centre frequency = Operation Frequency
- 3. The resolution bandwidth of 300 Hz and the video bandwidth of 1 kHz were used.
- 4. Span: 3kHz, Sweep time: Auto
- 5. Set the EUT to continue transmitting mode. Allow the trace to stabilize. Use the "N dB down" function of SPA to define the bandwidth.
- 6. Measured the spectrum width with power higher than 20dB below carrier.
- 7. Measured the 99% OBW.
- 8. Record the plots and Reported.

## 7.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)



Spectrum Analyzer



## 7.4 MEASUREMENT RESULTS

Test Data of Occupied Bandwidth and -20dB Bandwidth								
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (kHz)	-20dB Bandwidth (kHz)	Limits (MHz)	Pass or Fail			
Backscatter	0.1246	0.690	0.812	N/A	Pass			

## Test Graphs of Occupied Bandwidth&-20dB Bandwidth

Center Freq 124.600 kHz	Tri;	SENSE:INT nter Freq: 124.600 kHz g: Free Run Avg Hol ten: 20 dB	Radio St d:>10/10	AMNov 22, 2022 d: None wice: BTS	Frequency
10 dB/div Ref 20.00 dBm					
10.0 0.00					Center Freq 124.600 kHz
-10.0					
-40.0					
Center 124.6 kHz #Res BW 300 Hz		#VBW 1 kHz	Sweep	pan 3 kHz 40.87 ms	CF Step 300 Hz
Occupied Bandwidth	690 Hz	Total Power	0.70 dBm		<u>Auto</u> Man Freq Offset
Transmit Freq Error x dB Bandwidth	-57 Hz 812 Hz	OBW Power x dB	99.00 % -20.00 dB		0 Hz
MSG			STATUS		



# 8. AC POWER LINE CONDUCTED EMISSION TEST


## 8.1 LIMITS OF LINE CONDUCTED EMISSION TEST

Framerau	Maximum RF Line Voltage					
Frequency	Q.P. (dBµV)	Average (dBµV)				
150kHz~500kHz	66-56	56-46				
500kHz~5MHz	56	46				
5MHz~30MHz	60	50				

Note: 1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

## 8.2 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)





## 8.3 PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

#### 8.4 FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.



#### **8.5 MEASUREMENT RESULTS**



#### MEASUREMENT RESULT: "agc fin"

2022/11/14	9:13						
Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
MHz	dBµV	dB	dBµV	dB			
			-				
0.154000	47.20	6.9	66	18.6	QP	L1	GND
1.950000	38.90	6.4	56	17.1	QP	L1	GND
2.226000	38.90	6.5	56	17.1	QP	L1	GND
2.506000	40.00	6.5	56	16.0	QP	L1	GND
2.786000	39.00	6.5	56	17.0	QP.	L1	GND
3.342000	38.80	6.5	56	17.2	QP	L1	GND
					~		

#### MEASUREMENT RESULT: "agc fin2"

2022/11/14 9:	13							
Frequency	Level	Transd	Limit	Margin	Detector	Line	PE	
MHz	dBµV	dB	dBµV	dB				
1.950000	39.00	6.4	46	7.0	AV	L1	GND	
2.226000	38.80	6.5	46	7.2	AV	L1	GND	
2.506000	39.90	6.5	46	6.1	AV	L1	GND	
2.786000	38.80	6.5	46	7.2	AV	L1	GND	
3.062000	38.90	6.5	46	7.1	AV	L1	GND	
3.342000	38.80	6.5	46	7.2	AV	L1	GND	


#### **RESULT: PASS**

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd





#### MEASUREMENT RESULT: "agc\_fin"

2022/11/14 9: Frequency MHz	18 Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.154000 1.950000 2.230000 2.506000 2.786000 3.342000	47.00 39.10 38.50 40.00 39.40 39.00	6.9 6.4 6.5 6.5 6.5 6.5	66 56 56 56 56	18.8 16.9 17.5 16.0 16.6 17.0	QP QP QP QP QP QP	N N N N N	GND GND GND GND GND GND

#### MEASUREMENT RESULT: "agc\_fin2"

2022/11/14 9:	18							
Frequency	Level	Transd	Limit	Margin	Detector	Line	PE	
MHz	dBµV	dB	dBµV	dB				
1.950000	39.10	6.4	46	6.9	AV	N	GND	
2.230000	38.20	6.5	46	7.8	AV	N	GND	
2.506000	40.00	6.5	46	6.0	AV	N	GND	
2.786000	39.00	6.5	46	7.0	AV	N	GND	
3.062000	38.70	6.5	46	7.3	AV	N	GND	
3.342000	38.90	6.5	46	7.1	AV	N	GND	

#### **RESULT: PASS**

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Report No.: AGC01559221103FE10 Page 30 of 30

# APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC01559221103AP01

# APPENDIX B: PHOTOGRAPHS OF TEST EUT

Refer to the Report No.: AGC01559221103AP02

-----END OF REPORT-----



# Conditions of Issuance of Test Reports

 All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd. (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.