

FCC Test Report

Report No.: AGC15705240617FR01

FCC ID	:	2AANZMSMS
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	Wireless Magnetic Speaker
BRAND NAME	:	BREAKOUT
MODEL NAME	:	BRK-MSMS-GLD, BRK-MSMS-PNK, BRK-MSMS-BLK, BRK-MSMS-BLU, BRK-MSMS-XXX, BRK-MSMS
APPLICANT	:	DGL Group LTD.
DATE OF ISSUE	:	Jun. 19, 2024
STANDARD(S)	:	FCC Part 15 Subpart C §15.247
REPORT VERSION	:	V1.0







Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Jun. 19, 2024	Valid	Initial Release



Table of Contents

1. General Information	5
2. Product Information	6
2.1 Product Technical Description	
2.2 Test Frequency List	6
2.3 Related Submittal(S) / Grant (S)	7
2.4 Test Methodology	7
2.5 Special Accessories	7
2.6 Equipment Modifications	7
2.7 Antenna Requirement	7
3. Test Environment	8
3.1 Address of the Test Laboratory	
3.2 Test Facility	
3.3 Environmental Conditions	9
3.4 Measurement Uncertainty	
3.5 List of Equipment Use	
4.System Test Configuration	
4.1 EUT Configuration	
4.2 EUT Exercise	
4.3 Configuration of Tested System	
4.4 Equipment Used In Tested System	
4.5 Summary of Test Results	
5. Description of Test Modes	
6. Duty Cycle Measurement	
7. RF Output Power Measurement	
7.1 Provisions Applicable	
7.2 Measurement Procedure	
7.3 Measurement Setup (Block Diagram of Configuration)	
7.4 Measurement Result	
8. 6dB Bandwidth Measurement	
8.1 Provisions Applicable	
8.2 Measurement Procedure	
8.3 Measurement Setup (Block Diagram of Configuration)	
8.4 Measurement Results	
9. Power Spectral Density Measurement	
9.1 Provisions Applicable	
9.2 Measurement Procedure	
9.3 Measurement Setup (Block Diagram of Configuration)	
9.4 Measurement Results	



10. Conducted Band Edge And Out-of-Band Emissions	
10.1 Provisions Applicable	
10.2 Measurement Procedure	
10.3 Measurement Setup (Block Diagram of Configuration)	
10.4 Measurement Results	
11. Radiated Spurious Emission	
11.1 Measurement Limit	
11.2 Measurement Procedure	
11.3 Measurement Setup (Block Diagram of Configuration)	
11.4 Measurement Result	
12. AC Power Line Conducted Emission Test	
12.1 Measurement Limit	
12.2 Measurement Setup (Block Diagram of Configuration)	
12.3 Preliminary Procedure of Line Conducted Emission Test	
12.4 Final Procedure of Line Conducted Emission Test	
12.5 Measurement Results	
Appendix I: Photographs of Test Setup	
Appendix II: Photographs of Test EUT	



1. General Information

Applicant	DGL Group LTD.
Address	2045 Lincoln Highway, 3rd Floor, Edison, NJ 08817, United States
Manufacturer	DGL Group LTD.
Address	2045 Lincoln Highway, 3rd Floor, Edison, NJ 08817, United States
Factory	N/A
Address	N/A
Product Designation	Wireless Magnetic Speaker
Brand Name	BREAKOUT
Test Model	BRK-MSMS-GLD
Series Model(s)	BRK-MSMS-PNK, BRK-MSMS-BLK, BRK-MSMS-BLU, BRK-MSMS-XXX, BRK-MSMS
Difference Description	Only the color of the product appearance is different, everything else is completely consistent.
Date of receipt of test item	Jun. 07, 2024
Date of Test	Jun. 07, 2024 - Jun. 19, 2024
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCER-FCC-BLE-V1

Note: The test results of this report relate only to the tested sample identified in this report.

Thea Huang Prepared By Thea Huang Jun. 19, 2024 (Project Engineer) in. **Reviewed By** Calvin Liu Jun. 19, 2024 (Reviewer) Than Approved By Max Zhang Jun. 19, 2024

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

(Authorized Officer)



2. Product Information

2.1 Product Technical Description

Frequency Band	2400MHz-2483.5MHz
Operation Frequency Range	2402MHz-2480MHz
Bluetooth Version	V5.3
Modulation Type	BLE GFSK 1Mbps GFSK 2Mbps
Number of channels	40
Carrier Frequency of Each Channel	40 Channels (37 Data channels + 3 advertising channels)
Channel Separation	2 MHz
Maximum Transmitter Power	0.375dBm
Hardware Version	V1.0
Software Version	V1.0
Antenna Designation	PCB Antenna
Antenna Gain	-0.58dBi
Power Supply	DC 3.7V by battery or DC 5V by adapter

2.2 Test Frequency List

Frequency Band	Channel Number	Frequency		
	0	2402 MHz		
	1	2404 MHz		
2400~2483.5MHz	:	:		
	19	2440MHz		
	:	:		
	38	2478 MHz		
	39	2480 MHz		
Note: $f = 2402 + 2*k$ MHz, $k = 0,, 39$ f is the operating frequency (MHz); k is the operating channel.				



2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: 2AANZMSMS, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
4	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules

2.5 Special Accessories

Not available for this EUT intended for grant.

2.6 Equipment Modifications

Not available for this EUT intended for grant.

2.7 Antenna Requirement

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi

EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is -0.58dBi.



3. Test Environment

3.1 Address of the Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories).

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



3.3 Environmental Conditions

	Normal Conditions
Temperature range (°C)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106
Power supply	DC 3.7V by battery or DC 5V by adapter

3.4 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard

uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	U _c = ±2 %
Uncertainty of Occupied Channel Bandwidth	U _c = ±2 %



3.5 List of Equipment Use

• R	RF Conducted Test System							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
\boxtimes	AGC-ER-E036	Spectrum Analyzer	Agilent	N9020A	MY49100060	2024-05-24	2025-05-23	
\boxtimes	AGC-ER-E062	Power Sensor	Agilent	U2021XA	MY54110007	2024-02-01	2025-01-31	
\boxtimes	AGC-ER-E063	Power Sensor	Agilent	U2021XA	MY54110009	2024-02-01	2025-01-31	
\boxtimes	AGC-ER-A001	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-09-21	2025-09-20	
\boxtimes	AGC-ER-E083	Signal Generator	Agilent	E4421B	US39340815	2024-05-23	2025-05-22	
\boxtimes	N/A	RF Connection Cable	N/A	1#	N/A	Each time	N/A	
\boxtimes	N/A	RF Connection Cable	N/A	2#	N/A	Each time	N/A	

• F	Radiated Spurious Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2024-02-01	2025-01-31	
\boxtimes	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23	
\boxtimes	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2024-05-28	2025-05-27	
\boxtimes	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04	
\boxtimes	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10	
	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2024-03-31	2025-03-30	
\square	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-09-24	2025-09-23	
\boxtimes	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2022-08-04	2024-08-03	
\boxtimes	AGC-EM-A119	2.4G Filter	SongYi	N/A	N/A	2024-05-23	2025-05-22	
\boxtimes	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08	
	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08	

• A	AC Power Line Conducted Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
\boxtimes	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2024-05-28	2025-05-27	
\boxtimes	AGC-EM-A130	6dB Attenuator	Eeatsheep	LM-XX-6-5W	DC-6GZ	2023-06-09	2025-06-08	
\square	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2024-05-28	2025-05-27	



• Te	Test Software							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information			
	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71			
	AGC-EM-S003	RE Test System	FARA	EZ-EMC	VRA-03A			
	AGC-ER-S012	BT/WIFI Test System	Tonscend	JS1120-2	2.6			
	AGC-EM-S011	RSE Test System	Tonscend	TS+-Ver2.1(JS36-RSE)	4.0.0.0			



4.System Test Configuration

4.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise


The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of Tested System

Radiated Emission Configure:



Conducted Emission Configure:



4.4 Equipment Used In Tested System

The following peripheral devices and interface cables were connected during the measurement:

I Test Accessories Come From The Laboratory

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable			
1	Adapter	Huawei	HW-200440C00					
2	Control Box		USB-TTL					
	Test Accessories Come From The Manufacturer							
NIa		Manufacturer		On a sification lufarmation	Cabla			

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1					



4.5 Summary of Test Results

Item	FCC Rules	Description of Test	Result
1	§15.203&15.247(b)(4)	Antenna Equipment	Pass
2	§15.247 (b)(3)	RF Output Power	Pass
3	§15.247 (a)(2)	6 dB Bandwidth	Pass
4	§15.247 (e)	Power Spectral Density	Pass
5	§15.247 (d)	Conducted Band Edge and Out-of-Band Emissions	Pass
6	§15.209	Radiated Emission& Band Edge	Pass
7	§15.207	AC Power Line Conducted Emission	Pass



5. Description of Test Modes

	Summary Table of Test Cases					
	Data Rate / Modulation					
Test Item	Bluetooth – LE(1Mbps) / GFSK					
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps(Battery powered or AC/DC adapter)					
Radiated & Conducted Test Cases	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps(Battery powered or AC/DC adapter)					
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps(Battery powered or AC/DC adapter)					
AC Conducted Emission	Mode 1: Bluetooth Link + Battery + USB Cable (Charging from AC Adapter)					

Note:

- Only the result of the worst case was recorded in the report, if no other cases. 1.
- 2. 3. The battery is full-charged during the test.
- For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 4. For Conducted Test method, a temporary antenna connector is provided by the manufacture.
 - Software Setting Diagram



6. Duty Cycle Measurement

The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = Peak. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Operating mode	T(µs)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/ T Minimum VBW (kHz)
BLE_1Mbps	364	85.40	0.685	2.747
BLE_2Mbps	N/A	N/A	N/A	N/A

Remark:

2. The duty cycle of each frequency band mode reflects the determination requirements of the low channel measurement value

Bluetooth – LE for 1Mbps	Bluetooth – LE for 2Mbps
Agelend Spectrum Audgrer Swegt SM Status ALSALATIO OSS3/35/PM/An 19 200 Center Freq 2.4020000000 GHz Frequency Arg Type: RMS PMC Tool P	N/A

The test plots as follows:

^{1.} Duty Cycle factor = 10 * log (1/ Duty cycle)



7. RF Output Power Measurement

7.1 Provisions Applicable

For DTSs employing digital modulation techniques operating in the bands 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W.


7.2 Measurement Procedure

For Peak Power, the testing follows ANSI C63.10 Section 11.9.1.1 Method Max peak power:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the RBW > DTS bandwidth
- 3. Set the VBW \geq [3 x RBW].
- 4. Span≥[3 x RBW].
- 5. Sweep= auto couple.
- 6. Detector Function= Peak.
- 7. Trace mode= Max hold.
- 8. Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.
- For Average power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G:
- 1. The RF output of EUT was connected to the power meter by RF cable and attenuator.
- 2. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Measure the conducted output power and record the results in the test report.


7.3 Measurement Setup (Block Diagram of Configuration)

For Average power test setup






For peak power test setup



7.4 Measurement Result

Test Data of Conducted Output Power							
Test Mode	Test Frequency (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail			
	2402	0.295	≪30	Pass			
GFSK_1Mbps	2440	0.375	≪30	Pass			
	2480	-0.089	≪30	Pass			





Test Graphs of Conducted Output Power



Phot: Freq 2.480000000 GHz Phot: Fast +++ Trig: Free Run Matter: 40 dB Avg Type: Log-Pur AvgHold: 100/100 Trig: Frequency 0 dB/dlv Ref 30.00 dBm -0.089 dBm -0.089 dBm Center Freq 2.480000000 GHz 0 dB/dlv Ref 30.00 dBm -0.089 dBm -0.089 dBm Center Freq 2.48000000 GHz 0 dB/dlv Ref 30.00 dBm -0.089 dBm -0.089 dBm Center Freq 2.48000000 GHz 0 dB/dlv Image: Start Frequency Start Frequency Start Frequency 0 dB/dlv Image: Start Frequency Center Frequency Auto Tune 0 dB/dlv Image: Start Frequency Start Frequency Start Frequency 0 dB/dlv Image: Start Frequency Start Frequency Center Frequency 0 dB/dlv Image: Start Frequency Start Frequency Start Frequency 0 dB/dlv Image: Start Frequency Start Frequency Start Frequency 0 dB/dlv Image: Start Frequency Start Frequency Start Frequency 0 dB/dlv Image: Start Frequency Start Frequency Start Frequency 0 dB/dlv Image: Start Frequency Start Frequency Start Frequency 0 dB/dlv	Agilent Spectrum Analyzer - Swept					
Mkr1 2.480 108 GHz -0.089 dBm Auto Tune 0 dB/dlv Ref 30.00 dBm 0.089 dBm Center Freq 2.48000000 GHz 100 1		000 GHz	Trig: Free Run	Avg Type: Log-Pwr	TRACE 1 2 3 4 5 6	Frequency
Center Freq 248000000 GHz 248200000 GHz 248250000 GHz 2482500000 GHz 248250000 GHz 248			#Atten: 40 dB	Mkr1	2.480 108 GHz	Auto Tune
000 1	20.0					
200 Stop Free 201 Stop Free 202 Stop Free 203 Stop Free 204 Stop Free 205 Stop Free 206 Stop Free 207 Stop Free 208 Stop Free 209 Stop Free 200 Stop Free 201	0.00		♦ ¹			
Auto 500.000 kH Auto 600.000 kH 500 500 500 500 500 500 500 500 500 50	20.0					
2000 Span 5.000 MHz Res BW 1.5 MHz #VBW 5.0 MHz Sweep 1.066 ms (1000 pts)	40.0					500.000 kH
Center 2.480000 GHz Span 5.000 MHz Res BW 1.5 MHz #VBW 5.0 MHz Sweep 1.066 ms (1000 pts)	50.0					
SG STATUS	Center 2.480000 GHz #Res BW 1.5 MHz	#VBW	5.0 MHz	Sweep 1	Span 5.000 MHz .066 ms (1000 pts)	
	ISG			STATUS		



8. 6dB Bandwidth Measurement

8.1 Provisions Applicable


The minimum 6 dB bandwidth shall be 500 kHz.

8.2 Measurement Procedure

The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).

- 1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously.
- Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
- For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the OBW and set the Video bandwidth (VBW) ≥ 3 * RBW.
- 5. Measure and record the results in the test report.

8.3 Measurement Setup (Block Diagram of Configuration)






8.4 Measurement Results

Test Data of Occupied Bandwidth and DTS Bandwidth							
Test Mode	Test Frequency (MHz)	Occupied Bandwidth (MHz)	DTS BW (MHz)	DTS BW Limits (MHz)	Pass or Fail		
	2402	1.032	0.508	≥0.5	Pass		
GFSK_1Mbps	2440	1.030	0.505	≥0.5	Pass		
	2480	1.031	0.503	≥0.5	Pass		


Test Graphs of Occupied Bandwidth












Test Graphs of DTS Bandwidth







9. Power Spectral Density Measurement

9.1 Provisions Applicable


The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

9.2 Measurement Procedure

The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.

- 1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously.
- Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz in order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
- 4. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
- 5. Measure and record the results in the test report.
- The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

9.3 Measurement Setup (Block Diagram of Configuration)







9.4 Measurement Results

Test Data of Conducted Output Power Spectral Density					
Test Mode	Test Frequency (MHz)	Power density (dBm/3kHz)	Limit (dBm/3kHz)	Pass or Fail	
GFSK_1Mbps	2402	-19.140	≪8	Pass	
	2440	-19.103	≪8	Pass	
	2480	-19.936	≤8	Pass	

Test Graphs of Conducted Output Power Spectral Density









10. Conducted Band Edge and Out-of-Band Emissions

10.1 Provisions Applicable


The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the PSD procedure.

10.2 Measurement Procedure

- Reference level measurement
- 1. Set instrument center frequency to DTS channel center frequency
- 2. Set the span to \geq 1.5 times the DTS bandwidth
- 3. Set the RBW = 100 kHz
- 4. Set the VBW \geq 3 x RBW
- 5. Detector = peak
- 6. Sweep time = auto couple
- 7. Trace mode = max hold
- 8. Allow trace to fully stabilize
- Emission level measurement
- 1. Set the center frequency and span to encompass frequency range to be measured
- 2. RBW = 100kHz
- 3. VBW = 300kHz
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep time = auto couple
- 7. The trace was allowed to stabilize


10.3 Measurement Setup (Block Diagram of Configuration)

Spectrum Analyzer






10.4 Measurement Results




Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands























Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands



11. Radiated Spurious Emission

11.1 Measurement Limit

FCC Part 15.209 Limit in the below table to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

11.2 Measurement Procedure

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds.

Any rep Ashang alternative b(provided pther, transmitter aloperates a for is longer than o 0.e4n seconds) e Orbin cases in where is the Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



1MHz/3MHz for Peak, 1MHz/3MHz for Average

pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.

- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

 Spectrum Parameter
 Setting

 Start ~Stop Frequency
 9kHz~150kHz/RB 200Hz for QP

 Start ~Stop Frequency
 150kHz~30MHz/RB 9kHz for QP

 Start ~Stop Frequency
 30MHz~1000MHz/RB 120kHz for QP

 Start ~Stop Frequency
 1GHz~26.5GHz

The following table is the setting of spectrum analyzer and receiver.

Start ~Stop Frequency

Receiver Parameter	Setting	
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP	
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP	
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP	



• Quasi-Peak Measurements below 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

Peak Measurements above 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize


<u>Average Measurements above 1GHz</u>

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW ≥ [3 × RBW]
- 4. Detector = Power averaging (rms)
- 5. Averaging type = power (i.e., rms)
- 6. Sweep time = auto
- 7. Perform a trace average of at least 100 traces.
- 8. The applicable correction factor is [10*log (1 / D)], where D is the duty cycle. The factor had been edited in the "Input Correction" of the Spectrum Analyzer.




11.3 Measurement Setup (Block Diagram of Configuration)






Radiated Emission Test Setup 30MHz-1000MHz



Radiated Emission Test Setup Above 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com




11.4 Measurement Result

Radiated Emission Below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

			Radia	ted Emiss	ion Test Res	ults at 30MH	z-1GHz			
	lame	Wire	eless Magnetic	Speaker		Model Na	ime	BRK-MSN	IS-GLD	
Temp	erature	22.7	22.7 ℃				Relative Humidity 59.8%		9.8%	
Press	ure	960	960hPa				age	DC 3.7V k	by battery	
Test N	lode	Mode 2				Antenna	Polarity	Horizonta		
	130 120				FCC Part 15	C				
	110									
	100 90									
	80									
	[W/\180 70 60 50									
	90 60 190 50									
	40							5	6	
	30	\wedge		~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~	man 1	m m	mark want	new many mark		
	10	~~		~	~~~~					
	-10									
	30M			100M	Frequency[H	-1			1G	
	-	QP Limi QP Dete			Frequency(n	2]				
		C QF Dele								
Final I	Data List									
NO.	Freq [MHz		Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	
1	59.1		24.08	17.64	40.00	15.92	100	353	Horizontal	
2	100.8	31	28.68	17.03	43.50	14.82	100	186	Horizontal	
3	141.5	55	28.23	16.13	43.50	15.27	100	18	Horizontal	
4	191.9	99	26.71	11.38	43.50	16.79	100	165	Horizontal	
5	616.8	35	31.53	25.57	46.00	14.47	100	165	Horizontal	
6	866.1	4	35.61	29.80	46.00	10.39	100	345	Horizontal	





			Radia	ted Emiss	ion Test Resu	ults at 30MHz	z-1GHz		
EUT N	lame	Wirel	Wireless Magnetic Speaker				me	BRK-MSMS-GLD	
Tempe	erature	22.7°C			Relative Humidity		59.8%		
Press							Test Voltage		y battery
Test Mode Mode 2						Antenna	Polarity	Vertical	
	130				FCC Part 15C				
	120 110								
	100								
	90								
	80 5 70								
	۲0								
	50								
	40	*	* ² * ³	4				4 5	
	20	\sim	~~~~~~~~~~*	in the	man 1		- August	when the weather the second states	
	10				· North	more man			
	0								
	-10 30M	1		100M		L I	1		1G
	_				Frequency[Hz]				
Final F)ata List	QP Limit QP Detecto	— Vertical PK or						
	Data List	QP Detecto	or	Factor	Limit	Margin	Height	Angle	
Final D	Data List Freq [MHz	QP Detecto		Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
	Freq	QP Detecto	Level						Polarity Vertical
NO.	Freq [MHz	• QP Detecto	Level [dBµV/m]	[dB]	[dBµV/m]	[dB]	[cm]	[°]	-
NO. 1	Freq [MHz 38.73		Level [dBµV/m] 32.96	[dB] 10.64	[dBµV/m] 40.00	[dB] 7.04	[cm] 100	[°] 271	Vertical
NO. 1 2	Freq [MHz 38.73 43.54		Level [dBµV/m] 32.96 33.62	[dB] 10.64 12.03	[dBµV/m] 40.00 40.00	[dB] 7.04 6.38	[cm] 100 100	[°] 271 50	Vertical Vertical
NO. 1 2 3	Freq [MHz 38.73 43.54 61.04	.] 3 3 4 1	Level [dBµV/m] 32.96 33.62 34.23	[dB] 10.64 12.03 17.54	[dBµV/m] 40.00 40.00 40.00	[dB] 7.04 6.38 5.77	[cm] 100 100 100	[°] 271 50 84	Vertical Vertical Vertical

RESULT: Pass

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.



UT Name	Wireles	ss Magnetic Spea	aker	Model Name		BRK-MS	BRK-MSMS-GLD	
Temperature22.7°C				Relative Humidity		59.8%	59.8%	
ressure	960hP	960hPa			Test Voltage DC 3.7V by battery			
Test Mode 1				Antenna Polarity		Horizont	Horizontal	
Frequency	Meter Readi	ing Factor	Emissio	n Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµ\	//m)	(dBµV/m)	(dB)	value Type	
4804.000	48.61	0.08	48.6	69	74	-25.31	peak	
4804.000	37.42	0.08	37.	5	54	-16.5	AVG	
7206.000	42.16	2.21	44.3	37	74	-29.63	peak	
7206.000	32.47	2.21	34.6	68	54	-19.32	AVG	
Remark:								
Factor = Anter	na Factor +	Cable Loss – Pre	-amplifier.					
Factor = Anter	na Factor +	Cable Loss – Pre	-amplifier.					
Factor = Anter		Cable Loss – Pre ss Magnetic Spea	•	Mode	el Name	BRK-MS	SMS-GLD	
			•		I Name	BRK-MS 59.8%	SMS-GLD	
UT Name	Wireles	ss Magnetic Spea	•	Relat		59.8%	SMS-GLD	
UT Name	Wireles 22.7℃	ss Magnetic Spea a	•	Relat	ive Humidity	59.8%		
UT Name Temperature Pressure Test Mode	Wireles 22.7°C 960hPa Mode 2	ss Magnetic Spea a 1	aker	Relat Test V Anter	ive Humidity Voltage nna Polarity	59.8% DC 3.7V Vertical		
UT Name Temperature Pressure Test Mode	Wireles 22.7℃ 960hPa Mode 2	ss Magnetic Spea a 1	aker	Relat Test V Anter	ive Humidity Voltage nna Polarity Limits	59.8% DC 3.7V Vertical Margin		
UT Name remperature ressure rest Mode	Wireles 22.7°C 960hPa Mode 2 Meter Readi (dBµV)	ss Magnetic Spea a 1 ing Factor (dB)	Emission (dBµ\	Relat Test V Anter n Level //m)	ive Humidity Voltage nna Polarity Limits (dBµV/m)	59.8% DC 3.7V Vertical Margin (dB)	' by battery - Value Type	
EUT Name Temperature Pressure Test Mode Frequency (MHz) 4804.000	Wireles 22.7 °C 960hPa Mode ^ Meter Readia (dBµV) 47.64	ss Magnetic Spea a 1 ing Factor (dB) 0.08	Emission (dBµ\ 47.7	Relat Test V Anter n Level //m)	ive Humidity Voltage nna Polarity Limits (dBµV/m) 74	59.8% DC 3.7V Vertical Margin (dB) -26.28	' by battery - Value Type peak	
EUT Name Temperature Pressure Test Mode Frequency (MHz) 4804.000 4804.000	Wireles 22.7 °C 960hPa Mode ^ Meter Readi (dBµV) 47.64 37.52	a ing Factor (dB) 0.08 0.08	Emission (dBµ\ 47.7 37.	Relat Test V Anter n Level //m) 72 6	ive Humidity Voltage nna Polarity Limits (dBµV/m) 74 54	59.8% DC 3.7V Vertical Margin (dB) -26.28 -16.4	' by battery Value Type peak AVG	
UT Name emperature ressure est Mode Frequency (MHz) 4804.000 4804.000 7206.000	Wireles 22.7 °C 960hPa Mode ^ Meter Readit (dBµV) 47.64 37.52 42.19	a ing Factor (dB) 0.08 2.21	Emission (dBµ\ 47.7 37. 44.	Relat Test V Anter n Level //m) 72 6 4	ive Humidity Voltage nna Polarity Limits (dBµV/m) 74 54 74	59.8% DC 3.7V Vertical Margin (dB) -26.28 -16.4 -29.6	Value Type Value Type AVG peak	
EUT Name Temperature Pressure Test Mode Frequency (MHz) 4804.000 4804.000	Wireles 22.7 °C 960hPa Mode ^ Meter Readi (dBµV) 47.64 37.52	a ing Factor (dB) 0.08 0.08	Emission (dBµ\ 47.7 37.	Relat Test V Anter n Level //m) 72 6 4	ive Humidity Voltage nna Polarity Limits (dBµV/m) 74 54	59.8% DC 3.7V Vertical Margin (dB) -26.28 -16.4	' by battery Value Type peak AVG	
UT Name emperature ressure est Mode Frequency (MHz) 4804.000 4804.000 7206.000	Wireles 22.7 °C 960hPa Mode ^ Meter Readit (dBµV) 47.64 37.52 42.19	a ing Factor (dB) 0.08 2.21	Emission (dBµ\ 47.7 37. 44.	Relat Test V Anter n Level //m) 72 6 4	ive Humidity Voltage nna Polarity Limits (dBµV/m) 74 54 74	59.8% DC 3.7V Vertical Margin (dB) -26.28 -16.4 -29.6	Value Type Value Type AVG peak	

Radiated Emissions Test Results for Above 1GHz

RESULT: Pass



UT Name	Wireless	Magnetic Spea	ker	Model Name		BRK-MS	BRK-MSMS-GLD	
emperature	22.7 ℃	22.7℃ 960hPa		Relative Humidity Test Voltage		59.8%	59.8% DC 3.7V by battery	
ressure	960hPa					DC 3.7\		
est Mode	Mode 2			Anten	na Polarity	Horizon	Horizontal	
Frequency	Meter Reading	Factor	Emission		Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/i	,	(dBµV/m)	(dB)		
4880.000	47.62	0.14	47.76		74	-26.24	peak	
4880.000	38.42	0.14	38.56		54	-15.44	AVG	
7320.000	42.61	2.36	44.97		74	-29.03	peak	
7320.000	31.28	2.36	33.64	4	54	-20.36	AVG	
		•			•			
Remark: Factor = Anter	nna Factor + Ca	ble Loss – Pre-	amplifier.					
		ble Loss – Pre-		Mode	I Name	BRK-MS	SMS-GLD	
Factor = Anter			iker		I Name ive Humidity	BRK-MS 59.8%	SMS-GLD	
Factor = Anter	Wireless		iker	Relati		59.8%	SMS-GLD	
Factor = Anter	Wireless 22.7℃		iker	Relati Test V	ve Humidity	59.8%		
Factor = Anter	Wireless 22.7℃ 960hPa Mode 2	Magnetic Spea	iker	Relati Test V Anter	ve Humidity /oltage na Polarity	59.8% DC 3.7 Vertical	/ by battery	
Factor = Anter	Wireless 22.7°C 960hPa Mode 2 Meter Reading	Magnetic Spea	iker Emission	Relati Test \ Anten	ive Humidity /oltage ina Polarity Limits	59.8% DC 3.7 Vertical Margin		
Factor = Anter	Wireless 22.7°C 960hPa Mode 2 Meter Reading (dBµV)	Magnetic Spea	ker Emission (dBµV/i	Relati Test V Anten	Limits (dBµV/m)	59.8% DC 3.7 Vertical Margin (dB)	/ by battery Value Type	
Factor = Anter	Wireless 22.7 °C 960hPa Mode 2 Meter Reading (dBµV) 47.91	Magnetic Spea	Emission (dBµV/r 48.05	Relati Test V Anten Level (m) 5	Limits (dBµV/m) 74	59.8% DC 3.7 Vertical Margin (dB) -25.95	/ by battery	
Factor = Anter	Wireless 22.7 °C 960hPa Mode 2 Meter Reading (dBµV) 47.91 38.42	Magnetic Spea	Emission (dBµV// 48.05	Relati Test V Anten Level (m) 5 6	Limits (dBµV/m)	59.8% DC 3.7 Vertical Margin (dB)	/ by battery Value Type peak	
Factor = Anter	Wireless 22.7 °C 960hPa Mode 2 Meter Reading (dBµV) 47.91	Magnetic Spea	Emission (dBµV/r 48.05	Relati	ive Humidity /oltage ina Polarity Limits (dBµV/m) 74 54	59.8% DC 3.7 Vertical Margin (dB) -25.95 -15.44	/ by battery Value Type peak AVG	
Factor = Anter	Wireless 22.7 °C 960hPa Mode 2 Meter Reading (dBµV) 47.91 38.42 42.34	Factor (dB) 0.14 0.14 2.36	Emission (dBµV/i 48.05 38.56 44.7	Relati	Limits (dBµV/m) 74 54 74	59.8% DC 3.7 Vertical Margin (dB) -25.95 -15.44 -29.3	/ by battery Value Type peak AVG peak	
Factor = Anter	Wireless 22.7 °C 960hPa Mode 2 Meter Reading (dBµV) 47.91 38.42 42.34	Factor (dB) 0.14 0.14 2.36	Emission (dBµV/i 48.05 38.56 44.7	Relati	Limits (dBµV/m) 74 54 74	59.8% DC 3.7 Vertical Margin (dB) -25.95 -15.44 -29.3	/ by battery Value Type peak AVG peak	

Radiated Emissions Test Results for Above 1GHz

RESULT: Pass




JT Name	e Wireless Magnetic Speaker			el Name	BRK-MS	BRK-MSMS-GLD	
mperature	22.7 ℃	- .		tive Humidity	59.8%	59.8%	
essure	960hPa			Voltage	DC 3.7V	DC 3.7V by battery	
st Mode				nna Polarity	Horizonta		
				,			
Frequency	Meter Reading	Factor	Emission Leve	Limits	Margin		
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type	
4960.000	48.62	0.22	48.84	74	-25.16	peak	
4960.000	37.42	0.22	37.64	54	-16.36	AVG	
7440.000	42.36	2.64	45	74	-29	peak	
7440.000	31.25	2.64	33.89	54	-20.11	AVG	
Remark:							
Factor = Anter	nna Factor + Cab	le Loss – Pre-	amplifier.			_	
Factor = Anter		le Loss – Pre- agnetic Speal		el Name	BRK-MS	MS-GLD	
			ker Mod	el Name tive Humidity	BRK-MS 59.8%	MS-GLD	
JT Name	Wireless M		ker Mod Rela		59.8%	MS-GLD by battery	
JT Name mperature	Wireless M 22.7℃		ker Mod Rela Test	tive Humidity	59.8%		
JT Name mperature essure st Mode	Wireless M 22.7℃ 960hPa Mode 3	agnetic Speal	ker Mod Rela Test Ante	tive Humidity Voltage nna Polarity	59.8% DC 3.7V Vertical		
IT Name mperature essure st Mode Frequency	Wireless M 22.7℃ 960hPa Mode 3 Meter Reading	agnetic Speal	ker Mod Rela Test Ante Emission Leve	tive Humidity Voltage nna Polarity	59.8% DC 3.7V Vertical Margin	by battery	
JT Name mperature essure st Mode Frequency (MHz)	Wireless M 22.7°C 960hPa Mode 3 Meter Reading (dBµV)	agnetic Speal Factor (dB)	Ker Mod Rela Test Ante Emission Leve (dBµV/m)	tive Humidity Voltage mna Polarity	59.8% DC 3.7V Vertical Margin (dB)	by battery Value Type	
JT Name mperature essure st Mode Frequency (MHz) 4960.000	Wireless M 22.7 °C 960hPa Mode 3 Meter Reading (dBµV) 47.65	agnetic Speal Factor (dB) 0.22	ker Mod Rela Test Ante (dBµV/m) 47.87	tive Humidity Voltage mna Polarity	59.8% DC 3.7V Vertical Margin (dB) -26.13	by battery Value Type peak	
JT Name mperature essure st Mode Frequency (MHz) 4960.000 4960.000	Wireless M 22.7 °C 960hPa Mode 3 Meter Reading (dBµV) 47.65 37.42	agnetic Speal Factor (dB) 0.22 0.22	ker Mod Rela Test Ante Emission Leve (dBµV/m) 47.87 37.64	tive Humidity Voltage nna Polarity Limits (dBµV/m) 74 54	59.8% DC 3.7V Vertical Margin (dB) -26.13 -16.36	by battery Value Type peak AVG	
JT Name mperature essure st Mode Frequency (MHz) 4960.000 4960.000 7440.000	Wireless M 22.7 °C 960hPa Mode 3 Meter Reading (dBµV) 47.65 37.42 41.05	Factor (dB) 0.22 2.64	ker Mod Rela Test Ante Emission Leve (dBμV/m) 47.87 37.64 43.69	tive Humidity Voltage mna Polarity Limits (dBµV/m) 74 54 74	59.8% DC 3.7V Vertical Margin (dB) -26.13 -16.36 -30.31	by battery Value Type peak AVG peak	
JT Name mperature essure st Mode Frequency (MHz) 4960.000 4960.000	Wireless M 22.7 °C 960hPa Mode 3 Meter Reading (dBµV) 47.65 37.42	agnetic Speal Factor (dB) 0.22 0.22	ker Mod Rela Test Ante Emission Leve (dBµV/m) 47.87 37.64	tive Humidity Voltage nna Polarity Limits (dBµV/m) 74 54	59.8% DC 3.7V Vertical Margin (dB) -26.13 -16.36	by battery Value Type peak AVG	
JT Name mperature essure st Mode Frequency (MHz) 4960.000 4960.000 7440.000	Wireless M 22.7 °C 960hPa Mode 3 Meter Reading (dBµV) 47.65 37.42 41.05	Factor (dB) 0.22 2.64	ker Mod Rela Test Ante Emission Leve (dBμV/m) 47.87 37.64 43.69	tive Humidity Voltage mna Polarity Limits (dBµV/m) 74 54 74	59.8% DC 3.7V Vertical Margin (dB) -26.13 -16.36 -30.31	by battery Value Type peak AVG peak	
JT Name mperature essure st Mode Frequency (MHz) 4960.000 7440.000 7440.000	Wireless M 22.7 °C 960hPa Mode 3 Meter Reading (dBµV) 47.65 37.42 41.05	Factor (dB) 0.22 2.64	ker Mod Rela Test Ante Emission Leve (dBμV/m) 47.87 37.64 43.69	tive Humidity Voltage mna Polarity Limits (dBµV/m) 74 54 74	59.8% DC 3.7V Vertical Margin (dB) -26.13 -16.36 -30.31	by battery Value Type peak AVG peak	
JT Name mperature essure st Mode Frequency (MHz) 4960.000 4960.000 7440.000 7440.000 Remark:	Wireless M 22.7 °C 960hPa Mode 3 Meter Reading (dBµV) 47.65 37.42 41.05	agnetic Speal Factor (dB) 0.22 0.22 2.64 2.64	Ker Mod Rela Rela Test Ante Emission Leve (dBµV/m) 47.87 37.64 43.69 34.99 Image: State of the state of th	tive Humidity Voltage mna Polarity Limits (dBµV/m) 74 54 74	59.8% DC 3.7V Vertical Margin (dB) -26.13 -16.36 -30.31	by battery Value Type peak AVG peak	

Radiated Emissions Test Results for Above 1GHz

RESULT: Pass

Note:


- 1. The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Pre-amplifier gain, Margin = Emission Level-Limit.
- 3. The "Factor" value can be calculated automatically by software of measurement system.






EUT Name	Wireless Magnetic Speaker	Model Name	BRK-MSMS-GLD
Temperature	22 °C	Relative Humidity	51%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 1	Antenna Polarity	Horizontal


Test Graph for Peak Measurement



Test Graph for Average Measurement




RESULT: Pass






EUT Name	Wireless Magnetic Speaker	Model Name	BRK-MSMS-GLD
Temperature	22 °C	Relative Humidity	51%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 1	Antenna Polarity	Vertical


Test Graph for Peak Measurement



Test Graph for Average Measurement




RESULT: Pass





EUT Name	Wireless Magnetic Speaker	Model Name	BRK-MSMS-GLD
Temperature	22 °C	Relative Humidity	51%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 3	Antenna Polarity	Horizontal


Test Graph for Peak Measurement



Test Graph for Average Measurement




RESULT: Pass





EUT Name	Wireless Magnetic Speaker	Model Name	BRK-MSMS-GLD
Temperature	22 °C	Relative Humidity	51%
Pressure	960hPa	Test Voltage	DC 3.7V by battery
Test Mode	Mode 3	Antenna Polarity	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: Pass

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



12. AC Power Line Conducted Emission Test

12.1 Measurement Limit


Francisco	Maximum RF Line Voltage				
Frequency	Q.P. (dBµV)	Average (dBµV)			
150kHz~500kHz	66-56	56-46			
500kHz~5MHz	56	46			
5MHz~30MHz	60	50			

Note:

1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

12.2 Measurement Setup (Block Diagram of Configuration)





12.3 Preliminary Procedure of Line Conducted Emission Test

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

12.4 Final Procedure of Line Conducted Emission Test

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.


12.5 Measurement Results





RESULT: Pass





RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com



Report No.: AGC15705240617FR01 Page 52 of 52

Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC15705240617AP01

Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC15705240617AP02

-----End of Report-----



Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.