

# FCC Test Report

Report No.: AGC157052305282FE02

FCC ID	:	2AANZSDIY
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	DIY Smart LED Strip
BRAND NAME	:	LEDEEZ
MODEL NAME	:	LE-SDIY-BLK, LE-SDIY, LE-SDIY-XXX (X is just a letter)
APPLICANT	:	DGL Group LTD.
DATE OF ISSUE	:	Jul. 21, 2023
STANDARD(S)	:	FCC Part 15.247
REPORT VERSION	:	V1.0
		sa Compliance sta







#### **REPORT REVISE RECORD**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Jul. 21, 2023	Valid	Initial Release



# **TABLE OF CONTENTS**

1. VERIFICATION OF COMPLIANCE	5
2. GENERAL INFORMATION	6
2.1. PRODUCT DESCRIPTION	6
2.2. TABLE OF CARRIER FREQUENCYS	6
2.3. RELATED SUBMITTAL(S)/GRANT(S)	7
2.4. TEST METHODOLOGY	7
2.5. SPECIAL ACCESSORIES	
2.6. EQUIPMENT MODIFICATIONS	
2.7. ANTENNA REQUIREMENT	7
3. MEASUREMENT UNCERTAINTY	8
4. DESCRIPTION OF TEST MODES	9
5. SYSTEM TEST CONFIGURATION	10
5.1. CONFIGURATION OF TESTED SYSTEM	10
5.2. EQUIPMENT USED IN TESTED SYSTEM	10
5.3. SUMMARY OF TEST RESULTS	10
6. TEST FACILITY	11
7. PEAK OUTPUT POWER	12
7.1. MEASUREMENT PROCEDURE	12
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	12
7.3. LIMITS AND MEASUREMENT RESULT	13
8. BANDWIDTH	15
8.1. MEASUREMENT PROCEDURE	15
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	15
8.3. LIMITS AND MEASUREMENT RESULTS	15
9. CONDUCTED SPURIOUS EMISSION	19
9.1. MEASUREMENT PROCEDURE	19
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	19
9.3. MEASUREMENT EQUIPMENT USED	19
9.4. LIMITS AND MEASUREMENT RESULT	19



10.1. MEASUREMENT PROCEDURE	
10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
10.3. MEASUREMENT EQUIPMENT USED	
10.4. LIMITS AND MEASUREMENT RESULT	
11. RADIATED EMISSION	28
11.1. MEASUREMENT PROCEDURE	
11.2. TEST SETUP	
11.3. LIMITS AND MEASUREMENT RESULT	30
11.4. TEST RESULT	30
12. LINE CONDUCTED EMISSION TEST	40
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST	40
12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	40
12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	41
12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	41
12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	42
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	44
APPENDIX B: PHOTOGRAPHS OF EUT	44



# **1. VERIFICATION OF COMPLIANCE**

Applicant	DGL Group LTD.
Address	2045 Lincoln Highway, 3rd Floor, Edison, NJ 08817, United States
Manufacturer	DGL Group LTD.
Address	2045 Lincoln Highway, 3rd Floor, Edison, NJ 08817, United States
Factory	N/A
Address	N/A
Product Designation	DIY Smart LED Strip
Brand Name	LEDEEZ
Test Model	LE-SDIY-BLK
Series Model	LE-SDIY, LE-SDIY-XXX (X is just a letter)
Declaration of Difference	All the same except for the model name and appearance color
Date of receipt of test item	May 29, 2023
Date of Test	May 29, 2023 - Jul. 21, 2023
Deviation	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Report Template	AGCRT-US-BLE/RF

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC part 15.247.

Zhou Cote Prepared By Sky Zhou Jul. 21, 2023 (Project Engineer) in Lin **Reviewed By** Calvin Liu Jul. 21, 2023 (Reviewer) Than Approved By Max Zhang Jul. 21, 2023 (Authorized Officer)

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com
 Web: http://www.agccert.com/



# 2. GENERAL INFORMATION

### 2.1. PRODUCT DESCRIPTION

The EUT is designed as a "DIY Smart LED Strip". It is designed by way of utilizing the GFSK technology to achieve the system operation.

A major technical description of EUT is described as following

Operation Frequency	2.402GHz to 2.480GHz
RF Output Power	2.300dBm (Max)
Bluetooth Version	V5.0
Modulation	BR⊡GFSK, EDR⊡π /4-DQPSK, ⊡8DPSK BLE⊠GFSK 1Mbps □GFSK 2Mbps
Number of channels	40 Channels
Antenna Designation	PCB Antenna (Comply with requirements of the FCC part 15.203)
Antenna Gain	0dBi
Hardware Version	V10
Software Version	V1.0
Power Supply	DC 5.0V by adapter

#### 2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency	
2400~2483.5MHz	0	2402 MHz	
	1	2404 MHz	
	:	:	
	38	2478 MHz	
	39	2480 MHz	



#### 2.3. RELATED SUBMITTAL(S)/GRANT(S)

This submittal(s) (test report) is intended for FCC ID: 2AANZSDIY filing to comply with the FCC Part 15.247 requirements.

#### 2.4. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

#### **2.5. SPECIAL ACCESSORIES**

Refer to section 5.2.

#### 2.6. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

#### 2.7. ANTENNA REQUIREMENT

This intentional radiator is designed with a permanently attached antenna of an antenna to ensure that no antenna other than that furnished by the responsible party shall be used with the device. For more information of the antenna, please refer to the APPENDIX B: PHOTOGRAPHS OF EUT.



# **3. MEASUREMENT UNCERTAINTY**

The reported uncertainty of measurement y  $\pm$ U, where expended uncertainty U is based on a standard

uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_{c} = \pm 2.7 \%$
Uncertainty of Occupied Channel Bandwidth	U <sub>c</sub> = ±2 %



### 4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel TX_2402MHz_GFSK_1Mbps
2	Middle channel TX_2440MHz_GFSK_1Mbps
3	High channel TX_2480MHz_GFSK_1Mbps

Note: 1. Only the result of the worst case was recorded in the report, if no other cases.

- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
  - 3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.

Software Setting				
R FCCTestTool V2.1				×
chip type YC11xx -	Bluetooth FCC te Frequency ModulationRate	st 2480MHZ GFSK	▼ SELECT ▼ SELECT	-
Select ROM Download	TX/RX BT/BLE/2.4G	TX BLE DATA	SELECT  SELECT  SELECT	-
ROM Path: C:\Users\admin\Desktop\ramcode.rom	Carrier/data Data Length	DH5	▼ SELECT	
set Frequency succeed set ModulationRate succeed set ModulationRate succeed set TX/RX succeed set TX/RX succeed set BT/BLF/2-46 succeed set Carrier/data succeed set Data Length succeed set Freq hop/fix succeed	Freq hop/fix	FIX	<u>SELECT</u>	-
CPU Stopped, PC 3145: downloading loading micro code 100% done. 2344 bytes of code written, 0.077s set Frequency succeed set ModulationRate succeed set TX/RX succeed set TX/RX succeed set TX/RX succeed set Carrier(Jata succeed set Carrier(Jata succeed set Freq hop/fix succeed set Freq hop/fix succeed set Freq hop/fix succeed set Frequency succeed set Frequency succeed				-
4				



# **5. SYSTEM TEST CONFIGURATION**

## **5.1. CONFIGURATION OF TESTED SYSTEM**

Radiated Emission Configure:

EUT

Conducted Emission Configure:

EUT AE

# 5.2. EQUIPMENT USED IN TESTED SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	DIY Smart LED Strip	LE-SDIY-BLK	2AANZSDIY	EUT
2	Control Box	USB-TTL	N/A	AE
3	Adapter	HW-200325CP01	DC 5V	AE

#### 5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
15.247 (b)(3)	Peak Output Power	Compliant
15.247 (a)(2)	6 dB Bandwidth	Compliant
15.247 (d)	Conducted Spurious Emission	Compliant
15.247 (e)	Maximum Conducted Output Power Density	Compliant
15.209	Radiated Emission	Compliant
15.207	Conducted Emission	Compliant



# 6. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Designation Number	CN1259
FCC Test Firm Registration Number	975832
A2LA Cert. No.	5054.02
Description	Attestation of Global Compliance (Shenzhen) Co., Ltd is accredited by A2LA

#### TEST EQUIPMENT OF CONDUCTED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESPI	101206	Jun. 03, 2023	Jun. 02, 2024
AMN	R&S	ESH2-Z5	100086	Jun. 03, 2023	Jun. 02, 2024
Test Software	R&S	ES-K1 (Ver.V1.71)	N/A	N/A	N/A

# TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESCI	100034	Jun. 03, 2023	Jun. 02, 2024
Wideband Antenna	SCHWARZBECK	VULB9168	D69250	May 11, 2023	May 10, 2025
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Jun. 01, 2023	May 31, 2024
Signal Analyzer	Aglient	N9020A	MY52090123	Jun. 03, 2023	Jun. 02, 2024
2.4GHz Filter	EM Electronics	N/A	N/A	Jun. 01, 2023	May 31, 2024
Attenuator	ZHINAN	E-002	N/A	Aug. 04, 2022	Aug. 03, 2024
Horn Antenna	SCHWARZBEC	BBHA 9170	#768	Oct. 31, 2021	Oct. 30, 2023
Active Loop Antenna (9K-30Mhz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 11, 2024
Horn Antenna	ETS	3117	00154520	Jun. 03, 2023	Jun. 02, 2024
Pre-amplifier	ETS	3117-PA	00246148	Aug. 04, 2022	Aug. 03, 2024
Test Software	FARA	V.RA-03A	N/A	N/A	N/A



# 7. PEAK OUTPUT POWER


#### 7.1. MEASUREMENT PROCEDURE

For peak power test:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. RBW ≥DTS bandwidth.
- 3. VBW≥3\*RBW.
- 4. SPAN≥VBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

#### 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) PEAK POWER TEST SETUP






Test Data of Conducted Output Power				
Test Mode	Test Channel (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail
	2402	2.300	≪30	Pass
GFSK 1M	2440	2.162	≪30	Pass
	2480	1.526	≪30	Pass



### Test Graphs of Conducted Output Power







# 8. BANDWIDTH

#### 8.1. MEASUREMENT PROCEDURE

6dB bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 kHz, VBW $\ge$ 3×RBW.
- 4. Set SPA Trace 1 Max hold, then View.

Occupied bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
  4. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.


# 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.

# 8.3. LIMITS AND MEASUREMENT RESULTS

Test Data of Occupied Bandwidth and DTS Bandwidth					
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (MHz)	-6dB Bandwidth (MHz)	Limits (MHz)	Pass or Fail
	2402	1.431	0.746	≥0.5	Pass
GFSK 1M	2440	1.435	0.746	≥0.5	Pass
	2480	1.430	0.746	≥0.5	Pass






#### Test Graphs of Occupied Bandwidth





#### Test\_Graph\_LE1M\_ANT1\_2480\_1Mbps\_OBW Test Graphs of DTS Bandwidth







Center 2.48 GHz #Res BW 100 kHz Span 3 MHz Sweep 1 ms **CF** Step #VBW 300 kHz 300.000 kHz Man Auto **Total Power** 6.86 dBm **Occupied Bandwidth** 1.4782 MHz Freq Offset 0 Hz -1.490 kHz 99.00 % **Transmit Freq Error OBW Power** x dB Bandwidth 746.3 kHz x dB -6.00 dB Test\_Graph\_LE1M\_ANT1\_2480\_1Mbps\_DTSBW



# 9. CONDUCTED SPURIOUS EMISSION

#### 9.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

#### 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.

#### 9.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.

#### 9.4. LIMITS AND MEASUREMENT RESULT


LIMITS AND MEASUREMENT RESULT				
Angliaghta Limita	Measurement Result			
Applicable Limits	Test Data	Criteria		
In any 100 kHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power.	At least -20dBc than the reference level	PASS		






#### Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands






















#### Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands



# **10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY**

#### **10.1. MEASUREMENT PROCEDURE**

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set the SPA Trace 1 Max hold, then View.

Note: The method of PKPSD in the KDB 558074 item 8.4 was used in this testing.

#### **10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)**

Refer to Section 7.2.

#### **10.3. MEASUREMENT EQUIPMENT USED**

Refer to Section 6.


#### **10.4. LIMITS AND MEASUREMENT RESULT**

	Test Data of Conducted Output Power Spectral Density				
Test Mode	Test Channel (MHz)	Power density (dBm/3kHz)	Limit (dBm/3kHz)	Pass or Fail	
	2402	-15.151	<b>≤8</b>	Pass	
GFSK 1M	2440	-15.329	≪8	Pass	
	2480	-16.022	≪8	Pass	

#### Test Graphs of Conducted Output Power Spectral Density









# **11. RADIATED EMISSION**

#### **11.1. MEASUREMENT PROCEDURE**

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.





#### 11.2. TEST SETUP

System Simulator

Radiated Emission Test-Setup Frequency Below 30MHz

#### RADIATED EMISSION TEST SETUP 30MHz-1000MHz







#### **11.3. LIMITS AND MEASUREMENT RESULT**

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

# 11.4. TEST RESULT


#### Radiated emission below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.



EUT	DIY Smart LED Strip	Model Name	LE-SDIY-BLK
Temperature	22.1°C	Relative Humidity	60.2%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal


#### Radiated emission from 30MHz to 1000MHz



#### **RESULT: PASS**



EUT	DIY Smart LED Strip	Model Name	LE-SDIY-BLK
Temperature	22.1°C	Relative Humidity	60.2%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical



### **RESULT: PASS**

Note: 1. Factor=Antenna Factor + Cable loss, Over=Measurement-Limit.

2. All test modes had been tested. The mode 1 is the worst case and recorded in the report.



#### Radiated emission above 1GHz

EUT	DIY Smart LED Strip	Model Name	LE-SDIY-BLK
Temperature	22.1°C	Relative Humidity	60.2%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin		
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type	
4804.000	48.56	0.08	48.64	74	-25.36	peak	
4804.000	38.34	0.08	38.42	54	-15.58	AVG	
7206.000	46.25	2.21	48.46	74	-25.54	peak	
7206.000	36.17	2.21	38.38	54	-15.62	AVG	
Remark:							
-actor = Anter	nna Factor + Cabl	e Loss – Pre-	amplifier.				

EUT	DIY Smart LED Strip	Model Name	LE-SDIY-BLK
Temperature	22.1°C	Relative Humidity	60.2%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4804.000	46.37	0.08	46.45	74	-27.55	peak
4804.000	37.24	0.08	37.32	54	-16.68	AVG
7206.000	44.94	2.21	47.15	74	-26.85	peak
7206.000	34.25	2.21	36.46	54	-17.54	AVG
Remark:						
actor = Anter	nna Factor + Cabl	e Loss – Pre-	amplifier			



EUT	DIY Smart LED Strip	Model Name	LE-SDIY-BLK
Temperature	22.1°C	Relative Humidity	60.2%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin		
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type	
4880.000	49.67	0.14	49.81	74	-24.19	peak	
4880.000	39.51	0.14	39.65	54	-14.35	AVG	
7320.000	47.07	2.36	49.43	74	-24.57	peak	
7320.000	36.82	2.36	39.18	54	-14.82	AVG	
Remark:							
actor = Anter	na Factor + Cab	e Loss – Pre-a	amplifier.				

EUT	DIY Smart LED Strip	Model Name	LE-SDIY-BLK
Temperature	22.1°C	Relative Humidity	60.2%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4880.000	46.83	0.14	46.97	74	-27.03	peak
4880.000	36.37	0.14	36.51	54	-17.49	AVG
7320.000	45.05	2.36	47.41	74	-26.59	peak
7320.000	34.79	2.36	37.15	54	-16.85	AVG
emark:						
Remark:						
actor = Anter	nna Factor + Cable	e Loss – Pre-	amplifier.			



EUT	DIY Smart LED Strip	Model Name	LE-SDIY-BLK
Temperature	22.1°C	Relative Humidity	60.2%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin		
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type	
4960.000	48.67	0.22	48.89	74	-25.11	peak	
4960.000	38.52	0.22	38.74	54	-15.26	AVG	
7440.000	46.79	2.64	49.43	74	-24.57	peak	
7440.000	35.47	2.64	38.11	54	-15.89	AVG	
Remark:							
actor = Anter	na Factor + Cabl	e Loss – Pre-a	amplifier.				

EUT	DIY Smart LED Strip	Model Name	LE-SDIY-BLK
Temperature	22.1°C	Relative Humidity	60.2%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Meter Reading	Factor	Emission Level	Limits	Margin	
(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
47.67	0.22	47.89	74	-26.11	peak
36.52	0.22	36.74	54	-17.26	AVG
45.75	2.64	48.39	74	-25.61	peak
34.03	2.64	36.67	54	-17.33	AVG
	(dBµV) 47.67 36.52 45.75	(dBµV)         (dB)           47.67         0.22           36.52         0.22           45.75         2.64	(dBµV)         (dB)         (dBµV/m)           47.67         0.22         47.89           36.52         0.22         36.74           45.75         2.64         48.39	(dBµV)         (dB)         (dBµV/m)         (dBµV/m)           47.67         0.22         47.89         74           36.52         0.22         36.74         54           45.75         2.64         48.39         74	(dBµV)         (dB)         (dBµV/m)         (dBµV/m)         (dB)           47.67         0.22         47.89         74         -26.11           36.52         0.22         36.74         54         -17.26           45.75         2.64         48.39         74         -25.61

|+actor = Antenna Factor + Cable Loss Pre-amplifier.

# **RESULT: PASS**

#### Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Margin=Emission Level-Limit.

The "Factor" value can be calculated automatically by software of measurement system.



EUT	DIY Smart LED Strip	Model Name	LE-SDIY-BLK
Temperature	20°C	Relative Humidity	51%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

#### Test result for band edge emission at restricted bands

Test Graph for Peak Measurement



Test Graph for Average Measurement



#### **RESULT: PASS**



#### Report No.: AGC157052305282FE02 Page 37 of 44

EUT	DIY Smart LED Strip	Model Name	LE-SDIY-BLK
Temperature	20°C	Relative Humidity	51%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



**RESULT: PASS** 



#### Report No.: AGC157052305282FE02 Page 38 of 44

EUT	DIY Smart LED Strip	Model Name	LE-SDIY-BLK
Temperature	20°C	Relative Humidity	51%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement



#### **RESULT: PASS**



EUT	DIY Smart LED Strip	Model Name	LE-SDIY-BLK
Temperature	20°C	Relative Humidity	51%
Pressure	985hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



#### **RESULT: PASS**

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



# **12. LINE CONDUCTED EMISSION TEST**


#### **12.1. LIMITS OF LINE CONDUCTED EMISSION TEST**

<b>F</b>	Maximum RF Line Voltage				
Frequency	Q.P.(dBuV)	Average(dBuV)			
150kHz~500kHz	66-56	56-46			
500kHz~5MHz	56	46			
5MHz~30MHz	60	50			

Note: 1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

# 12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





# 12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST


- The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

# 12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.





# 12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

#### MEASUREMENT RESULT: "agc\_fin"

2023/7/20 20:

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.170000 0.238000 0.478000 0.498000 1.002000 1.366000	47.50 41.50 35.10 40.60 34.20 36.00	6.1 6.1 6.1 6.2 6.2	65 62 56 56 56	17.5 20.7 21.3 15.4 21.8 20.0	QP QP QP QP QP	L1 L1 L1 L1 L1 L1	GND GND GND GND GND GND


#### MEASUREMENT RESULT: "agc fin2"

2023/7/20	20:15						
Frequenc	y Level	Transd	Limit	Margin	Detector	Line	PE
MH	lz dBµV	dB	dBµV	dB			
0.16600	0 36.00	6.1	55	19.2	AV	L1	GND
0.47400	0 27.10	6.1	46	19.3	AV	L1	GND
0.50600	0 35.40	6.2	46	10.6	AV	L1	GND
0.53400	0 29.60	6.2	46	16.4	AV	L1	GND
0.60200	0 28.40	6.2	46	17.6	AV	L1	GND
1.24200	26.60	6.2	46	19.4	AV	L1	GND

#### **RESULT: PASS**



#### LINE CONDUCTED EMISSION TEST-N



#### MEASUREMENT RESULT: "agc fin"

2023/7/20 20 Frequency MHz	:20 Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.506000 0.530000 1.354000 1.362000 1.370000 1.402000	41.20 38.90 30.90 36.40 35.20 35.90	6.2 6.2 6.2 6.2 6.2	56 56 56 56 56	14.8 17.1 25.1 19.6 20.8 20.1	QP QP QP QP QP QP	N N N N N	GND GND GND GND GND GND

#### MEASUREMENT RESULT: "agc\_fin2"

2023/7/20 Frequen	20:20 cy Level Hz dBuy		Limit dBuV	Margin dB	Detector	Line	PE
	π2 ασμν	ub ub	αbμv	uв			
0.4380	00 26.00	6.1	47	21.1	AV	N	GND
0.4700	00 27.90	6.1	47	18.6	AV	N	GND
0.5060	00 35.10	6.2	46	10.9	AV	N	GND
0.5380	00 30.40	6.2	46	15.6	AV	N	GND
0.6060	00 28.00	6.2	46	18.0	AV	N	GND
0.7380	00 24.60	6.2	46	21.4	AV	N	GND

#### **RESULT: PASS**



# APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC157052305282AP01

# **APPENDIX B: PHOTOGRAPHS OF EUT**

Refer to the Report No.: AGC157052305282AP02

----END OF REPORT----



# Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.