

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	Hover-1 Superfly Hoverboard
Test Model	H1-SPFY
Series Model	H1-SPFY-21BZ, H1-SPFY-BLK-21BZ, H1-SPFY-XXX-21BZ, DSA-SPFY, DSA-SPFY-21BZ, DSA-SPFY-BLK-21BZ, DSA-SPFY-XXX-21BZ, DSA-AH-SPFY, DSA-AH-SPFY-21BZ,
FCC ID	2AANZSPFY21B

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation.

3. CALCULATION

BR/EDR:

$$P_t = 1.050 \text{ dBm} = 1.27 \text{ mW}$$

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation $\text{SAR} = (1.27 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.480 \text{ GHz}}] = 0.40 < 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

BLE:

$$P_t = 1.396 \text{ dBm} = 1.38 \text{ mW}$$

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation $\text{SAR} = (1.38 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.480 \text{ GHz}}] = 0.43 < 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

4. CONCLUSION

The SAR evaluation is not required.