

BT

DUT: BRP AUDIO PORTABLE

Communication System: BT; Frequency: 2480 MHz;Duty Cycle: 46.72%

Medium: H2450 Medium parameters used: $f = 2480$ MHz; $\sigma = 1.833$ S/m; $\epsilon_r = 40.33$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.5 °C; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3970; ConvF(7.91, 7.91, 7.91); Calibrated: 2022/4/18;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1418; Calibrated: 2022/3/24
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1231
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

BACK-3DH5/Area Scan (9x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.00982 W/kg

BACK-3DH5/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.615 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 0.0130 W/kg

SAR(1 g) = 0.0158 W/kg; SAR(10 g) = 0.0074 W/kg

Maximum value of SAR (measured) = 0.00846 W/kg

