



# TEST REPORT

**Report Reference No.**..... : **TRE1506012801** R/C.....:76141

**FCC ID**..... : **2AAP6M1065**

**Applicant's name**..... : **SHENZHEN ZOWEE TECHNOLOGY CO., LTD.**

**Address**..... : Science &Technology Industrial Park of Privately Owned Enterprises, Pingshan, Xili, Nanshan District, Shenzhen, PR CHINA

**Manufacturer**..... : SHENZHEN ZOWEE TECHNOLOGY CO., LTD.

**Address**..... : Science &Technology Industrial Park of Privately Owned Enterprises, Pingshan, Xili, Nanshan District, Shenzhen, PR CHINA

**Test item description** ..... : **Tablet PC**

**Trade Mark** ..... : DOPO ,INSIGNIA,MEDION,Micromax,INCO,HAIER,gto,NOBIS, NUVISION,APEX

**Model/Type reference**..... : M1065

**Listed Model(s)** ..... : DPW10A-BT,NS-P10W6100, PT1065, S1065T, PC'TAB1065, P667A, Duplet III, W1058,NB1065, TM101W540L,TM101W545L

**Standard** ..... : **FCC CFR Title 47 Part 15 Subpart C Section 15.247**

**Date of receipt of test sample**.....: June 19, 2015

**Date of testing**.....: June 19, 2015- Aug 20, 2015

**Date of issue**.....: Aug 21, 2015

**Result**.....: **PASS**

Compiled by  
 ( position+printedname+signature)....: File administrators Candy Liu *Candy Liu*

Supervised by  
 (position+printedname+signature).....: Project Engineer Lion Cai *Lion Cai*

Approved by  
 (position+printedname+signature).....: RF Manager Hans Hu *Hans Hu*

**Testing Laboratory Name** ..... : **Shenzhen Huatongwei International Inspection Co., Ltd**

**Address**.....: Bldg3, Hongfa Hi-tech Industrial Park, Genyu Road, Shenzhen, China

**Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

## Contents

<b><u>1.</u></b>	<b><u>APPLICABLE STANDARDS AND TEST DESCRIPTION</u></b>	<b><u>3</u></b>
1.1.	Applicable Standards	3
1.2.	Test Description	3
<b><u>2.</u></b>	<b><u>SUMMARY</u></b>	<b><u>4</u></b>
2.1.	Client Information	4
2.2.	Product Description	4
2.3.	Operation state	5
2.4.	EUT configuration	5
2.5.	Modifications	5
<b><u>3.</u></b>	<b><u>TEST ENVIRONMENT</u></b>	<b><u>6</u></b>
3.1.	Address of the test laboratory	6
3.2.	Test Facility	6
3.3.	Equipments Used during the Test	7
3.4.	Environmental conditions	8
3.5.	Statement of the measurement uncertainty	8
<b><u>4.</u></b>	<b><u>TEST CONDITIONS AND RESULTS</u></b>	<b><u>9</u></b>
4.1.	Antenna requirement	9
4.2.	Conducted Emission (AC Main)	10
4.3.	Conducted Peak Output Power	15
4.4.	Power Spectral Density	16
4.5.	6dB bandwidth	19
4.6.	Restricted band (Conducted)	22
4.7.	Band edge and Spurious Emission (conducted)	27
4.8.	Spurious Emission (radiated)	40
<b><u>5.</u></b>	<b><u>TEST SETUP PHOTOS OF THE EUT</u></b>	<b><u>46</u></b>
<b><u>6.</u></b>	<b><u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u></b>	<b><u>47</u></b>

# 1. APPLICABLE STANDARDS AND TEST DESCRIPTION

## 1.1. Applicable Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB558074 D01 V03R02](#): Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS)

## 1.2. Test Description

ReportSection	Test Item	FCC Rule	Result
4.1	Antenna requirement	15.203/15.247 (c)	Pass
4.2	Line Conducted Emission (AC Main)	15.207	Pass
4.3	Conducted Peak Output Power	15.247 (b)(3)	Pass
4.4	Power Spectral Density	15.247 (e)	Pass
4.5	6dB Bandwidth	15.247 (a)(2)	Pass
4.6	Restricted band	15.247(d)/15.205	Pass
4.7/4.8	Spurious Emission	15.247(d)/15.209	Pass

Remark: The measurement uncertainty is not included in the test result.

## 2. SUMMARY

### 2.1. Client Information

Applicant:	SHENZHEN ZOWEE TECHNOLOGY CO., LTD.
Address:	Science & Technology Industrial Park of Privately Owned Enterprises, Pingshan, Xili, Nanshan District, Shenzhen, PR CHINA
Manufacturer:	SHENZHEN ZOWEE TECHNOLOGY CO., LTD.
Address:	Science & Technology Industrial Park of Privately Owned Enterprises, Pingshan, Xili, Nanshan District, Shenzhen, PR CHINA

### 2.2. Product Description

Name of EUT	Tablet PC
Trade Mark:	DOPO ,INSIGNIA,MEDION,Micromax,INCO,HAIER,gto,NOBIS,NUVISION, APEX
Model No.:	M1065
Listed Model(s):	DPW10A-BT,NS-P10W6100, PT1065, S1065T, PC'TAB1065, P667A, Duplet III, W1058,NB1065, TM101W540L,TM101W545L
Power supply:	DC3.70V From internal battery
Adapter information:	Model:NBS24J120150VU Input:100-240Va.c., 50/60Hz, 0.6A Output: 12.0Vd.c.,1.5A
<b>WIFI</b>	
Supported type:	802.11b/802.11g/802.11n(H20)/802.11n(H40)
Modulation:	802.11b: DSSS (DBPSK / DQPSK / CCK) 802.11g/n(H20)/n(H40): OFDM (BPSK / QPSK / 16QAM / 64QAM)
Operation frequency:	802.11b/g/n(H20): 2412MHz~2462MHz 802.11n(H40): 2422MHz~2452MHz
Channel number:	802.11b/g/n(H20): 11 802.11n(H40): 7
Channel separation:	5MHz
Antenna type:	PIFA Antenna
Antenna gain:	4.84dBi

Remark: There are two ways for connecting product's battery and trumpet ,one way is use the sector like case A,the other is change to weld directly like case B which have no obvious effect for the products' RF performance, All others are same.

### 2.3. Operation state

#### ◆ Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channel which were tested. the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

802.11b/g/n(H20)		802.11n(H40)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	01	--
02	2417	02	--
03	2422	03	2422
⋮	⋮	⋮	⋮
06	2437	06	2442
⋮	⋮	⋮	⋮
09	2452	09	2452
10	2457	10	--
11	2462	11	--

#### ◆ Data Rated

Preliminary tests were performed in different data rate, and found which the below bit rate is worst case mode, so only show data which it is a worst case mode.

Mode	datarate (worst mode)
802.11b	1Mbps
802.11g	6Mbps
802.11n(H20)	6.5Mbps (MCS0)
802.11n(H40)	13.5Mbps (MCS0)

#### ◆ Test mode

For RF test items:

the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions:

the EUT was set to connect with the WLAN AP under large package sizes transmission.

### 2.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

<input type="radio"/>	PowerCable	Length (m) :	/
		Shield :	/
		Detachable :	/
<input type="radio"/>	Multimeter	Manufacturer :	/
		Model No. :	/

### 2.5. Modifications

No modifications were implemented to meet testing criteria.

### **3. TEST ENVIRONMENT**

#### **3.1. Address of the test laboratory**

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd. (Gongming)  
Address: Bldg3, Hongfa Hi-tech Industrial Park, Genyu Road, Shenzhen, China  
Phone: 86-755-26748019 Fax: 86-755-26748089

#### **3.2. Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

##### **CNAS-Lab Code: L1225**

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories, Date of Registration: February 28, 2015. Valid time is until February 27, 2018.

##### **A2LA-Lab Cert. No. 2243.01**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing. Valid time is until Sept 30, 2015.

##### **FCC-Registration No.: 662850**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 662850, Renewal date Jul. 01, 2012, valid time is until Jun. 01, 2015.

##### **FCC-Registration No.: 317478**

Shenzhen Huatongwei International Inspection Co., Ltd. (Gongming EMC Laboratory) has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 317478, Renewal date July 18, 2014, valid time is until July. 18, 2017.

##### **IC-Registration No.: 5377A**

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377A on Dec. 31, 2013, valid time is until Dec. 31, 2016.

##### **IC-Registration No.: 5377B**

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. (Gongming EMC Laboratory) has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377B on September 3, 2014, valid time is until September 3, 2017.

##### **ACA**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

##### **VCCI**

The 3m Semi-anechoic chamber (12.2m×7.95m×6.7m) of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.:R-2484. Date of Registration: Dec. 20, 2012. Valid time is until Dec. 29, 2015.

Radiated disturbance above 1GHz measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-292. Date of Registration: Dec. 24, 2013. Valid time is until Dec. 23, 2016.

Main Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: C-2726. Date of Registration: Dec. 20, 2012. Valid time is until Dec. 19, 2015.

Telecommunication Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: T-1837. Date of Registration: May 07, 2013. Valid time is until May 06, 2016.

##### **DNV**

Shenzhen Huatongwei International Inspection Co., Ltd. has been found to comply with the requirements of DNV towards subcontractor of EMC and safety testing services in conjunction with the EMC and Low voltage Directives and in the voluntary field. The acceptance is based on a formal quality Audit and follow-ups according to relevant parts of ISO/IEC Guide 17025 (2005), in accordance with the requirements of the DNV Laboratory Quality Manual towards subcontractors. Valid time is until Aug. 24, 2016.

**3.3. Equipments Used during the Test**

Conducted Emission (AC Main)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal
1	Artificial Mains	Rohde&Schwarz	ESH2-Z5	100028	2014/11/01
2	EMI Test Receiver	Rohde&Schwarz	ESCI3	100038	2014/11/01
3	Pulse Limiter	Rohde&Schwarz	ESHSZ2	100044	2014/11/01
4	EMI Test Software	Rohde&Schwarz	ES-K1 V1.71	N/A	N/A

Radiated Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal
1	Ultra-Broadband Antenna	ShwarzBeck	VULB9163	538	2014/11/01
2	EMI TEST RECEIVER	Rohde&Schwarz	ESI 26	100009	2014/11/01
3	EMI TEST Software	Audix	E3	N/A	N/A
4	TURNTABLE	ETS	2088	2149	N/A
5	ANTENNA MAST	ETS	2075	2346	N/A
6	EMI TEST Software	Rohde&Schwarz	ESK1	N/A	N/A
7	HORNANTENNA	ShwarzBeck	9120D	1011	2014/11/01
8	Amplifer	Sonoma	310N	E009-13	2014/11/01
9	JS amplifer	Rohde&Schwarz	JS4-00101800-28-5A	F201504	2014/11/01
10	High pass filter	Compliance Direction systems	BSU-6	34202	2014/11/01
11	HORNANTENNA	ShwarzBeck	9120D	1012	2014/11/01
12	Amplifer	Compliance Direction systems	PAP1-4060	120	2014/11/01
13	Loop Antenna	Rohde&Schwarz	HFH2-Z2	100020	2014/11/01
14	TURNTABLE	MATURO	TT2.0	----	N/A
15	ANTENNA MAST	MATURO	TAM-4.0-P	----	N/A
16	Horn Antenna	SCHWARZBECK	BBHA9170	25841	2014/11/01
17	ULTRA-BROADBAND ANTENNA	Rohde&Schwarz	HL562	100015	2014/11/01

Maximum Peak Output Power / Power Spectral Density / 6dB Bandwidth / Band Edge Compliance of RF Emission / Spurious RF Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal
1	Spectrum Analyzer	Rohde&Schwarz	FSP	1164.4391.40	2014/11/01

The Cal.Interval was one year

### 3.4. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mbar

### 3.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system according to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)
Transmitter power Radiated	2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	1.60 dB	(1)
Radiated spurious emission 9KHz-40 GHz	2.20 dB	(1)
Conducted Emission 9KHz-30MHz	3.39 dB	(1)
Radiated Emission 30~1000MHz	4.24 dB	(1)
Radiated Emission 1~18GHz	5.16 dB	(1)
Radiated Emission 18-40GHz	5.54 dB	(1)
Occupied Bandwidth	-----	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=1.96$ .



## 4. TEST CONDITIONS AND RESULTS

### 4.1. Antenna requirement

#### Requirement

##### **FCC CFR Title 47 Part 15 Subpart C Section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

##### **FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):**

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

#### Test Result:

The antenna is integral antenna, the best case gain of the antenna is 4.84dBi.



WiFi/BT Antenna

## 4.2. Conducted Emission (AC Main)


### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

### TEST CONFIGURATION




### TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.

### TEST RESULTS

Test mode:AC 120V	WIFI	Polarization	L
-------------------	------	--------------	---



**MEASUREMENT RESULT: "GM0626540\_fin"**

6/26/2015 5:28PM


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.165000	53.80	10.2	65	11.4	QP	L1	GND
0.170000	53.50	10.2	65	11.5	QP	L1	GND
0.185000	44.50	10.2	64	19.8	QP	L1	GND
0.320000	29.20	10.2	60	30.5	QP	L1	GND
0.440000	33.10	10.2	57	24.0	QP	L1	GND
0.455000	32.80	10.2	57	24.0	QP	L1	GND

**MEASUREMENT RESULT: "GM0626540\_fin2"**

6/26/2015 5:28PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.170000	42.90	10.2	55	12.1	AV	L1	GND
0.225000	36.00	10.2	53	16.6	AV	L1	GND
0.450000	27.30	10.2	47	19.6	AV	L1	GND
0.490000	23.00	10.2	46	23.2	AV	L1	GND
1.445000	18.30	10.2	46	27.7	AV	L1	GND

Test mode: AC 120V	WIFI	Polarization	N
--------------------	------	--------------	---



**MEASUREMENT RESULT: "GM0626541\_fin"**

6/26/2015 5:31PM


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.165000	53.40	10.2	65	11.8	QP	N	GND
0.170000	53.20	10.2	65	11.8	QP	N	GND
0.180000	44.20	10.2	65	20.3	QP	N	GND
0.250000	34.20	10.2	62	27.6	QP	N	GND
0.335000	39.10	10.2	59	20.2	QP	N	GND
0.450000	35.10	10.2	57	21.8	QP	N	GND

**MEASUREMENT RESULT: "GM0626541\_fin2"**

6/26/2015 5:31PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.165000	41.30	10.2	55	13.9	AV	N	GND
0.225000	35.90	10.2	53	16.7	AV	N	GND
0.335000	30.00	10.2	49	19.3	AV	N	GND
0.390000	25.50	10.2	48	22.6	AV	N	GND
0.445000	27.00	10.2	47	20.0	AV	N	GND
0.505000	25.20	10.2	46	20.8	AV	N	GND

Test mode: AC 240V	WIFI	Polarization	L
--------------------	------	--------------	---



**MEASUREMENT RESULT: "GM0820510\_fin"**

8/20/2015 1:23PM


Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.177000	50.70	10.2	65	13.9	QP	L1	GND
0.181500	50.30	10.2	64	14.1	QP	L1	GND
0.231000	41.60	10.2	62	20.8	QP	L1	GND
0.276000	40.30	10.2	61	20.6	QP	L1	GND
0.357000	35.30	10.2	59	23.5	QP	L1	GND
0.456000	29.30	10.2	57	27.5	QP	L1	GND

**MEASUREMENT RESULT: "GM0820510\_fin2"**

8/20/2015 1:23PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.177000	37.20	10.2	55	17.4	AV	L1	GND
0.226500	32.90	10.2	53	19.7	AV	L1	GND
0.271500	33.20	10.2	51	17.9	AV	L1	GND
0.496500	23.30	10.2	46	22.8	AV	L1	GND
0.537000	23.10	10.2	46	22.9	AV	L1	GND
2.719500	21.50	10.3	46	24.5	AV	L1	GND

Test mode: AC 240V	WIFI	Polarization	N
--------------------	------	--------------	---



**MEASUREMENT RESULT: "GM0820509\_fin"**

8/20/2015 1:13PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.177000	52.80	10.2	65	11.8	QP	N	GND
0.222000	46.80	10.2	63	15.9	QP	N	GND
0.267000	44.30	10.2	61	16.9	QP	N	GND
0.312000	39.70	10.2	60	20.2	QP	N	GND
0.357000	37.10	10.2	59	21.7	QP	N	GND
0.537000	35.70	10.2	56	20.3	QP	N	GND

**MEASUREMENT RESULT: "GM0820509\_fin2"**

8/20/2015 1:13PM


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.181500	39.90	10.2	54	14.5	AV	N	GND
0.226500	34.40	10.2	53	18.2	AV	N	GND
0.271500	34.20	10.2	51	16.9	AV	N	GND
0.357000	29.20	10.2	49	19.6	AV	N	GND
0.532500	27.70	10.2	46	18.3	AV	N	GND
0.712500	24.10	10.2	46	21.9	AV	N	GND

### 4.3. Conducted Peak Output Power

#### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): **30dBm**

#### TEST CONFIGURATION



#### TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10: 2013 for compliance to FCC 47CFR 15.247 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector
4. Record the measurement data.

#### TEST RESULTS

Type	Channel	Output power (dBm)	Limit (dBm)	Result
802.11b	01	15.25	30.00	Pass
	06	15.26		
	11	14.87		
802.11g	01	15.24	30.00	Pass
	06	14.90		
	11	14.99		
802.11n(H20)	01	14.88	30.00	Pass
	06	14.91		
	11	14.52		
802.11n(H40)	03	14.37	30.00	Pass
	06	14.27		
	09	14.53		


### 4.4. Power Spectral Density

#### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e): **8dBm/3KHz**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### TEST CONFIGURATION



#### TEST PROCEDURE









1. Connect the antenna port(s) to the spectrum analyzer input,
2. Configure the spectrum analyzer as shown below:  
*Center frequency=DTS channel center frequency*  
*Span =1.5 times the DTS bandwidth*  
*RBW = 3 kHz ≤ RBW ≤ 100 kHz, VBW ≥ 3 × RBW*  
*Sweep time = auto couple*  
*Detector = peak*  
*Trace mode = max hold*
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.







#### TEST RESULTS

Type	Channel	Power Spectral Density(dBm/3KHz)	Limit (dBm/3KHz)	Result
802.11b	01	-10.27	8.00	Pass
	06	-11.29		
	11	-12.54		
802.11g	01	-19.60	8.00	Pass
	06	-17.35		
	11	-19.61		
802.11n(H20)	01	-18.52	8.00	Pass
	06	-19.59		
	11	-20.09		
802.11n(H40)	03	-23.22	8.00	Pass
	06	-22.29		
	09	-23.33		

Test plot as follows:







CH11

CH09


### 4.5. 6dB bandwidth

#### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2): **at least 500KHz**

*For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.*

#### TEST CONFIGURATION









#### TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).  
*Center Frequency = DTS channel center frequency*  
*Span = 2 x DTS bandwidth*  
*RBW = 100 kHz, VBW ≥ 3 x RBW*  
*Sweep time = auto couple*  
*Detector = Peak*  
*Trace mode = max hold*
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

#### TEST RESULTS







Type	Channel	6dB Bandwidth(MHz)	Limit (KHz)	Result
802.11b	01	10.08	≥500	Pass
	06	10.08		
	11	10.08		
802.11g	01	16.44	≥500	Pass
	06	16.50		
	11	16.50		
802.11n(H20)	01	17.70	≥500	Pass
	06	17.70		
	11	17.70		
802.11n(H40)	03	35.90	≥500	Pass
	06	35.90		
	09	35.80		

Test plot as follows:



CH11

CH11



CH11

CH09


## 4.6. Restricted band (Conducted)

### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

*In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).*

### TEST CONFIGURATION



### TEST PROCEDURE

1. According to KDB 558074 D01 V03R02 for Antenna-port conducted measurement. Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands.
  - 1) Measure the conducted output power (in dBm) using the Peak /averagedetector
  - 2) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level
  - 3) Add the appropriate maximum ground reflection factor to the EIRP level
    - 6 dB for frequencies  $\leq 30$  MHz
    - 4.7 dB for frequencies between 30 MHz and 1000 MHz
    - 0 dB for frequencies  $> 1000$  MHz
  - 4) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms
  - 5) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:  

$$E = \text{EIRP} - 20\log D + 104.8$$
 where:  
 E = electric field strength in dB $\mu$ V/m,  
 EIRP = equivalent isotropic radiated power in dBm  
 D = specified measurement distance in meters.
  - 6) Compare the resultant electric field strength level to the applicable limit
2. **Peak power measurement procedure**  
 Peak emission levels are measured by setting the instrument as follows  
 RBW = 1MHz, VBW  $\geq 3 \times$  RBW  
 Detector = Peak, Sweep time = auto  
 Trace mode = max hold  
 Allow sweeps to continue until the trace stabilizes.

*If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement*

### 3. **Average power measurement procedure**


Duty cycle  $< 98$  percent, but the duty cycle is not constant

- a) RBW = 1 MHz, VBW  $\geq 1/T$ .
- b) Video bandwidth mode or display mode
  - 1) The instrument shall be set to ensure that video filtering is applied in the power domain. Typically, this requires setting the detector mode to RMS and setting the Average-VBW Type to Power (RMS).
  - 2) As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some

instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode.

- c) Detector = Peak, Sweep time = auto.
- d) Trace mode = max hold.
- e) Allow max hold to run for at least 50 times (1/duty cycle) traces.


**TEST RESULTS**



Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level at 3m (dBuV/m)	Limit (dBuV/m)	Result	Test Value
2390.00	-40.94	4.78	0.00	59.10	74.00	Pass	Peak
2483.50	-46.79	4.78	0.00	53.25	74.00	Pass	
2390.00	-58.18	4.78	0.00	41.86	54.00	Pass	
2483.50	-58.12	4.78	0.00	42.89	54.00	Pass	

Note:

EIRP=Conducted Power + Antenna Gain + Ground Reflection factor  
 E = EIRP – 20log D + 104.8




Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level at 3m (dBuV/m)	Limit (dBuV/m)	Result	Test Value
2390.00	-41.78	4.84	0.00	58.32	74.00	Pass	Peak
2483.50	-42.40	4.84	0.00	57.70	74.00	Pass	
2390.00	-59.26	4.84	0.00	40.84	54.00	Pass	Average
2483.50	-58.65	4.84	0.00	41.45	54.00	Pass	

Note:

$EIRP = \text{Conducted Power} + \text{Antenna Gain} + \text{Ground Reflection factor}$

$E = EIRP - 20\log D + 104.8$






Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level at 3m (dBuV/m)	Limit (dBuV/m)	Result	Test Value
2390.00	-39.99	4.84	0.00	60.11	74.00	Pass	Peak
2483.50	-41.06	4.84	0.00	59.04	74.00	Pass	
2390.00	-58.45	4.84	0.00	41.65	54.00	Pass	Average
2483.50	-58.18	4.84	0.00	41.92	54.00	Pass	

Note:

EIRP=Conducted Power + Antenna Gain + Ground Reflection factor

E = EIRP – 20log D + 104.8



Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level at 3m (dBuV/m)	Limit (dBuV/m)	Result	Test Value
2390.00	-39.51	4.84	0.00	60.59	74.00	Pass	Peak
2483.50	-40.86	4.84	0.00	59.24	74.00	Pass	
2390.00	-41.30	4.84	0.00	58.80	54.00	Pass	Average
2483.50	-58.96	4.84	0.00	41.14	54.00	Pass	

Note:

EIRP=Conducted Power + Antenna Gain + Ground Reflection factor

E = EIRP – 20log D + 104.8


## 4.7. Band edge and Spurious Emission (conducted)

### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

*In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.*

### TEST CONFIGURATION



### TEST PROCEDURE


1. Connect the antenna port(s) to the spectrum analyzer input.
2. **Establish a reference level by using the following procedure**  
*Center frequency=DTS channel center frequency*  
*The span = 1.5 times the DTS bandwidth.*  
*RBW = 100 kHz, VBW ≥ 3 x RBW*  
*Detector = peak, Sweep time = auto couple, Trace mode = max hold*  
*Allow trace to fully stabilize*  
*Use the peak marker function to determine the maximum PSD level*


Note that the channel found to contain the maximum PSD level can be used to establish the reference level.


3. **Emission level measurement**  
Set the center frequency and span to encompass frequency range to be measured  
RBW = 100 kHz, VBW ≥ 3 x RBW  
Detector = peak, Sweep time = auto couple, Trace mode = max hold  
Allow trace to fully stabilize  
Use the peak marker function to determine the maximum amplitude level.
4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
5. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emissions relative to the limit.


### TEST RESULTS


Test plot as follows:


































### 4.8. Spurious Emission (radiated)


#### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

#### TEST CONFIGURATION


- 9KHz ~30MHz



- 30MHz ~ 1GHz



- Above 1GHz





**TEST PROCEDURE**

1. The EUT was setup according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. Use the following spectrum analyzer settings
  - (1) Span shall be wide enough to fully capture the emission being measured;
  - (2) Below 1GHz, RBW=120KHz, VBW=300KHz, Sweep=auto, Detector function=peak, Trace=max hold;  
*If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.*
  - (3) Above 1GHz, RBW=1MHz, VBW=3MHz for Peak value  
RBW=1MHz, VBW=10Hz for Average value.

**TEST RESULTS**


*Noted:*

*Have pre-scan all modulation mode, found the 802.11b mode which it was worst case, so only the worst case's data on the test report.*

**Measurement data:****■ 9kHz ~ 30MHz**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.


**■ 30MHz ~ 1GHz**



**MEASUREMENT RESULT: "GM08206055\_red"**

8/20/2015 5:27PM

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
138.640000	27.70	-18.1	43.5	15.8	QP	300.0	359.00	HORIZONTAL
210.420000	23.50	-14.0	43.5	20.0	QP	100.0	97.00	HORIZONTAL
304.510000	39.40	-13.6	46.0	6.6	QP	100.0	171.00	HORIZONTAL
368.530000	42.10	-11.6	46.0	3.9	QP	100.0	154.00	HORIZONTAL
394.720000	37.20	-10.9	46.0	8.8	QP	100.0	195.00	HORIZONTAL
948.590000	34.40	3.7	46.0	11.6	QP	100.0	5.00	HORIZONTAL



**MEASUREMENT RESULT: "GM08206056\_red"**

8/20/2015 5:29PM

Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
85.290000	31.20	-17.3	40.0	8.8	QP	100.0	292.00	VERTICAL
110.510000	30.80	-15.1	43.5	12.7	QP	100.0	175.00	VERTICAL
140.580000	35.50	-18.2	43.5	8.0	QP	100.0	292.00	VERTICAL
302.570000	35.20	-13.7	46.0	10.8	QP	100.0	232.00	VERTICAL
369.500000	37.20	-11.6	46.0	8.8	QP	100.0	331.00	VERTICAL
959.260000	34.80	3.9	46.0	11.2	QP	100.0	257.00	VERTICAL

## Above 1GHz

CH01 for 802.11b									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
4831.96	45.35	31.1	9.22	38.55	47.12	74.00	-26.88	Vertical	Peak
7242.05	38.86	36.0	10.87	38.11	47.62	74.00	-26.38	Vertical	
11500.02	35.58	39.1	13.49	37.88	50.29	74.00	-23.71	Vertical	
12160.00	*					74.00		Vertical	
4831.96	47.07	31.1	9.22	38.55	48.84	74.00	-25.16	Horizontal	
7242.05	39.16	36.0	10.87	38.11	47.92	74.00	-26.08	Horizontal	
9669.16	40.34	38.2	12.17	38.08	52.63	74.00	-21.37	Horizontal	
12160.00	*					74.00		Horizontal	
4831.96	33.59	31.1	9.22	38.55	35.36	54.00	-18.64	Vertical	Average
7242.05	26.52	36	10.87	38.11	35.28	54.00	-18.72	Vertical	
11500.02	24.08	39.1	13.49	37.88	38.79	54.00	-15.21	Vertical	
12160.00	*					54.00		Vertical	
4831.96	34.92	31.1	9.22	38.55	36.69	54.00	-17.31	Horizontal	
7242.05	27.08	36	10.87	38.11	35.84	54.00	-18.16	Horizontal	
9669.16	27.67	38.2	12.17	38.08	39.96	54.00	-14.04	Horizontal	
12160.00	*					54.00		Horizontal	
CH06 for 802.11b									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
4941.03	39.54	31.17	9.31	38.62	47.09	74.00	-26.91	Vertical	Peak
7413.52	35.86	36.13	10.93	38.14	46.55	74.00	-27.45	Vertical	
9748.00	37.79	37.45	8.84	35.53	46.40	74.00	-27.60	Vertical	
12185.00	*					74.00		Vertical	
4941.03	42.33	31.17	9.31	38.62	49.98	74.00	-24.02	Horizontal	
7413.52	37.78	36.13	10.93	38.14	48.55	74.00	-25.45	Horizontal	
9748.00	38.20	37.45	8.84	35.53	51.28	74.00	-22.72	Horizontal	
12185.00	*					74.00		Horizontal	
4941.03	33.37	31.17	9.31	38.62	35.23	54.00	-18.77	Vertical	Average
7413.52	25.51	36.13	10.93	38.14	34.43	54.00	-19.57	Vertical	
9748.00	23.87	37.45	8.84	35.53	34.63	54.00	-19.37	Vertical	
12185.00	*					54.00		Vertical	
4941.03	35.83	31.17	9.31	38.62	37.69	54.00	-16.31	Horizontal	
7413.52	27.26	36.13	10.93	38.14	36.18	54.00	-17.82	Horizontal	
9748.00	28.56	37.45	8.84	35.53	39.32	54.00	-14.68	Horizontal	
12185.00	*					54.00		Horizontal	

## Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.


CH11 for 802.11b									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
4944.99	45.36	31.17	9.31	38.62	47.22	74.00	-26.78	Vertical	Peak
8013.02	35.45	36.72	11.24	38.24	45.17	74.00	-28.83	Vertical	
9895.35	37.16	38.33	12.39	38.12	49.76	74.00	-24.24	Vertical	
12340.00	*					74.00		Vertical	
4944.99	49.00	31.17	9.31	38.62	50.86	74.00	-23.14	Horizontal	
7411.46	39.42	36.13	10.93	38.14	48.34	74.00	-25.66	Horizontal	
9895.35	41.02	38.33	12.39	38.12	53.62	74.00	-20.38	Horizontal	
12340.00	*					74.00		Horizontal	
4944.99	33.48	31.17	9.31	38.62	35.34	54.00	-18.66	Vertical	Average
8013.02	23.54	36.72	11.24	38.24	33.26	54.00	-20.74	Vertical	
9895.35	24.98	38.33	12.39	38.12	37.58	54.00	-16.42	Vertical	
12340.00	*					54.00		Vertical	
4944.99	37.17	31.17	9.31	38.62	39.03	54.00	-14.97	Horizontal	
7411.46	27.50	36.13	10.93	38.14	36.42	54.00	-17.58	Horizontal	
9895.35	28.93	38.33	12.39	38.12	41.53	54.00	-12.47	Horizontal	
12340.00	*					54.00		Horizontal	

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

## 5. Test Setup Photos of the EUT

Radiated Emission



Conducted Emission (AC Mains)



## 6. External and Internal Photos of the EUT

### External Photos of the EUT











### Internal Photos of the EUT

Case A:






SOCTOR


SOCTOR

SOCTOR

WIFI/BT Antenna







Case B:





Weld with wire

Weld with wire

Weld with wire

.....End of Report.....