



TEST REPORT

Report Reference No...... : **TRE1410009402** R/C.....:53771
FCC ID..... : **2AAP6M7054**
Applicant's name..... : **SHENZHEN ZOWEE TECHNOLOGY CO.,LTD**
Address..... : Science &Technology Industrial Park of Privately Owned Enterprises, Pingshan, Xili, Nanshan District, Shenzhen, PR CHINA
Manufacturer..... : SHENZHEN ZOWEE TECHNOLOGY CO.,LTD
Address..... : Science &Technology Industrial Park of Privately Owned Enterprises, Pingshan, Xili, Nanshan District, Shenzhen, PR CHINA
Test item description : **Internet Tablet**
Trade Mark : TMAX,APEX,DOPO,NOBIS,DAGE, NOVISION
Model/Type reference..... : M7054
Listed Model(s) : DPM7828,DPM7827,DPM7826, TM7005, TM7006, TM7008, NB7856, NB7866
Standard : **FCC CFR Title 47 Part 15 Subpart C Section 15.247**
Date of receipt of test sample..... : Oct 24, 2014
Date of testing..... : Oct 25 ~ Nov 04, 2014
Date of issue..... : Nov 04, 2014
Result..... : **PASS**

Compiled by
 (position+printed name+signature)...: File administrators Any Yang

Any Yang

Supervised by
 (position+printed name+signature)...: Project Engineer Lion Cai

Lion Cai

Approved by
 (position+printed name+signature)...: RF Manager Hans Hu

Hans Hu

Testing Laboratory Name : **Shenzhen Huatongwei International Inspection Co., Ltd**
Address..... : Bldg3, Hongfa Hi-tech Industrial Park, Genyu Road, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Contents

1.	<u>TEST STANDARDS AND TEST DESCRIPTION</u>	3
1.1.	Test Standards	3
1.2.	Test Description	3
2.	<u>SUMMARY</u>	4
2.1.	Client Information	4
2.2.	Product Description	4
2.3.	EUT operation mode	5
2.4.	EUT configuration	5
2.5.	Modifications	5
3.	<u>TEST ENVIRONMENT</u>	6
3.1.	Address of the test laboratory	6
3.2.	Test Facility	6
3.3.	Environmental conditions	7
3.4.	Statement of the measurement uncertainty	7
3.5.	Equipments Used during the Test	8
4.	<u>TEST CONDITIONS AND RESULTS</u>	9
4.1.	Antenna requirement	9
4.2.	Conducted Emission (AC Main)	10
4.3.	Conducted Peak Output Power	13
4.4.	Power Spectral Density	15
4.5.	6dB bandwidth	17
4.6.	Band Edge	19
4.7.	Spurious Emission (conducted)	22
4.8.	Spurious Emission (radiated)	26
5.	<u>TEST SETUP PHOTOS OF THE EUT</u>	32
6.	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	33

1. TEST STANDARDS AND TEST DESCRIPTION

1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB558074 D01 V03R02](#): Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247

1.2. Test Description

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
Line Conducted Emission (AC Main)	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	Pass
Power Spectral Density	15.247 (e)	Pass
6dB Bandwidth	15.247 (a)(2)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Remark: The measurement uncertainty is not included in the test result.

2. SUMMARY

2.1. Client Information

Applicant:	SHENZHEN ZOWEE TECHNOLOGY CO.,LTD
Address:	Science &Technology Industrial Park of Privately Owned Enterprises, Pingshan, Xili, Nanshan District, Shenzhen, PR CHINA
Manufacturer:	SHENZHEN ZOWEE TECHNOLOGY CO.,LTD
Address:	Science &Technology Industrial Park of Privately Owned Enterprises, Pingshan, Xili, Nanshan District, Shenzhen, PR CHINA

2.2. Product Description

Name of EUT	Internet Tablet
Trade Mark:	TMAX,APEX,DOPO,NOBIS,DAGE, NOVISION
Model No.:	M7054
Listed Model(s):	DPM7828,DPM7827,DPM7826, TM7005, TM7006, TM7008, NB7856, NB7866
Power supply:	DC 3.7V From Internal Battery
Adapter information:	Model No.:JK050150-S02USU Input: AC 100-240V~, 50/60Hz, 0.3A Output: DC 5.0V 1.5A
BT4.0+BLE	
Supported type:	Supported BT4.0+EDR (compatible)
Modulation:	GFSK
Operation frequency:	2402MHz~2480MHz
Channel number:	40
Channel separation:	2MHz
Antenna type:	Internal Antenna
Antenna gain:	2.0dBi

Operation Frequency List:

Channel	Frequency (MHz)
0	2402
1	2404
⋮	⋮
18	2438
19	2440
20	2442
⋮	⋮
38	2478
39	2480

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

2.3. EUT operation mode

The EUT has been tested under test mode condition. The Applicant provides software to control the EUT for staying in continuous transmitting and receiving mode for testing.

The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

2.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

<input type="radio"/>	Power Cable	Length (m) :	/
		Shield :	/
		Detachable :	/
<input type="radio"/>	Multimeter	Manufacturer :	/
		Model No. :	/

2.5. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Test Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd
Address: Bldg3, Hongfa Hi-tech Industrial Park, Genyu Road, Shenzhen, China
Phone: 86-755-26715686 Fax: 86-755-26748089

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories, Date of Registration: Mar. 01, 2012. Valid time is until February 28, 2015.

A2LA-Lab Cert. No. 2243.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing. Valid time is until Sept 30, 2015.

FCC-Registration No.: 662850

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 662850, Renewal date Jul. 01, 2012, valid time is until Jun. 01, 2015.

FCC-Registration No.: 317478

Shenzhen Huatongwei International Inspection Co., Ltd. (Gongming EMC Laboratory) has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 317478, Renewal date July 18, 2014, valid time is until July. 18, 2017.

IC-Registration No.: 5377A

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377A on Dec. 31, 2013, valid time is until Dec. 31, 2016.

IC-Registration No.: 5377B

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. (Gongming EMC Laboratory) has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377B on September 3, 2014, valid time is until September 3, 2017.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

VCCI

The 3m Semi-anechoic chamber (12.2m×7.95m×6.7m) of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.:R-2484. Date of Registration: Dec. 20, 2012. Valid time is until Dec. 29, 2015.

Radiated disturbance above 1GHz measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-292. Date of Registration: Dec. 24, 2013. Valid time is until Dec. 23, 2016.

Main Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: C-2726. Date of Registration: Dec. 20, 2012. Valid time is until Dec. 19, 2015.

Telecommunication Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: T-1837. Date of Registration: May 07, 2013. Valid time is until May 06, 2016.

DNV

Shenzhen Huatongwei International Inspection Co., Ltd. has been found to comply with the requirements of DNV towards subcontractor of EMC and safety testing services in conjunction with the EMC and Low voltage Directives and in the voluntary field. The acceptance is based on a formal quality Audit and follow-ups according to relevant parts of ISO/IEC Guide 17025 (2005), in accordance with the requirements of the DNV Laboratory Quality Manual towards subcontractors. Valid time is until Aug. 24, 2016.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

3.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system according to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)
Transmitter power Radiated	2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	1.60 dB	(1)
Radiated spurious emission 9KHz-40 GHz	2.20 dB	(1)
Conducted Emission 9KHz-30MHz	3.39 dB	(1)
Radiated Emission 30~1000MHz	4.24 dB	(1)
Radiated Emission 1~18GHz	5.16 dB	(1)
Radiated Emission 18-40GHz	5.54 dB	(1)
Occupied Bandwidth	-----	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

3.5. Equipments Used during the Test

AC Power Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal Due
1	Artificial Mains	Rohde&Schwarz	ESH2-Z5	100028	2015/11/01
2	EMI Test Receiver	Rohde&Schwarz	ESCI3	100038	2015/11/01
3	Pulse Limiter	Rohde&Schwarz	ESHSZ2	100044	2015/11/01
4	EMI Test Software	Rohde&Schwarz	ES-K1 V1.71	N/A	N/A

Radiated Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal Due
1	Ultra-Broadband Antenna	ShwarzBeck	VULB9163	538	2015/11/01
2	EMI TEST RECEIVER	Rohde&Schwarz	ESI 26	100009	2015/11/01
3	EMI TEST Software	Audix	E3	N/A	N/A
4	TURNTABLE	ETS	2088	2149	N/A
5	ANTENNA MAST	ETS	2075	2346	N/A
6	EMI TEST Software	Rohde&Schwarz	ESK1	N/A	N/A
7	HORN ANTENNA	ShwarzBeck	9120D	1011	2015/11/01
8	Amplifer	Sonoma	310N	E009-13	2015/11/01
9	JS amplifer	Rohde&Schwarz	JS4-00101800-28-5A	F201504	2015/11/01
10	High pass filter	Compliance Direction systems	BSU-6	34202	2015/11/01
11	HORN ANTENNA	ShwarzBeck	9120D	1012	2015/11/01
12	Amplifer	Compliance Direction systems	PAP1-4060	120	2015/11/01
13	Loop Antenna	Rohde&Schwarz	HFH2-Z2	100020	2015/11/01
14	TURNTABLE	MATURO	TT2.0	----	N/A
15	ANTENNA MAST	MATURO	TAM-4.0-P	----	N/A
16	Horn Antenna	SCHWARZBECK	BBHA9170	25841	2015/11/01
17	ULTRA-BROADBAND ANTENNA	Rohde&Schwarz	HL562	100015	2015/11/01

Maximum Peak Output Power / Power Spectral Density / 6dB Bandwidth / Band Edge Compliance of RF Emission / Spurious RF Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal Due
1	Spectrum Analyzer	Rohde&Schwarz	FSP	1164.4391.40	2015/11/01
2	Power Meter	Anritsu	MA2411B	100258	2015/11/01

The Cal.Interval was one year

4. TEST CONDITIONS AND RESULTS

4.1. Antenna requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Test Result:

The antenna is integral antenna, the best case gain of the antenna is 2.0 dBi



4.2. Conducted Emission (AC Main)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION




TEST PROCEDURE

1. The EUT was setup according to ANSI C63.4: 2009 and tested according to ANSI C63.10:2009 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.

TEST RESULTS

Test mode:	Polarization	L
------------	--------------	---

SCAN TABLE: "Voltage (9K-30M)FIN"
 Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "CE1401028001_fin"

10/28/2014 10:15AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.154000	45.00	12.3	66	19.8	QP	L1	GND
0.242000	42.50	11.8	62	19.5	QP	L1	GND
0.358000	39.50	10.9	59	19.3	QP	L1	GND
0.470000	34.10	10.1	57	22.4	QP	L1	GND
1.726000	37.60	10.1	56	13.4	QP	L1	GND


MEASUREMENT RESULT: "CE1401028001_fin2"

10/28/2014 10:15AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.330000	31.90	11.2	50	17.6	AV	L1	GND
0.374000	32.90	10.8	48	15.5	AV	L1	GND
0.462000	27.10	10.1	47	19.6	AV	L1	GND
1.770000	27.90	10.1	46	13.1	AV	L1	GND

Test mode:		Polarization	N
------------	--	--------------	---

SCAN TABLE: "Voltage (9K-30M)FIN"
 Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "CE1401028000_fir"

10/28/2014 10:11AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.154000	45.80	12.3	66	20.0	QP	N	GND
0.158000	45.80	12.3	66	19.8	QP	N	GND
0.202000	42.00	12.0	64	21.5	QP	N	GND
0.246000	40.90	11.8	62	21.0	QP	N	GND
1.406000	36.20	10.1	56	19.8	QP	N	GND

MEASUREMENT RESULT: "CE1401028000_fir2"

10/28/2014 10:11AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.158000	29.20	12.3	56	26.4	AV	N	GND
0.358000	31.10	10.9	49	17.7	AV	N	GND
1.046000	20.40	10.1	46	25.6	AV	N	GND
1.298000	21.30	10.1	46	24.7	AV	N	GND
1.754000	22.60	10.1	46	23.4	AV	N	GND

4.3. Conducted Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): **30dBm**

TEST CONFIGURATION




TEST PROCEDURE


1. The EUT was tested according to ANSI C63.10: 2009 and KDB 558074 D01 V03R02 for compliance to FCC 47CFR 15.247 requirements.
2. Connect the antenna port(s) to the spectrum analyzer input,
3. Configure the spectrum analyzer as shown below:
 Center frequency=DTS channel center frequency
 Set the RBW \geq DTS bandwidth, VBW $\geq 3 \times$ RBW, Span $\geq 3 \times$ RBW
 Sweep time = auto couple
 Detector = peak
 Trace mode = max hold
4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
5. Use the peak marker function to determine the maximum amplitude level within the RBW.
6. Record the measurement data.

TEST RESULTS


Channel	Output power (dBm)	Limit (dBm)	Result
0	0.35	30.00	Pass
19	0.59		
39	0.09		



CH0



CH19



CH39

4.4. Power Spectral Density

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e): **8dBm/3KHz**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST CONFIGURATION




TEST PROCEDURE

1. According to KDB 558074 D01 V03R02 Method PKPSD (peak PSD) This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.
2. Analyzer set:
Center frequency =Channel center frequency
RBW =3 kHz~100 kHz, VBW ≥3RBW, Detector=Peak, Span=1.5 times the bandwidth
3. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
4. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


TEST RESULTS

Channel	Power Spectral Density (dBm/3KHz)	Limit (dBm/3KHz)	Result
0	-14.57	8.00	Pass
19	-14.36		
39	-14.58		


Test plot as follows:



CH0



CH19



CH39

4.5. 6dB bandwidth

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2): **at least 500KHz**

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer
2. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.
3. According to KDB 558074 D01 V03R02 for one of the following procedures may be used to determine the modulated DTS device signal bandwidth.
Center frequency =Channel center frequency
RBW =100 kHz, VBW ≥3RBW, Detector=Peak,
4. Allow the trace to stabilize.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST RESULTS

Channel	6dB Bandwidth (KHz)	Limit (KHz)	Result
0	729.81	≥ 500	Pass
19	728.90		
39	727.67		

Test plot as follows:

<p>Agilent R T</p> <p>Ch Freq 2.402 GHz Trig Free</p> <p>Occupied Bandwidth</p>		<p>Freq/Channel</p> <p>Center Freq 2.40200000 GHz</p> <p>Start Freq 2.40100000 GHz</p> <p>Stop Freq 2.40300000 GHz</p> <p>CF Step 200.000000 kHz <small>Auto Man</small></p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On <small>Off</small></p> <p>Scale Type Log <small>Lin</small></p>
<p>Ref 11 dBm #Atten 20 dB</p> <p>Center 2.402 GHz Span 2 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 5 ms (401 pts)</p>		
<p>Occupied Bandwidth Occ BW % Pwr 99.00 %</p> <p>1.0327 MHz x dB -6.00 dB</p> <p>Transmit Freq Error -584.451 Hz</p> <p>x dB Bandwidth 729.817 kHz</p>		

CHO

<p>Agilent R T</p> <p>Ch Freq 2.44 GHz Trig Free</p> <p>Occupied Bandwidth</p>		<p>Freq/Channel</p> <p>Center Freq 2.44000000 GHz</p> <p>Start Freq 2.43900000 GHz</p> <p>Stop Freq 2.44100000 GHz</p> <p>CF Step 200.000000 kHz <small>Auto Man</small></p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On <small>Off</small></p> <p>Scale Type Log <small>Lin</small></p>
<p>Ref 11 dBm #Atten 20 dB</p> <p>Center 2.44 GHz Span 2 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 5 ms (401 pts)</p>		
<p>Occupied Bandwidth Occ BW % Pwr 99.00 %</p> <p>1.0351 MHz x dB -6.00 dB</p> <p>Transmit Freq Error -699.375 Hz</p> <p>x dB Bandwidth 728.908 kHz</p>		

CH19

<p>Agilent R T</p> <p>Ch Freq 2.48 GHz Trig Free</p> <p>Occupied Bandwidth</p>		<p>Meas Setup</p> <p>Avg Number 10 On <small>Off</small></p> <p>Avg Mode Exp <small>Repeat</small></p> <p>Max Hold On <small>Off</small></p> <p>Occ BW % Pwr 99.00 %</p> <p>OBW Spar 2.00000000 MHz</p> <p>x dB -6.00 dB</p> <p>Optimize Ref Level</p>
<p>Ref 11 dBm #Atten 20 dB</p> <p>Center 2.48 GHz Span 2 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 5 ms (401 pts)</p>		
<p>Occupied Bandwidth Occ BW % Pwr 99.00 %</p> <p>1.0367 MHz x dB -6.00 dB</p> <p>Transmit Freq Error -50.845 Hz</p> <p>x dB Bandwidth 727.672 kHz</p>		

CH39

4.6. Band Edge

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION




TEST PROCEDURE

1. According to KDB 558074 D01 V03R02 for Antenna-port conducted measurement. Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz for peak detector and RBW=1MHz, VBW=10Hz, Peak detector for average measurement.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.
6. Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency
7. Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level
8. Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies \leq 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies $>$ 1000 MHz).
9. For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
10. Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:


$$E = \text{EIRP} - 20\log D + 104.8$$
 where:
 E = electric field strength in dB μ V/m,
 EIRP = equivalent isotropic radiated power in dBm
 D = specified measurement distance in meters.
11. Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.
12. Compare the resultant electric field strength level to the applicable regulatory limit.
13. Perform radiated spurious emission test dures until all measured frequencies were complete.

TEST RESULTS

Mode: **GFSK** Test channel: **2402MHz**




Peak




Average

Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level at 3m (dBuV/m)	Detector	Limit (dBuV/m)	Result
2390.00	-49.38	2.00	0.00	47.88	Peak	74.00	Pass
2402.15	0.35	2.00	0.00	97.61	Peak		Pass
2390.00	-57.95	2.00	0.00	39.31	Average	54.00	Pass
2402.12	-7.60	2.00	0.00	89.66	Average		Pass

Mode: **GFSK** Test channel: **2480MHz**



Peak



Average

Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level at 3m (dBuV/m)	Detector	Limit (dBuV/m)	Result
2480.09	0.50	2.00	0.00	97.76	Peak		Pass
2483.50	-33.66	2.00	0.00	63.60	Peak	74.00	Pass
2479.98	-16.87	2.00	0.00	80.39	Average		Pass
2483.50	-44.23	2.00	0.00	53.03	Average	54.00	Pass

4.7. Spurious Emission (conducted)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE


1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=100 KHz and VBW=300KHz, scan up through 10th harmonic

TEST RESULTS

Test plot as follows:


Test channel

2402MHz



30MHz~3GHz



3GHz~15GHz



15GHz~26.5GHz


Test channel

2440MHz



30MHz~3GHz



3GHz~15GHz



15GHz~26.5GHz


Test channel

2480MHz



30MHz~3GHz

3GHz~15GHz



15GHz~26.5GHz

4.8. Spurious Emission (radiated)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION

- Below 1GHz



- Above 1GHz



TEST PROCEDURE


1. The EUT was setup according to ANSI C63.4: 2009 and tested according to ANSI C63.10:2009 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4:2009 on radiated measurement.
5. The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.
6. For Frequencies below 1 GHz, RBW= 120 kHz, testing was performed with CISPR16 compliant test receiver with QP detector. Above 1 GHz tests were performed using a spectrum analyser using the following settings:
Peak RBW=VBW= 1MHz , Peak detector
Average RBW 1MHz , VBW=10Hz, Peak detector
7. These settings as per ANSI C63.10

TEST RESULTS***For 9KHz to 30MHz***

Frequency (MHz)	Level (dBuV/m)@3m	Limit Line (dBuV/m)@3m	Margin (dB)	Detector	Result
13.45	42.37	69.54	-27.17	QP	PASS
24.63	40.85	69.54	-28.69	QP	PASS

Measurement data:


■ Below 1GHz



MEASUREMENT RESULT: "RE141030010_red"

10/30/2014 7:56PM

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Asimuth deg	Polarisation
72.680000	26.60	-19.8	40.0	13.4	QP	300.0	98.00	HORIZONTAL
103.720000	31.40	-14.0	43.5	12.1	QP	100.0	133.00	HORIZONTAL
154.160000	34.80	-18.0	43.5	8.7	QP	100.0	231.00	HORIZONTAL
195.870000	36.30	-14.6	43.5	7.2	QP	100.0	119.00	HORIZONTAL
258.920000	32.60	-15.6	46.0	13.4	QP	100.0	148.00	HORIZONTAL
944.710000	34.60	3.3	46.0	11.4	QP	100.0	244.00	HORIZONTAL



MEASUREMENT RESULT: "RE141030009_red"

10/30/2014 7:53PM

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	azimuth deg	Polarization
53.280000	28.20	-15.3	40.0	11.8	QP	100.0	354.00	VERTICAL
59.100000	29.80	-15.6	40.0	10.2	QP	100.0	354.00	VERTICAL
80.440000	28.80	-19.0	40.0	11.2	QP	100.0	47.00	VERTICAL
102.750000	33.90	-13.9	43.5	9.6	QP	100.0	147.00	VERTICAL
198.780000	36.00	-14.5	43.5	7.5	QP	100.0	88.00	VERTICAL
921.430000	33.60	3.0	46.0	12.4	QP	100.0	105.00	VERTICAL

Above 1GHz

Test channel:	0
---------------	---

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804	39.03	31.28	5.66	35.29	40.68	74	-28.97	Vertical
7206	33.65	36.22	6.87	35.15	41.59	74	-23.81	Vertical
9608	36.42	37.85	8.8	35.55	47.52	74	-20.27	Vertical
12010	38.07	38.25	8.9	35.84	49.38	74	-20.95	Vertical
14412	38.44	39.25	9.2	36.15	50.74	74	-19.28	Vertical
4804	39.71	31.28	5.66	35.29	41.36	74	-30.77	Horizontal
7206	33.58	36.22	6.87	35.15	41.52	74	-25.42	Horizontal
9608	36.76	37.85	8.8	35.55	47.86	74	-22.15	Horizontal
12010	38.06	38.25	8.9	35.84	49.37	74	-22.48	Horizontal
14412	39.18	39.25	9.2	36.15	51.48	74	-21.32	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804	34.1	31.28	5.66	35.29	35.75	54	-18.25	Vertical
7206	28.59	36.22	6.87	35.15	36.53	54	-17.47	Vertical
9608	26.48	37.85	8.8	35.55	37.58	54	-16.42	Vertical
12010	29.16	38.25	8.9	35.84	40.47	54	-13.53	Vertical
14412	28.08	39.25	9.2	36.15	40.38	54	-13.62	Vertical
4804	33.6	31.28	5.66	35.29	35.25	54	-18.75	Horizontal
7206	28.92	36.22	6.87	35.15	36.86	54	-17.14	Horizontal
9608	26.14	37.85	8.8	35.55	37.24	54	-16.76	Horizontal
12010	30.45	38.25	8.9	35.84	41.76	54	-12.24	Horizontal
14412	27.95	39.25	9.2	36.15	40.25	54	-13.75	Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test channel:	19
---------------	----

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882	38.68	31.26	5.65	35.27	40.32	74	-33.68	Vertical
7323	34.86	36.2	6.86	35.13	42.79	74	-31.21	Vertical
9764	35.49	37.83	8.79	35.53	46.58	74	-27.42	Vertical
12205	38.08	38.78	8.95	35.95	49.86	74	-24.14	Vertical
14412	39.28	39.64	9.27	36.74	51.45	74	-22.55	Vertical
4882	38.67	31.26	5.65	35.27	40.31	74	-33.69	Horizontal
7323	33.59	36.2	6.86	35.13	41.52	74	-32.48	Horizontal
9764	36.59	37.83	8.79	35.53	47.68	74	-26.32	Horizontal
12205	38.17	38.78	8.95	35.95	49.95	74	-24.05	Horizontal
14412	39.2	39.64	9.27	36.74	51.37	74	-22.63	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882	34.21	31.26	5.65	35.27	35.85	54	-18.15	Vertical
7323	28.76	36.2	6.86	35.13	36.69	54	-17.31	Vertical
9764	26.65	37.83	8.79	35.53	37.74	54	-16.26	Vertical
12205	28.6	38.78	8.95	35.95	40.38	54	-13.62	Vertical
14412	28.35	39.64	9.27	36.74	40.52	54	-13.48	Vertical
4882	34.25	31.26	5.65	35.27	35.89	54	-18.11	Horizontal
7323	28.59	36.2	6.86	35.13	36.52	54	-17.48	Horizontal
9764	26.67	37.83	8.79	35.53	37.76	54	-16.24	Horizontal
12205	29.01	38.78	8.95	35.95	40.79	54	-13.21	Horizontal
14412	28.21	39.64	9.27	36.74	40.38	54	-13.62	Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test channel:	39
---------------	----

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960	40	31.44	5.87	35.46	41.85	74	-32.15	Vertical
7440	33.53	36.38	7.08	35.32	41.67	74	-32.33	Vertical
9920	34.13	38.01	9.01	35.72	45.43	74	-28.57	Vertical
12400	37.64	38.95	8.98	36.05	49.52	74	-24.48	Vertical
14880	39.03	39.87	9.34	36.88	51.36	74	-22.64	Vertical
4960	39.57	31.44	5.87	35.46	41.42	74	-32.58	Horizontal
7440	33.49	36.38	7.08	35.32	41.63	74	-32.37	Horizontal
9920	36.05	38.01	9.01	35.72	47.35	74	-26.65	Horizontal
12400	37.82	38.95	8.98	36.05	49.7	74	-24.3	Horizontal
14880	38.49	39.87	9.34	36.88	50.82	74	-23.18	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960	33.62	31.42	5.87	35.46	35.45	54	-18.55	Vertical
7440	28.51	36.36	7.08	35.32	36.63	54	-17.37	Vertical
9920	26.11	37.99	9.01	35.72	37.39	54	-16.61	Vertical
12400	28.48	38.95	8.98	36.05	40.36	54	-13.64	Vertical
14880	28.36	39.87	9.34	36.88	40.69	54	-13.31	Vertical
4960	33.55	31.42	5.87	35.46	35.38	54	-18.62	Horizontal
7440	28.35	36.36	7.08	35.32	36.47	54	-17.53	Horizontal
9920	26.24	37.99	9.01	35.72	37.52	54	-16.48	Horizontal
12400	28.31	38.95	8.98	36.05	40.19	54	-13.81	Horizontal
14880	28.04	39.87	9.34	36.88	40.37	54	-13.63	Horizontal

Remark:


1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

5. Test Setup Photos of the EUT

Radiated Emission (30MHz-1GHz)



Radiated Emission (above 1GHz)



Conducted Emission (AC Mains)



6. External and Internal Photos of the EUT

Reference to the test report No. TRE1410009401

.....End of Report.....