



Neutron Engineering Inc.

FCC RF EXPOSURE REPORT

FCC ID: 2AAP800003

Project No. : 1402C182
Equipment : FULL SIZE BLUETOOTH SPEAKER
Model : BTV3
Applicant : Guoguang Electric Co.,Ltd.
Address : No.8 Jinghu Road, Xinhua Street, Huadu Reg,
Guangzhou, China

According: : FCC Guidelines for Human Exposure IEEE C95.1

Neutron Engineering Inc.

No.3, Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.

TEL : (0769) 8318-3000 FAX : (0769) 8319-6000



MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Field Antenna:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Note
1	N/A	WA-P-LA-03-115	PCB	N/A	1.57	TX/RX



Neutron Engineering Inc.

Maximum measured transmitter power:

Output Power (dBm)	Out Power (mW)	Limit (mW)
4.36	2.73	10

According to FCC KDB447498 V05, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

The maximum measured output peak power of this EUT is 2.73 Mw, therefore all of them are less than 10mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold