

# TEST REPORT

**Product Name** : TWS Earbuds with Digital Display  
**Model Number** : MA-3915, V40089W, V40089W-BLK,  
V40089W-WHT, MUZ3012, MUZ3012-WHT  
**FCC ID** : 2AAPK-MA-3915

**Prepared for** : Shenzhen Kingsun Enterprises Co., Ltd.  
**Address** : 25/F, CEC Information Building, Xinwen Rd., Shenzhen,  
Guangdong, P.R.China

**Prepared by** : EMTEK (SHENZHEN) CO., LTD.  
**Address** : Building 69, Majialong Industry Zone, Nanshan District,  
Shenzhen, Guangdong, China

Tel: (0755) 26954280  
Fax: (0755) 26954282

**Report Number** : ENS2304280322W00102R  
**Date(s) of Tests** : May 16, 2023 to June 07, 2023  
**Date of issue** : June 07, 2023

## Table of Contents

1. TEST RESULT CERTIFICATION .....	3
2. EUT SPECIFICATION .....	5
3. TEST REQUIREMENT .....	6
4. MEASUREMENT RESULT .....	7



# 1. TEST RESULT CERTIFICATION

Applicant : Shenzhen Kingsun Enterprises Co., Ltd.  
 Address : 25/F, CEC Information Building, Xinwen Rd.,Shenzhen, Guangdong, P.R.China  
 Manufacturer : Shenzhen Kingsun Enterprises Co., Ltd.  
 Address : 25/F, CEC Information Building, Xinwen Rd.,Shenzhen, Guangdong, P.R.China  
 Factory : Shenzhen Ning Tong Da Electronics Co., Ltd  
 Address : 3 / F, Building A1, Changrui Industrial Park, No. 55 Guanlan Guihuapinshun Road, Longhua District, Shenzhen  
 EUT : TWS Earbuds with Digital Display  
 Model Name : MA-3915, V40089W, V40089W-BLK, V40089W-WHT, MUZ3012, MUZ3012-WHT  
 Trademark : N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1093	PASS

The above equipment was tested by EMTEK(SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : May 16, 2023 to June 07, 2023

*Una Yu*

Prepared by : \_\_\_\_\_

Una Yu /Editor

*Joe Xia*

Reviewer : \_\_\_\_\_

Joe Xia/Supervisor

*Lisa Wang*

Approve & Authorized Signer : \_\_\_\_\_

Lisa Wang/Manager



## Modified History

Version	Report No.	Revision Date	Summary
	ENS2304280322W00102R	/	Original Report



## 2. EUT Specification

Characteristics	Description
<b>Product:</b>	TWS Earbuds with Digital Display
<b>Model Number:</b>	MA-3915, V40089W, V40089W-BLK, V40089W-WHT, MUZ3012, MUZ3012-WHT All products are the same, only the model number and color of appearance are different Here we selected MA-3915 for all the test
<b>Sample:</b>	1#
<b>Device Type:</b>	Bluetooth V5.3
<b>Data Rate:</b>	1Mbps for GFSK modulation 2Mbps for $\pi/4$ -DQPSK modulation 3Mbps for 8DPSK modulation
<b>Modulation:</b>	GFSK, $\pi/4$ -DQPSK, 8DPSK
<b>Operating Frequency Range(s) :</b>	2402-2480MHz
<b>Number of Channels:</b>	0.66 dBm(0.001164W)
<b>Transmit Power Max:</b>	Chip Antenna
<b>Antenna Gain:</b>	2.67 dBi
<b>Power supply:</b>	DC 5V from USB, DC 3.7V from battery
<b>Evaluation applied:</b>	<input type="checkbox"/> MPE Evaluation <input checked="" type="checkbox"/> SAR Evaluation

### 3. Test Requirement

#### RF EXPOSURE EVALUATION

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR,<sup>24</sup> where

- $f_{\text{(GHz)}}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>25</sup>
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is  $< 5$  mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

## 4. Measurement Result

Antenna gain: 2.67 dBi

When a single module works, the measurement results are as follows:

BT1

Transmit Frequency (MHz)	Mode	Measured Power (dBm)	E.I.R.P (dBm)	Tune up Power (dBm)	Max tune up power (dBm)	Calculation Result	1-g SAR
2402	GFSK	-0.68	1.99	1±1	2	0.4912658	3
2441	GFSK	-1.68	0.99	0±1	1	0.3933815	3
2480	GFSK	-1.13	1.54	1±1	2	0.4991785	3
2402	π/4-DQPSK	0.05	2.72	2±1	3	0.6184670	3
2441	π/4-DQPSK	-0.89	1.78	1±1	2	0.4952379	3
2480	π/4-DQPSK	-0.47	2.20	2±1	3	0.6284284	3
2402	8DPSK	0.66	3.33	3±1	4	0.7786038	3
2441	8DPSK	-0.54	2.13	2±1	3	0.6234676	3
2480	8DPSK	-0.12	2.55	2±1	3	0.6284284	3

According to KDB 447498, no stand-alone required for BT antenna, and no simultaneous SAR measurement is required.

\*\*\* End of Report \*\*\*